Geotextiles

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Woven Geotextile	IS 16391 (Part 1),IS 13162; IS 14714; IS 2454; IS 15570; IS 6359	ISO 10318-1 (Geosynthetics — Terms and Definitions — Geotextiles and Geotextile-related Products); ISO 10319 (Geosynthetics — Wide-width Tensile Test),ISO 10321; ISO 11058; ISO 12236; ISO 12956; ISO 13427; ISO 13433	ASTM D4595 (Tensile Properties of Geotextiles by the Wide-Width Strip Method); ASTM D4491 (Water Permeability of Geotextiles); ASTM D4751 (Apparent Opening Size of Geotextiles); ASTM D6241 (Static Puncture Strength of Geotextiles and Geogrids),ASTM D4632; ASTM D4533; ASTM D4833; ASTM D5261; ASTM D5101; ASTM D5321	DIN EN ISO 10319 (Geotextiles — Wide-Width Tensile Test); DIN EN ISO 12956 (Determination of Characteristic Opening Size); DIN EN ISO 11058 (Water Permeability Characteristics); DIN EN ISO 12236 (CBR Puncture Test)	GRI GT Series (Geosynthetic Research Institute Specifications); FHWA Geosynthetics Guidelines (Highway Applications); AASHTO M288 (Geotextile Specification for Highway Applications)
Nonwoven Geotextile	IS 16391 (Part 2),IS 13162; IS 14714; IS 2454; IS 15570; IS 6359	ISO 10318-1 (Geosynthetics — Terms and Definitions — Geotextiles and Geotextile-related Products); ISO 10319 (Geosynthetics — Wide-width Tensile Test),ISO 10321; ISO 11058; ISO 12236; ISO 12956; ISO 13427; ISO 13433	ASTM D4632 (Grab Breaking Load and Elongation of Geotextiles); ASTM D4491 (Water Permeability of Geotextiles); ASTM D4751 (Apparent Opening Size of Geotextiles); ASTM D6241 (Static Puncture Strength of Geotextiles and Geogrids),ASTM D4533; ASTM D4833; ASTM D5261; ASTM D5101; ASTM D5321	DIN EN ISO 10319 (Wide-Width Tensile Test); DIN EN ISO 12956 (Characteristic Opening Size); DIN EN ISO 11058 (Water Permeability); DIN EN ISO 12236 (CBR Puncture Resistance)	GRI GT Series; FHWA Geosynthetic Guidelines; AASHTO M288
Drainage Geotextile	IS 16391 (appropriate part),IS 13162; IS 14714; IS 2454; IS 15570; IS 6359	ISO 11058 (Geotextiles and Geotextile-related Products — Determination of Water Permeability Characteristics Normal to the Plane),ISO 10319; ISO 10321; ISO 12236; ISO 12956; ISO 13427; ISO 13433	ASTM D4491 (Water Permeability of Geotextiles); ASTM D4751 (Apparent Opening Size of Geotextiles); ASTM D4632 (Grab Tensile Properties of Geotextiles); ASTM D6241 (Static Puncture Strength of Geotextiles and Geogrids),ASTM D4533; ASTM D4833; ASTM D5261; ASTM D5101; ASTM D5321	DIN EN ISO 12958 (In-Plane Water Flow Capacity); DIN EN ISO 11058 (Water Permeability); DIN EN ISO 10319 (Tensile Properties); DIN EN ISO 12236 (Puncture Resistance)	GRI GT Series; EPA Subtitle D (Drainage Systems); FHWA Geotechnical Guidelines
Railway Geotextile	IS 16391,IS 13162; IS 14714; IS 2454; IS 15570; IS 6359	ISO 10318-1 (Geosynthetics — Terms and Definitions — Geotextiles and Geotextile-related Products); ISO 12956 (Geotextiles and Geotextile-related Products — Determination of Characteristic Opening Size),ISO 10319; ISO 10321; ISO 11058; ISO 12236; ISO 13427; ISO 13433	ASTM D4595 (Wide-Width Tensile Properties of Geotextiles); ASTM D6241 (Static Puncture Strength of Geotextiles and Geogrids); ASTM D4491 (Water Permeability of Geotextiles); ASTM D4751 (Apparent Opening Size of Geotextiles),ASTM D4632; ASTM D4533; ASTM D4833; ASTM D5261; ASTM D5101; ASTM D5321	DIN EN ISO 10319 (Wide-Width Tensile Test); DIN EN ISO 13431 (Tensile Creep Properties); DIN EN ISO 12956 (Characteristic Opening Size); DIN EN ISO 11058 (Water Permeability)	AREMA Manual for Railway Engineering (Rail Applications); FHWA Geosynthetic Guidelines; Railway Authority Specifications
Road Geotextile	IS 16391,IS 13162; IS 14714; IS 2454; IS 15570; IS 6359	ISO 10318-1 (Geosynthetics — Geotextiles and Geotextile-related Products); ISO 10319 (Wide-width Tensile Test); ISO 12956 (Characteristic Opening Size),ISO 10321; ISO 11058; ISO 12236; ISO 13427; ISO 13433	ASTM D4595 (Tensile Properties of Geotextiles); ASTM D4632 (Grab Breaking Load and Elongation); ASTM D6241 (Static Puncture Strength of Geotextiles and Geogrids); ASTM D4355 (Deterioration of Geotextiles from Exposure to Ultraviolet Light),ASTM D4491; ASTM D4533; ASTM D4833; ASTM D4751; ASTM D5261; ASTM D5101; ASTM D5321	DIN EN ISO 10319 (Tensile Properties); DIN EN ISO 12236 (CBR Puncture Resistance); DIN EN ISO 12956 (Characteristic Opening Size); DIN EN ISO 11058 (Water Permeability)	AASHTO M288; FHWA Geosynthetic Guidelines; GRI GT Series
Geotextiles for permanent erosion control in hard armor systems					
Geotextiles used as					

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
protection (or cushioning) materials					

Source field: Textile and Textile Products