Home Textiles

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Bed Sheet (Cotton)	IS 17629:2021,IS 1964; IS 1969; IS 6489; IS 7902; IS 2977; IS 1954; IS 2970; IS 2454; IS 1067; IS 15570; IS 6359	ISO 12947-2 (Textiles — Determination of Abrasion Resistance of Fabrics by the Martindale Method); ISO 3801 (Textiles — Woven Fabrics — Determination of Mass per Unit Length and Mass per Unit Area), ISO 12945; ISO 12947; ISO 13934; ISO 13936; ISO 13937; ISO 22198; ISO 7211; ISO 7771	ASTM D5034 (Breaking Strength and Elongation of Textile Fabrics); ASTM D3776 (Mass Per Unit Area); ASTM D737 (Air Permeability); ASTM D3512 (Pilling Resistance),ASTM D5035; ASTM D2261; ASTM D1424; ASTM D3773; ASTM D3774; ASTM D3107; ASTM D1388; ASTM D4966; ASTM D3884; ; ASTM D1683; ASTM D3940	DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 12127 (Mass per Unit Area); DIN EN ISO 105-C06 (Colour Fastness to Washing)	OEKO-TEX Standard 100 (Textile Safety); GOTS (Organic Cotton Applications); Better Cotton Initiative Guidelines
Pillow Cover; Quilt Cover	IS 745 (Bed Linen),IS 1964; IS 1969; IS 6489; IS 7902; IS 2977; IS 1954; IS 2970; IS 2454; IS 1067; IS 15570; IS 6359	ISO 3801 (Textiles — Woven Fabrics — Determination of Mass per Unit Area); ISO 12947-2 (Abrasion Resistance of Textile Fabrics), ISO 12945; ISO 12947; ISO 13934; ISO 13936; ISO 13937; ISO 22198; ISO 7211; ISO 7771	ASTM D5034 (Breaking Strength and Elongation of Textile Fabrics); ASTM D3776 (Mass Per Unit Area); ASTM D3512 (Pilling Resistance); ASTM D4966 (Abrasion Resistance by Martindale Tester),ASTM D5035; ASTM D2261; ASTM D1424; ASTM D3773; ASTM D3774; ASTM D3107; ASTM D1388; ASTM D3884; ASTM D737; ; ASTM D1683; ASTM D3940	DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 105-C06 (Colour Fastness); DIN EN ISO 12945-2 (Pilling Resistance)	OEKO-TEX Standard 100; GOTS (Organic Textile Applications); Textile Exchange Standards
Comforter	IS 17567 (Filled Bedding Products),IS 1964; IS 1969; IS 6489; IS 7902; IS 2977; IS 1954; IS 2970; IS 2454; IS 1067; IS 15570; IS 6359	ISO 12952-1 (Textiles — Assessment of the Ignitability of Bedding Items — General Ignition Source); ISO 12952-2 (Bedding Ignition Source — Match-flame Equivalent),ISO 3801; ISO 12945; ISO 12947; ISO 13934; ISO 13936; ISO 13937; ISO 22198; ISO 7211; ISO 7771	ASTM D1518 (Thermal Resistance of Textile Materials); ASTM D3776 (Mass Per Unit Area); ASTM D5034 (Breaking Strength and Elongation); ASTM D3574 (Flexible Cellular Materials, where filling material applies),ASTM D5035; ASTM D2261; ASTM D1424; ASTM D3773; ASTM D3774; ASTM D3107; ASTM D1388; ASTM D4966; ASTM D3884; ASTM D737; ; ASTM D1683; ASTM D3940	DIN EN ISO 12127 (Mass per Unit Area); DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 11092 (Thermal Resistance and Water Vapour Permeability); DIN EN ISO 13934-1 (Tensile Properties)	OEKO-TEX Standard 100; Responsible Down Standard (RDS, where down filling applies); GREENGUARD Gold Certification
Blanket	IS 894:1980; IS 3371 (where applicable),IS 1964; IS 1969; IS 6489; IS 7902; IS 2977; IS 1954; IS 2970; IS 2454; IS 1067; IS 15570; IS 6359	ISO 12952-1 (Textiles — Assessment of the Ignitability of Bedding Items); ISO 12952-2 (Bedding Items — Ignition Source Testing),ISO 3801; ISO 12945; ISO 12947; ISO 13934; ISO 13936; ISO 13937; ISO 22198; ISO 7211; ISO 7771	ASTM D1518 (Thermal Resistance of Textile Materials); ASTM D5034 (Breaking Strength and Elongation); ASTM D3512 (Pilling Resistance); ASTM D3776 (Mass Per Unit Area),ASTM D5035; ASTM D2261; ASTM D1424; ASTM D3773; ASTM D3774; ASTM D3107; ASTM D1388; ASTM D4966; ASTM D3884; ASTM D737; ; ASTM D1683; ASTM D3940	DIN EN ISO 12947-2 (Textiles — Determination of Abrasion Resistance by Martindale Method); DIN EN ISO 12945-2 (Textiles — Determination of Fabric Propensity to Surface Pilling); DIN EN ISO 11092 (Textiles — Physiological Effects — Thermal Resistance and Water Vapour Resistance); DIN EN ISO 13934-1 (Textiles — Tensile Properties of Fabrics)	OEKO-TEX Standard 100 (Textile Product Safety); Woolmark Standards (where wool content applies); GREENGUARD Gold Certification (Indoor Textile Applications)
Bath Towel; Hand Towel; Kitchen Towel	IS 7056 (Terry Towels and Toweling Fabrics),IS 1964; IS 1969; IS 6489; IS 7902; IS 2977; IS 1954; IS 2970; IS 2454; IS 1067; IS 15570; IS 6359	ISO 9073-6 (Textiles — Test Methods for Nonwovens — Absorption, where applicable); ISO 3801 (Textiles — Mass per Unit Area), ISO 12945; ISO 12947; ISO 13934; ISO 13936; ISO 13937; ISO 22198; ISO 7211; ISO 7771	ASTM D3776 (Mass Per Unit Area of Fabric); ASTM D5034 (Breaking Strength and Elongation); ASTM D4966 (Abrasion Resistance by Martindale Tester); (Surface Absorption of Textile Fabrics),ASTM D5035; ASTM D2261; ASTM D1424; ASTM D3773; ASTM D3774; ASTM D3107; ASTM D1388; ASTM D3884; ASTM D737; ASTM	DIN EN ISO 13934-1 (Textiles — Tensile Properties of Fabrics); DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 12945-2 (Pilling Resistance); DIN EN ISO 105-C06 (Colour Fastness to Washing)	OEKO-TEX Standard 100 (Textile Safety); GOTS (Organic Textile Applications); Better Cotton Initiative Standards (where applicable)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
			D1683; ASTM D3940		
Curtain Fabric	IS 15741 (Curtain and Drapery Fabrics),IS 1964; IS 1969; IS 6489; IS 7902; IS 2977; IS 1954; IS 2970; IS 2454; IS 1067; IS 15570; IS 6359	ISO 12947-2 (Textiles — Abrasion Resistance by Martindale Method); ISO 105-B02 (Textiles — Colour Fastness to Artificial Light),ISO 3801; ISO 12945; ISO 12947; ISO 13934; ISO 13936; ISO 13937; ISO 22198; ISO 7211; ISO 7771	ASTM D5034 (Breaking Strength and Elongation); ASTM D3776 (Mass Per Unit Area); ASTM D737 (Air Permeability); ASTM E84 (Surface Burning Characteristics of Building Materials, where flame application applies),ASTM D5035; ASTM D2261; ASTM D1424; ASTM D3773; ASTM D3774; ASTM D3107; ASTM D1388; ASTM D4966; ASTM D3884; ; ASTM D1683; ASTM D3940	DIN EN ISO 13934-1 (Tensile Properties of Fabrics); DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 105-B02 (Colour Fastness to Artificial Light); DIN EN ISO 11092 (Thermal and Water Vapour Resistance, where applicable)	OEKO-TEX Standard 100; GREENGUARD Gold Certification (Indoor Air Quality); NFPA 701 (Flame Propagation of Textiles, where applicable)
Upholstery Fabric	IS 15768 (Upholstery Fabrics),IS 12673; IS 15741; IS 2454; IS 1067; IS 15570; IS 6359	ISO 12947-2 (Textiles — Determination of Abrasion Resistance by the Martindale Method),ISO 12945; ISO 12947	ASTM D5034 (Breaking Strength and Elongation of Textile Fabrics); ASTM D3884 (Abrasion Resistance of Textile Fabrics); ASTM D3512 (Pilling Resistance of Textile Fabrics); ASTM D737 (Air Permeability of Textile Fabrics),ASTM D4157; ASTM D3597; ASTM D4158; ASTM D4771; ASTM E1353	DIN EN ISO 12947-2 (Martindale Abrasion Resistance); DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 12945-2 (Pilling Resistance); DIN EN ISO 105-B02 (Colour Fastness to Artificial Light)	California TB117-2013 (Furniture Flammability); NFPA 701 (where applicable); GREENGUARD Gold Certification

Source field: Textile and Textile Products