Knitted Fabric

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Single Jersey; Rib Knit; Interlock Fabric	IS 14704 (Knitted Fabrics),IS 11247; IS 1966; IS 2454; IS 1067; IS 15570; IS 6359	ISO 1833 (Textiles — Quantitative Chemical Analysis, where applicable); ISO 4920 (Surface Wetting Resistance, where applicable),ISO 8388; ISO 13938; ISO 14932; ISO 22960	ASTM D4966 (Abrasion Resistance of Textile Fabrics — Martindale Tester); ASTM D3512 (Pilling Resistance of Textile Fabrics); ASTM D5034 (Breaking Strength and Elongation); ASTM D3776 (Mass Per Unit Area of Fabric),ASTM D3786; ASTM D3887; ASTM D4970; ASTM D3511; ASTM D2594; ASTM D3106; ASTM D6797; ASTM D4032	DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 12945-2 (Pilling Resistance); DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 5084 (Thickness of Textiles)	OEKO-TEX Standard 100; AATCC Textile Testing Methods; Textile Exchange Standards
Fleece Fabric	IS 14704 (Knitted Fabrics),IS 11247; IS 1966; IS 2454; IS 1067; IS 15570; IS 6359	ISO 1833 (Textiles — Fibre Composition, where applicable),ISO 8388; ISO 13938; ISO 14932; ISO 22960	ASTM D3512 (Pilling Resistance of Textile Fabrics); ASTM D5034 (Breaking Strength and Elongation); ASTM D3776 (Mass Per Unit Area of Fabric); ASTM D737 (Air Permeability of Textile Fabrics),ASTM D3786; ASTM D3887; ASTM D4970; ASTM D3511; ASTM D2594; ASTM D3106; ASTM D6797; ASTM D4032	DIN EN ISO 12945-2 (Pilling Resistance); DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 12947-2 (Abrasion Resistance); DIN EN ISO 12127 (Mass per Unit Area)	OEKO-TEX Standard 100; Polartec Performance
Sportswear Fabric	IS 2150:1989: Specification for men's and boys' woven dress-suits, sportswear, jackets, slacks, and trousers.IS 4375:1975: Specification for cotton knitted sports shirts.IS 15853:2009: Woven suitings made from cotton, man-made fibers, and blends (frequently referenced for uniform and institutional active apparel),IS 16474; IS 16008; IS 16246; IS 2454; IS 15570; IS 6359	ISO 20932-1 (Textiles — Elastic Fabrics — Part 1: Determination of Elastic Properties of Narrow Fabrics); ISO 15487 (Textiles — Method for Assessing Appearance After Washing and Drying, where applicable), ISO 25705; ISO 4674	ASTM D5034 (Breaking Strength and Elongation of Textile Fabrics); ASTM D737 (Air Permeability of Textile Fabrics); ASTM D1518 (Thermal Resistance of Textile Materials); ASTM D5587 (Tearing Strength of Fabrics by Trapezoid Procedure),ASTM E96; ASTM D6413; ASTM D4157; ASTM D1777; ASTM F1868; ASTM D5061	DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 9237 (Air Permeability of Textiles); DIN EN ISO 11092 (Thermal Resistance and Water Vapour Permeability); DIN EN ISO 105-C06 (Colour Fastness)	OEKO-TEX Standard 100 (Textile Safety); AATCC Textile Performance Testing; Textile Exchange Standards (where recycled/sustainable fibres apply); bluesign® System Requirements
Spacer Fabric	IS 14704 (Knitted Fabrics),IS 16474; IS 16008; IS 16246; IS 2454; IS 15570; IS 6359	ISO 7211-1 (Textiles — Woven Fabrics — Construction Methods), where applicable, ISO 25705; ISO 4674	ASTM D737 (Air Permeability of Textile Fabrics); ASTM D3574 (Flexible Cellular Materials, where cushioning structures apply); ASTM D5034 (Breaking Strength and Elongation); ASTM D3776 (Mass Per Unit Area of Fabric),ASTM E96; ASTM D6413; ASTM D4157; ASTM D1777; ASTM F1868; ASTM D1518; ASTM D5587; ASTM D5061	DIN EN ISO 13934-1 (Tensile Properties); DIN EN ISO 3385 (Fatigue Testing of Flexible Cellular Materials, where spacer structures apply); DIN EN ISO 9237 (Air Permeability); DIN EN ISO 12947-2 (Abrasion Resistance)	OEKO-TEX Standard 100; AATCC Textile Testing Methods; Automotive Textile Industry Specifications (where used in seating/interiors); Textile Industry Performance Requirements

Source field: Textile and Textile Products