WP1: Measurements

Brian Trammell, ETH, WP1 lead Second Review, Zürich, 3 October 2017



measurement

architecture

experimentation



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 688421. The opinions expressed and arguments employed reflect only the authors' view. The European Commission is not responsible for any use that may be made of that information..

Supported by the Swiss State Secretariat for Education, Research and Innovation under contract number 15.0268.

The opinions expressed and arguments employed herein do not necessarily reflect the official views of the Swiss Government.

Objectives



- Initial and large-scale measurements of Internet path transparency in the Internet
 - Input to middlebox modeling (WP2)
 - Input to path layer architecture (WP3)
- Development of measurement tools
 - PATHspider, copycat, tracebox, revelio, ...
- Access to measurement data and analysis
 - Path Transparency Observatory (PTO)





Objectives: Progress M7-M18



- Initial and large-scale measurements of Internet path transparency in the Internet
 - Completion of Tracebox study as input to WP2
 - Confirmation of viability of UDP encaps for path layer
- Development of measurement tools
 - Building PATHspider into a measurement platform
- Access to measurement data
 - Initial PTO deployment
 - Continue PTO development based on lessons learned





Overview - Who does what?



Partner	MM	Task 1.1 Methodology and Tools	Task 1.2 Initial Measurement	Task 1.3 Large-Scale Measurement	Task 1.4 Data Model and Observatory
ETH	20	✓ pathspider	√ ECN,TFO	✓ Edit D1.3	✓ Edit D1.2
ULg	12	√ tracebox + copycat	√ UDP/TCP, middlebox survey		
UoA	15	√ pathspider	√ ECN, DSCP	√ DSCP	
ZHAW	8				✓
SRL	6	√ revelio		NAT detection, ECN on MONROE	



Summary



Transition to large scale measurement

Further development of core tools (PATHspider)

 Lessons learned from PTO applied to build a better, more sustainable observatory



Measurements Published and Presented



- "Observing Internet Path Transparency" at AIMS 2017, San Diego, 1 Mar 2017
- "Principles for Measurability in Protocol Design" in ACM SIGCOMM CCR 2017
- "Path Transparency Measurements from the Mobile Edge with PATHspider" at IEEE/IFIP Workshop on Mobile Network Measurement (MNM'17), Dubin, June 2017
- "copycat: Testing Differential Treatment of New Transport Protocols in the Wild" at ANRW 2017,
 Prague, 15 Jul 2017
- "Tracking transport-layer evolution with PATHspider" at ANRW 2017, Prague, 15 Jul 2017
- "A First Look at the Prevalence and Persistence of Middleboxes in the Wild" (tracebox) at ITC 29, Genoa, 4-8 Sep 2017 (WP1/WP2)
- A. M. Mandalari, A. Lutu, A. Dhamdhere, M. Bagnulo, kc claffy. Tracking the Big NAT across Europe and the US. arXiv cs.NI 1704.01296. April 2017.
- R. Zullo, A Pescapè, K. Edeline, B. Donnet. "Hic Sunt NATs: Uncovering Address Translation with a Smart Traceroute" MNM'17, June 2017.






WP1 Measurements and Tools




- tracebox
 - Middlebox Survey → WP2
- PATHspider
 - ECN, ECN++
 - DSCP
- Path Transparency Observatory (PTO)
 - version 3











 Detect modifications by comparing packet headers reflected in ICMP Time Exceeded on a hop by hop basis



Dataset



- 14 tracebox campaigns
 - one every ~ 5 day
 - over 70 days
- 89 PlanetLab vantage points
 - 594,241 destinations
 - 9 ports tested
 - 0.5×10^9 probes sent
- Results
 - 948,457 responsive intermediate hops overall
 - 59,861 HTTP only
 - 2,978 ASes crossed




Prevalence - Deployment



- Deployed MB vs.
 IP interfaces
 - alias resolution: CAIDA ITDK


In general, < 5%
hops per AS modify
packets





Prevalence - Position






- Border: 4,210 (52.6%)
- Internal: 2,931 (36.6%)
- Other: conflict or unable to derive position (9.1%) or moved (1.7%)
- Most ASes tend to deploy most of their MBs at their border
 - 65 ASes (19%) deploy the majority of their MBs in their core network.



Persistence - Overview






- 51% are stable
- 38% are slightly dynamic ([1:4])
- 11% are highly intermittent ([4:10])





PATHSpider - Review



- Active measurement of path transparency
- Basic methodology
 - 1. throw a bunch of packets at the Internet
 - 2. see what happens.
- Ideal: two-ended A/B testing
- Scalable: one-ended A/B testing
- Multiple sources isolate on-path from near-target impairment
- PATHspider provides a framework for generalizing and scaling the one-ended approach.
- Details: see https://pathspider.net










PATHSpider - Design Review





- Configurator: puts system into configuration A or B (e.g., sysctl)
- Workers: generate test traffic
- Observer: passively observes test traffic
- Merger: combine information about active measurement with passive observations.
- Plugins allow for customizing traffic generation and observation for each kind of test (ECN, DSCP, TFO, etc.)
- Output fed into Path Transparency
 Observatory



PATHspider - progress




- spiderweb: Automated cloud measurement
 - Cloud node provisioning via Saltstack
 - Automated upload to PTO
- MONROE integration
- Stability and sustainability improvements → 2.0 release
 - plugin and observer generalization
 - use of libcurl for connections

WIP: tracebox integration



PATHspider Methodology Example: Explicit Congestion Notification (ECN)





- Connect with and without ECN
- Measure ecn.connectivity.status
 - works: off + on OK
 - broken: off OK, on fails
 - transient: on OK, off fails
 - offline: no connection
- Measure ecn.codepoint.seen
 - Determine whether negotiation leads to ECT marking
 - Load path to attempt to induce CE marking






On Censorship and ECN Interference



- Automated measurements reduce the noise floor on path-dependent ECN connectivity issues.
- Geolocation of targets
 with path-dependency:
 most probable in countries
 with documented
 heterogeneous TCP-layer
 censorship firewalls.








PATHspider Results: DSCP



Table 3: DSCP summary statistics for popular Web servers, September 2016 and January 2017

September 2016		January 2017						
IPv	IPv4 IPv6 IPv4		74	IPv6		Description		
n = 620 611 $n = 52 766$		n =620 611		n =52 766				
hosts	pct	hosts	pct	hosts	pct	hosts	pct	
35 768	5.76%	24 422	46.28%	63 177	10.18%	28 985	54.93%	Completely failed to connect
584 843	94.24%	28 344	53.72%	557 434	89.82%	23 781	45.06%	Successfully connted with DSCP 0 (default); of which:
2 321	0.40%	156	0.55%	1 770	0.32%	124	0.52%	Failed to connect when DSCP 46 (EF) used;
2 170	0.37%	154	0.54%	1 334	0.24%	121	0.50%	but succeeded from at least one vantage point
584 692	99.99%	28 342	99.99%	556 998	99.92%	23 778	99.98%	Successfully connected with 46 (EF)



- Negligible blocking of a common DSCP codepoint (Expedited Forwarding, 46) from DigitalOcean vantage points.
 - Most blocking seems pathdependent.
- DSCP on return not dependent on DSCP on request.



Measuring ECN++



Feedback	Packet	TCP ECN flags (NS:CWR:	Allowed IP ECN		
mode	1 acket	Description	flags	ECN	ECN++
Non-ECN	All	ECN disabled	000	00	00
ECN	SYN	ECN setup SYN	011	00	00
	SYN/ACK	ECN setup SYN/ACK	001	00	XX
		Regular	000	XX	XX
	Data	Echo CE	001	XX	XX
		CWnd Reduced	010	XX	XX
	Control & RTX	Same as data packet	00	XX	

- ECN++ [draft-bagnulo-tswg-generalized-ecn]: ECN on control packets
- Test path support for SYN+ECT, pure ACK + ECT, FIN + ECT
- Revisit path support for SYN/ACK + ECT (RFC 5562)
- Multiple tools: tracebox, PATHspider
- Multiple platforms: MONROE (11 mobile) Planetlab (multiple fixed)
- Under submission



Path Transparency Observatory



- Demo at last review, initial at AIMS 2017 presentation
- Lessons learned:
 - Internal data model based on automated analysis made experimentation far too rigid.
 - Reliance on "big data" technologies results in lots of overhead and very little win; frameworks lock you in.
 - RESTful API design works better when fully embraced.

Outcome: PTO3, in progress



Path Transparency Observatory Data Model



 1st stage (raw) analysis converts raw data in any format to base observation four-tuples:


- t: time interval during which observation is valid
- p: path, a sequence of path elements from observation point or source to target or destination
- c: condition observed (within a defined space of conditions)
- v: optional value associated with condition observed
- nth stage produces derived observations from base observations





Path Transparency Observatory Design (refined)







Path Transparency Observatory API (now more RESTful)



- Raw data organized into campaigns containing files
 - /raw/campaign/file: extensible metadata
 - /raw/campaign/file/data: content, immutable
- Analysis performed by analyzers
 - /analysis/analyzer: extensible metadata
- Observations produced by analysis organized into sets
 - /obs/set: extensible metadata, provenance via references to raw data and analyzer by URL
 - /obs/set/data: content, immutable but can be deprecated
- Queries become result sets that can be externally referenced
 - /query/id: status of running query, result metadata
 - /query/id/result: content, immutable



Path Transparency Observatory Advantages of Further Development



- Raw data storage as raw files with metadata in sidecar
 - ease of backup and replication
- Observation storage in relational database
 - Grouping into sets makes provenance tractable
 - Interface via /obs API and to analyzers via ndjson
- Analyzer interface: UNIX stdin/stdout and commandline
 - Analysis tools may be written in any language, tested without the PTO framework, generalized beyond PTO
- RESTful API makes every stage of analysis referencable
 - Full provenance through link traversal:
 /query → /obs → /analysis + /obs → /analysis + /raw



Outlook



- Transition to tool maintenance (new T1.5, if extended)
 - PTO3, PATHspider 2.0

- Continue large scale measurement campaigns
 - Cloud providers, MONROE

