

PATHspider: A tool for active measurement of path transparency

Iain Learmonth
iain@erg.abdn.ac.uk

Brian Trammell
trammell@tik.ee.ethz.ch


Mirja Kühlewind
mirja.kuehlewind@tik.ee.ethz.ch

Gorry Fairhurst
gorry@erg.abdn.ac.uk


Introduction

PATHspider performs large-scale A/B testing between two different protocols or different protocol extensions to detect protocol-dependent connectivity issues and differential treatment. The A/B test itself is easily customized via a plugin framework.

Connectivity problems can arise from the increasing number of middleboxes in the Internet where either accidental or intentional manipulation causes a connection to fail.



Architecture



Each plugin consists of functions for generating test traffic, observing the resulting packets, and merging data into pre-analyzed observations. Each plugin handles a particular type of impairment (e.g. ECN, TFO, DSCP).

Getting Started

PATHspider is available in Debian unstable:
apt install pathspider

0.9.0 alpha was released shortly before ANRW!

Active development on new plugins (e.g. SCTP, UDP-Lite, MPTCP), enhancements, and integration with the MAMI Path Transparency Observatory continues.


Results

Explicit Congestion Notification (ECN)

State of ECN server-side deployment, as measured from a Digital Ocean vantage point in Amsterdam on 13 June 2016:

	IPv4	IPv6	all
No ECN connectivity issues	99.5%	99.9%	99.5%
ECN successfully negotiated	70.0%	82.8%	70.5%

ECN negotiation by Alexa rank bin: note this is nearly uniform, but higher-ranked servers tend to disable ECN:



DiffServ Code Points (DSCP)

Initial study: 10006 out of 96978 (10.31%) of Alexa Top 100k websites had unexpected, non-zero DSCP values. More measurement is necessary to better characterize these anomalies.

TCP Fast Open (TFO)

Initial study: 330 IPv4 and 32 IPv6 addresses in Alexa Top 1M are TFO-capable (of which 278 and 28 are Google properties). DDoS prevention services, enterprise firewalls, and CPE tend to interfere with TFO. More measurement is necessary to analyze impairments.

Learn more at <https://pathspider.mami-project.eu/>

measurement

architecture

experimentation

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 688421.
The opinions expressed and arguments employed reflect only the authors' view. The European Commission is not responsible for any use that may be made of that information.
Supported by the Swiss State Secretariat for Education, Research and Innovation under contract number 15.0268.
The opinions expressed and arguments employed herein do not necessarily reflect the official views of the Swiss Government.

