

```
CREATE DATABASE RESTAURANT;
```

```
USE RESTAURANT;
```

```
CREATE TABLE resturnt
```

```
(
```

```
RID INT PRIMARY KEY,
```

```
RNAME VARCHAR(20),
```

```
CONTACTNO INT
```

```
);
```

```
INSERT INTO resturnt(RID , RNAME , CONTACTNO)
```

```
VALUES
```

```
(1076,"RADHUNI",81522),
```

```
(3026, "FOOD CLUB",71552),
```

```
(1157, "LA BAMBA" ,73582),
```

```
(8413, "TAKEOUT" ,85832),
```

```
(1102,"MAMA-VAGNE",55079);
```

Table: **resturnt**

Columns:

RID int(11) PK
RNAME varchar(20)
CONTACTNO int(11)

	RID	RNAME	CONTACTNO
▶	1076	RADHUNI	81522
	1102	MAMA-VAGNE	55079
	1157	LA BAMBA	73582
	3026	FOOD CLUB	71552
	8413	TAKEOUT	85832
*	NULL	NULL	NULL

```
CREATE TABLE CUSTOMER
```

```
(
```

```
CUSID INT PRIMARY KEY,
```

```

CUSNAME VARCHAR (30),CNTNO INT,

RID INT,

foreign key(RID) references resturnt(RID)

);

```

```

INSERT INTO CUSTOMER(CUSID , CUSNAME , CUSTNO , RID)

VALUES

(221019, "SAIF" , 70512 , 1157),

(221020, "SHARIF" , 75510 , 1157),

(221021, "HASAN" , 16518 , 1157),

(221022, "SAYED" , 17519 , 1157),

(221023, "ANIQ" , 11519 , 1157),

(221024, "ROKON" , 16441 , 1102),

(221025, "SADIA" , 15851 , 1102);

```

Table: customer

Columns:

CUSID	int(11) PK
CUSNAME	varchar(30)
CUSTNO	int(11)
RID	int(11)

	CUSID	CUSNAME	CUSTNO	RID
▶	221019	SAIF	70512	1157
	221020	SHARIF	75510	1157
	221021	HASAN	16518	1157
	221022	SAYED	17519	1157
	221023	ANIQ	11519	1157
	221024	ROKON	16441	1102
	221025	SADIA	15851	1102
*	NULL	NULL	NULL	NULL

```

CREATE TABLE RESTAURANT_INFO

(

RNAME varchar(20) NOT NULL PRIMARY KEY,

ADDRESS VARCHAR(20)

);

```

```

INSERT INTO RESTAURANT_INFO(RNAME , ADDRESS)
VALUES
("MAMA-VAGNE" , "ISLAMABAD"),
("RADHUNI" , "NAWABGANJ"),
("FOOD CLUB" , "NAWABGANJ"),
("LA BAMBA" , "LAHORE"),
("TAKEOUT" , "BANANI");

```

Table: **restaurant_info**

Columns:

RNAME varchar(20)
 PK
ADDRESS varchar(20)

	RNAME	ADDRESS
▶	FOOD CLUB	NAWABGANJ
	LA BAMBA	LAHORE
	MAMA-VAGNE	ISLAMABAD
	RADHUNI	NAWABGANJ
	TAKEOUT	BANANI
★	NULL	NULL

```

CREATE TABLE WAITER
(
WID int NOT NULL PRIMARY KEY,
WNAME varchar(30),
CUSID INT ,
ORDER_NO INT ,
foreign key(CUSID) references CUSTOMER(CUSID),
foreign key(ORDER_NO) references ORDERR(ORDER_NO)
);

```

```

INSERT INTO WAITER(WID , WNAME , CUSID , ORDER_NO)
VALUES
(101, "PAUL",221023,6),
(102,"SAKIL",221019,6),

```

(103,"GOPAUL",221020,1),

(104,"SAKILA",221021,2),

(110, "JAMIL",221022,3),

(111,"PAUL",221024,4),

(119,"ASAD",221025,5);

INSERT INTO WAITER(WID , WNAME)

VALUES

(201, "HADDI"),

(202, "BUDDY");

Table: waiter

Columns:

WID int(11) PK
WNAME varchar(30)
CUSID int(11)
ORDER_NO int(11)

	WID	WNAME	CUSID	ORDER_NO
▶	101	PAUL	221023	6
	102	SAKIL	221019	6
	103	GOPAUL	221020	1
	104	SAKILA	221021	2
	110	JAMIL	221022	3
	111	PAUL	221024	4
	119	ASAD	221025	5
	201	HADDI	NULL	NULL
	202	BUDDY	NULL	NULL
•	NULL	NULL	NULL	NULL

CREATE TABLE ORDERR

(

ORDER_NO int NOT NULL PRIMARY KEY,

NO_OF_ITEM INT

);

INSERT INTO ORDERR(ORDER_NO , NO_OF_ITEM)

VALUES

(01,03),
 (02,01),
 (03,05),
 (04,01),
 (05,01),
 (06,10);

Table: **orderr**

Columns:

ORDER_NO int(11)
 PK
 NO_OF_ITEM int(11)

	ORDER_NO	NO_OF_ITEM
▶	1	3
	2	1
	3	5
	4	1
	5	1
	6	10
*	HULL	HULL

```
CREATE TABLE ORDER_INFO
(
  NO_OF_ITEM INT NOT NULL PRIMARY KEY,
  ORDER_TIME VARCHAR(20)
);
```

```
INSERT INTO ORDER_INFO(NO_OF_ITEM , ORDER_TIME)
VALUES
(01,"10 MINS"),
(02,"10 MINS"),
(05,"25 MINS"),
(03,"20 MINS"),
(10,"35 MINS"),
(04,"15 MINS");
```

Table: **order_info**

Columns:

NO_OF_ITEM int(11) PK
ORDER_TIME varchar(20)

	NO_OF_ITEM	ORDER_TIME
▶	1	10 MINS
	2	10 MINS
	3	20 MINS
	4	15 MINS
	5	25 MINS
	10	35 MINS
•	NULL	NULL

CREATE TABLE FOOD

(

FOOD_NO INT NOT NULL PRIMARY KEY,

QUANTITY INT ,

DESCRIPTIONN VARCHAR(60),

ORDER_NO INT,

foreign key(ORDER_NO) references ORDERR(ORDER_NO)

);

INSERT INTO FOOD(FOOD_NO , QUANTITY , DESCRIPTIONN , ORDER_NO)

VALUES

(510,1, "NEHARI", 1),

(600, 1,"BEEF BURGER", 2),

(601,3,"COLD DRINKS" ,3),

(152, 1, "MASALA DOSA",4),

(111,1,"CHICKEN PARM",5),

(501,2,"SIZZLING PRAWN", 6);

Table: **food**

Columns:

FOOD_NO int(11) PK
QUANTITY int(11)
DESCRIPTIONN varchar(60)
ORDER_NO int(11)

	FOOD_NO	QUANTITY	DESCRIPTIONN	ORDER_NO
▶	111	1	CHICKEN PARM	5
	152	1	MASALA DOSA	4
	501	2	SIZZLING PRAWN	6
	510	1	NEHARI	1
	600	1	BEEF BURGER	2
	601	3	COLD DRINKS	3
•	NULL	NULL	NULL	NULL

```

CREATE TABLE FOOD_DETAILS
(
  FOOD_NO INT,
  QUANTITY INT,
  PRICE INT,
  foreign key(FOOD_NO) references FOOD(FOOD_NO)
);

INSERT INTO FOOD_DETAILS(FOOD_NO , QUANTITY , PRICE)
VALUES
(601,1,20),
(501,1,1050),
(600, 1,400),
(510,1,150),
(152,1,100),
(111,1,400);

```

Table: food_details

	FOOD_NO	QUANTITY	PRICE
►	601	1	20
	501	1	1050
	600	1	400
	510	1	150
	152	1	100
	111	1	400

```

CREATE TABLE CHEF
(
  CHEFID INT NOT NULL ,
  CHEFNAME VARCHAR(30),
  ORDER_NO INT,
  foreign key(ORDER_NO) references ORDERR(ORDER_NO)
);

```

);

```
INSERT INTO CHEF(CHEFID , CHEFNAME , ORDER_NO)
```

```
VALUES
```

```
(201, "TONNY",1),
```

```
(201, "TONNY",2),
```

```
(205,"KHALID", 3),
```

```
(205,"KHALID", 4),
```

```
(205,"KHALID",5),
```

```
(207,"BONY",6);
```

Table: chef

	CHEFID	CHEFNAME	ORDER_NO
▶	201	TONNY	1
	201	TONNY	2
	205	KHALID	3
	205	KHALID	4
	205	KHALID	5
	207	BONY	6

```
CREATE TABLE BILL
```

```
(
```

```
BILLNO INT NOT NULL PRIMARY KEY,
```

```
ORDER_DTL VARCHAR(30),
```

```
PRICE INT,
```

```
CUS_ID INT,
```

```
foreign key(CUS_ID) references CUSTOMER(CUSID)
```

```
);
```

```
INSERT INTO BILL(BILLNO , ORDER_DTL , PRICE , CUS_ID)
```

```
VALUES
```

```
(11, "NEHARI",150, 221020),
```



```

(12, "BEEF BURGER",400, 221021),
(13, "SIZZLING PRAWN",1050, 221023),
(14, "SIZZLING PRAWN",1050 , 221019),
(15, "MASALA DOSA",100,221024),
(16, "CHICKEN PARM",400 ,221025);

```

Table: bill

Columns:

BILLNO	int(11) PK
ORDER_DTL	varchar(30)
PRICE	int(11)
CUS_ID	int(11)

	BILLNO	ORDER_DTL	PRICE	CUS_ID
▶	11	NEHARI	150	221020
	12	BEEF BURGER	400	221021
	13	SIZZLING PRAWN	1050	221023
	14	SIZZLING PRAWN	1050	221019
	15	MASALA DOSA	100	221024
	16	CHICKEN PARM	400	221025
✱	NULL	NULL	NULL	NULL

```

CREATE TABLE BILL_DTLS
(
PRICE VARCHAR(10) PRIMARY KEY,
VAT VARCHAR(15)
);

```

```

INSERT INTO BILL_DTLS(PRICE , VAT)
VALUES("20PKR","3PKR"),
("400PKR","60PKR"),
("150PKR","22.5PKR"),
("100PKR","15PKR");

```

Table: bill_dtls

	PRICE	VAT
▶	100PKR	15PKR
	150PKR	22.5PKR
	20PKR	3PKR
	400PKR	60PKR
✱	NULL	NULL

Display foods, food_no which ordered by customers?

```
SELECT F.DESCRPTIONN , F.FOOD_NO , W.CUSID  
FROM FOOD F , waiter W WHERE F.ORDER_NO = W.ORDER_NO;
```

	DESCRIPTIONN	FOOD_NO	CUSID
▶	SIZZLING PRAWN	501	221023
	SIZZLING PRAWN	501	221019
	NEHARI	510	221020
	BEEF BURGER	600	221021
	COLD DRINKS	601	221022
	MASALA DOSA	152	221024
	CHICKEN PARM	111	221025

Display waiter name who take order?

```
SELECT W.WNAME FROM WAITER W , FOOD F  
WHERE W.ORDER_NO = F.ORDER_NO;
```

	WNAME
▶	PAUL
	SAKIL
	GOPAUL
	SAKILA
	JAMIL
	PAUL
	ASAD

Display customer name his contact no and restaurant name?

```
SELECT C.CUSNAME , C.CUSTNO , R.RNAME  
FROM customer C , resturant R  
WHERE C.RID=R.RID;
```

	CUSNAME	CUSTNO	RNAME
►	SAIF	70512	LA BAMB
	SHARIF	75510	LA BAMB
	HASAN	16518	LA BAMB
	SAYED	17519	LA BAMB
	ANIQ	11519	LA BAMB
	ROKON	16441	MAMA-VAGNE
	SADIA	15851	MAMA-VAGNE

Display the customers name and contact no. who goes La Bamba?

```
SELECT CUSNAME,custno FROM CUSTOMER WHERE RID=(SELECT RID FROM resturnt
WHERE RNAME= "LA BAMB")
```

	CUSNAME	custno
►	SAIF	70512
	SHARIF	75510
	HASAN	16518
	SAYED	17519
	ANIQ	11519

Display waiter name who takes order from Sadia?

```
SELECT WNAME FROM WAITER WHERE CUSID=(SELECT CUSID FROM CUSTOMER WHERE
CUSNAME="SADIA")
```

Result Grid	
	WNAME
►	ASAD

Display customer name who orders sizzling prawn?

```
SELECT CUSNAME FROM CUSTOMER WHERE CUSID IN (SELECT CUSID FROM WAITER WHERE
ORDER_NO=(SELECT ORDER_NO FROM FOOD WHERE DESCRIPTION="SIZZLING PRAWN"))
```

	CUSNAME
►	ANIQ
	SAIF