Problem List

Dynamic Layout Premium 0

Description Editorial Solutions (180) Submissions

Java Auto

2860. Happy Students

Hint

Medium 103 212

Companies

You are given a **0-indexed** integer array `nums` of length `n` where `n` is the total number of students in the class. The class teacher tries to select a group of students so that all the students remain happy.

The i^{th} student will become happy if one of these two conditions is met:

- The student is selected and the total number of selected students is **strictly greater than** `nums[i]`.
- The student is not selected and the total number of selected students is **strictly less than** `nums[i]`.

Return *the number of ways to select a group of students so that everyone remains happy.*

Example 1:

```
Input: nums = [1,1]
Output: 2
Explanation:
The two possible ways are:
The class teacher selects no student.
The class teacher selects both students to form the group.
If the class teacher selects just one student to form a group then
the both students will not be happy. Therefore, there are only two
```

```java
        int i = totSel;

        while ( i < sortedList.size() && lessThanAnyNonSel == true ) {
            if ( sortedList.get(i) <= totSel ) {
               lessThanAnyNonSel = false;
            }
            i++;
        }

        return lessThanAnyNonSel;
    }

    private boolean noneIncludedCase( List<Integer> nums ) {

        List<Integer> sortedList = nums.stream().sorted().collect( Collectors.toList() );

        System.out.println( "sortedList: " + sortedList );

        boolean greaterThanZero = true;
        int i = 0;

        while ( i < nums.size() && greaterThanZero == true ) {
            if ( sortedList.get(i) <= 0 ) {
               greaterThanZero = false;
            }
--NORMAL--
```

Saved to local Ln 1, Col 1

Testcase Result

```
[6, 0, 3, 3, 6, 7, 2, 7]
sortedList: [0, 2, 3, 3, 6, 6, 7, 7]
```

Console Run Submit