

Association Rule Mining

UTKARSH GAIKWAD

Association Rule Mining Example

Amazon Items that are frequently bought together

Frequently bought together



This item: Dell Vostro 3420 Laptop, Intel i3-1115G4/8GB/512GB/14.0"...

₹37,990⁰⁰

+



Dell WM118 Wireless Mouse, 2.4 Ghz with USB Nano Receiver, Optical Tracking, 12-Months...

₹569⁰⁰

+



Dell Essential Backpack 15 (ES1520P)

₹1,790⁰⁰

Total price: ₹40,349.00


Add all three to Cart

i These items are dispatched from and sold by different sellers.
[Show details](#)

Example of ARM in Big Basket website

Frequently Bought Together

27% Off



2 pcs (Approx. 450g-500g)


Fresho
Fresho Sweet Corn (Loose)

2 pcs - Rs 44

MRP ~~Rs 60.27~~ Rs 44

ADD

36% Off



1 pc


Fresho
Fresho Spring Onion - With roots

1 pc - Rs 10.50

MRP ~~Rs 16.44~~ Rs 10.50

ADD

27% Off



4 pcs (Approx. 450g-500g)


Fresho
Fresho Apple - Royal Gala Economy

4 pcs - Rs 170

MRP ~~Rs 232.88~~ Rs 170

ADD

58% Off



100 g


Fresho
Fresho Mint Leaves - Cleaned, without roots

100 g - Rs 7.50

MRP ~~Rs 17.81~~ Rs 7.50

ADD

27% Off



500 g - Rs 29


Fresho
Fresho Cucumber - English (Loose)

500 g - Rs 29

MRP ~~Rs 39.73~~ Rs 29

ADD

27% Off



1 pc (Approx. 500-900g)

Fresho
Fresho Muskmelon - Netted Small

1 pc - Rs 38

MRP ~~Rs 52.05~~ Rs 38

ADD

Support

Support refers to the default popularity of an item and can be calculated by finding number of transactions containing a particular item divided by total number of transactions. Suppose we want to find support for item B. This can be calculated as:

$$\text{Support}(B) = (\text{Transactions containing } B) / (\text{Total Transactions})$$

For instance if out of 1000 transactions, 100 transactions contain Ketchup then the support for item Ketchup can be calculated as:

$$\text{Support}(\text{Ketchup}) = (\text{Transactions containing Ketchup}) / (\text{Total Transactions})$$

$$\begin{aligned}\text{Support}(\text{Ketchup}) &= 100/1000 \\ &= 10\%\end{aligned}$$

Confidence

Confidence refers to the likelihood that an item B is also bought if item A is bought. It can be calculated by finding the number of transactions where A and B are bought together, divided by total number of transactions where A is bought. Mathematically, it can be represented as:

$$\text{Confidence}(A \rightarrow B) = (\text{Transactions containing both (A and B)}) / (\text{Transactions containing A})$$

Coming back to our problem, we had 50 transactions where Burger and Ketchup were bought together. While in 150 transactions, burgers are bought. Then we can find likelihood of buying ketchup when a burger is bought can be represented as confidence of Burger \rightarrow Ketchup and can be mathematically written as:

$$\text{Confidence}(\text{Burger} \rightarrow \text{Ketchup}) = (\text{Transactions containing both (Burger and Ketchup)}) / (\text{Transactions containing A})$$

$$\begin{aligned}\text{Confidence}(\text{Burger} \rightarrow \text{Ketchup}) &= 50/150 \\ &= 33.3\%\end{aligned}$$

Lift

$Lift(A \rightarrow B)$ refers to the increase in the ratio of sale of B when A is sold. $Lift(A \rightarrow B)$ can be calculated by dividing $Confidence(A \rightarrow B)$ divided by $Support(B)$. Mathematically it can be represented as:

$$Lift(A \rightarrow B) = (Confidence(A \rightarrow B)) / (Support(B))$$

Coming back to our Burger and Ketchup problem, the $Lift(Burger \rightarrow Ketchup)$ can be calculated as:

$$Lift(Burger \rightarrow Ketchup) = (Confidence(Burger \rightarrow Ketchup)) / (Support(Ketchup))$$

$$\begin{aligned} Lift(Burger \rightarrow Ketchup) &= 33.3/10 \\ &= 3.33 \end{aligned}$$

Lift basically tells us that the likelihood of buying a Burger and Ketchup together is 3.33 times more than the likelihood of just buying the ketchup. A Lift of 1 means there is no association between products A and B. Lift of greater than 1 means products A and B are more likely to be bought together. Finally, Lift of less than 1 refers to the case where two products are unlikely to be bought together.

Steps Involved in Apriori Algorithm

For large sets of data, there can be hundreds of items in hundreds of thousands transactions. The Apriori algorithm tries to extract rules for each possible combination of items. For instance, Lift can be calculated for item 1 and item 2, item 1 and item 3, item 1 and item 4 and then item 2 and item 3, item 2 and item 4 and then combinations of items e.g. item 1, item 2 and item 3; similarly item 1, item 2, and item 4, and so on.

As you can see from the above example, this process can be extremely slow due to the number of combinations. To speed up the process, we need to perform the following steps:

1. Set a minimum value for support and confidence. This means that we are only interested in finding rules for the items that have certain default existence (e.g. support) and have a minimum value for co-occurrence with other items (e.g. confidence).
2. Extract all the subsets having higher value of support than minimum threshold.
3. Select all the rules from the subsets with confidence value higher than minimum threshold.
4. Order the rules by descending order of Lift.

Thank you

UTKARSH GAIKWAD

A solid orange horizontal bar spanning the width of the slide at the bottom.