

```
In [1]: # Colab + Local compatible Loader
import os
import numpy as np
import pandas as pd

CANDIDATES = ['diabetes.csv', 'lab05/diabetes.csv', '/content/diabetes.csv']
data_path = next((x for x in CANDIDATES if os.path.exists(x)), None)
print('Using:', data_path)
assert data_path is not None, 'diabetes.csv not found - upload it in Colab Files'
df = pd.read_csv(data_path, encoding='ascii', delimiter=',')

df.head()
```

Using: diabetes.csv

```
Out[1]:
```

	Glucose	BloodPressure	SkinThickness	Insulin	BMI	DiabetesPedigreeFunction	Age
0	148	72.0	35	169.5	33.6	0.627	50
1	85	66.0	29	102.5	26.6	0.351	31
2	183	64.0	32	169.5	23.3	0.672	32
3	89	66.0	23	94.0	28.1	0.167	21
4	137	40.0	35	168.0	43.1	2.288	33

```
In [2]: from sklearn.model_selection import train_test_split
# Prepare features and target variable
X = df[['Age', 'BMI', 'BloodPressure', 'Insulin', 'Glucose', 'DiabetesPedigreeFu
y = df['Outcome']

# Split the data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_

from sklearn.linear_model import LogisticRegression

# Initialize and train the logistic regression model
model = LogisticRegression(max_iter=1000)
model.fit(X_train, y_train)
```

```
Out[2]:
```

▼ LogisticRegression ⓘ ?

► Parameters

► Fitted attributes

```
In [3]: X_test
```

Out[3]:

	Age	BMI	BloodPressure	Insulin	Glucose	DiabetesPedigreeFunction
668	43	34.0	58.0	190.0	98	0.430
324	21	35.7	75.0	102.5	112	0.148
624	21	30.8	64.0	102.5	108	0.158
690	34	24.6	80.0	102.5	107	0.856
473	50	29.9	90.0	102.5	136	0.210
...	...	...	...	...	...	...
355	49	30.4	88.0	169.5	165	0.302
534	24	33.3	56.0	56.0	77	1.251
344	57	36.8	72.0	102.5	95	0.485
296	29	28.0	70.0	360.0	146	0.337
462	39	35.3	70.0	49.0	74	0.705

154 rows × 6 columns

```
In [4]: # Weights
print(model.coef_)

# Constant / intercept
print(model.intercept_)

[[ 0.04559683  0.09394991 -0.00964773  0.00442035  0.03010364  0.48521205]]
[-9.2358725]
```

```
In [5]: from sklearn.metrics import accuracy_score, confusion_matrix, roc_curve, auc
# Predict on the test set
y_pred = model.predict(X_test)

# Calculate the accuracy score
accuracy = accuracy_score(y_test, y_pred)
print(f'Accuracy Score: {accuracy:.4f}')
```

Accuracy Score: 0.7597

```
In [6]: y_pred
```

```
Out[6]: array([0, 0, 0, 0, 0, 1, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 0,
               0, 0, 0, 1, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1, 0, 0, 1, 0, 1, 1, 0,
               0, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1,
               0, 1, 0, 1, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 1, 0,
               0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 1, 0, 1, 0, 1, 1, 1, 0, 0, 1, 0, 0,
               0, 0, 0, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1,
               0, 0, 1, 0, 0, 1, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 1, 0])
```

```
In [7]: import matplotlib
matplotlib.use('Agg') # headless-safe backend (works on Colab too)
import matplotlib.pyplot as plt
import seaborn as sns

# Generate the confusion matrix and visualize using heatmap
cm = confusion_matrix(y_test, y_pred)
```

```
plt.figure(figsize=(6, 5))
sns.heatmap(cm, annot=True, fmt='d', cmap='Blues')
plt.title('Confusion Matrix')
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.show()
```

C:\Users\HP\AppData\Local\Temp\ipykernel_12508\3555294998.py:14: UserWarning: FigureCanvasAgg is non-interactive, and thus cannot be shown
plt.show()

In [8]: 21,35.7,75.0,102.5,112,0.148

Out[8]: (21, 35.7, 75.0, 102.5, 112, 0.148)