DMP FILE IMPORT

CREAT USER

CREATE USER testt

IDENTIFIED BY "Manar";

PRIVILIGES

GRANT CREATE SESSION TO testt;

Importing an Oracle Dump File Using `IMP.EXE`

Purpose:
`IMP.EXE` is Oracle's traditional Import utility used to restore data and database objects from a `.DMP` file.

Command:

imp.exe TESTT/Manar@//192.168.113.42:1521/orclpdb

FILE=C:\orcle\test.dmp FULL=Y

Command Components

Component	Explanation
`imp.exe`	Oracle Import utility
`testt/Manar`	Oracle username and password
`192.168.113.42`	IP address of the Oracle database server
`1521`	Oracle Listener port
`orclpdb`	Database service name
`FILE=...test.dmp`	Location of the dump file
`FULL=Y`	Imports the complete database export

Here, I used Oracle's IMP utility to import the dump file. The command connects to the Oracle database using the TESTT user, specifies the database server IP, port, and service name, and then identifies the test.dmp file as the source. FULL=Y tells Oracle to perform a full import of the export.

C:\orcle\instantclient\instantclient_23_26>imp.exe

testt/Manar@//192.168.113.42:1521/orclpdb

FILE=C:\orcle\test.dmp FULL=y