Quiz 1

Qes1)

1. Uniquely identifies each row
2. Cannot contain NULL values
3. Each table has only one primary key
4. Can consist of one or multipls columns
5. has an index created automatically

Qes2)

```
SELECT concat(e.first_name,' ',e.Last_name) AS "FULL_NAME",
to_char((e.salary * 12) + (e.salary * 12 * NVL(e.commission_pct, 0)),'$999999') AS
"ANNUAL SALARY",
NVL(TO_CHAR(e.commission_pct), 'NO COMMISSION') AS "COMMISSION",  d.department_name
AS "DEPARTMENT_ NAME",
 l.city AS "CITY"
from hr.EMPLOYEES e
join hr.DEPARTMENTS d
On e.department_id=d.department_id
join hr.LOCATIONS l
on d.LOCATION_ID=l.LOCATION_ID
order by FULL_NAME ,'ANNUAL SALARY' DESC
```

Qes3)

```
SELECT
    CONCAT(e.first_name, ' ' || e.last_name) AS "Employee Name",
    e.job_id AS "Job Title",
    d.department_name AS "Department",
    TO_CHAR(e.hire_date, 'DAY-MONTH-YYYY') AS "Hire Date"
FROM hr.employees e
JOIN hr.departments d
    ON e.department_id = d.department_id
WHERE e.department_id IN (10, 20, 50)
ORDER BY "Employee Name" ;
```

Qes4)

```
SELECT *
FROM hr.employees
WHERE EXTRACT(YEAR FROM hire_date) = 1998;
```

Qes5)

```
SELECT *
FROM hr.employees
WHERE manager_id IS NULL;
```

Qes6)

```
SELECT concat(first_name,' ',LAST_NAME) as "FULL_NAME",to_char(HIRE_DATE,'DAY-
MONTH-YYYY') as "Hire Date",
```

```
TRUNC(MONTHS_BETWEEN(CURRENT_DATE, hire_date)) AS "Total Working Months",
TRUNC((CURRENT_DATE - hire_date) / 7) AS "Total Working Weeks"
FROM hr.employees
WHERE hire_date BETWEEN TO_DATE('20-FEB-1998', 'DD-MON-YYYY')
                    AND TO_DATE('01-MAY-1998', 'DD-MON-YYYY')
```

Qes7)

```
SELECT
    d.department_name,
    MAX(e.salary) AS maximum_salary,
    MIN(e.salary) AS minimum_salary,
    SUM(e.salary) AS total_salary,
    AVG(e.salary) AS average_salary
FROM hr.employees e
JOIN hr.departments d
    ON e.department_id = d.department_id
GROUP BY d.department_name
```

Qes8)

```
SELECT
    salary,
    RPAD('*', FLOOR(salary / 1000), '*') AS "Salary Stars"
FROM hr.employees
order by salary
```

Qes9)

Case1: the count will be 5

Case 2 :: the count will be 4

Qes10)

```
SELECT *

 FROM employees

WHERE first_name LIKE '__e%';
```

Qes11)

```
SELECT Customer_ID

FROM customers

GROUP BY Customer_ID

HAVING COUNT(Customer_ID) > 1;
```