NameLock

Across-episodenameand terminology consistency check for translated microdrama scripts

Name:_Irlapati Manas Chandra_____Rollno:____23045062____Branch:___Chemical_____ | Problem3: Find your own problem

Who has the problem, and how I know

Person: alocalisation QAreviewer at a studio that releases the same show in many languages; one step: checking that character names, places and key terms stay the same across episodes of a translated version. **Why I believe it is real:** Kuku makes stories in many languages, and episodes translated one at a time by AI can spell a name differently each time. **My own evidence:** [FILL IN from research_worksheet.md: shows and languages checked, examples of drift you saw, review comments counted, who you spoke to]. Until filled in, this is a hypothesis.

Why this over Problems 1 and 2

Itmultiplies across everyshow-languagepair Kuku ships, is cheap to run, and its output is directly checkable (a flagged spelling either is or is not an error). Problem 1 serves one task on one show at a time; Problem 2 is outside Kuku's own work. [Your reasoning here.]

What I built (smallest useful thing)

Input: a folder of episode scripts and an optional glossary of decisions (canonical term to banned variants; a list of names that are different people on purpose). **Output:** a list and CSV of suspect spellings (e.g. Aarav vs Arav) and glossary violations (e.g. 'Grandma' where the glossary says 'Dadi'), with episode numbers. **Code only:** names are found from speaker labels, capitalised words and scene headings, then compared by spelling similarity and consonant skeleton (Meera and Mira share 'mr'). A model is not needed; one could later judge ambiguous pairs. **The human reviewer decides;** nothing is edited.

Does it work? Real runs and honest failures

Run	Result	What happened
run1_first_attempt	3/4 name errors; glossary 2/2; 1 false alarm 4/4;	Missed 'Rathod' vs 'Rathore': my code skipped the first word of scene headings, where place names sit. Also flagged Anita vs Amita, two different characters.
run2_after_heading_fix	glossary 2/2; 1 false alarm 4/4;	Heading bug fixed. The Anita/Amita false alarm remains.
run3_with_allowlist	glossary 2/2; 0 false alarms	The false alarm is removed only because I told the tool the two names are distinct; a new real pair of similar names would be flagged again.

Honest limits

Inputsare **synthetic**, written by me with the errors planted, so recall of 4/4 is optimistic. It will not catch a name rendered completely differently, a wrong translation, or consistent but wrong terms. It needs Latin-script or transliterated text and has not been tested on Devanagari, Tamil or other scripts. Similar real names will always cause false alarms. **Real-script test:** [FILL IN after running on a real translated script: errors found, false alarms, reviewer's verdict].

How I'd know it worked with a real team, and scale

Takethe errors QA already loggedon5shows; measure recall,the share of flags QA accepts, and QA minutes per episode before vs after. At scale it runs per show-language on every new episode in seconds with no model cost; the glossary grows from QA decisions and is shared across languages of one show; optionally a model reviews only ambiguous pairs.

Tools and where AI got it wrong

Claude drafted thecode and synthetic episodes. **Where it was wrong:** its first version ignored the first word of every line, so it missed place names in scene headings (found by my planted-error test), and its similarity rule raised a false alarm on two legitimate names. Python only; no paid tools.