

DISTRACTION-AWARE SHADOW DETECTION AND REMOVAL USING DEEP LEARNING

PRESENTATION

TEAM

URVI SHAH

22BCE1174

urvisamir.shah2022@vitstudent.ac.in

MANAS DUTT

22BCE1350

manas.dutt2022@vitstudent.ac.in

ISHAN SHARMA

22BCE1489

ishan.sharma2022@vitstudent.ac.in


MONISH S

22BCE1783

monish.s2022a@vitstudent.ac.in


INDEX

- 1.INTRODUCTION
- 2.PROBLEM STATEMENT
- 3.OBJECTIVE
- 4.EXISTING METHODS & LIMITATIONS
- 5.SOLUTION
- 6.PROPOSED SYSTEM ARCHITECTURE
- 7.METHODOLOGY
- 8.DATASET DESCRIPTION
- 9.EVALUATION METRICS
- 10.COMPARISON WITH OTHER METHODS
- 11.RESULT DISCUSSION
- 12.IMPROVEMENTS
- 13.CONCLUSION
- 14.REFERENCES




INTRODUCTION

- Shadows in images make computer vision tasks like object detection and segmentation difficult, especially when shadow and non-shadow regions look similar.
- Traditional and deep learning methods often misclassify these confusing areas, leading to errors.
- Distraction-aware networks use attention to focus on ambiguous regions, improving shadow detection and removal accuracy.




PROBLEM STATEMENT

- Shadows in natural images degrade the performance of computer vision systems.
- Challenges include handling mixed illumination, delicate shadow borders, and complex surface details, which can result in misclassification and poor image restoration.



OBJECTIVE

To develop an efficient deep learning-based system for automatic shadow detection and removal in natural scene images. The goals are:

1. Accurate shadow localization using a distraction-aware ResNeXt-50 backbone with Dynamic Attention Module (DAM) to handle soft/fragmented shadows¹⁴.
 2. High-quality artifact-free restoration via lightweight encoder-decoder networks that preserve texture/illumination²⁶.
 3. Computational efficiency through optimized architecture design (2.5 mins/epoch training on RTX 3080) while maintaining 93.72% accuracy on ISTD dataset¹.
 4. Generalization to diverse shadow types including partial occlusions, diffuse boundaries, and mixed illumination scenarios
- 

EXISTING METHODS & LIMITATIONS

- **Traditional methods:** Use physics-based models, color invariance, and regional contrast but struggle with complex lighting, textured surfaces, and soft boundaries.
- **Deep learning methods:** Improve feature extraction and edge detection but still face difficulties with highly discontinuous or gradually fading shadows, leading to misclassifications

SOLUTION

A two-stage framework:

Stage 1:

Shadow detection using a ResNeXt-50 backbone with a Dynamic Attention Module (DAM) to focus on shadow-relevant regions.

Stage 2:

Lightweight encoder-decoder network for shadow removal, combining the original image and predicted shadow map to generate a shadow-free output.

PROPOSED SYSTEM ARCHITECTURE

- ShadowDESDNet: Uses ResNeXt-50 and DAM to extract features and generate a shadow probability map
- Shadow Removal Network: Takes the original image and shadow map as input to reconstruct a shadow-free image.
- The two-stage design decouples detection and restoration for specialized feature learning

METHODOLOGY

- **Detection:** Input image **ShadowDESDNet**
Shadow map.
- **Removal:** Concatenate input image and
shadow map **Shadow removal network**
Shadow-free image.
- **Training:** Uses **Binary Cross-Entropy loss**
for **detection** and **L1 loss** for **removal**,
combined in the total loss function

DATASET DESCRIPTION

- Uses the ISTD benchmark dataset with 1,870 triplets: shadowed image, binary shadow mask, and corresponding shadow-free image.
- Images resized to 256×256, with data augmentation (flipping, brightness adjustment) and normalization

Visual inspection for removal:
color consistency,
texture, artifact suppression

ACCURACY

PRECISION

F1 SCORE

RECALL


EVALUATION METRICS

COMPARISON WITH OTHER METHODS

- Present comparative table of performance on ISTD dataset:
 - Show how ShadowDESDNet compares to DSCNet, DSNet, MTMTNet, FDRNet, SDCNet, MSADNet, and DESDNet.

Method	Accuracy	Precision	Recall	F1 Score
DSCNet	97.34%	99.10%	94.84%	96.79%
DSNet	97.54%	99.35%	88.56%	93.63%
MTMTNet	97.70%	99.25%	88.43%	93.35%
FDRNet	97.83%	99.85%	88.95%	93.94%
SDCNet	97.89%	98.80%	90.60%	94.46%
MSADNet	97.87%	98.82%	90.59%	94.07%
DESDNet	98.49%	99.52%	91.88%	94.07%
ShadowDESDNet	93.72%	91.45%	92.18%	91.81%

RESULT



Metric	Score
Accuracy	93.72%
Precision	91.45%
Recall	92.18%
F1 Score	91.81%

RESULT DISCUSSION

- The method achieves 93.72% accuracy and 91.81% F1 score on ISTD.
- Qualitative results show accurate boundary detection, effective handling of soft/partial shadows, and artifact-free, natural-looking outputs.

IMPROVEMENTS


- Video extension: Adapt the framework for video by adding temporal consistency, ensuring stable and coherent shadow detection and removal across frames.
- Real-time & edge deployment: Optimize the model to run efficiently on resource-limited devices, enabling fast and practical use in real-world applications.
- Uncertainty & adaptive attention: Integrate uncertainty estimation and dynamic attention mechanisms to improve robustness and handle varying lighting conditions automatically.

CONCLUSION

We presented a two-stage deep learning framework for robust shadow detection and removal in natural images. Key contributions include:

- Simplified architecture using ResNeXt-50 with a Dynamic Attention Module (DAM) for precise shadow localization, eliminating complex multi-stage training.
- Efficient feature refinement via DAM, enhancing boundary accuracy while suppressing background noise.
- Lightweight encoder-decoder network for artifact-free shadow removal, balancing computational efficiency and performance.

Evaluations on the ISTD dataset demonstrate strong results (93.72% accuracy, 91.81% F1-score) and robust handling of soft shadows, partial occlusions, and complex boundaries. Qualitative outcomes confirm natural texture/illumination preservation, validating the framework's practicality for real-world applications. Future work will extend the method to video and edge-device deployment.



REFERENCES

- [1] Z. Zheng, X. Mei, H. Wang, et al., "Distraction-aware shadow detection," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2019, pp. 5168–5177.
- [2] B. Du, L. Wang, and S. Xu, "Distraction-Aware Edge Enhancement for Shadow Detection in Remote Sensing Images," IEEE Geoscience and Remote Sensing Letters.
- [3] Y. Chen, X. Liang, Y. Zhan, et al., "A multi-task mean teacher for semi supervised shadow detection," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2020, pp. 5611–5620.
- [4] X. Liu, Z. Chen, Y. Zhang, et al., "A shadow detection algorithm based on multiscale spatial attention mechanism for aerial remote sensing images," IEEE Geoscience and Remote Sensing Letters, vol. 19, 2022, Art. no. 8700911.

- [5] Y. Chen, W. Sun, et al., "Slice-to-slice context transfer and uncertain region calibration network for shadow detection in remote sensing imagery," *ISPRS J. Photogramm. Remote Sens.*, vol. 203, pp. 12–23, Sep. 2023.
- [6] X. Hu, L. Zhu, C.-W. Fu, et al., "Direction-aware spatial context features for shadow detection and removal," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 42, no. 11, pp. 2795–2808, 2020.
- [7] L. Zhu, X. Hu, and M.-M. Cheng, "Bidirectional feature pyramid network with recurrent attention residual modules for shadow detection," in *Proc. Eur. Conf. Comput. Vis. (ECCV)*, 2018, pp. 121–136.
- [8] Y. Sun, Z. Wei, et al., "Adaptive illumination mapping for shadow detection in raw images," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, 2023.

THANK YOU