```
#include <iostream>
using namespace std;

class Node {
public:
    int data;
    Node* next;


    Node(int value) {
        data = value;
        next = NULL;
    }
};

class Stack {
private:
    Node* top;
public:

    Stack() {
        top = NULL;
    }

    bool isEmpty() {
        return top == NULL;
    }

    void push(int value) {
        Node* newNode = new Node(value);
        newNode->next = top;


        top = newNode;
        cout << value << "\n";
    }


    int pop() {

        if (isEmpty()) {
            cout << "Cannot pop from an empty stack.\n";
            return -1;
        }

        Node* temp = top;
        int poppedValue = top->data;
        top = top->next;
```

```
        delete temp;

        return poppedValue;
    }

    int peek() {
        if (isEmpty()) {
            cout << "Stack is empty.\n";
            return -1;
        }
        return top->data;
    }

    ~Stack() {
        while (!isEmpty()) {
            pop();
        }
    }
};


int main() {
    Stack s;
    s.push(22);
    s.push(18);
    s.push(55);
    s.push(70);

    cout << "Top element: " << s.peek() << "\n\n";

    cout << s.pop() << "\n";
    cout << s.pop() << "\n";

    cout << "Top element after pops: " << s.peek() << "\n\n";


    cout << s.pop() << "\n";

    s.pop();

    return 0;
}
//[Running] cd "c:\Users\STUDENT\Desktop\manasi kulkarni 209\" && g++
stackusing_linklist.cpp -o stackusing_linklist && "c:\Users\STUDENT\Desktop\manasi
kulkarni 209\"stackusing_linklist
//22
//18
//55
```

```
//70
//Top element: 70

//70
//55
//Top element after pops: 18

//18

//[Done] exited with code=0 in 0.347 seconds
```