

Configurations

- ☐ install : pip install djangorestframework
- ☐ create serializers.py:

serializers.py

```
# serializers.py

from rest_framework import serializers
from .models import TweetModel

class TweetSerializer(serializers.ModelSerializer):
    class Meta:
        model = TweetModel
        fields = ['id', 'content', 'likes']

    def get_likes(self, obj):
        return obj.likes.count()

    def validate_content(self, value):
        if len(value)>MAX_TWEET_LENGTH:
            raise serializers.ValidationError("This tweet is too long")
        return value
```

- ☐ You can add custom fields with @property decorator in model class.
 - ☐ We don't need to create fields for the properties as class variables.
 - ☐ Just add them to fields list.
- ☐ To rename field name in json sent by serializer, add argument source='old_name'

```
class TweetSerializer(serializers.ModelSerializer):
    likes = serializers.SerializerMethodField(read_only=True)
    og_tweet = TweetCreateSerializer(read_only=True)

    class Meta:
        model = Tweet
        fields = ['id', 'content', 'likes', 'is_retweet', "parent"]

    def get_likes(self, obj):
        return obj.likes.count()
```

views.py

```
# views.py

from rest_framework.response import Response
from rest_framework.decorators import api_view, permission_classes
```

```

from rest_framework.permissions import IsAuthenticated
from .serializer import TweetSerializer
from .model import TweetModel

@api_view(['POST']) # Only allows post request
@permission_classes([IsAuthenticated]) # This should be below of api_view,
else it gives some internal error.
def tweet_create_view(request, *args, **kwargs):
    serializer = TweetSerializer(data=request.POST)
    if serializer.is_valid(raise_exception=True):
        serializer.save(user=request.user)
        return Response(serializer.data, status=201)
    return Response({}, status=400) # This is not needed because of
raise_exception=True

@api_view(['GET'])
def tweet_list_view(request, *args, **kwargs):
    qs = TweetModel.objects.all()
    serializer = TweetSerializer(qs, many=True)
    return Response(serializer.data, status=200)

@api_view(['GET'])
def tweet_detail_view(request, tweet_id, *args, **kwargs):
    qs = TweetModel.objects.filter(id=tweet_id)
    if not qs.exists():
        return Response({'message': 'Tweet not found'}, status=404)
    serializer = TweetSerializer(qs.first())
    return Response(serializer.data, status=200)

@api_view(['DELETE', 'POST'])
@permission_classes([IsAuthenticated])
def tweet_delete_view(request, tweet_id, *args, **kwargs):
    qs = TweetModel.objects.filter(id=tweet_id)
    if not qs.exists():
        return Response({'message': 'Tweet not found', status=404})
    if not qs.filter

```

- ❑ To change the types of Authentication that give access to views,
 - ❑ Create REST_FRAMEWORK dictionary with 'DEFAULT_AUTHENTICATION_CLASSES':['list', 'of', 'classes', 'from', 'documentation']
 - ❑ Add permission_classes decorator and pass the list of permission classes from from rest_framework.permissions.

settings.py

- ❑ add to INSTALLED_APPS: 'rest_framework'

```

REST_FRAMEWORK = {
    'DEFAULT_AUTHENTICATION_CLASSES': [
        # 'rest_framework.authentication.BasicAuthentication',

```

```

        'rest_framework.authentication.SessionAuthentication',
    ],
    'DEFAULT_RENDERER_CLASSES': [
        'rest_framework.renderers.JSONRenderer',
        # 'rest_framework.renderers.BrowsableAPIRenderer',
    ]
}

```

JS

- ☐ xhr.setRequestHeader('Content-Type', 'applications/json')
- ☐ CSRF javascript
 - []

```

function getCookie(name) {
    let cookieValue = null;
    if (document.cookie && document.cookie !== '') {
        const cookies = document.cookie.split(';');
        for (let i = 0; i < cookies.length; i++) {
            const cookie = cookies[i].trim();
            // Does this cookie string begin with the name we want?
            if (cookie.substring(0, name.length + 1) === (name +
'=')) {
                cookieValue =
decodeURIComponent(cookie.substring(name.length + 1));
                break;
            }
        }
    }
    return cookieValue;
}
const csrftoken = getCookie('csrftoken');

```

- ☐ xhr.setRequestHeader('X-CSRFToken', csrftoken)

Adding Like functionality

```

# models.py
class TweetLikeModel(models.Model):
    user = models.ForeignKey(User, on_delete=CASCADE)
    tweet = models.ForeignKey('TweetModel', on_delete=CASCADE)
    timestamp = models.DateTimeField(auto_add_now=True)

class TweetModel(models.Model):
    likes = models.ManyToManyField(User, related_name='tweet_user',
blank=True, through=TweetLike)

# If you don't need timestamp, you can remove through attribute and
associate them directly.

```

```

# serializers.py
class TweetActionSerializer(serializers.Serializer):
    id = serializers.IntegerField()
    action = serializers.CharField()

    def validate_action(self, value):
        value = value.lower().strip()
        if not value in TWEET_ACTION_OPTIONS:
            raise serializers.ValidationError(f"Actions can only be:
{*TWEET_ACTION_OPTIONS}")
        return value

# views.py
@api_view(['POST'])
@permission_classes([IsAuthenticated]) # see django_rest_framework.md to
refer this.
def tweet_action_view(request, tweet_id, *args, **kwargs):
    qs = TweetModel.filter(id=tweet_id)
    if not qs.exists():
        return Response({'message', 'Tweet not found'}, status=404)

    serializer = TweetActionSerializer(obj)
    like, unlike, retweet = 'like', 'unlike', 'retweet'

    if serializer.is_valid(raise_exception=True):
        data = serializer.validated_data
        action = data.get('action')
        if action == like:
            obj.likes.add(request.user)
        elif action == unlike:
            obj.likes.remove(request.user)
        elif action == retweet:
            # Something needs to be done.
            pass
        else:
            assert False, 'Invalid action has been validated by
TweetActionValidator !!!😬'
        return Response({'message': 'Tweet action successful'}, status=200)
    return Response({'message': 'Invalid Tweet'}, status=400)
    ...

# admin.py
class TweetLikeAdmin(admin.TabularInline):
    model = TweetLike

admin.site.register(TweetAdmin, TweetLikeAdmin)

```

- ☐ When using Content-Type: application/json, use request.data instead of request.POST.
- ☐ Logic for retweeting
 - ☐ Add a self linking ForeignKey in TweetModel called parent.

- ☐ When someone retweets, create new tweet and its parent attribute to the original tweet.
- ☐ Make the TweetSerializer readonly and copy original one to TweetCreateSerializer.

```
class TweetSerializer(serializers.ModelSerializer):
    likes = serializers.SerializerMethodField(read_only=True)
    content = serializers.SerializerMethodField(read_only=True)
    class Meta:
        model = TweetModel
        fields = ['id', 'content', 'likes']
    def get_likes(self, obj):
        return obj.likes.count()
```

tests.py

- ☐ Create a user and add a tweet in it in setup function (from models itself).
- ☐ Refer ApiClient in django-rest-framework documentation -> testing.