Homework 3: Microarchitecture Reverse Engineering Across Machines

Manas Reddy Thumma (mrthumm2)
ECE 492/592, Fall 2026, Track B

GitHub: *[add link]*
Overleaf: *[add link]*

Selected questions (115 points)

Q	Exercise	Points
1	Confirm the processor is pipelined	10
2	Confirm out-of-order execution	10
3	Confirm branch prediction	10
15	Estimate pipeline depth	10
14	Estimate instructions fetched per cycle	10
4	Reverse engineer the ROB size	30
5	Reverse engineer the physical register file size and class	35
	Total	**115**

Machines. Artemisia (Intel Xeon Gold 5420+, Sapphire Rapids) and Crux (Intel Core i7-9700, Coffee Lake Refresh). **Enclave.** Intel SGX on both machines, with native and enclave runs of every experiment. **AI use.** Claude Chat helped with the original plan, and Claude Code was used throughout, including running experiments and drafting this report. See Section 10 and `AI_LOG.md`.

Summary of measured results

		Crux		Artemisia	
Q	Measure	Native	SGX	Native	SGX
1	Independent `add` IPC (dependent: 1.00)	3.99	4.02	4.73	4.72
2	Cycles for 1 miss	360	615	361	415
2	2 independent misses with consumers, in misses	1.02	1.14	1.04	1.08
3	Random pattern, cycles per branch	14.4	14.3	14.1	14.2
15	Cycles per mispredict	19.4	19.0	22.3	22.2
14	Instructions per cycle	4	4	about 6	about 6
14	Legacy fetch, bytes per cycle	16	16	$\geq$29	$\geq$29
4	ROB entries	224–225	224–225	499–500	499–500
5	Free integer registers	145	142	215	215
5	Free vector registers	148	147	244	263
5	`mix` knee (separate classes)	208	208	427	429

Both processors are pipelined, execute out of order, predict branches and have separate integer and vector register files. All conclusions come from timing alone. PMU counters were used only afterwards, as a check. The main findings: Artemisia's ROB is about twice the size of Crux's, and the enclave leaves core structures essentially unchanged on both machines. Its memory cost differs sharply: a miss costs about 70% more in the Crux enclave and 15% more in the Artemisia enclave.

1 Machines and setup

	Crux	Artemisia
CPU	Intel Core i7-9700 @ 3.00 GHz	Intel Xeon Gold 5420+
Microarchitecture	Coffee Lake Refresh	Sapphire Rapids (Golden Cove cores)
Family / model / stepping	6 / 158 / 13	6 / 143 / 8
Topology	1 socket, 8 cores, no SMT	2 sockets × 28 cores × 2 threads
Last-level cache	12 MiB	52.5 MiB per socket
OS	Ubuntu 24.04.5	el9
Kernel	6.8.0-88 native, 6.8.0-147 SGX	6.17.8 (el9.elrepo)
Compiler / Python	GCC 13.3.0 / 3.12.3	GCC 11.5.0 / 3.9.25
AVX-512	No	Yes
SGX generation	SGX1 only (CPUID leaf 0x12)	`rdtsc` permitted in enclaves
Usable EPC	93 MiB	Roughly 1 GiB per socket
Intel SGX SDK	2.30	2.23
PMU access	Blocked by default (paranoid level 4); set to 2 with sudo for validation only	User-space counting available

Measurement method. Every experiment runs through one shared harness with the same kernels on both machines. It pins to one core with `taskset` (CPU 2) and reports how busy the SMT sibling is, where one exists. Times come from `rdtsc`. To convert ticks to core cycles, each run times a long dependent `add` chain at 1 add per cycle, and checks the result against a dependent `imul` chain, which should measure 3 cycles. A second calibration at the end of the run records clock drift. Coarse sweeps use 11 trials and step-1 zooms use 21. Tables report medians, and plots show min–max bands.

Enclave platform and configuration. Intel SGX SDK in hardware mode, debug enclave, signed with a self-generated key (possible because both platforms have flexible launch control). The kernels, the timer reads, the calibration and the test data all run inside the enclave, and the host only handles setup and output. An ECALL costs about 16k cycles on Artemisia and is never inside a timed region. The heap is static (no EDMM), with 4 KB EPC pages; native runs also use 4 KB pages so the two are comparable. The LVI mitigation is off because its `lfence`s would serialize the loads these experiments measure, so a production enclave could behave differently. Native and enclave builds share one driver and the same kernels.

Crux enclave adaptations. Crux needed two changes that Artemisia did not, both selected at run time or by run settings rather than in the kernels:

- **Timer.** `rdtsc` crashes an enclave on Crux, which has SGX1 only. Instead, a host thread on another core (CPU 7) continuously publishes the TSC to shared memory, and the enclave reads that value immediately before and after each kernel. The enclave does not exit during a timed region. Runs last millions of cycles, so the timer's coarser resolution does not matter. Calibration still measures `imul` latency near 3 cycles (2.99–3.16).
- **Memory.** Crux's EPC is only 93 MiB, so the two 128 MiB chains used elsewhere would force enclave paging. Its enclave runs use two 40 MiB chains with an 84 MiB heap. Run times were stable with no sign of paging.

Limits on the Crux native-vs-enclave comparison. Three things differ between these runs besides the enclave itself, so absolute times are not strictly like-for-like: the kernel (6.8.0-88 native, 6.8.0-147 enclave, because the machine was updated when SGX was enabled and native was not rerun); the chain size (128 vs. 40 MiB); and the active timer thread, which keeps a second core busy. The clock calibrates to about 1.52–1.56 cycles per TSC tick in the enclave runs and usually 1.56 natively. Times are converted with each run's own calibration, so knee positions and ratios should be little affected.

Access limitations. PMU counters are not visible inside the enclave, so all PMU checks are native. Crux has no AVX-512, so the Q5 `ymm16-31` test cannot run there.

2 Q1: Is the processor pipelined?

Method. Run the same instruction as one dependency chain and as 8 independent chains. A dependent chain cannot exceed 1/latency instructions per cycle, so an independent version beating that means several instructions are in flight at once. `imul` is the cleanest test: it has 3-cycle latency and a single port, so 1 IPC when independent means a new multiply enters every cycle while older ones are still in progress.

```
add_dep:    .rept 1000              add_indep: .rept 125
            add %rdx, %rax                     add %rdx, %rax
            .endr                              add %rdx, %rbx    ... 8 registers
                                               .endr
```




Figure 1: Q1: IPC of dependent and independent chains (median, min–max, 11 trials).

	Crux			Artemisia		
Variant	Native	PMU	SGX	Native	PMU	SGX
`add_dep`	1.000	1.001	0.994	1.000	1.001	1.001
`add_indep`	3.993	4.029	4.022	4.726	4.721	4.722
`imul_dep`	0.333	0.334	0.334	0.333	0.331	0.333
`imul_indep`	1.000	1.004	1.008	1.000	1.023	1.001

Conclusion. Both processors are pipelined and superscalar. On both, independent `imul`s run at three times the rate of dependent ones. Crux's independent `add`s reach 3.99 IPC and Artemisia's reach 4.73. **Enclave:** no meaningful change on either machine, as expected for a core property. Crux's enclave values sit within about 1% of native, and the 4.02 is slightly above 4, probably because the clock moved a little between calibration and measurement. **PMU check:** agrees within 2.3%. This also validates the cycle calibration, which is otherwise circular because `add_dep` equals 1 by construction.

3 Q2: Does the processor execute out of order?

Method. Two pointer chases run over random cycles of 128 MiB each (40 MiB in the Crux enclave), much larger than either LLC, so loads miss to DRAM. Two loads on the same chain must take 2 misses. Two loads on independent chains take about 1 miss if they overlap. Back-to-back overlap alone could also happen on an in-order core with a non-blocking cache, so the key variant places 4 instructions that consume load A's result before load B. An in-order core would stall at those consumers, and only an out-of-order core can issue B past them.

```
1:  mov (%rax), %rax    # load A (chain p): misses
    lea 1(%rax), %r8    # consumers of A: an in-order core stalls here
    add %r8, %r9
    add %r9, %r10
    add %r10, %r11
    mov (%rcx), %rcx    # load B (chain q): independent miss
    dec %rdx
    jnz 1b
```




Figure 2: Q2: cycles per iteration by variant (median, min–max, 11 trials).

	Crux native		Crux SGX		Artemisia native		Artemisia SGX	
Variant	Cycles	Misses	Cycles	Misses	Cycles	Misses	Cycles	Misses
1 miss	360	1.00	615	1.00	361	1.00	415	1.00
2 dependent	705	1.96	1223	1.99	722	2.00	808	1.94
2 indep., with consumers	366	1.02	699	1.14	377	1.04	451	1.08
2 independent	365	1.01	697	1.13	366	1.01	434	1.04
2 indep., 64 NOPs	368	1.02	691	1.12	367	1.02	436	1.05
2 indep., 128 NOPs	392	1.09	731	1.19	370	1.03	440	1.06
2 indep., 192 NOPs	422	1.17	759	1.23	376	1.04	448	1.08

Conclusion. Both processors execute out of order: with consumers in between, two misses still cost about one. **Machine difference:** 192 NOPs cost Crux more (1.17 misses vs. 1.04), which fits a narrower core taking longer to get through the filler and a ROB of 224 sitting close to that filler size. **Enclave:** the conclusion is the same on both machines, since two misses still cost far less than two. A miss costs 15% more on Artemisia (415 vs. 361 cycles) and about 70% more on Crux (615 vs. 360), consistent with encrypted EPC memory. Crux's smaller enclave chains should, if anything, lower its miss cost, so the gap is probably not an artifact of chain size. Overlap is also weaker in the Crux enclave (1.13 misses vs. 1.01). The much larger cost may reflect Crux's older client SGX memory protection, but I did not test that. **PMU check:** not performed.

4 Q3: Does the processor predict branches?

Method. A loop executes one conditional branch per array element, driven by the element's value. Both paths do one `add`, so patterns differ only in predictability. If a random 50/50 pattern costs far more than learnable patterns with the same direction mix, the processor is speculating on direction. The branch is in assembly so the compiler cannot turn it into a `cmov`. Each pattern array is 1 MiB, trained with one pass, then timed over 4 passes.

```
.Lloop:  movzbl (%rdi,%rcx), %r8d
         test   %r8d, %r8d
         jnz    .Ltaken          # <-- branch under test
         add    %r10, %r9
         jmp    .Ljoin
.Ltaken: add    %r10, %rax
.Ljoin:  inc    %rcx
         cmp    %rsi, %rcx
         jb     .Lloop
```




Figure 3: Q3: cycles per branch by pattern (median, min–max, 11 trials).

	Crux				Artemisia		
Pattern	Native	PMU	Miss rate	SGX	Native	PMU	SGX
`taken`	3.60	3.51	0.00000	3.59	2.01	1.85	2.30
`nottaken`	3.77	4.04	0.00000	3.69	2.00	2.05	2.00
`alt`	5.16	4.99	0.00001	5.01	3.00	2.66	3.00
`period:16`	4.01	4.33	0.00000	4.01	2.95	3.03	3.07
`period:64`	4.71	–	–	4.63	3.33	–	3.33
`period:256`	7.13	–	–	7.15	3.42	–	3.43
`period:1024`	11.30	–	–	11.18	3.50	–	3.49
`period:4096`	14.16	–	–	14.24	3.55	–	3.55
`period:16384`	14.41	–	–	14.18	12.18	–	12.83
`period:65536`	14.35	–	–	14.19	13.68	–	13.62
`random`	14.43	14.24	0.49994	14.25	14.14	14.28	14.16

Conclusion. Both processors predict branches. Random costs about 9–11 cycles more per branch than learnable patterns with the same mix. **Machine difference:** Artemisia learns patterns up to period 4096, while Crux starts degrading by period 256 and reaches random-level cost at period 4096. This is consistent with a smaller history or table capacity on Crux, though I did not isolate which. **Enclave:** identical within noise on both machines, including the Crux no-miss costs and where its pattern learning falls off. **PMU check:** the slow pattern misses at 0.5 and the fast ones at essentially 0, on both machines (Artemisia's `random` miss rate is 0.49967). **Open question:** on Crux, no-miss patterns still cost 3.5–5.0 cycles, with `alt` the most expensive. PMU shows this is not misprediction, so the cause is probably in the front end. I did not measure the cause. The JCC erratum microcode mitigation is one candidate, but this is untested.

5 Q15: How deep is the pipeline?

Method (timing only). A mispredict discards fetched work, and the front end must refill. Time lost per mispredict therefore estimates the distance from the front end to branch resolution. It is a *lower bound* on depth, not a stage count, because it excludes stages after execute and overlap can hide part of it. The difficulty without counters is knowing the number of mispredicts. A fair coin solves this: for independent 50/50 outcomes, every predictor misses half the time in expectation, because nothing it can observe helps. With a perfectly predicted pattern as the baseline:

```
P   = (t["bias:0.50"] - t["alt"]) / 0.5          # same 50/50 path mix, no mispredicts
P16 = (t["bias:0.50"] - t["period:16"]) / 0.5    # alternative baseline, shows sensitivity
```

Dividing by $\min(F, 1-F)$ at other taken probabilities F gives only an upper bound on P, since real predictors miss more than that on biased noise.




Figure 4: Q15, timing only: left, cost against taken probability; right, miss rate implied by timing.

Cycles per mispredict	Crux Native	Crux SGX	Artemisia Native	Artemisia SGX
Timing: fair coin vs. `alt`	**19.4**	**19.0**	**22.3**	**22.2**
Timing: fair coin vs. `period:16`	20.6	20.3	22.5	22.6
PMU: `random` vs. `alt`, measured miss rate	18.5	–	23.2	–
PMU: `random` vs. `period:16`, measured miss rate	19.8	–	22.5	–
PMU: `random` vs. mean of `taken`, `nottaken`, measured rate	20.9	–	24.7	–
PMU: slope of cycles against measured miss rate, over `bias:F`	21.6	–	24.0	–

Conclusion. Crux loses about 19–21 cycles per mispredict and Artemisia about 22–23, so Crux has the shorter refill path. These are lower bounds on fetch-to-execute depth. **Enclave:** unchanged on both machines (Crux 19.0 vs. 19.4, Artemisia 22.2 vs. 22.3). **PMU check:** the method's assumptions hold, with `random` missing at 0.4999 and `alt` at about 0 on Crux. PMU estimates span 18.5–21.6 on Crux and 22.5–24.7 on Artemisia, and timing-implied miss rates are within 0.022 of the PMU on Crux and 0.013 on Artemisia. The remaining uncertainty is the baseline, since no-miss patterns differ in cost. Figure 5 shows the validation. Its per-F values for Crux read low at small F (down to 10.7) because that calculation's baseline rises toward `alt`, which is expensive on Crux; those values should not be taken as the penalty.




Figure 5: Q15, PMU validation only: measured miss rate, and penalty implied by the assumed and measured rates.

6 Q14: How many instructions are fetched per cycle?

Method. Long unrolled blocks of NOPs of each length $L = 1$–15 bytes leave the front end as the only limit. With short NOPs the limit is instructions per cycle, so IPC flattens. With long NOPs the limit is bytes per cycle, so bytes per cycle flattens and IPC falls as $1/L$. The block size K selects the path: a small K runs from the micro-op cache, which measures delivery rather than fetch, and a larger K forces legacy fetch and decode.

```
nop_4_4096:
1:  .rept 4096
    .byte 0x0f, 0x1f, 0x40, 0x00     # nopl 0x0(%rax)
    .endr
    dec %rdi
    jnz 1b
    ret
```




Figure 6: Q14: Crux native (top), Crux SGX (middle) and Artemisia native (bottom). The Artemisia SGX figure is effectively identical to native and is in the repository.

	Crux native	Crux SGX	Artemisia (native, SGX)
IPC ceiling	4.0	4.0	about 6.0
Legacy fetch ($K = 6144$)	16 B/cycle	16 B/cycle	$\geq$29 B/cycle ($L = 5$)
Micro-op cache ($K = 256$)	up to 60 B/cycle	up to 60 B/cycle	up to 63 B/cycle
Largest footprint ($K = 16384$, $L \geq 10$)	about 13 B/cycle	about 16 B/cycle	12.8 B/cycle

Conclusion. Crux fetches and decodes about 4 instructions per cycle with a clean 16 B/cycle legacy limit. Artemisia sustains about 6 per cycle with a legacy rate of at least 29 B/cycle; its ceiling was not reached before the footprint passed 32 KiB. **Machine difference:** Artemisia falls to 12.8 B/cycle as soon as the footprint passes 32 KiB. Crux instead holds about 16 B/cycle to roughly 150 KiB natively before dropping, and I did not determine why. **Enclave:** the ceilings match native on both machines. The one difference is on Crux at the largest footprints, which hold about 16 B/cycle in the enclave but drop to about 13 natively. I can't attribute that to the enclave, since the kernel and timer thread also differ between those runs. **PMU check:** whole-program totals only, which cannot confirm the per-path limits, so this is not treated as validation. **Open item:** on Crux, 3-byte NOPs reach only about 3.3 IPC with legacy decode, below the neighbouring lengths. This is unexplained.

7 Q4: How large is the ROB?

Method. This follows Henry Wong's technique ("Measuring Reorder Buffer Capacity," 2013), extending Q2. A missing load A blocks retirement at the head of the ROB. An independent load B can overlap with it only if B is already allocated, which requires $N + 2 \leq$ ROB size. Below that limit an iteration costs about 1 miss, and above it about 2. NOPs are the filler because they occupy a ROB entry but write no register and need no scheduler or load/store entry, so the ROB fills first. I sweep coarsely (step 8), then at step 1 around each machine's own knee.

```
1:  mov (%rax), %rax    # miss A
    nop                 # ... N NOPs
    mov (%rcx), %rcx    # miss B (independent chain)
    nop                 # ... N NOPs
    dec %rdx
    jnz 1b
```




Figure 7: Q4: step-1 sweep around each machine's knee (21 trials).

	Crux native	Crux SGX	Artemisia native	Artemisia SGX
Overlap holds up to	about $N = 218$	about $N = 218$	about $N = 492$	about $N = 492$
Partial ramp	219–222	219–222	493–497	493–497
Fully serialized from	$N =$ **223**	$N =$ **223**	$N =$ **498**	$N =$ **498**
Per-trial crossing (of 21)	223 in 21	223 in 21	497–498 in 18	497–498 in 21
Cycles below / at knee	550 / 750	965 / 1327	617 / 764	741 / 923
Measured ROB	**224–225**	**224–225**	**499–500**	**499–500**
Published (not measured)	224	224	512	512

Conclusion. ROB is about 224–225 entries on Crux and about 499–500 on Artemisia. The range reflects whether the first serialized N is read as ROB − 1 or ROB − 2. **Machine difference:** Crux matches its published size, while Artemisia measures about 12 entries (2.3%) below its published size. I can't explain this gap from the data, nor the short ramp before each knee. One untested hypothesis is that the previous iteration's load B can still be at the ROB head when load A issues. **Enclave:** the knee does not move on either machine, even with Crux's smaller chains. Only the plateaus rise, because enclave misses cost more. **PMU check:** not performed.

8 Q5: How large is the physical register file, and of which class?

Method. This uses the Q4 loop, but every filler instruction writes a register, and that write holds a physical register until retirement. If registers run out before the ROB does, the knee moves to a smaller N, giving the number of *free* registers of that class. `int` uses `add r,r` and `ymm` uses `vpaddd`. Zeroing idioms and `mov r,r` are avoided, because rename can handle them without allocating a register. `mix` alternates the two: with one shared file, the knee would stay near the smaller single-class knee; with separate files, each fills at half the rate, so the knee moves out until twice the integer knee or the ROB limits it. Controls vary flag-writing, chains and immediates.

```
1:  mov (%rax), %rax    # miss A
    add %r8, %r8        # int filler: each writes a fresh physical register
    add %r9, %r9
    vpaddd %ymm0, %ymm0, %ymm1   # ymm filler; mix alternates add and vpaddd
    mov (%rcx), %rcx    # miss B
    ...
```




Figure 8: Q5: step-1 sweeps (21 trials). Labels give the halfway crossing for each filler.

Filler	Writes	Crux		Artemisia	
		Native	SGX	Native	SGX
`nop` (Q4)	Nothing	223	223	498	498
`add r,r` (`int`)	GPR + flags	**145**	**142**	**215**	**215**
`andn`	GPR + flags	143	140	213	212
`shlx`	GPR only	143	141	208	208
`lea (r,r)`	GPR only	138	137	213	212
`lea 1(r)`	GPR only, reg+imm	142	139	No knee	No knee
`lea 1(rbp)`	GPR only, reg+imm	142	139	No knee	No knee
`vpaddd ymm`	Vector	**148**	**147**	**244**	**263**
`mix`	Both, alternating	**208**	**208**	**427**	**429**
Published integer PRF (not measured)		180		280	
Published vector PRF (not measured)		168		about 332	

Conclusions.

- **Register sizes:** about 145 free integer and 148 free vector registers on Crux, and about 215 and 244 on Artemisia. These are free counts, so the total is a lower bound: committed architectural state, at least 16 GPRs, occupies entries too.
- **Register class:** integer and vector are separate files on both machines, since `mix` runs well past both single-class knees. On Artemisia it reaches about twice the integer knee. On Crux twice the integer knee (290) exceeds the ROB, so the ROB should cap it.
- **Flags:** not a separate limit, since flag-writing and flag-free fillers give the same knee.
- **Machine difference:** on Artemisia, `lea` with a register plus immediate shows no register limit and runs to the ROB, which suggests rename handles it without allocating a register. On Crux the same instruction hits the normal limit.

Enclave on Crux. All knees stay close to native. The integer knees sit 1–3 lower, the vector knee moves from 148 to 147, and `mix` stays at 208. Crux has no AVX-512 and so no `ymm16-31` state, and the Artemisia vector shift described next does not appear here.

Enclave on Artemisia. Integer and `mix` knees are unchanged. The vector knee is 263 in the enclave against 244 natively. This appears to be architectural state rather than a hardware effect: writing `ymm16-31` first moves the enclave's median knee to 244 and changes nothing natively. In-use bits from `xgetbv(1)` show that glibc leaves those registers in use in a native process, and the enclave's libc does not. The matching native sweep with glibc's AVX-512 paths disabled gave 255 in one noisy run, so that step is unconfirmed.

Open questions. On Crux, `mix` at 208 is about 15 short of the ROB knee (223), in both native and enclave runs, and I have no explanation. The separate-files conclusion does not depend on it. The knees also sit below published totals by more than 16 architectural registers (Crux: 145 + 16 = 161 vs. 180; Artemisia: 215 + 16 = 231 vs. 280, where an idle SMT sibling's state could account for part of the gap). **PMU check:** not performed; the stall-event names vary by generation.

9 Challenges and limitations

- **SGX on Artemisia and tooling.** SGX was first disabled in BIOS, and then access needed the `sgx` group. Gramine's install was incomplete, so the enclave backend was built on the Intel SGX SDK instead, after confirming `rdtsc` works natively inside the enclave with the same resolution (calibration within 0.6%).
- **SGX on Crux.** SGX was initially off in firmware, so the native runs came first. Once enabled, enclaves failed in sequence: the SDK's runtime library is only a stub without the Platform Software libraries, the first ECALL then crashed because `rdtsc` is illegal in an SGX1 enclave, and the default chains were about three times the 93 MiB EPC. The adaptations are in Section 1. The SDK and those libraries were placed in my home directory, with no system-wide install. The Artemisia enclave results were not rerun with the new timer, since its enclaves can use `rdtsc` directly.

- **No-SMT crash.** The first Crux run produced no data: with no sibling, the harness's sibling lookup matched nothing, and `set -e` with `pipefail` ended each script before the benchmark ran. This was fixed in the shared harness and doesn't affect Artemisia's results.
- **Clock changes on Crux.** The calibrated clock usually measured about 4.68 GHz but fell as low as about 4.48 GHz, consistent with turbo limits as other cores wake (not confirmed). In the first run this distorted Q1 and Q2 (`add_dep` read 0.957), so both were rerun. The final Q1 and Q2 data show drift of at most 0.02%. Occasional dips remain in the min–max bands.
- **Biased-coin analysis.** The first Q15 analysis treated $\min(F, 1 - F)$ as the miss rate, so the "penalty" drifted from 43 to 22 cycles. These values are upper bounds, and the method now uses only the fair coin.
- **Bimodal timing.** On Artemisia, `taken` and `nottaken` flip between about 2.0 and 3.2 cycles from trial to trial, for an unknown reason. It affects small-F estimates but not the Q15 result. Other users' load also caused whole-trial slowdowns, visible in the bands but not the medians.
- **Questions not attempted.** TLB (6–9), BTB (10–12), predictor type (13) and SMT sharing (16) were not selected.

10 AI use

Track B, with AI use disclosed. Claude Chat (Anthropic) helped me with the original plan, including the question selection. I then used Claude Code (Anthropic) in the VS Code extension, with Claude Opus 5.5 for the logged sessions. It wrote most of the harness, ran the experiments and PMU checks on both machines from my sessions, helped analyse results, and drafted this report. I made the final choice of questions and plan, and the decisions recorded in `AI_LOG.md`, which is the full log and is included in the submission.

11 Reproduction

Requirements: `gcc`, `make`, `python3` with `numpy` and `matplotlib`. For enclave runs: the Intel SGX SDK in `/opt/intel/sgxsdk` or set through `SGX_SDK`, `openssl` and a session in the `sgx` group.

```
common/preflight.sh 2        # check tools, CPU features, the pin CPU, LLC, SGX, perf
common/run_all.sh 2          # all experiments and zooms, then plots; adds SGX if usable
common/run_sgx1.sh 2 40      # SGX on a small-EPC SGX1 machine (Crux): 40 MiB chains
common/pmu_verify.sh 2       # validation only: needs perf_event_paranoid <= 2
common/plot_all.sh           # figures -> q*/plots/compare/ (all machines overlaid)
common/plot_all.sh crux      # figures -> q*/plots/crux/
```

Timing results are in `q*/results/<machine>/<mode>.csv`, with step-1 sweeps under `zoom/`. PMU results are separate, under `pmu/`, and the validation tables are generated in `report/pmu_tables.md`. Each question's folder has a README with its commands, and `machines/` records each machine's `lscpu` and `cpuinfo`.