

How to setup MongoDB - Four sharded replicas in Windows 10 on Single machine/Laptop

----- USE Following steps sequentially in windows cmd prompt.

1) setup config servers

Open windows cmd prompt

```
cd \  
mkdir data\config1  
mkdir data\config2  
mkdir data\config3  
mkdir data\logs
```

Open multiple windows cmd prompt's as needed to run each of these individually cmd prompt

```
mongod --configsvr --dbpath data/config1 --port 2011 --replSet rs0 --bind_ip localhost  
mongod --configsvr --dbpath data/config2 --port 2012 --replSet rs0 --bind_ip localhost  
mongod --configsvr --dbpath data/config3 --port 2013 --replSet rs0 --bind_ip localhost
```

---connect to config1 server

Open windows cmd prompt

```
mongo --port 2011
```

```
rs.initiate(  
  {  
    _id: "rs0",  
    configsvr: true,  
    members: [  
      { _id : 0, host : "localhost:2011" },  
      { _id : 1, host : "localhost:2012" },  
      { _id : 2, host : "localhost:2013" }  
    ]  
  }  
)
```

2) setup shard1

Open windows cmd prompt

```
cd \  
mkdir data\shard1\rs2
```

```
mkdir data\shard1\rs2
mkdir data\shard1\rs3
```

Open multiple windows cmd prompt's as needed to run each of these individually cmd prompt

```
mongod --shardsvr --replSet shard1rs --port 20010 --dbpath data/shard1/rs1 --bind_ip
localhost
mongod --shardsvr --replSet shard1rs --port 20011 --dbpath data/shard1/rs2 --bind_ip
localhost
mongod --shardsvr --replSet shard1rs --port 20012 --dbpath data/shard1/rs3 --bind_ip
localhost
```

---connect to shard1 host
Open windows cmd prompt

```
mongo --port 20010
```

```
rs.initiate(
{
  _id: "shard1rs",
  members: [
    { _id : 0, host : "localhost:20010" },
    { _id : 1, host : "localhost:20011" },
    { _id : 2, host : "localhost:20012" }
  ]
}
)
```

3) setup shard2

Open windows cmd prompt

```
cd \
mkdir data\shard2\rs2
mkdir data\shard2\rs2
mkdir data\shard2\rs3
```

Open multiple windows cmd prompt's as needed to run each of these individually cmd prompt

```
mongod --shardsvr --replSet shard2rs --port 20013 --dbpath data/shard2/rs1
mongod --shardsvr --replSet shard2rs --port 20014 --dbpath data/shard2/rs2
mongod --shardsvr --replSet shard2rs --port 20015 --dbpath data/shard2/rs3
```

Open windows cmd prompt

```

mongo --port 20013
rs.initiate(
{
  _id: "shard2rs",
  members: [
    { _id : 0, host : "localhost:20013" },
    { _id : 1, host : "localhost:20014" },
    { _id : 2, host : "localhost:20015" }
  ]
}
)

```

4) setup shard3

Open windows cmd prompt

```

cd \
mkdir data\shard3\rs2
mkdir data\shard3\rs2
mkdir data\shard3\rs3

```

Open multiple windows cmd prompt's as needed to run each of these individually cmd prompt

```

mongod --shardsvr --replSet shard3rs --port 20016 --dbpath data/shard3/rs1 --bind_ip
localhost
mongod --shardsvr --replSet shard3rs --port 20017 --dbpath data/shard3/rs2 --bind_ip
localhost
mongod --shardsvr --replSet shard3rs --port 20018 --dbpath data/shard3/rs3 --bind_ip
localhost

```

Open windows cmd prompt

```

mongo --port 20016
rs.initiate(
{
  _id: "shard3rs",
  members: [
    { _id : 0, host : "localhost:20016" },
    { _id : 1, host : "localhost:20017" },
    { _id : 2, host : "localhost:20018" }
  ]
}
)

```

5) setup shard4

Open windows cmd prompt

```
cd \  
mkdir data\shard4\rs2  
mkdir data\shard4\rs2  
mkdir data\shard4\rs3
```

Open multiple windows cmd prompt's as needed to run each of these individually cmd prompt

```
mongod --shardsvr --replSet shard4rs --port 20019 --dbpath data/shard4/rs1 --bind_ip  
localhost  
mongod --shardsvr --replSet shard4rs --port 20020 --dbpath data/shard4/rs2 --bind_ip  
localhost  
mongod --shardsvr --replSet shard4rs --port 20021 --dbpath data/shard4/rs3 --bind_ip  
localhost
```

Open windows cmd prompt

```
mongo --port 20019  
rs.initiate(  
  {  
    _id: "shard4rs",  
    members: [  
      { _id : 0, host : "localhost:20019" },  
      { _id : 1, host : "localhost:20020" },  
      { _id : 2, host : "localhost:20021" }  
    ]  
  }  
)
```

6) setup mongos and add shards

Open windows cmd prompt

```
cd \  
mongos --configdb "rs0/localhost:2011,localhost:2012,localhost:2013" --logpath  
data/logs/log.mongos0 --port 27200
```

--connect to mongos and add shards:

Open windows cmd prompt

```
mongo --port 27200
```

```
mongos> use config
mongos> sh.addShard("shard1rs/localhost:20010")
mongos> sh.addShard("shard2rs/localhost:20013")
mongos> sh.addShard("shard3rs/localhost:20016")
mongos> sh.addShard("shard4rs/localhost:20019")
```

```
mongos> sh.status()
```

```
db.shards.find()
```

7)enable sharding on mongoMart and at collection level

```
use mongoMart
sh.enableSharding("mongoMart")
```

---enable sharding on collection level

```
sh.shardCollection("mongoMart.shop",{ "_id":"hashed" })
```

```
for (var i =1;i<=100;i++) db.shop.insert({x:i})
```

```
mongos> db.shop.find().count()
100
```

verfiy distribution and enjoy:

```
mongos> db.shop.getShardDistribution()
```

connect to each shards primary and verify counts

Create additional collections:

```
sh.shardCollection("mongoMart.restaurants",{ "_id":"hashed" })
```

```
mongoimport --port 27200 --db mongoMart --collection restaurants --file restaurants.json
```

```
2021-05-24T11:32:59.200-0400  connected to: mongod://localhost:27200/
2021-05-24T11:33:02.200-0400  [#.....] mongoMart.restaurants    7.56MB/144MB
(5.3%)
2021-05-24T11:33:05.200-0400  [##.....] mongoMart.restaurants
13.8MB/144MB (9.6%)
2021-05-24T11:33:08.200-0400  [##.....] mongoMart.restaurants
16.1MB/144MB (11.2%)
```

2021-05-24T11:33:11.200-0400 [###.....] mongoMart.restaurants
21.9MB/144MB (15.2%)
2021-05-24T11:33:14.201-0400 [####.....] mongoMart.restaurants
26.9MB/144MB (18.7%)
2021-05-24T11:33:17.200-0400 [#####.....] mongoMart.restaurants
34.7MB/144MB (24.1%)
2021-05-24T11:33:20.201-0400 [#####.....] mongoMart.restaurants
42.6MB/144MB (29.7%)
2021-05-24T11:33:23.201-0400 [#####.....] mongoMart.restaurants
50.0MB/144MB (34.8%)
2021-05-24T11:33:26.200-0400 [#####.....] mongoMart.restaurants
55.0MB/144MB (38.3%)
2021-05-24T11:33:29.200-0400 [#####.....] mongoMart.restaurants
61.5MB/144MB (42.8%)
2021-05-24T11:33:32.201-0400 [#####.....] mongoMart.restaurants
67.0MB/144MB (46.6%)
2021-05-24T11:33:35.200-0400 [#####.....] mongoMart.restaurants
74.4MB/144MB (51.8%)
2021-05-24T11:33:38.201-0400 [#####.....] mongoMart.restaurants
82.3MB/144MB (57.3%)
2021-05-24T11:33:41.202-0400 [#####.....] mongoMart.restaurants
90.3MB/144MB (62.8%)
2021-05-24T11:33:44.201-0400 [#####.....] mongoMart.restaurants
98.2MB/144MB (68.3%)
2021-05-24T11:33:47.200-0400 [#####.....] mongoMart.restaurants
104MB/144MB (72.6%)
2021-05-24T11:33:50.201-0400 [#####.....] mongoMart.restaurants
110MB/144MB (76.4%)
2021-05-24T11:33:53.200-0400 [#####.....] mongoMart.restaurants
115MB/144MB (79.8%)
2021-05-24T11:33:56.200-0400 [#####.....] mongoMart.restaurants
120MB/144MB (83.4%)
2021-05-24T11:33:59.201-0400 [#####.....] mongoMart.restaurants
126MB/144MB (87.8%)
2021-05-24T11:34:02.200-0400 [#####.....] mongoMart.restaurants
134MB/144MB (93.3%)
2021-05-24T11:34:05.200-0400 [#####.....] mongoMart.restaurants
140MB/144MB (97.7%)
2021-05-24T11:34:07.325-0400 [#####] mongoMart.restaurants
144MB/144MB (100.0%)
2021-05-24T11:34:07.325-0400 1000000 document(s) imported successfully. 0 document(s)
failed to import

```
mongo> db.restaurants.getShardDistribution()
```