
Python: functions

Intro. to computing

`https://mandarm.github.io/computing.html`

Functions I


Function parameters (zero or more, comma separated)
def is_prime(n):
"""
Function for checking whether a given
number is prime
Input(s):
non-negative integer n
Output:
True or False depending on whether n is
prime or not
"""
if n == 0 or n == 1:
return False
for i in range(2, 1+int(math.sqrt(n))):
if n % i == 0:
return False
return True
Function header
Docstring
(optional)
Function body

Functions II

- *Parameters* (or formal parameters): `n` in the above example
- *Arguments* (or actual parameters): value passed when the function is actually called

  Example: `is_prime(4)`, `is_prime(5)` — `4` and `5` are arguments
- `return` statements
  - may be followed by an optional expression (including `None`)
  - multiple occurrences permitted (as in example above)
  - no `return` statement OR no expression after `return`
    $\Rightarrow$ function returns `None`
- *Function call signature*: number and type of arguments + return value (cf. $f : D_1 \times D_2 \times \cdots \times D_k \rightarrow R$)

Naming conventions

- Use lowercase letters
- Use underscore (_) as word separator

Example: `read_data()` preferred to `readData()`

Parameters / arguments

- Number of arguments: fixed vs. variable
- Type of arguments: positional vs. named
- Type of arguments: required (compulsory) vs. optional
- **Special markers:** `/`, `*`, `**`

Variadic parameters

```
def multiply2(x, y): # 2 arguments
    return x * y

def multiply(*args): # could also use *numbers
    product = 1
    for x in args:
        product *= x
    return product

def multiply_flexible(initial, *numbers):
    product = initial
    for x in numbers:
        product *= x
    return product
```

- **Variadic parameter** ≡ accepts variable number of arguments
- Parameter name prefixed with *, e.g., `*args`, `*numbers`
- Parameter becomes a tuple containing *remaining* (0 or more) arguments

Variadic parameters

```
def multiply2(x, y): # 2 arguments
    return x * y

def multiply(*args): # could also use *numbers
    product = 1
    for x in args:
        product *= x
    return product

def multiply_flexible(initial, *numbers):
    product = initial
    for x in numbers:
        product *= x
    return product
```

What happens if you swap `initial` and `*numbers`

- **Variadic parameter** ≡ accepts variable number of arguments
- Parameter name prefixed with *, e.g., `*args`, `*numbers`
- Parameter becomes a tuple containing ~~*remaining*~~ (0 or more) arguments

Positional vs. named arguments I

```
def multiply_flexible(*numbers, initial):
    product = initial
    for x in numbers:
        product *= x
    return product

>>> multiply_flexible(2,3,4,10)          # carefully study error message
>>> multiply_flexible(2,3,4,initial=10) # 240
```

- **All** arguments preceding *non-empty* `*args` must be passed by position.
- **All** arguments following `*args` must be named arguments, i.e., passed using `parameter_name=value` format.

Positional vs. named arguments II

```
def example(x, y, *, a, b, c):
    print("x =", x, "\ny =", y, "\na =", a, "\nb =", b,"\nc =", c)

example(1,2,3) # ERROR: takes 2 positional arguments but 3 were given
example(1,2,b=3,c=4,a=5)      # OK
example(y=2,x=1,b=3,c=4,a=5) # OK
example(b=3,c=4,a=5,y=2,x=1) # OK
```

order of named arguments does not matter

- `*` (without a parameter name) does not match anything.
- Arguments preceding `*` may be passed by position or as named argument, i.e., using `parameter_name=value` format.
- **All** arguments following *first* named argument must also be named arguments, i.e., all positional arguments must precede all named arguments.
- **All** arguments following `*` must be named arguments.

This rule applies even when a variadic parameter (`*` or `*args`) is not used.

Positional vs. named arguments III

Positional-only arguments

- Can use `/` to force *preceding* arguments to be passed as positional arguments only

  (introduced in Python 3.8)


Digression: `help()` function

Run `help(variable or function name)` to see inbuilt documentation on the corresponding type or function.

Examples:

```
>>> a = [2,1]
>>> help(a)
>>> help(len)    # len(obj, /)
>>> help(sum)    # sum(iterable, /, start=0)
```

Summary: variadic, positional, and named parameters



- Optional
- `kwargs` ≡ dict containing all remaining arguments (must be in `name=value` form)

Optional; anything to the left of this is **positional** only; **cannot** be passed in `name=value` form.

- Optional: anything to the right of this is **named** only; cannot be passed by position
- `args` ≡ tuple containing all arguments upto and excluding first `name=value` type argument
- `args` omitted ⇒ passing arguments is an error
- if one or more argument(s) is supplied for `args`, all preceding arguments must be **positional**

- *When calling*, all positional arguments must precede all named arguments.

Required vs. optional arguments

- **Optional parameter** $\equiv$ parameter for which default value is provided in function header

  When calling the function, caller can

  - omit the argument
  - provide a value (same as / different from the default)

- *All parameters following first optional parameter must also be optional, with defaults provided.*
- Defaults **cannot** be provided for variadic (or preceding) parameters.
- Default parameter values evaluated **once** when function is defined
  - using mutable objects as default may lead to unexpected results

```
def func(x, items=[]): # 2nd call onwards, items is non-empty
    items.append(x)
    return items
```

  $\Rightarrow$ preferable to use only immutable objects as default values

More examples

```
def example2(x, y, *gobble, a=10, b=20, c=30):
    print("x =", x, "\ny =", y, "\na =", a, "\nb =", b,"\nc =", c)
    print("gobble =", *gobble)

example2(x=1,y=2)
x = 1
y = 2
a = 10
b = 20
c = 30
gobble =

example2(1,2,3,4,5)
x = 1
y = 2
a = 10
b = 20
c = 30
gobble = 3 4 5
```

Digression: * and ** as operators

- *: *unpack* a sequence
- **: *unpack* a dictionary into tuples

```
def example3(a, b, c, param1, param2, param3, param4):
    print("a =", a, \
          "b =", b, \
          "c =", c, \
          "param1 =", param1,
          "param2 =", param2,
          "param3 =", param3,
          "param4 =", param4)

>>> t = [ 1, 2, 3 ]
>>> d = {"param1" : 'a', "param2" : 'b', "param3" : 'c', "param4" : 'd'}
>>> example(t, d)     # ERROR
>>> example(*t, **d)  # works as expected
```

Things to keep in mind

- All required arguments must be provided (cannot be omitted).
- Multiple values should not be provided for any parameter.
- `name` part of any `name = value` argument must match a parameter name.
- Arguments are fully evaluated left-to-right before executing function body.

Parameter passing, return values

Parameter passing

- Function parameters $\equiv$ names that are *references* to the actual input objects

  $\Rightarrow$ function works on 'original' input objects, **not copies**

  $\Rightarrow$ changes made to mutable arguments are visible in the calling function

```
def reverse_in_place(L):
    for i in range(len(L) // 2):
        L[i], L[-i-1] = L[-i-1], L[i]

def sum_squares(L):
    L = [ x*x for x in L ]    # NOTE: local L is reassigned to a NEW
    list
    return sum(L)

>>> L = [1,2,3]
>>> reverse_in_place(L)
>>> sum_squares(L)            # L is not changed
>>> L
```

Return values

- To return multiple values, place them in a tuple.
- Values returned in a tuple can be unpacked to individual variables.

```
def quotient_and_remainder(dividend, divisor):
    return (dividend//divisor, dividend % divisor) # brackets optional

q, r = quotient_and_remainder(25, 7)
```

Scope rules

Local names

- All function parameters
- *All variables that are assigned in function body* (see example below)
- All other names (used but **not** assigned in function body) ≡ global names (must exist)
- `global x` ≡ `x` refers to global name, *even if* `x` *is assigned* in function body

generally considered to be bad style / avoidable

```
x = 10
def example5():
    print(x)      # x not assigned => global
>>> example5()   # prints 10

def example5():
    print(x)      # x not bound yet
    x = 20        # x is assigned => local
>>> example5()   # ERROR: UnboundLocalError
```

```
def example6():
    global x
    print(x)
    x = 20
>>> example6()
>>> x   # updated to 20
```

Will not cover: nested functions, `nonlocal`

Anonymous / lambda functions

Lambda functions I

- Anonymous function
- Takes any number of comma-separated arguments
- Body must consist of a *single* expression (≡ return value)
  (multiple statements, non-expression statements not allowed)

Examples:

```
import math
# Names given to anonymous functions for convenience
x = lambda theta: math.sin(theta) + math.cos(theta)
y = lambda theta: math.sin(theta + math.pi/4) * (2 ** 0.5)
print(x(math.pi/3), y(math.pi/3))

l1 = [ (1893, "Mahalanobis"), (1890, "Fisher"), (1777, "Gauss"), \
       (1894, "Neyman"), (1920, "CR Rao") ]
l2 = [ ("Mahalanobis", 1893), ("Gauss", 1777), ("Fisher", 1890), \
       ("Neyman", 1894), ("CR Rao", 1920) ]
sorted(l1)
sorted(l2)
```

Lambda functions II

```
sorted(l1, key=lambda x: x[1])
sorted(l1, key=lambda x: len(set(x[1])))
sorted(l2, key=lambda x: x[1])

def rh_derivative(f, x):
    h = 1e-8
    return (f(x+h) - f(x))/h

rh_derivative(math.sqrt, 4)
rh_derivative(lambda x: 3*x*x + 2*x, 10)
```

Globals in lambdas

- Value used $\equiv$ current value when `lambda` is *called* (**not** value at definition time)
- To use value at the time of definition, use it as default value

```
x = 2
f = lambda y, x=x: x * y
x = 3
g = lambda y, x=x: x * y
print(f(10))        # 20
print(g(10))        # 30
```

References

- *Python in a Nutshell*, 4th ed., Chapter 3, last section (Functions).
- *Python Distilled*, Chapter 5.