
# Python: container types (lists, strings, dictionaries, sets)

Intro. to computing

`https://mandarm.github.io/computing.html`

# Container types



# Container types I

- Lists: mutable sequence
  - elements accessed using *indices*, and **can be changed**
  - creating lists

```
l = [ 11, "y", 7.4 ]
l = []      # empty list
l = list(range(0,100,10)) # generally, list(iterable)
numbers = [10, 16, -2, 22, -98]
```

**Later:** using list comprehension

- Strings (`str`) : immutable sequence
  - elements accessed using *indices*, but **cannot be changed**
- Dictionaries: mutable
  - example: `{ 1:11, 2:"y", 3:7.4, 3.14:"pi" }`
  - elements accessed using *keys* (must be distinct)

# Container types II

- Sets: mutable, not “subscriptable” (indexable)
  - example: `{ 11, "y", 7.4 }`
- Tuples `(11, "y", 7.4)`: like lists, but immutable

# Lists: operations

**(applicable to immutable sequences also)**

| Operation | Result |
|---|---|
| `x in s` | true if an item of `s` is equal to `x`, else false*** |
| `x not in s` | false if an item of `s` is equal to `x`, else true*** |
| `s + t` | concatenation of `s` and `t`, does not change `s`, `t` |
| `s * n` or `n * s` | equivalent to concatenating `s` `n` times†† |
| `len(s)` | length of `s` |

*** for strings, `x` can also be a substring, e.g.,
`"gg" in "eggs" "ana" in "banana"`

†† **later:** may lead to unexpected behaviour

**Exercise:** try using a negative value for `n`.

# Lists: indexing and slicing

## Indexing

| | | | | | |
|---|---|---|---|---|---|
| Negative indexes | | `-n` | `-(n+1)` | `...` | `-2` | `-1` |
| `s` | = | `[ 10,` | `20,` | `...` | `40,` | `50, ]` |
| Positive indexes | | `0` | `1` | `...` | `n-2` | `n-1` |

note: $-0 \equiv 0$

**Slicing:** `s[start:end:step]`

- `start`: starting index, **default** `0`, *included* in slice
- `end`: ending index, **default** `len(s)`, *excluded* from slice
- `step`: skip `step` elements (`step` must be non-zero)
  - if `step` is positive, and `start >= end`, slice is empty.
  - if `step` is negative,
    - `start` must be greater than `end` (`start <= end` → slice is empty);
    - elements are listed in reverse order.
      example: `[22, 16, 10, -2, -98][10:0:-1]`
      → `[-98, -2, 10, 16]`

# [Correction] List slicing: more about `start` and `end`

**How 'unusual' values of `start`, `end` are handled**

1. If `start` (or `end`) is negative, it is replaced by `len(l) + start` (or `len(l) + end`).
2. If `start` or `end` are omitted, `None`, or *out of range*, they are replaced by appropriate ***end values***.

***End values:*** `0`, or `-1`, or `len(s)`, or `len(s)-1` as appropriate, depending on the sign of `step` (see examples below)

**Examples:**

- `l[n:0:-1]` prints elements in reverse order, starting from `n` (or `len(l)-1` if `n >= len(l)`), upto and **excluding** first element (index `0`)
- `l[n:-1:-1]` (`n >= len(l)`) prints empty list
  - `end` (`-1`) replaced by `len(l)-1` (rule 1)
  - either `n <= len(l)-1`, or is replaced by `len(l)-1`
- `l[n : -len(l)-1 : -1]` prints elements in reverse order, starting from `n` (or `len(l)-1` if `n >= len(l)`), upto and **including** first element
  - `end` (`-len(l)-1`) replaced (**once!**) by `-1` (rule 1)
- `l[::-1]` prints all elements in reverse order

-1 written by user is different from -1 obtained by replacement!

# Lists: more operations

**(applicable to mutable sequences only)**

| Operation | Result |
|---|---|
| `s[i] = x` | item `i` of `s` is replaced by `x` |
| `del s[i]` | removes item `i` of `s` |
| `s[i:j] = t` | slice of `s` from `i` to `j` is replaced by the contents of `t` |
| | `i==j` $\rightarrow$ contents of `t` inserted in place of *empty slice* at index `i` |
| `del s[i:j:k]` | removes the elements of `s[i:j:k]` from the list, `:k` optional |
| | same as `s[i:j:k] = []` |
| `s[i:j:k] = t` | elements of `s[i:j:k]` are replaced by those of `t` |
| | `:k` optional, but if not 1, `s[i:j:k]` and `t` must have same length |
| `s += t` | extends `s` with contents of `t` |
| `s *= n` | updates `s` with its contents repeated `n` times |

# Lists: some useful functions I

**(applicable to immutable sequences also)**

- `s.count(val)`: number of occurrences of `val` in sequence `s`
- `s.index(val)`
  `s.index(value, start)`
  `s.index(value, start, stop)`
  index of the **first** occurrence of `value` in sequence `s`, but error if it does not occur

Later: exceptions (errors) and how to handle them

**Usage:**

```
s = [ 0, 1, 2, 3, 2, 0, 1, 0, 3, 2]
s.count(0)
[ 0, 1, 2, 3, 2, 0, 1, 0, 3, 2].count(3)
```

# Lists: some useful functions II

**(applicable to mutable sequences only)**

- `s.append(value)`
- `s.insert(index, value)`
  - if `index` is out of range, it is replaced by appropriate end value (as for slicing)

    **example:**

```
>>> numbers = [16, 10]
>>> numbers.insert(-10,100) # numbers == [100, 16, 10]
>>> numbers.insert(100,200) # numbers == [100, 16, 10, 200]
```

- `s.pop(index)`: `index` optional, **default** is -1
  - get the item at `index` and remove it from the sequence
  - `index` *must be valid*, i.e., between `-n` and `n-1` (both inclusive)

# Lists: some useful functions III

- `s.remove(value)`: remove the first item that matches `value`, but error if it does not occur
- `s.extend(sequence)`
- `s.reverse()`, `reversed(s)`: **note the difference!**

# Lists: more useful functions

**If the elements can be compared**

- `min(l)` smallest item of `l`
- `max(s)` largest item of `s`
- `sort()`, `sorted()`
- `sum()` for numeric types

```
numbers = [10, 16, -2, 22, -98]
sorted(numbers)     # [-98, -2, 10, 16, 22]
reversed(numbers)   # <list_reverseiterator object at ...>
numbers.sort()      # changes in place
numbers.reverse()   # changes in place
```

**Note the difference** between `sorted()` (returns a list) and `reversed()` (returns an iterable).

# *Strings (`str` type)*

# Creating strings

- Single, double, triple quotes
- `str()` function applied to any variable or expression
  (creates printable string representation of the variable / expression)
- Two adjacent string literals separated by only whitespace automatically joined into single string literal

```
s1 = 'allows embedded "double" quotes'
s2 = "allows embedded 'single' quotes"
s3 = '''Three single
(allows multiple embedded newlines and ") quotes'''
s4 = """Three double
(allows multiple embedded newlines and ') quotes"""
s5 = str(['P', 'y', 't', 'h', 'o', 'n'])   # NOT "Python"
s6 = str([1, 2, 3, 4])
s7 = str({"sky" : "blue", "grass" : "green", "blood" : "red"})
s8 = "hello" ' world'
```

# Digression: escape sequences, 'raw' strings

```
>>> s4
"Three double \n(allows multiple embedded newlines and ') quotes"
>>> print(s4)
>>> s = 'hi\n'
>>> print(s)
>>> len(s)
```

**Escape sequences:** character sequences starting with a backslash (\) that denote some other character that may be hard to type / represent directly

**Examples:**

- `\t` ≡ tab (somewhat useful for lining things up in columns)
- `\r` ≡ carriage return (takes cursor back to beginning of line)
  (try `print("hello\nworld")` and `print("hellooooooo\rworld")`)

**Raw strings**

- strings prefixed with `r`, e.g., `r"hi\n"`
- escape sequences treated literally, do **NOT** have special meaning
  (try `print(r"hello\nworld")` and `print(r"hellooooooo\rworld")`)

# Lists: operations

**(applicable to immutable sequences also)**

| Operation | Result |
|---|---|
| `x in s` | true if an item of `s` is equal to `x`, else false*** |
| `x not in s` | false if an item of `s` is equal to `x`, else true*** |
| `s + t` | concatenation of `s` and `t`, does not change `s`, `t` |
| `s * n` or `n * s` | equivalent to concatenating `s` `n` times†† |
| `len(s)` | length of `s` |

*** for strings, `x` can also be a substring, e.g.,
`"gg" in "eggs" "ana" in "banana"`

†† **later:** may lead to unexpected behaviour

**Exercise:** try using a negative value for `n`.

# String functions: character types

**Digression: non-English languages and Unicode**

- `s.isalpha()`: all characters in `s` are letters,

  Examples: `'Letters and spaces'.isalpha()`, `'LettersOnly'.isalpha()`
- `s.islower()`: all characters in `s` are lowercase
- `s.isupper()`: as above
- `s.isdigit()`, `s.isnumeric()`
- `s.isalnum()`
- `s.isspace()`: blanks, tabs, newlines, etc.

`s` must have at least one character of the desired type

# String functions: changing case

Strings are **immutable**; all functions return a modified copy.

- `s.upper()`: all *cased* characters are converted to uppercase

  **Question:** Is `s.upper().isupper()` guaranteed to return `True`?
- `s.lower()`: as above
- `s.swapcase()`: uppercase characters are converted to lowercase and vice versa
- `s.capitalize()`: first character is capitalised, rest is lowercased

# String functions: searching

`end`, or both `start` and `end` may be omitted

- `in` operator, e.g., `"ana" in "banana"`
- `s.find(substring, start, end)`: returns lowest index in the string where substring `sub` is found, -1 if `sub` is not found

  **Question:** What is the difference between `find` and `index`?
- `s.rfind(substring, start, end)`: as above, but returns highest index
- `s.startswith(prefix, start, end)`
  - possible to check whether `s` with any of a number of prefixes by using a *tuple* of strings in place of `prefix`
- `s.endswith(suffix, start, end)`: as above
- `s.count(sub, start, end)`: returns number of *non-overlapping* occurrences of `sub` in `s` (or appropriate slice of `s`)

  **Question:** What happens when `sub` is the empty string (`""`)?

# String functions: replacing

- `s.removeprefix(somestring)`: if the string starts with `somestring`, remove it from the returned copy, otherwise return the original string `s`
- `s.removesuffix(somestring)`: as above
- `s.strip()` or `s.strip("some string")`: any leading / trailing characters that are in the specified string is removed

  (if no arguments are provided, leading and trailing *whitespace* is removed)

  Examples: `"  abcd  ".strip()`, `"  abcd  ".strip("dcba")`, `"ad  abcd  bc".strip("dcba")`
- `s.lstrip()`, `s.rstrip()`: as above, but only leading (`lstrip`) OR trailing (`rstrip`) characters are removed

  **Question:** What is the difference between ⟨`lstrip()`, `removeprefix()`⟩and ⟨`rstrip()`, `removesuffix()`⟩?
- `s.replace(oldstring, newstring, count)`: occurrences of `oldstring` are replaced by `newstring`
  - if `count` (optional) is not specified or negative, all occurrences are replaced; otherwise only the first `count` occurrences are replaced

  **Question:** What happens if `oldstring` is `""`?

# String functions: splitting I

- `s.partition(seperator-string)`: split the string at the *first* occurrence of `separator-string`; return a tuple containing 3 strings: (a) part before the separator, (b) separator, (c) part after the separator.
  - separator not found $\Rightarrow$ tuple contains `s`, `""` and `""`
- `s.rpartition(seperator-string)`: as above, but use the *last* occurrence of `separator-string`

## Digression: tuples

- Like lists, but *immutable*
- Use round brackets `( )` instead of square brackets `[ ]`

```
>>> t1 = ('a', 'b')
>>> t2 = tuple([1, 2, 3])
>>> t3 = (t1[1], t2[0])
```

# String functions: splitting II

- `s.split(seperator-string)`
  `s.split(sep="seperator-string")`
  Return list of "words" obtained by splitting `s` wherever `seperator-string` (must be non-empty) appears (can optionally specify maximum number of pieces)

  **Examples:**

```
'1,,2,3'.split(',')
# ['1', '', '2', '3']   (empty string because of consecutive commas)

'1,2,,3,'.split(',')    # ['1', '2', '', '3', '']
'1<>2<>3<4'.split('<>') # ['1', '2', '3<4']

# maxsplit=1 means at most 2 pieces
'1,2,3'.split(',', maxsplit=1)  # ['1', '2,3']
```

  **Question:** What happens is `separator-string` does not occur in `s`?

  **Question:** What happens if `s` is the empty string?

# String functions: splitting III

- `s.split()` or `s.split(None)`
  - return list of "words" obtained by splitting `s` wherever *one or more whitespace characters* appear(s)
  - *leading or trailing whitespace is eaten up*

**Examples:**

```
'1 2 3'.split()           # ['1', '2', '3']
'   1   2   3   '.split()  # ['1', '2', '3']
'1 2 3'.split(maxsplit=1)  # ['1', '2 3']
```

**Homework:** find out about `s.splitlines()`

# String functions: joining

`s.join(iterable)`: return string formed by concatenating elements of iterable (must be strings) in iterable, with `s` inserted between successive elements

```
>>> ' followed by '.join(['abc', 'def', 'ghi'])
>>> '-'.join('Python')   # 'P-y-t-h-o-n'
```

# **Homework:** String functions related to formatting

- `s.zfill(width)`
- `s.ljust(width, fillchar)`,
  `s.rjust(width, fillchar)`,
  `s.center(width, fillchar)`
- `s.format()`

# *Dictionaries (`dict` type)*

# Dictionaries / mappings

- Set of *key-value* pairs
- Keys must be hashable
  - numbers, strings allowed as keys
  - lists, dictionaries not allowed as keys
- Keys need not be of same type
- Keys have to be distinct
- Creating dictionaries

```
d1 = { 2026: "1st year",  2025: "2nd year", 2024: "3rd year"}
d2 = { "1st year": 2026,  "2nd year": 2025, "3rd year": 2024}
d3 = {'one': 1, 'two': 2, 'three': 3}

# each item must have exactly 2 elements
d4 = dict([(1, 'jan'), (2, 'feb')])
d5 = dict([('two', 2), ('one', 1), ('three', 3)])
d6 = dict({'three': 3, 'one': 1, 'two': 2})


# also possible to use key=value notation
a = dict(one=1, two=2, three=3)
```

# Dictionaries

```
d1 = { 2026: "1st year",  2025: "2nd year", 2024: "3rd year"}
d2 = { "1st year": 2026,  "2nd year": 2025, "3rd year": 2024}
d3 = {'one': 1, 'two': 2, 'three': 3}

# each item must have exactly 2 elements
d4 = dict([(1, 'jan'), (2, 'feb')])
d5 = dict([('two', 2), ('one', 1), ('three', 3)])
d6 = dict({'three': 3, 'one': 1, 'two': 2})

# also possible to use key=value notation
a = dict(one=1, two=2, three=3)
```




- Two dictionaries with same (key, value) pairs (regardless of ordering) are **equal** (==).
- Ordering comparisons between dictionaries (<, <=, >=, >) are invalid.

# Accessing values

- Use *key* as index to access *value*

```
print(d1[2026], d1[2024], d2["2nd year"])
print(d4[1])
```

- Key must exist in the dictionary (as a key)
- Values that compare equal (such as 1, 1.0, and True) can be used interchangeably to index the same dictionary entry.

**Exercise:** Try the following.

```
>>> d3[1]
>>> d4[1.0]
>>> d4[True]
>>> d1 = { 2026: "1st year",  2026: "2nd year", 2024: "3rd year"}
>>> d3 = dict([(1, 'jan'), (2, 'feb'), (1, 'January'])
```

# Basic operations/functions I

- `d.get(key, default-value)`: like `d[key]` but never returns error
  - `default-value` is optional
  - if `key` is not in `d`, return `default-value`, or `None` if default is not provided
- `d[key] = value` (`key` does not have to be an existing key in `d`)
- `d.setdefault(key, default-value)`
  - if `key` is in `d`, return its value;
  - otherwise, insert `key` with `default-value` and return `default-value`
  - if `default-value` (optional) is not provided, use `None`

# Basic operations/functions II

- `d.pop(key)`, `d.pop(key, default)`
  - if `key` is in dictionary, *remove* it and return its value
  - if `key` is not in dictionary, return `default`
  - if `key` is not in dictionary, and `default` is not given → ERROR
- `d.popitem()`: remove and return a (key, value) pair from `d` (in Last In First Out (LIFO) order)
- `del d[key]`: remove entry corresponding to `key` (*must exist!*) from `d`
- `d.clear()`: remove *all* entries in `d`

- `key in d`, `key not in d`, `not key in d`
- `list(d)`: return list of all *keys* currently in `d`
- `len(d)`: number of items in the dictionary `d`

# Dictionaries: ‘bulk’ updates

- `d.update(key1=value1, key2=value2, ...)`
  `d.update(dict2)`
  `d.update(iterable)` must contain tuples / other iterables of length two

  Add given key/value pairs to the dictionary `d` (existing keys are updated)
- `d1 | d2`: create new dictionary by merging dictionaries `d1` and `d2` (for common keys, values in `d2` are retained)
- `d1 |= d2`: similar
  - `d1` is updated
  - `d2` may be dictionary or iterable (as for `update`)

# Dictionary views I

**Dictionary view object:** provide a *dynamic* view on the dictionary's entries, i.e., when the dictionary changes, the view is **auto-updated**.

**Functions:**

- `d.keys()`: return new view of the dictionary's keys
- `d.values()`: return **new** view of the dictionary's values
- `d.items()`: return **new** view of the dictionary's *items*, i.e., (key, value) pairs
- `len()` and membership (`in`) work for dictionary views

# Dictionary views II

```
d1 = { 2026: "1st year",  2025: "2nd year", 2024: "3rd year"}
k1 = d1.keys()
v1 = d1.values()
e1 = d1.items()
# Print k1, v1, e1

d1[2027] = "Next incoming batch"
# Print k1, v1, e1 again: automatically get updated values
del d1[2027]
# Print k1, v1, e1 again: automatically get updated values

2026 in k1
(2024, "3rd year") in e1
```

# Dictionary views III

## Warning: counterintuitive property

```
>>> k2 = d1.keys()
>>> k1 == k2
True
>>> v2 = d1.values()
>>> v1 == v2
False
>>> e2 = d2.items()
>>> e1 == e2
False
```

# Dictionaries: iteration and order of items I

```
for k in d1
for k in d1.values()
for k in reversed(d1)
for k in reversed(d1.items())
```

etc.

} work as expected

- Dictionaries preserve insertion order.
- Updating a key does not change its position.
- Keys added after deletion are inserted at the end.
- Dictionaries (also views) are reversible.

# Dictionaries: iteration and order of items II

```
d = {"one": 1, "two": 2, "three": 3, "four": 4}
list(d)                 # ['one', 'two', 'three', 'four']
list(d.values())        # [1, 2, 3, 4]
d["one"] = 42
del d["two"]
d["two"] = None
# Check d.keys(), d.values(), etc. again
list(reversed(d))
list(reversed(d.values()))
```

# *Sets*

# Sets

- *Unordered* collection $\Rightarrow$ no indexing, slicing, sorting
- Elements have to be *hashable* and *distinct*
- Intended uses: removing duplicates from a sequence + set operations
- `set` type $\longrightarrow$ mutable, *not hashable*
  - cannot be used as dictionary key or element of another set
- `frozenset` type $\longrightarrow$ immutable, hashable
- Creating sets

```
S1 = {'BStat', 'BSDS', 'BMath'} # not permitted for frozenset
S2 = set()                      # empty set
S3 = frozenset({'BStat', 'BSDS', 'BMath'}) # OK, also frozenset(S1)
S4 = set('Indian Statistical Institute')
S5 = set(['MStat', 'MMath', 'MSQE'])
S6 = set([S1])      # Try removing [ ]
S7 = set([ [1,3,5], [2,4,6] ]) # Try removing inner [ ]
S8 = set([S3])      # Try removing [ ]
```

# Basic operations

- Checking emptiness: `bool(S)` (`True` iff `S` is non-empty)

```
if S: print("Not empty")          if not S: print("Empty")
else: print("Empty")              else: print("Not empty")
```

- Membership: `x in S`, `x not in S`,
- Cardinality: `len(S)`
- Iteration: `for x in S`

# Operations on sets, frozensets I

- `S1.isdisjoint(S2)`
- `S1.issubset(S2)`, `S1 <= S2`
- `S1 < S2`: checks whether `S1` is a *proper* subset of `S2`
- `S1.issuperset(S2)`, `S1 >= S2`
- `S1 > S2`: as above
- `S1.union(S2, S3, ...)`, `S1 | S2 | S3 |...`: returns *new* set

## Difference between `S1.union(S2)` and `S1 |S2`

- `union` function: accepts any iterable as argument
  Example: `S6.union([1,2,3], [2,4,1])` → OK
- `|` operator: all operands must be sets (or set-like)
  Example: `S6 | [1,2,3]` → ERROR

# Operations on sets, frozensets II

- `S1.intersection(S2, S3, ...)`, `S1 & S2 & S3 & ...`
- `difference()`, or `-`: multiple arguments may be given
- `S1.symmetric_difference(S2)`, `^`
- Sets and frozensets may be mixed; result has type of first operand

# Operations on sets I

**(applicable to sets (mutable) only)**

- `S1.add(element1)` (note: only *one* element at a time)
- `S1.remove(element1)` (ERROR if `element` is not a member)
- `S1.discard(element1)` (*no error* if `element` is not a member)
- `S1.pop()`: remove and return *arbitrary* element, ERROR if `S1` is empty
- `S1.clear()`: remove *all* elements

- `S1.add(element1)` (note: only *one* element at a time)
- `S1.update(S2, ...)`, `S1 |= S2 | S3 | ...`
- `S1.intersection_update(S2, ...)`, `S1 &= S2 & S3 & ...`
- `S1.difference_update(S2, ...)`, `S1 -= S2 | S3 |...` **NOTE!**
- `S1.symmetric_difference_update(S2)`, `S1 ^= S2`

# Set operations on dict views I

- Keys views: keys are unique and hashable
  - support set-like operations, and operations with sets
- Items views:
  - ~~support set-like operations (keys are unique and hashable)~~
    support set-like operations *if all values in an items view are hashable*
  - support operations with sets *if all values in an items view are hashable*
- Values views: **NOT** set-like
- For set operators, set-like views accept *any iterable* as the other operand

  **But recall:** for set **operators**, sets can only accept other sets as operands.

***Official documentation*** *(`library/stdtypes.html#dictionary-view-objects`)*
*Items views also have set-like operations since the (key, value) pairs are unique and the keys are hashable. If all values in an items view are hashable as well, then the items view can interoperate with other sets.*

# Set operations on dict views II

**Examples:**

```
# Set
computer_types = { "laptop", "desktop", "server", "mobile", "tablet" }

# Example in which values are hashable
brands1 = {'lenovo': 5, 'hp': 5, 'asus': 3, 'acer': 2}
keys1 = brands1.keys()
values1 = brands1.values()

# Example in which values are hashable
brands2 = {'ibm': 1, 'sony': 3, 'dell': 5, 'apple': 4, 'msi': 1}
keys2 = brands2.keys()
values2 = brands2.values()

# Example in which values are NOT hashable
models = {"lenovo": [ "yoga", "ideapad", "thinkpad", "loq" ], \
          "apple" : [ "macbook air 13", "macbook air 15", "macbook pro"
    ] }
```

# Set operations on dict views III

```
# keys and values appear in the same order (insertion / creation order)
list(keys1)          # ['lenovo', 'hp', 'asus', 'acer']
list(values1)        # [5, 5, 3, 2]

# dict views: set operations and operations with sets
computer_types | keys1 | models.keys()    # mixing sets and key views OK
computer_types | keys1 | brands2.items()  # OK (values are hashable)
computer_types | keys1 | models.items()   # NOT OK

(keys1 | keys2) & models.keys()
brands1.items() ^ brands2.items() == brands1.items() | brands2.items()
brands2.items() | [5, 5, 3, 2]            # any iterable OK

computer_types | [5, 5, 3, 2]            # NOT OK
computer_types | set([5, 5, 3, 2])       # OK
```

# *Comprehensions and generator expressions*

# List comprehensions I

- Concise way to create lists (also sets, dicts) from other iterables
- Elements of new list typically obtained by
  - applying some operation to each member of the other iterable, OR
  - selecting only elements of the other iterable that satisfy some condition

**Examples**

```
squares = [x*x for x in range(10)]
roots = [x**0.5 for x in range(10)]
odd_nums = [ x for x in range(10) if x%2 == 1 ]
capitalized = [ s.capitalize() for s in ["bengaluru", "chennai",
                                         "delhi", "kolkata"] ]
```

- General form:
  [ <expression> <for clause> <more for or if clauses (optional)> ]

LATER: `map()` and `filter()`

# List comprehensions II

```
# Using list comprehension
newlist = [ <expression> for <clause1> if <condition1>
                         for <clause2> if <condition2> ]

# Without using list comprehension
newlist = []
for <clause1>:
    if <condition1>:
        for <clause2>:
            if <condition2>:
                newlist.append(<expression>)
```

# List comprehensions III

**Examples:**

```
# Using list comprehension
l = [ (x, y)  for x in [1,2,3]  for y in [3,1,4]  if x != y ]

# Without using list comprehension
l = []
for x in [1,2,3]:
    for y in [3,1,4]:
        if x != y:
            l.append((x, y))

# Flattening a list
L = [[1,2,3], [4,5,6], [7,8,9]]
l = [num for list_element in L for num in list_element]
```

# List comprehensions IV

```
A = [  [1, 2, 3, 4],  [5, 6, 7, 8],  [9, 10, 11, 12]  ]

# Without ANY listcomp
transposed = []
for i in range(len(A[0])):
    transposed_row = []
    for row in A:
        transposed_row.append(row[i])
    transposed.append(transposed_row)

# Without NESTED listcomp
transposed = []
for i in range(len(A[0])):
    transposed.append([row[i] for row in A])

# Using NESTED listcomp
A_transpose = [ [row[i] for row in A] for i in range(len(A[0])) ]
```

# Dictionary and set comprehensions

```
brands = {'ibm': 1, 'sony': 3, 'dell': 5, 'apple': 4, 'msi': 1}
inverse_map = { brands[k]:k for k in brands }
brands |= inverse_map

consonants = {x for x in 'some long string' if c not in 'aeiou'}
```

# Generator expressions I

- General form: (same as for list comprehensions, except for enclosing brackets)
  ( <expression> <for clause> <more for or if clauses (optional)> )
- Interpretation: as for list comprehensions, **BUT**
  - list comprehension: entire list is generated and stored in memory
  - generator expression: elements are
    - *generated on demand* **ONCE** (more soon)
    - deleted from memory after they are iterated over

    $\Rightarrow$ generator expressions take much less memory
- Generator expression generating from mutable object (e.g., list) evaluated at *time of use*, NOT *time of creation*

```
mylist = ["a", "b", "c"]
gen = (elem + "1" for elem in mylist)
mylist.clear()
for x in gen: print (x)    # prints nothing
```

# Generator expressions II

**Examples:**

```
list_comp = [x ** 2 for x in range(10) if x % 2 == 0]
gen_exp = (x ** 2 for x in range(10) if x % 2 == 1)
print(list_comp)      # [0, 4, 16, 36, 64]
print(gen_exp)        # <generator object <genexpr> at ...>

print(list_comp[2])   # 16
list_comp += [100]    # OK

print(gen_exp[2])     # ERROR!
gen_exp += list_comp  # ERROR!
print(list(gen_exp))  # [1, 9, 25, 49, 81]
```

# Comprehensions vs. generator expressions I

## Broad thumbrules

- Use list comprehension if you need
  - indexing, slicing, or other list operations. e.g., reversing
  - multiple passes over the data, e.g., sorting
- Use generator expression if you need
  - only one pass over the data, e.g., `sum()`, `max()`, `min()`
  - `any()` or `all()`
  - to process very large quantities of data

# Comprehensions vs. generator expressions II

## Examples

```
# In the following examples, the full list has to be generated anyway
# => better to use listcomp
gen_exp = (x ** 2 for x in range(10) if x % 2 == 1)
list_comp += gen_exp

' '.join( str(i) for i in range(10) )

# Genexps generate sequence ONCE
l = (x ** 2 for x in range(10) if x % 2 == 0)
print("First pass")
for i in l: print(i)  # As expected
print("Second pass")
for i in l: print(i)  # Nothing is printed!!
print("More passes")
for i in (x ** 2 for x in range(10) if x % 2 == 0): print(i)
for i in (x ** 2 for x in range(10) if x % 2 == 0): print(i)
```

# Comprehensions vs. generator expressions III

## Difference between genexps and iterators

```
l1 = range(5)
l2 = (x ** 2 for x in range(5) )
for i in l1:           # Repeat nested for loops
    for j in l1:       #   with l2 instead of l1
        print(i, j)
```

## Pathological example with 'infinite' sequence

```
from itertools import count # "infinite" generator
from math import log

listcomp = [ log(i) for i in count(10) ]
genexp = ( log(i) for i in count(10) )
for x in genexp:
    print(x)
    input('Continue?')
```

# Digression: `any()` and `all()`

- `any(iterable)`: return `True` if any element of `iterable` evaluates to `True`; otherwise (or if iterable is empty), return `False`
- `all(iterable)`: return `True` if all elements of `iterable` evaluates to `True`, or if iterable is empty

Condition is vacuously true

**Lazy evaluation / short-circuiting behaviour:** *stop evaluating a Boolean condition as soon as its truth value is determined*

$\Rightarrow$ stop checking elements of `iterable` for

- `any()` $\rightarrow$ as soon as `True` element is found
- `all()` $\rightarrow$ as soon as `False` element is found

**Question:** which is preferable as argument to `any()`, `all()`: genexp or listcomp?

# *Odds and ends*

# Lists of sublists: * vs. comprehension

```
ls1 = [[] for i in range(3)]
ls1[0].append(10)
ls1[1].append(20)
ls1.append(30)
print(ls1)          # [[10], [20], [], 30]

ls2 = [[]]*3        # [ [], [], [] ] 3 references to the SAME empty list
ls2[0].append(10)   # [ [10], [10], [10] ]
ls2[1].append(20)   # ls2[0] and ls2[1] refer to the SAME list
ls2.append(30)
print(ls2)          # [[10, 20], [10, 20], [10, 20], 30]
```

- List comprehension: elements are newly created
- Concatenation using *: items are **referenced** multiple times, **NOT** copied

  $\Rightarrow$ results with mutable elements may be unexpected (as above)

  **Question:** what if elements are immutable?

# Lists of sublists: * vs. comprehension (CONTD.)

**Elements are references to immutable objects:**

```
x = 10
l = [ x ] * 4
x = 20
# Q1. does l change?
l[0] += 1
# Q2. do all elements of l change or only l[0]?
```

**Elements are references to mutable objects:**

```
l = [ [] ] * 3          # l = [[],[], []] (3 references to SAME empty list)
l[0] = l[0] + [1, 2]    # l = [[1,2], [], []] (l[0] reassigned to new list)
l[1].append(3)          # l = [[1,2], [3], [3]] (l[1], l[2] refer to same list)
l[2] += [4, 5]          # l = [[1,2], [3,4,5], [3,4,5]] (+= modifies in place)
l[2] = l[0] + l[2]      # l = [[1,2], [3,4,5], [1,2,3,4,5]] (= reassigns)
```

## Simple (=) vs. augmented assignments (+=, etc.)

For mutable objects, simple assignments reassign, but augmented assignments modify in place;
$\Rightarrow$ `l[2] += [4, 5]` is like `l[1].append(3)` rather than `l[2] = l[0] + l[2]`.

# Lists of sublists: * vs. comprehension (CONTD.)

**Elements are references to mutable objects (dictionaries):**

```
brands = {'ibm': 1, 'sony': 3, 'dell': 5, 'apple': 4, 'msi': 1}
l = [ brands ] * 2  # brands, l[0] and l[1] all refer to the same object
brands["hp"] = 5
l[1]["lenovo"] = 10
```

**Elements are references to mutable objects (sets):**


```
computer_types = { "laptop", "desktop", "server", "mobile", "tablet" }
l = [ computer_types ] * 2   # as above
computer_types.add("wearable")
l[1].add("embedded")
```

# Making sense of the above I

- **Objects:** values, e.g., numbers, sequences, dictionaries, sets, etc.
  - each object occupies memory
  - each object has unique *identity*
    - `id(obj)`: return unique identity of `obj` (often its memory address)
- **References:** names used in a Python program for the above
- **Assigning a value to a variable** (say `X`):
  - `X` now *references* (refers to) / *is bound to* the object / value on RHS
  - **reassignment**: `X` points to a different object
    $\Rightarrow$ object that `X` referred to earlier **not** overwritten, remains unchanged

# Making sense of the above II

```
x = 10
x = 20
x = 30
print(id(10))
print(id(20))
print(id(30))
print(id(x))
x -= 10
print(id(x))
l1 = [10, 20]
l2 = [10, 20]
l3 = []
l4 = []
l5 = l6 = []
print(id(l1), id(l1[0]), id(l1[1])
print(id(l2), id(l2[0]), id(l3[1])
print(id(l3) == id(l4))
print(id(l5) == id(l6))
```



# Making sense of the above III

- When a name is used in an assignment
  - as an *l-value* $\longrightarrow$it may be reassigned to another object
  - as an *r-value* $\longrightarrow$the object it references is used in its place

# Iterating over a changing iterable I

**Thumbrule:** avoid unless you clearly understand what is happening

## Problems

```
numbers = [1, 2, 4, 3]
for n in numbers:
    if n % 2 == 0:
        numbers.remove(n)
print(numbers)  # Expected: [1, 3]; actual: [1, 4, 3] (4 is skipped)

# Infinite loop
l = [1, 2]
for i in l:
    l.append(i*i)
    print(l)
    input("Continue?")
```

# Iterating over a changing iterable II

```
# Error! (dictionary changed size during iteration)
brands = {'ibm': 1, 'sony': 3, 'dell': 5, 'apple': 4, 'msi': 1}
for k in brands: brands[brands[k]] = k
for k in brands.keys(): brands[brands[k]] = k

#  Error! (set changed size during iteration)
S = {1, 2, 4, 3}
for element in S:
    if element % 2: S.remove(element)
```

# Iterating over a changing iterable III

**Solutions:**

- Lists: use list comprehension or slicing

```
for n in numbers[:]:    # slicing creates a (shallow) copy
    if n % 2 == 0:
        numbers.remove(n)
```

- Dictionaries: use dictionary comprehension or (static) list of current keys `list(dictionary.keys())`
- Sets: use set comprehension or `list(s)`