

Windows Subsystem for Linux (WSL)

Intro. to Computing

`https://mandarm.github.io/computing.html`

Installation

- Open Windows PowerShell (WPS).
- Run `wsl --install`.
 - If it says Downloading: Ubuntu, type Control-C to abort.
- Run `wsl --update`.
(should say most recent version is already installed)
- If you do not already have a copy of <https://releases.ubuntu.com/26.04/ubuntu-26.04-wsl-amd64.wsl>, download it.
- Double-click the file to launch the installer.
- After installation is complete, run `sudo apt update && sudo apt upgrade`.
- Close the window or type Control-D to exit.
- Run `wsl` in WPS to start WSL again.

■ How do Windows locations appear in WSL and vice versa?

- `C:\` $\equiv$ `/mnt/c`
- `/` $\equiv$ `\\wsl.localhost\Ubuntu-26.04` or `\\wsl$` (in Windows File explorer address bar)

■ **General guideline:** for best performance, avoid working across environments (Windows and WSL)

- When programming in WSL, store files under `/home/student` (or `/home/cssc ...`)
not `/mnt/c/Users/CSSC/Project` or `C:\Users\CSSC\Project`
- Exception (for now): edit your Python programs using Windows; run them using WSL.

■ **Warning re: file/directory names:**

Windows $\rightarrow$ case-insensitive, Linux $\rightarrow$ case-sensitive

Mixing Windows and WSL commands

- Using Windows executables from WSL: include .exe extension

Examples:

```
explorer.exe .
```

```
notepad.exe "C:\temp\foo.txt"
```

```
notepad.exe C:\\temp\\foo.txt
```

- Using Linux programs from Windows: add wsl before command name

Examples:

```
wsl ls -l
```

References

Official docs: <https://learn.microsoft.com/en-us/windows/wsl>