

Agent

Agent Permissions

Antigravity uses a unified permission system to control what actions the Agent can perform on your behalf. Every action is represented as a **permission resource** that can be placed into one of three lists:

- **Allow:** The action is auto-approved without prompting.
- **Deny:** The action is blocked immediately.
- **Ask:** The Agent pauses and asks for your approval before proceeding.

Resource String Format

Every entry in the Allow, Deny, or Ask list follows the format:

```
action(target)
```

Where `action` is one of the supported action types and `target` is a pattern describing what the permission covers.

Supported Actions

Action	Target Format	Matching
<code>command</code>	<code>command(prefix)</code> or <code>command(*)</code>	Matches commands by prefix. <code>command(git)</code> matches <code>git add</code> , <code>git commit</code> , etc.
<code>read_file</code>	<code>read_file(/path)</code>	Matches the file or everything under the directory. Paths must be literal and absolute. Globs (<code>*.go</code>), regex, and <code>~</code> are not supported.
<code>write_file</code>	<code>write_file(/path)</code>	Same as <code>read_file</code> . Also implicitly covers <code>read_file</code> for the same path.

Agent

mcp

mcp(server/tool) ,
mcp(server/*) , or
mcp(*)

Matches by exact server name. `server/*` covers all tools on that server.

Examples

Allow list — these actions run without prompting:

text



```
command(git)                # Any git command
command(npm run build)       # Build commands
read_file(/home/user/project) # Read anything in
the project
write_file(/home/user/project/src) # Edit files under
src/
read_url(example.com)        # Fetch any public
page
mcp(workspace/*)             # All workspace
tools
```

Deny list — these actions are always blocked:

text



```
command(rm)                  # No rm commands
command(sudo)                 # No sudo
write_file(/home/user/.ssh)  # No writes to .ssh
```

Ask list — the Agent pauses and asks before proceeding:

text



```
command(*)                   # Prompt for every
command                      # Prompt for every
mcp(*)                       # Prompt for every
MCP tool call
```

 Agent

< Agent Modes / Settings

Rules / Workflows >