

Here is how to rename a network interface on CentOS or RHEL 7.

First, let's disable the predictable naming rule. For that, you can pass "net.ifnames=0" kernel parameter during boot. This is achieved by editing /etc/default/grub and adding "net.ifnames=0" to GRUB_CMDLINE_LINUX variable.

```
GRUB_TIMEOUT=5
GRUB_DISTRIBUTOR="$(sed 's, release .*$,,g' /etc/system-release)"
GRUB_DEFAULT=saved
GRUB_DISABLE_SUBMENU=true
GRUB_TERMINAL_OUTPUT="console"
GRUB_CMDLINE_LINUX="rd.lvm.lv=centos/swap vconsole.font=latarcyrheb-sun16 rd.lvm
.lv=centos/root crashkernel=auto vconsole.keymap=us net.ifnames=0 rhgb quiet"
GRUB_DISABLE_RECOVERY="true"
```



Then run this command to regenerate GRUB configuration with updated kernel parameters.

```
$ sudo grub2-mkconfig -o /boot/grub2/grub.cfg

[dev@centos7 ~]$ sudo grub2-mkconfig -o /boot/grub2/grub.cfg
Generating grub configuration file ...
Found linux image: /boot/vmlinuz-3.10.0-123.el7.x86_64
Found initrd image: /boot/initramfs-3.10.0-123.el7.x86_64.img
Warning: Please don't use old title 'CentOS Linux, with Linux 3.10.0-123.el7.x86_64' for GRUB_DEFAULT, use 'Advanced options for CentOS Linux>CentOS Linux, with Linux 3.10.0-123.el7.x86_64' (for versions before 2.00) or 'gnulinux-advanced-ec9b5a3a-c3c7-4535-af0a-fcb32db03246>gnulinux-3.10.0-123.el7.x86_64-advanced-ec9b5a3a-c3c7-4535-af0a-fcb32db03246' (for 2.00 or later)
Found linux image: /boot/vmlinuz-0-rescue-fea4c40c8eef4c72b48679402379a432
Found initrd image: /boot/initramfs-0-rescue-fea4c40c8eef4c72b48679402379a432.img
done
[dev@centos7 ~]$
```

Next, edit (or create) a udev network naming rule file (/etc/udev/rules.d/70-persistent-net.rules), and add the following line. Replace MAC address and interface with your own.

```
$ sudo vi /etc/udev/rules.d/70-persistent-net.rules
```

```
SUBSYSTEM=="net", ACTION=="add", DRIVERS=="*", ATTR{address}=="08:00:27:a9:7a:e1", NAME="eth0"
```

```
$sudo mv /etc/sysconfig/network-scripts/ifcfg-eno16777736 /etc/sysconfig/network-scripts/ifcfg-eth0
```

Step5# Edit "/etc/sysconfig/network-scripts/ifcfg-eth0 " configuration file and set the value of "Name" field to "eth0?".

```
1 # vim /etc/sysconfig/network-scripts/ifcfg-eth0
TYPE=Ethernet
BOOTPROTO=dhcp
DEFROUTE=yes
IPV4_FAILURE_FATAL=no
IPV6INIT=yes
IPV6_AUTOCONF=yes
IPV6_DEFROUTE=yes
IPV6_FAILURE_FATAL=no
```

NAME=eth0

UUID=5ae10208-855b-41af-99e7-0673d3792d15

ONBOOT=yes

HWADDR=00:0C:29:C7:25:AE

PEERDNS=yes

PEERROUTES=yes

IPV6_PEERDNS=yes

IPV6_PEERROUTES=yes

?

Finally, reboot the machine, and verify the new interface name.

```
[dev@centos7 ~]$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: sushi: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP q
len 1000
    link/ether 08:00:27:a9:7a:e1 brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic sushi
        valid_lft 86362sec preferred_lft 86362sec
    inet6 fe80::a00:27ff:fea9:7ae1/64 scope link
        valid_lft forever preferred_lft forever
[dev@centos7 ~]$
[dev@centos7 ~]$
```

Note that it is still your responsibility to configure the renamed interface. If the network configuration (e.g., IPv4 settings, firewall rules) is based on the old name (before change), you need to update network configuration to reflect the name change.