Manual for Delete CSV File Columns (s-DCSVFC.R)

2026-11-07

© 2026 Peter B. Mandeville.

This work is distributed under a Creative Commons Attribution 4.0 International License (CC BY 4.0).
To view full license terms, visit http://creativecommons.org/licenses/by/4.0/.

Suggested Citation & Attribution:

Mandeville, P. B. (2026). Utilities: Manual for Delete CSV File Columns (s-DCSVFC.R).

Description:
This utility reads a **CSV** file, safely removes specified columns, and writes the resulting cleaned dataset to a target file. It preserves raw data types (preventing unwanted string/date auto-conversion), verifies column presence, logs dataset dimensions before and after processing, and warns the user if any targeted columns are missing.

Instructions for Use:

1. Prerequisites:
Ensure the following packages are installed before running the script:

```
install.packages(c("dplyr", "readr", "fs"))
```

2. Execution Steps:

1. Configure File Paths & Targets: Set input, output, and deletion parameters.
Open **s-DCSVFC.R** and set your desired file paths and the list of column names to drop:

```
input_file       <- "titanic1.csv" output_file      <-
"titanic2.csv" fields_to_delete <- c("PassengerId", "Name")
```

2. Run the Utility: Source the script or call the function directly.
Execute the script from your **RStudio** environment, interactive console, or pipeline script:

```
source("s-DCSVFC.R")
```

(Alternatively, import the script and call remove_csv_columns(in_path, out_path, drop_cols) directly in another workflow).

3 .Review Console Summary: Check dimensions and deleted fields in the **R** console.
The script logs processing results directly to the console:

```
Original dimensions: 891 rows x 12 columns

Cleaned dimensions:  891 rows x 10 columns

Removed column(s):   PassengerId, Name

Cleaned dataset successfully written to 'titanic2.csv'

---- s-DCSVFC.R script execution completed ----
```