Merge CSV Files (s-MCSVF.R)

2026-11-07

© 2026 Peter B. Mandeville.

This work is distributed under a Creative Commons Attribution 4.0 International License (CC BY 4.0).
To view full license terms, visit http://creativecommons.org/licenses/by/4.0/.

Suggested Citation & Attribution:

Mandeville, P. B. (2026). Utilities: Manual for Merge CSV Files (s-MCSVF.R).

Description:
This R utility consolidates multiple **CSV** files with matching schemas into a single output file. Built on **readr** and **dplyr**, it validates file existence, handles mismatched schemas, filters out empty files, and prevents data type conflicts.

Instructions for Use:

1. Prerequisites:

Ensure you have **R** installed along with the **dplyr** and **readr** packages:

```
install.packages(c("dplyr", "readr"))
```

2. Configuration & Execution Steps:

1. Set Configuration Parameters: Specify file paths and merge settings.
Open **s-MCSVF.R** and modify the **CONFIG** list:

- Add full file paths to **input_files**.
- Set **output_file** to your desired destination path.
- Leave **force_character_types = FALSE** by default.

2. Execute Main Process: Run the script directly in R or RStudio.
Execute the main() function or run the full script. The console will report the merge progress:

```
Starting merge operation...
```

```
Success! Merged 3 file(s) into 1250 total rows.
Destination: E:/Analysis/Utilities/MCSVF/PRTFL-2026-c.csv
```

3. Handle Type Errors (If Prompted): Resolve data type mismatches if triggered.
If input **CSV** files contain conflicting column data types (e.g., text values in an otherwise numeric column), the script will stop with an error. Set **force_character_types = TRUE** in **CONFIG** and re-run to force uniform string parsing.