```
<!doctype html>
<html lang="en">
<head>
<meta charset="utf-8">
<title>HTML in Nota</title>
<link rel="stylesheet" href="HTML.css">
</head>
<body>

<h1><img src="HTML.svg" alt=""> HTML in Nota</h1>

<h2 id="the-page-is-the-page">The page is the page</h2>
<p>
  Nota does not read this file and lay it out its own way, the way it does a
  <code>.md</code> or a <code>.tex</code>. It hands the file to WebKit, so what
  you see is what a browser sees: this page's doctype, its
  <a href="HTML.css">own stylesheet</a> beside it, the
  <a href="#links">colours it asked for</a>, and its pictures.
</p>

<h2 id="live">Live</h2>
<p>
  Type in the column beside this one. The page follows about 150 ms after you
  stop, from the editor's text rather than from the file, so unsaved edits are
  the page. It keeps its scroll while it reloads, so an edit near the bottom
  does not send you back to the top.
</p>

<h2 id="links">Links</h2>
<p>
  <a href="#the-page-is-the-page">This one</a> is an anchor in this page, so it
  stays here and scrolls. <a href="https://developer.mozilla.org/en-US/docs/Web/HTML">This
  one</a> leaves, so it opens in your browser: Nota is an editor with a preview
  beside it, not a browser with an editor beside it.
</p>

<h2 id="scripts">Scripts</h2>
<p>
```

```
  A field is a field, and a button is a button. The script that listens to
  both is <a href="HTML.js">HTML.js</a> beside this file, and it runs here the
  way it would in a browser. Type, then click.
</p>
<p class="script-row">
  <input type="text" id="say" placeholder="Type here" autocomplete="off"
spellcheck="false">
  <button type="button" id="click-me">Click me</button>
</p>
<p id="click-status">the script has not run yet</p>

<script src="HTML.js"></script>

<footer>Saved as <code>.html</code> or <code>.htm</code>, in any case you
like.</footer>

</body>
</html>

```