Install Visual Studio Code (VSCode)

EVASCO, MARK ANGELO L.

Git 2.42.0.2 Setup

Adjusting the name of the initial branch in new repositories
What would you like Git to name the initial branch after "git init"?

○ Let Git decide
   Let Git use its default branch name (currently "master") for the initial branch in newly created repositories. The Git project intends to change this default to a more inclusive name in the near future.

○ Override the default branch name for new repositories
   NEW! Many teams already renamed their default branches; common choices are "main", "trunk" and "development". Specify the name "git init" should use for the initial branch:
   main

   This setting does not affect existing repositories.

   Back   Next   Cancel

Git 2.42.0.2 Setup

Choosing the SSH executable
Which Secure Shell client program would you like Git to use?

○ Use bundled OpenSSH
   This uses ssh.exe that comes with Git.

○ Use external OpenSSH
   NEW! This uses an external ssh.exe. Git will not install its own OpenSSH (and related) binaries but use them as found on the PATH.

   Back   Next   Cancel

Git 2.42.0.2 Setup

Choosing HTTPS transport backend
Which SSL/TLS library would you like Git to use for HTTPS connections?

○ Use the OpenSSL library
   Server certificates will be validated using the ca-bundle.crt file.

○ Use the native Windows Secure Channel library
   Server certificates will be validated using Windows Certificate Stores.
   This option also allows you to use your company's internal Root CA certificates distributed e.g. via Active Directory Domain Services.

   Back   Next   Cancel

Git 2.42.0.2 Setup

Configuring the terminal emulator to use with Git Bash
Which terminal emulator do you want to use with your Git Bash?

○ Use MinTTY (the default terminal of MSYS2)
   Git Bash will use MinTTY as terminal emulator, which sports a resizable window, non-rectangular selections and a Unicode font. Windows console programs (such as interactive Python) must be launched via 'winpty' to work in MinTTY.

○ Use Windows' default console window
   Git will use the default console window of Windows ("cmd.exe"), which works well with Win32 console programs such as interactive Python or node.js, but has a very limited default scroll-back, needs to be configured to use a Unicode font in order to display non-ASCII characters correctly, and prior to Windows 10 its window was not freely resizable and it only allowed rectangular text selections.

   Back   Next   Cancel

Git 2.42.0.2 Setup

Choose the default behavior of `git pull`
What should `git pull` do by default?

○ Default (fast-forward or merge)
   This is the standard behavior of `git pull`: fast-forward the current branch to the fetched branch when possible, otherwise create a merge commit.

○ Rebase
   Rebase the current branch onto the fetched branch. If there are no local commits to rebase, then this is equivalent to fast-forward.

○ Only ever fast-forward
   Fast-forward to the fetched branch. Fail if this is not possible.

   Back   Next   Cancel