

A Study on Simulation of Quantum Error Correction Codes by Using MATLAB Program

매트랩을 활용한 양자 오류 부호의 모의 실험 연구

저자 (Authors)	Duc Manh Nguyen, Sunghwan Kim
출처 (Source)	한국통신학회 학술대회논문집 , 2016.1, 248-249 (2 pages) Proceedings of Symposium of the Korean Institute of communications and Information Sciences , 2016.1, 248-249 (2 pages)
발행처 (Publisher)	한국통신학회 Korea Institute Of Communication Sciences
URL	http://www.dbpia.co.kr/Article/NODE06609989
APA Style	Duc Manh Nguyen, Sunghwan Kim (2016). A Study on Simulation of Quantum Error Correction Codes by Using MATLAB Program. 한국통신학회 학술대회논문집, 248-249.
이용정보 (Accessed)	울산대학교 203.250.64.*** 2018/03/23 20:13 (KST)

저작권 안내

DBpia에서 제공되는 모든 저작물의 저작권은 원저작자에게 있으며, 누리미디어는 각 저작물의 내용을 보증하거나 책임을 지지 않습니다. 그리고 DBpia에서 제공되는 저작물은 DBpia와 구독 계약을 체결한 기관소속 이용자 혹은 해당 저작물의 개별 구매자가 비영리적으로만 이용할 수 있습니다. 그러므로 이에 위반하여 DBpia에서 제공되는 저작물을 복제, 전송 등의 방법으로 무단 이용하는 경우 관련 법령에 따라 민, 형사상의 책임을 질 수 있습니다.

Copyright Information

Copyright of all literary works provided by DBpia belongs to the copyright holder(s) and Nurimedia does not guarantee contents of the literary work or assume responsibility for the same. In addition, the literary works provided by DBpia may only be used by the users affiliated to the institutions which executed a subscription agreement with DBpia or the individual purchasers of the literary work(s) for non-commercial purposes. Therefore, any person who illegally uses the literary works provided by DBpia by means of reproduction or transmission shall assume civil and criminal responsibility according to applicable laws and regulations.

매트랩을 활용한 양자 오류 부호의 모의 실험 연구

웬 만 득, 김성환

울산대학교

nguyenmanhduc18@gmail.com, sungkim@ulsan.ac.krA Study on Simulation of Quantum Error Correction Codes
by Using MATLAB ProgramDuc Manh Nguyen, Sunghwan Kim
University of Ulsan

요 약

In this work, we introduce basic notations of quantum operations and quantum error correcting codes via quantum circuit model. Then, the simplest quantum error correction codes is explained and proved to correct quantum errors via MATLAB environment.

I. Introduction

Starting with the ideas of P. Benioff (1980) and R. Feynman (1982) [1], quantum theory of information has been developed. Until now, quantum processing devices have a great deal of potential for various tasks such as factorizing large number, searching a pattern in database, cryptography. And they showed better performances than classical computers even if the best currently known algorithms are considered in classical processing devices [2].

However, to realize that potential, methods to protect fragile quantum states from unwanted evolution, errors are needed [3]. Hence, quantum error correcting codes (QECC) have been developed to protect quantum information from these errors [4].

Before implementing the error correcting codes, the necessary step is simulation in the classical computer. In this work, two basic QECC codes are first introduced. Then, the analysis and simulation is taken by MATLAB.

The rest of the paper is organized as follows. In section 2, we introduce the theory of qubits and quantum elementary operations. The quantum error correction and the solution to simulate in MATLAB are discussed in section 3. Finally, the conclusion is listed in Section 4.

II. Qubit and quantum elementary operations

Quantum theory uses qubit to represent information, the quantum systems with two levels such as: two polarization states of photons, two energy levels of atoms, etc. A qubit, denoted as $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, can be considered to have both values of $|0\rangle$ and $|1\rangle$ at the same time, the probability of value $|0\rangle$ is $|\alpha|^2$ and probability of

value $|1\rangle$ is $|\beta|^2$. This concept known as superposition is the main property of quantum computation since it allows gate operations to deal with several values in one step. Hence, the amount of information that can be represented is infinite. A qubit can be representing in vector form:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle = \alpha \begin{bmatrix} 1 \\ 0 \end{bmatrix} + \beta \begin{bmatrix} 0 \\ 1 \end{bmatrix} = \begin{bmatrix} \alpha \\ \beta \end{bmatrix}.$$

According to the probability, the condition $|\alpha|^2 + |\beta|^2 = 1$ must be satisfied. A quantum memory register is a physical system composed of n qubits, that is multiple by tensor product of some qubits. Generally, the n qubits state denote as:

$$|\psi\rangle = \sum_{i_k \in \{0,1\}} \alpha_{i_1 i_2 \dots i_n} |i_1\rangle \otimes |i_2\rangle \otimes \dots \otimes |i_n\rangle = \sum_i \alpha_i |i\rangle,$$

where $i = \sum_{k=1}^n 2^{n-k} i_k$. Hence, a state vector of n qubits

quantum system is considered as superposition of the states that make up a base in 2^n dimensional complex Hilbert space.




Figure 1. Summary of basic quantum gates.

In this paper, quantum circuit model is used. In this model, operations are applied to qubit by quantum gates [5]. Mathematically, we simulate the quantum

gate via the matrix representation. Note that the condition for any quantum gate is revertible and the invert gate that move $U|\psi\rangle$ back to $|\psi\rangle$ satisfy $U^{-1} = U^\dagger$, so U is unitary matrix. Some important quantum gates are showing in **Figure 1**. In quantum depolarizing channel, \mathbf{I}_2 (the identity matrix), \mathbf{X} , \mathbf{Z} and \mathbf{Y} form orthogonal basis of linear space of operators acting on qubit and any error acting on qubit can be represented as the combination of \mathbf{I}_2 , \mathbf{X} , \mathbf{Z} and \mathbf{Y} . Hence, there are only three types of errors that can effect on a qubit the flip error, phase error and flip-phase error. Generally, the error operators that effect to n qubits have the form: $E = e_1 \otimes e_2 \otimes \dots \otimes e_n$ where $e_i \in \{\mathbf{I}, \mathbf{X}, \mathbf{Y}, \mathbf{Z}\}$.

III. Simulation quantum error correction code

MATLAB is a computing environment that based on the operation with matrices. Hence it is useful tool in simulating the matrix formalism of quantum process. The representation of one qubit can be represented base on 2 dimensional Hilbert space $|\psi\rangle = \begin{bmatrix} \alpha \\ \beta \end{bmatrix}$.

The state of quantum register n qubits can be given by the tensor product of n qubits. Any circuit is given as the series of unitary transformation applied to the quantum state. These transformations are represented by matrices form. As calculating by true table, two new matrices combined of CNOT gate is presented in **Figure 2** and **Figure 3**.




Figure 2. New CNOT-1.




Figure 3. New CNOT-2.

The simplest quantum error correction code is 3-qubit repetition code that can correct one error: bit flip or phase flip. To extend the first full quantum code, 9-qubit Shor is created by Shor [6], which can correct bit-flip, phase-flip or the combination bit, phase flip error. The quantum error correction code is simulated by quantum circuit model; they are showing in the **Figure 4, 5** for 3-qubit repetition code as well as the 9-qubit Shor code. The quantum circuit starts with the information qubit via *kron* function in MATLAB for 3-qubits, 9-qubits, after transformation by encode step, the logical states or encoded qubits are created. For example, two logical basis states of 3-qubit are defined as: $|0_L\rangle = |000\rangle$; $|1_L\rangle = |111\rangle$ for 3-qubit repetition as well as

$$|0_L\rangle = \frac{1}{\sqrt{8}}(|000\rangle + |111\rangle) \otimes (|000\rangle + |111\rangle) \otimes (|000\rangle + |111\rangle);$$

$$|1_L\rangle = \frac{1}{\sqrt{8}}(|000\rangle - |111\rangle) \otimes (|000\rangle - |111\rangle) \otimes (|000\rangle - |111\rangle);$$

for 9-qubits Shor code. Using matrices transformation, the states after applying error and decoding can be found. The final states show us the correction state can be recovered the syndrome $|S_e\rangle$ tell us which error has applied to logical states.




Figure 4. Circuit for X-error QECC.

IV. Conclusion

The paper presents basic information on quantum error correction, using MATLAB environment the 3-qubits repetition and 9-qubits Shor code have been proved to correct. Such simulation of simplest QECC help us better understanding of design and quantum error correction and quantum mechanism for further.




Figure 5. Circuit for Z-error QECC

ACKNOWLEDGMENT

This research was supported by Basic Science Research Program through the National Research Foundation of Korea(NRF) funded by the Ministry of Science, ICT & Future Planning(NRF-2014R1A1A1004521)

References

- [1]Richard P. Feynman, "Simulating physics with computers", Int.J.Theor.Phys, vol. 21, is. 6, pp. 467-488,1982.
- [2]Noson.S. Yanofsky, Micro.A. Mannucci, "Quantum computing for computer scientists", Cambridge University Press New York, NY, USA, 2008.
- [3]Peter W. Shor, "Scheme for reducing decoherence in quantum memory". Phys. Rev. A, vol. 52, no. 4 , 1995.
- [4]Gaitan F, "Quantum error correction and fault tolerant quantum computing", CRC Press, Inc, BocaRaton. FL. USA (2007).
- [5]R. Cleve, C. Macchiavello, G.M. Palma, and A. Zeilinger,"An introduction to quantum complexity theory", World Scientific, pp.103-127, 2000.
- [6]Simon J. Devitt, Kae Nemoto, William J. Munro, "Quantum error correction for beginners", Rep.Prog.Phys, vol. 76, no. 7, 2013.