
## **Target Design**

- 1. Each WATL affiliated location shall purchase an official target protractor/stencil.
- 2. The small hole on the left of the stencil will have a screw that will be drilled through it into the center of the middle board. (Approximately 24 inches in the center of the board. That will make 60 inches from the floor).
  - 1. A black, 20mm marker will then be used to draw the remaining circles.
  - 2. Holes are 22mm thick to allow for a marker to fit that has 1/2" thick felt.
  - 3. Lines are to be 20mm thick.
  - 4. The inner Bullseye is to be colored in red and outlined in a black waterproof pen.
  - 5. The entire bullseye area (inner red circle and unmarked 5 ring) must be 3.5" inches in diameter inside the center ring. The center of the inner bullseye must be 24" inches (60.96 cm) from the bottom of the board. This should make the center of the bullseye 60" from the floor.
    - 1. The inner bullseye (inner red circle) should be 1.5" in diameter, outlined with a black, waterproof pen.
  - 6. Targets with the inner bullseye and 5 ring design are only required for sanctioned league and tournament play. Venues may leave the entire bullseye (3.5") for day-to-day, non-league operations.
- 3. The bullseye (center red circle) must be 3.5" inches in diameter inside the center ring. The bullseye must be 24" inches (60.96 cm) from the bottom of the board. This should make the center of the bullseye 60" from the floor.
- 4. The Killshot (2 blue circles) are 1.5" inches in diameter and positioned inside the 1 point ring.
  - 1. The bottom of the Killshot is positioned approximately 35.25 inches from the bottom of the board to the bottom of the Killshot and 2.5 inches from the outer side of the board ensuring they are centered inside the 1 point outer ring. This should make the bottom of the Killshot 71.25" from the floor.
  - 2. The Killshot should be 1.5" in diameter, outlined with a red, waterproof ballpoint pen that clearly shows/denotes the Killshot, thereby eliminating overspray or bleeding caused by markers. The red outline of the ballpoint pen will count as a scoring area, but any blue that bleeds outside of the red outline will not.
- 5. All targets must be level (no slanting of the targets are allowed).
- 6. Targets will have no marking other than the lines, bullseye, and Killshots
- 7. "#WATL" or "World Axe throwing League" is required to be listed prominently on either the header or footer boards
- 8. Projected Targets are not WATL compliant. Only boards with physical markings are permitted.









The entire area of the inner and outer bullseye should measure 3.5 inches inside the ring. The red of the bullseye should be 1.5 inches, outline in black waterproof pen, as shown below.



The Killshot should be 2.5 inches inside the board to the outer side and outlined in red waterproof pen, as shown below.



We recommend your ceiling be at least 10<sup>FT</sup> tall

