

Computational Methods in Physics (PHY 365)

FA23

Dr. Muhammad Kamran

Department of Physics

COMSATS University Islamabad

Lab 13

MATLAB's quad function

- `quad` numerically evaluates the integral, using **adaptive Simpson quadrature**.

MATLAB's quad function

- `quad` numerically evaluates the integral, using **adaptive Simpson quadrature**.
- `q = quad(fun , a , b)` tries to approximate the integral of function **fun** from `a` to `b` to within an error of 10^{-6} using recursive adaptive Simpson quadrature.
 - ◇ **fun** is a **function handle**.
 - ◇ Limits `a` and `b` must be finite.
 - ◇ The function `y = fun(x)` should accept a vector argument `x` and return a vector result `y`, the integrand evaluated at each element of `x`.

MATLAB's quad function

- `quad` numerically evaluates the integral, using **adaptive Simpson quadrature**.
- `q = quad(fun , a , b)` tries to approximate the integral of function **fun** from `a` to `b` to within an error of 10^{-6} using recursive adaptive Simpson quadrature.
 - ◇ **fun** is a **function handle**.
 - ◇ Limits `a` and `b` must be finite.
 - ◇ The function `y = fun(x)` should accept a vector argument `x` and return a vector result `y`, the integrand evaluated at each element of `x`.
- `q = quad(fun , a , b , tol)` uses an absolute error tolerance “tol” instead of the default.

MATLAB's quad function

- **Problem:** Compute the following integral using quad function.

$$I = \int_0^2 \frac{1}{x^3 - 2x - 5} dx.$$

MATLAB's quad function

- **Problem:** Compute the following integral using quad function.

$$I = \int_0^2 \frac{1}{x^3 - 2x - 5} dx.$$

- **The interval**

x_lower = 0;

x_upper = 2;

MATLAB's quad function

- **Problem:** Compute the following integral using quad function.

$$I = \int_0^2 \frac{1}{x^3 - 2x - 5} dx.$$

- **The interval**

`x_lower = 0;`

`x_upper = 2;`

- **The integrand**

`f = @(x) 1 ./ (x.^3 - 2 * x - 5);`

MATLAB's quad function

- Calling the quad function

```
quad_int = quad(f , x_lower , x_upper);
```

MATLAB's quad function

- Calling the quad function

```
quad_int = quad(f , x_lower , x_upper);
```

- Displaying the result

```
fprintf('The approximate value of the integral is %3.4f \n',  
quad_int)
```

MATLAB's dblquad function

- `q = dblquad(fun , xmin , xmax , ymin , ymax)` calls the `quad` function to evaluate the double integral $\text{fun}(x,y)$ over the rectangle $(x_{\min} \leq x \leq x_{\max}, y_{\min} \leq y \leq y_{\max})$.
- `q = dblquad(fun , xmin , xmax , ymin , ymax , tol , method)` uses the quadrature function specified as `method`, instead of the default `quad`.
 - ◇ Valid values for `method` are `@quadl` or the function handle of a user-defined quadrature method that has the **same calling sequence** as `quad` and `quadl`.

MATLAB's dblquad function

- **Problem:** Compute the following integral using dblquad function.

$$I = \int_0^{\pi} \int_{\pi}^{2\pi} [y \sin(x) + x \cos(y)] dx dy.$$

MATLAB's dblquad function

- **Problem:** Compute the following integral using dblquad function.

$$I = \int_0^{\pi} \int_{\pi}^{2\pi} [y \sin(x) + x \cos(y)] dx dy.$$

- **The intervals**

x_lower = pi;

x_upper = 2 * pi;

y_lower = 0;

y_upper = pi;

MATLAB's dblquad function

- The integrand

```
f = @(x , y)  y .* sin (x) + x .* cos (y);
```

- Calling the dblquad function

```
dblquad_int = dblquad (f, x_lower, x_upper, y_lower,  
y_upper);
```

MATLAB's dblquad function

- The integrand

```
f = @(x , y)  y .* sin (x) + x .* cos (y);
```

- Calling the dblquad function

```
dblquad_int = dblquad (f, x_lower, x_upper, y_lower,  
y_upper);
```

- Displaying the result

```
fprintf('The approximate value of the integral is %3.4f \n',  
dblquad_int)
```

References

- <https://www.mathworks.com/help/matlab/ref/quad.html>
- <https://www.mathworks.com/help/matlab/ref/dblquad.html>
- <https://www.mathworks.com/help/matlab/ref/quadl.html>