

1

A white slide with a thin black border. At the top is the word 'Content' in blue. Below it is a bulleted list of topics:

- Edges:
  - Detection
  - Linking
- Feature extraction
  - Global features
  - Local features
  - Matching
- Applications

At the bottom is the HUST SOICT logo and the text 'SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY'.

2

## Local features vs Global features

- Two types of features are extracted from the image:
  - local and global features (descriptors)
- **Global features**
  - Describe the **image as a whole** to the generalize the entire object
  - Include contour representations, shape descriptors, and texture features
    - Examples: Invariant Moments (Hu, Zernike), Histogram Oriented Gradients (HOG), PHOG, and Co-HOG,...
- **Local feature:**
  - the local features **describe the image patches** (key points in the image) of an object
  - represents the texture/color in an image patch
    - Examples: SIFT, SURF, LBP, BRISK, MSER and FREAK, ...



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

3

## Feature extraction

- **Global features**
  - Color / Shape / Texture
- Local features



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

4

4

## Global features?

How to distinguish these objects?



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

5

## Types of features

- Contour representation, Shape features
- Color descriptors
- Texture features




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

6

6

## Color features

- Histogram



7

## Distance / Similarity

- L1 ou L2 (euclidian) distances are often used


$$d_{L1}(H, G) = \sum_{i=1}^N |h_i - g_i|$$

- Histogram intersection

$$\cap(H, G) = \frac{\sum_i \min(h_i, g_i)}{\sum_i g_i}$$

## Advantages of histogram


- Invariant to basic geometric transformations:
  - Rotation
  - Translation
  - Zoom (Scaling)




9

## Some inconveniences

- The **similarity between colors in adjacent colors (bin)** is not taken into account




- The **spatial distribution of pixel values** is **not considered**: 2 different images may have the same histogram



## Some inconveniences

- **Background effect:**  $d(I_1, I_2) \neq d(I_1, I_3)$




- **Color representation dependency** (color space), device dependency, ...


## Texture features

- A **texture** can be defined as
  - a region with variation of intensity
  - as a spatial organization of pixels

A texture can be **periodic** (a pattern that repeats itself) ...



...or **non-periodic** (no pattern, more disorganized)



## Texture features

- There are several methods for analyzing textures:
  - First order statistics
    - Statistics on histogram
  - Co-occurrence matrices
    - Searching patterns
  - Frequential analysis
    - Gabor filter
  - ...
- The most difficult is to find a good representation (good parameters) for each texture




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

13

13

## Texture features



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

14

14

## First order statistics

- Histogram-based: mean, variance, skewness, kurtosis, energy, entropy, ...

$$\mu = \frac{1}{n} \sum_{i=0}^{H_g} h(i)$$

$$E = \sum_{i=0}^{H_g} (P(i))^2$$

$$\sigma^2 = \frac{1}{n-1} \sum_{i=0}^{H_g} (h(i) - \mu)^2 \quad H = -\sum_{i=0}^{H_g} P(i) \log(P(i))$$

$$s = \frac{1}{n\sigma^3} \sum_{i=0}^{H_g} (h(i) - \mu)^3$$

$$P(i) = \frac{h(i)}{n}$$

$$k = \frac{1}{n\sigma^4} \sum_{i=0}^{H_g} (h(i) - \mu)^4$$

$h(i)$  : số điểm ảnh ở mức xám i



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

is.hust.edu.vn


15

15


## First order statistics

- Skewness vs. kurtosis (red: normal distribution with mean = 5, variance = 4)


© www.scratchapixel.com



Negative Skew  
(large tail to the left)



Positive Skew  
(large tail to the right)



positive and negative kurtosis



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


is.hust.edu.vn

16

16

## GLCM (Grey Level Co-occurrence Matrices)

- The idea here is to identify **gray level that repeat themselves** given a **distance** and a **direction**
  - *Co-occurrence matrices (Haralick)*
- **Matrix of size  $Ng \times Ng$** 
  - $Ng$  is the number of gray level in the image (256x256)
  - We often reduce that number to 8x8, 16x16 or 32x32
- Many matrices, one for each distance and direction
  - **Distance** : 1, 2, 3 (,4, ...)
  - **Direction** :  $0^\circ$ ,  $45^\circ$ ,  $90^\circ$ ,  $135^\circ$  (, ...)
- Processing time can be very long



17

## GLCM

$$CM_{d,\beta}(c_i, c_j) = \frac{\text{card}(\{p_1, p_2 \mid I(p_1) = c_i, I(p_2) = c_j, N_{d,\beta}(p_1, p_2) = \text{true}\})}{\text{card}(\{p_1, p_2 \mid N_{d,\beta}(p_1, p_2) = \text{true}\})}$$

$N_{d,\beta}(p_1, p_2) = \text{true}$        $p_2$  is a neighbor of  $p_1$  at a distance  $d$  direction  $\beta$



18

18

## GLCM

- Example on how to compute these matrices:

1	4	4	3
4	2	3	2
1	2	1	4
1	2	2	3

Image

	1	2	3	4
1	?	?	?	?
2	?	?	?	?
3	?	?	?	?
4	?	?	?	?

Matrix for distance=1  
and direction=0°



We loop over the image and for each pair of pixels following the given distance and orientation, we increment the co-occurrence matrix



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

19

## GLCM

- Example on how to compute these matrices:

1	4	4	3
4	2	3	2
1	2	1	4
1	2	2	3

Image

	1	2	3	4
1	0	0	0	1
2	0	0	0	0
3	0	0	0	0
4	0	0	0	0

Matrix for distance=1 and  
direction=0°

Pair of neighbor pixels (1,4)




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

20


## GLCM

- Example on how to compute these matrices:



## GLCM

- Example on how to compute these matrices:



## GLCM

- Example on how to compute these matrices (final):

1	4	4	3
4	2	3	2
1	2	1	4
1	2	2	3

Image

	1	2	3	4
1	0	2	0	2
2	1	1	2	0
3	0	1	0	0
4	0	1	1	1

Matrix for distance=1  
and direction=0°



	1	2	3	4
1	0	2	1	0
2	1	1	0	0
3	0	0	0	1
4	0	2	1	0

Matrix for distance=1  
and direction=45°



...and so on for each matrix (several matrices at the end)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

23

## GLCM

- Most important/popular parameters computed from GLCM:

$$Energy = \sum_i \sum_j CM_d^2(i, j) \quad \text{minimal when all elements are equal}$$

$$entropy = -\sum_i \sum_j CM_d(i, j) \log(CM_d(i, j)) \quad \begin{array}{l} \text{a measure of chaos,} \\ \text{maximal when all elements are equal} \end{array}$$

$$contrast = \sum_i \sum_j (i - j)^2 CM_d(i, j) \quad \begin{array}{l} \text{small values when big elements} \\ \text{are near the main diagonal} \end{array}$$

$$idm = \sum_i \sum_j \frac{1}{1 + (i - j)^2} CM_d(i, j) \quad \begin{array}{l} idm \text{ (inverse differential moment) has small} \\ \text{values when big elements are far from the} \\ \text{main diagonal} \end{array}$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

is.hust.edu.vn

24

24

## GLCM

- Haralick features:

- For each GLCM, we can compute up to **14 (13)** **parameters** characterizing the texture, of which the most important : mean, variance, energy, inertia, entropy, inverse differential moment
- Ref: <http://haralick.org/journals/TexturalFeatures.pdf>



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

is.hust.edu.vn

25

25

## Invariances

- Rotation?
  - Average on all directions
- Scaling?
  - Multi-resolutions



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

26

26

## Texture features comparision




Figure 10. Comparison of results for all considered features on each data set. Each horizontal dotted box displays results for one data set. The  $x$ -axis shows normalized results (between 0 and 100) according to the minimum and maximum classification rates achieved for each data set. The vertical slashed box on the right-hand side selects the feature extraction methods that achieved the best results throughout all data sets.



Source : William Robson Schwartz et al. Evaluation of Feature Descriptors for Texture Classification – 2012 JEI  
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY  
is.hust.edu.vn

27

## Shape features

- Contour-based features
  - Chain coding, polygon approximation, geometric parameters, angular profile, surface, perimeter, ...
- Region based:
  - Invariant moments, ...




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

28

28


## Shape features



29

29


## Examples: Freeman chain coding



30

30

## Examples: angular profile, ...



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

31

31

## Examples : Image moments

- Moment 
$$M_{ij} = \sum_x \sum_y x^i y^j I(x, y)$$

$$M_{0,0} = \text{area of the region } D$$

$$(M_{0,1}, M_{1,0}) = \text{centroid of } D$$

- Central moments:

$$\mu_{pq} = \sum_x \sum_y (x - \bar{x})^p (y - \bar{y})^q I(x, y)$$

$$\bar{x} = \frac{M_{10}}{M_{00}} \quad \bar{y} = \frac{M_{01}}{M_{00}}$$

Invariant to translation



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

32

32

## Invariant moments (Hu's moments)

invariant to  
translation,  
scale, and  
rotation, and  
reflection

$$I_1 = \eta_{20} + \eta_{02}$$

$$I_2 = (\eta_{20} - \eta_{02})^2 + 4\eta_{11}^2$$

$$I_3 = (\eta_{30} - 3\eta_{12})^2 + (3\eta_{21} - \eta_{03})^2$$

$$I_4 = (\eta_{30} + \eta_{12})^2 + (\eta_{21} + \eta_{03})^2$$

$$I_5 = (\eta_{30} - 3\eta_{12})(\eta_{30} + \eta_{12})[(\eta_{30} + \eta_{12})^2 - 3(\eta_{21} + \eta_{03})^2] + (3\eta_{21} - \eta_{03})(\eta_{21} + \eta_{03})[3(\eta_{30} + \eta_{12})^2 - (\eta_{21} + \eta_{03})^2]$$

$$\eta_{ij} = \frac{\mu_{ij}}{\mu_{00}}$$

$$I_6 = (\eta_{20} - \eta_{02})[(\eta_{30} + \eta_{12})^2 - (\eta_{21} + \eta_{03})^2]$$

Change for  
image  
reflection

$$I_7 = (3\eta_{21} - \eta_{03})(\eta_{30} + \eta_{12})[(\eta_{30} + \eta_{12})^2 - 3(\eta_{21} + \eta_{03})^2] + (\eta_{30} - 3\eta_{12})(\eta_{21} + \eta_{03})[3(\eta_{30} + \eta_{12})^2 - (\eta_{21} + \eta_{03})^2]$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

33

33

## Examples : Hu's moments

6 images and their Hu Moments

id	Image	H[0]	H[1]	H[2]	H[3]	H[4]	H[5]	H[6]
K0	K	2.78871	6.50638	9.44249	9.84018	-19.593	-13.1205	19.6797
S0	S	2.67431	5.77446	9.90311	11.0016	-21.4722	-14.1102	22.0012
S1	S	2.67431	5.77446	9.90311	11.0016	-21.4722	-14.1102	22.0012
S2	S	2.65884	5.7358	9.66822	10.7427	-20.9914	-13.8694	21.3202
S3	S	2.66083	5.745	9.80616	10.8859	-21.2468	-13.9653	21.8214
S4	?	2.66083	5.745	9.80616	10.8859	-21.2468	-13.9653	-21.8214

<https://www.learnopencv.com/wp-content/uploads/2018/12/HuMoments-Shape-Matching.png>



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

34

34

# Feature extraction

- Global features
- **Local features**
  - Interest point detector
  - Local descriptor

## Why local features?

- Image matching: a challenging problem



## Image matching

by [Diva Sian](#)by [swashford](#)by [scgbt](#)

Slide credit: Steve Seitz



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


39

39

## Harder Still?



NASA Mars Rover images



Slide credit: Steve Seitz




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

40

40

## Answer Below (Look for tiny colored squares)



NASA Mars Rover images with SIFT feature matches  
(Figure by Noah Snavely)

Slide credit: Steve Seitz

- Recognition of specific objects/scenes



Sivic and Zisserman, 2003



D. Lowe 2002


## Motivation for using local features

- Global representations have major limitations
- Instead, describe and match only local regions
- Increased robustness to


— Occlusions



— Articulation



— Intra-category variations



Source: CS131 - Juan Carlos Niebles and Ranjay Krishna



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

43

43

## Local features and alignment

- We need to match (align) images
- Global methods sensitive to occlusion, lighting, parallax effects. So look for local features that match well.
- How would you do it by eye?



[Darya Frolova and Denis Simakov]




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

44

44

## Local features and alignment

- Detect feature points in both images
- Find corresponding pairs



[Darya Frolova and Denis Simakov]



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

45

45

## Local features and alignment

- Detect feature points in both images
- Find corresponding pairs
- Use these pairs to align images





[Darya Frolova and Denis Simakov]



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

46

## Local features for image matching



# Local features

- Objectifs:

- Look for similar objects/regions
- Partial query



- Solution:

- Describing **local regions**
- Adding **spatial constraints** if need



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


49

49

# Local feature extraction

- Local features: how to determine image patches / local regions

Dividing into patches with regular grid



Without knowledge about image content



Keypoint detection



Based on the content of image



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

50

50

## Common Requirements

- Problem 1:

- Detect the same point *independently* in both images



No chance to match!

We need a repeatable detector!

- Problem 2:

- For each point correctly recognize the corresponding one



We need a reliable and distinctive descriptor!





SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: Darya Frolova, Denis Simakov

51

51

## Invariance: Geometric Transformations



Slide credit: Steve Seitz




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

52

52

## Invariance: Geometric Transformations



Levels of Geometric Invariance

Slide credit: Steve Seitz



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

53

53

## Invariance: Photometric Transformations



- Often modeled as a linear transformation:
  - Scaling + Offset

Slide credit: Tinne Tuytelaars



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

54

54

## Requirements

- Region extraction needs to be **repeatable** and **accurate**
  - **Invariant** to translation, rotation, scale changes
  - **Robust** or **covariant** to out-of-plane ( $\approx$ affine) transformations
  - **Robust** to lighting variations, noise, blur, quantization
- **Locality**: Features are local, therefore robust to occlusion and clutter
- **Quantity**: We need a sufficient number of regions to cover the object
- **Distinctiveness**: The regions should contain “interesting” structure
- **Efficiency**: Close to real-time performance



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

55

55

## Main questions

- **Where** will the interest points come from?
  - What are salient features that we'll *detect* in multiple views?
- How **to describe** a local region?
- How to **establish correspondences**, i.e., compute matches?



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

56

56

# Feature extraction

- Global features
- **Local features**
  - **Interest point detector**
  - Local descriptor
  - Matching




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

57

57

## Interest points: why and where?



Yarbus eye tracking

Source : Derek Hoiem, Computer Vision, University of Illinois.



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

58

58

## Interest points: why and where?

- Where will the interest points come from?




Figure 4.3: Image pairs with extracted patches below. Notice how some patches can be localized or matched with higher accuracy than others.

## Keypoint Localization


- Goals:
  - Repeatable detection
  - Precise localization
  - Interesting content

⇒ Look for two-dimensional signal changes



Slide credit: Bastian Leibe

## Finding Corners



- Key property:
  - In the region around a corner, image gradient has two or more dominant directions
- Corners are *repeatable* and *distinctive*

C.Harris and M.Stephens. ["A Combined Corner and Edge Detector."](#) *Proceedings of the 4th Alvey Vision Conference*, 1988.




Slide credit: Svetlana Lazebnik

62


62

## Corners as distinctive interest points


- Design criteria
  - We should easily recognize the point by looking through a small window (*locality*)
  - Shifting the window in *any direction* should give *a large change* in intensity (*good localization*)



"flat":  
no change in  
all directions



"edge":  
no change along  
the edge  
direction



"corner":  
significant change  
in all directions

Slide credit: Alyosha Efros



63

63

## Corners versus edges



$$\begin{aligned}\sum I_x^2 &\rightarrow \text{Large} \\ \sum I_y^2 &\rightarrow \text{Large}\end{aligned}$$

Corner



$$\begin{aligned}\sum I_x^2 &\rightarrow \text{Small} \\ \sum I_y^2 &\rightarrow \text{Large}\end{aligned}$$

Edge



$$\begin{aligned}\sum I_x^2 &\rightarrow \text{Small} \\ \sum I_y^2 &\rightarrow \text{Small}\end{aligned}$$

Nothing



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

64

64

## Harris detector formulation


Change of intensity for the shift  $[u, v]$ :

$$E(u, v) = \sum_{x, y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$


Window function

Shifted intensity

Intensity

Window function  $W(x, y) =$ 

1 in window, 0 outside



Gaussian



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Source: R. Szeliski


65

65

## Corner Detection by Auto-correlation

Change in appearance of window  $w(x,y)$  for shift  $[u,v]$ :

$$E(u, v) = \sum_{x,y} w(x, y) [I(x+u, y+v) - I(x, y)]^2$$




66

## Corner Detection by Auto-correlation

Change in appearance of window  $w(x,y)$  for shift  $[u,v]$ :

$$E(u, v) = \sum_{x,y} w(x, y) [I(x+u, y+v) - I(x, y)]^2$$



67

## Corner Detection by Auto-correlation

Change in appearance of window  $w(x,y)$  for shift  $[u,v]$ :

$$E(u,v) = \sum_{x,y} w(x,y) [I(x+u, y+v) - I(x, y)]^2$$

We want to discover how  $E$  behaves for small shifts

But this is **very slow** to compute naively.

$O(\text{window\_width}^2 * \text{shift\_range}^2 * \text{image\_width}^2)$

$O(11^2 * 11^2 * 600^2) = 5.2 \text{ billion of these}$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

68

68



## Corner Detection by Auto-correlation

Change in appearance of window  $w(x,y)$  for shift  $[u,v]$ :

$$E(u,v) = \sum_{x,y} w(x,y) [I(x+u, y+v) - I(x, y)]^2$$

We want to discover how  $E$  behaves for small shifts

But we know the response in  $E$  that we are looking for – **strong peak**. → Approximation



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

69

69

## Harris detector formulation

- This measure of change can be approximated by:

$$E(u, v) \approx [u \ v] M \begin{bmatrix} u \\ v \end{bmatrix}$$

where  $M$  is a  $2\times 2$  matrix computed from image derivatives:

$$M = \sum_{x,y} w(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

↑  
Sum over image region – the area  
we are checking for corner

$$M = \begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} = \sum \begin{bmatrix} I_x \\ I_y \end{bmatrix} [I_x \ I_y]$$

Slide credit: Rick Szeliski



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

75

75

## What does this matrix reveal?

- First, let's consider an axis-aligned corner:

$$M = \begin{bmatrix} \sum I_x^2 & \sum I_x I_y \\ \sum I_x I_y & \sum I_y^2 \end{bmatrix} = \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix}$$






Image  $I$



$I_x$



$I_y$



$I_x I_y$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: David Jacobs

76

76

## What does this matrix reveal?

- First, let's consider an axis-aligned corner:

$$M = \begin{bmatrix} \sum I_x^2 & \sum I_x I_y \\ \sum I_x I_y & \sum I_y^2 \end{bmatrix} = \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix}$$


- This means:
  - Dominant gradient directions align with  $x$  or  $y$  axis
  - If either  $\lambda$  is close to 0, then this is not a corner, so look for locations where both are large.
- What if we have a corner that is not aligned with the image axes?



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: David Jacobs

77


77

## General case

- Since  $M$  is symmetric, we have  $M = R^{-1} \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix} R$

(Eigenvalue decomposition)

- We can visualize  $M$  as an ellipse with axis lengths determined by the eigenvalues and orientation determined by a rotation matrix  $R$



adapted from Darya Frolova, Denis Simakov

78




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

78

## Interpreting the eigenvalues

- Classification of image points using eigenvalues of  $M$ :



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


Slide credit: Kristen Grauman

79

79

## Corner response function

$$\theta = \det(M) - \alpha \text{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha(\lambda_1 + \lambda_2)^2$$



- Fast approximation
  - Avoid computing the eigenvalues
  - $\alpha$ : constant (0.04 to 0.06)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: Kristen Grauman

80


80

## Window Function $w(x,y)$

$$M = \sum_{x,y} w(x,y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

- Option 1: uniform window

– Sum over square window




1 in window, 0 outside

$$M = \sum_{x,y} \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

– Problem: not rotation invariant

- Option 2: Smooth with Gaussian

– Gaussian already performs weighted sum



– Result is rotation invariant

$$M = g(\sigma) * \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide credit: Bastian Leibe

81


81

## Summary: Harris Detector [Harris88]

- Compute second moment matrix (autocorrelation matrix)

$$M(\sigma_I, \sigma_D) = g(\sigma_I) * \begin{bmatrix} I_x^2(\sigma_D) & I_x I_y(\sigma_D) \\ I_x I_y(\sigma_D) & I_y^2(\sigma_D) \end{bmatrix}$$


1. Image derivatives



2. Square of derivatives



3. Gaussian filter  $g(\sigma)$



- Compute corner response

4. Cornerness function - two strong eigenvalues

$$\begin{aligned} \theta &= \det[M(\sigma_I, \sigma_D)] - \alpha[\text{trace}(M(\sigma_I, \sigma_D))]^2 \\ &= g(I_x^2)g(I_y^2) - [g(I_x I_y)]^2 - \alpha[g(I_x^2) + g(I_y^2)]^2 \end{aligned}$$



5. Perform non-maximum suppression



C.Harris and M.Stephens, "A Combined Corner and Edge Detector," Proceedings of the 4th Alvey Vision Conference: pages 147—151, 1988.

Slide credit: Krystian Mikolajczyk

82

82

## Harris Detector: Workflow




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide adapted from Darya Frolova, Denis Simakov

83

83

## Harris Detector: Workflow

computer corner responses  $\theta$ 

SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide adapted from Darya Frolova, Denis Simakov

84

84

## Harris Detector: Workflow

Take points where  $\theta > \text{threshold}$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide adapted from Darya Frolova, Denis Simakov

85

## Harris Detector: Workflow

Take only the local maxima of  $\theta$ , where  $\theta > \text{threshold}$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide adapted from Darya Frolova, Denis Simakov

86

86

## Harris Detector: Workflow

Resulting Harris points




Slide adapted from Darya Frolova, Denis Simakov


87

87

## Harris Detector – Responses [Harris88]



Effect: A very precise corner detector.



Slide credit: Krystian Mikolajczyk

88

88

## Harris Detector: Properties

- Translation invariance?



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


Slide credit: Kristen Grauman

89

89

## Harris Detector: Properties

- Translation invariance
- Rotation invariance?



Ellipse rotates but its shape (i.e.  
eigenvalues) remains the same

*Corner response  $\theta$  is invariant to image rotation*

Slide credit: Kristen Grauman




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

90

90

## Harris Detector: Properties

- Translation invariance
- Rotation invariance
- Scale invariance?




Slide credit: Kristen Grauman

## Scale invariance: how to?

- Exhaustive search
- Invariance
- Robustness

## Exhaustive search

- Multi-scale approach



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


Slide adapted from T. Tuytelaars ECCV 2006 tutorial

93

93

## Invariance

- Extract patch from each image individually



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide adapted from T. Tuytelaars ECCV 2006 tutorial

94

94


## Automatic scale selection

- Solution:

- Design a function on the region, which is “scale invariant” (*the same for corresponding regions, even if they are at different scales*)

Example: average intensity. For corresponding regions (even of different sizes) it will be the same.

- For a point in one image, we can consider it as a function of region size (patch width)



95


## Automatic scale selection

- Common approach:

Take a local maximum of this function

Observation: region size, for which the maximum is achieved, should be *invariant* to image scale.

Important: this scale invariant region size is found in each image **independently**!



96

## Automatic Scale Selection



$$f(I_{i_1 \dots i_m}(x, \sigma)) = f(I_{i_1 \dots i_m}(x', \sigma'))$$

Same operator responses if the patch contains the same image up to scale factor.

K. Grauman, B. Leibe




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

97


97

## Example

Function responses for increasing scale (scale signature)



$$f(I_{i_1 \dots i_m}(x, \sigma))$$



$$f(I_{i_1 \dots i_m}(x', \sigma))$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


K. Grauman, B. Leibe

98

98

## Example


Function responses for increasing scale (scale signature)



99

## Example


Function responses for increasing scale (scale signature)



100

## Example


Function responses for increasing scale (scale signature)



101

## Example


Function responses for increasing scale (scale signature)



102

## Scale Invariant Detection

- A “good” function for scale detection:  
has one stable sharp peak



- For usual images: a good function would be one which responds to contrast (sharp local intensity change)



103

## What is a useful signature function?

- Functions for determining scale  $f = \text{Kernel} * \text{Image}$

Kernels:

$$L = \sigma^2 (G_{xx}(x, y, \sigma) + G_{yy}(x, y, \sigma))$$


(Laplacian)

$$DoG = G(x, y, k\sigma) - G(x, y, \sigma)$$

(Difference of Gaussians)

where Gaussian

$$G(x, y, \sigma) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{x^2+y^2}{2\sigma^2}}$$




Note: both kernels are invariant to scale and rotation



104

## What is a useful signature function?

- Laplacian-of-Gaussian = “blob” detector



Source: K. Grauman, B. Leibe




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

105

## Characteristic scale

- We define the **characteristic scale** as the scale that produces **peak of Laplacian response**



T. Lindeberg (1998). ["Feature detection with automatic scale selection."](#) *IJCV* 30 (2): pp 77–116.





SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Source: Lana Lazebnik

106

## Laplacian-of-Gaussian (LoG)

- Interest points:  
Local maxima in scale space of LoG



⇒ List of  
( $x, y, \sigma$ )

Source: K. Grauman, B. Leibe



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

107

## Example: Scale-space blob detector



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Source: Lana Lazebnik

108

## Example: Scale-space blob detector



$\sigma = 11.9912$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Source: Lana Lazebnik

109

## Example: Scale-space blob detector




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Source: Lana Lazebnik

110

## Alternative approach

Approximate LoG with Difference-of-Gaussian (DoG).




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

111

## Alternative approach

- Approximate LoG with Difference-of-Gaussian (DoG):
  - 1. Blur image with  $\sigma$  Gaussian kernel
  - 2. Blur image with  $k\sigma$  Gaussian kernel
  - 3. Subtract 2. from 1.

Small  $k$  gives a closer approximation to LoG, but usually we want to build a scale space quickly out of this.  $k = 1.6$  gives an appropriate scale space,  $k = \sqrt{2}$




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Source: K. Grauman, B. Leibe

112

## Find local maxima in position-scale space of DoG





113

## Harris-Laplacian

- Harris-Laplacian<sup>1</sup>

*Find local maximum of:*

- Harris corner detector in space  
(image coordinates)
- Laplacian in scale



Characteristic scale  
<sup>1</sup>K.Mikolajczyk, C.Schmid. "Indexing Based on Scale Invariant Interest Points". ICCV 2001  
<sup>2</sup>D.Lowe. "Distinctive Image Features from Scale-Invariant Keypoints". IJCV 2004

114


## Scale Invariant Detectors

115

- **Harris-Laplacian<sup>1</sup>**

*Find local maximum of:*


- Harris corner detector in space (image coordinates)
- Laplacian in scale



- **SIFT (D.Lowe)<sup>2</sup>**

*Find local maximum of:*

- Difference of Gaussians in space and scale



<sup>1</sup> K.Mikolajczyk, C.Schmid. "Indexing Based on Scale Invariant Interest Points". ICCV 2001

<sup>2</sup> D.Lowe. "Distinctive Image Features from Scale-Invariant Keypoints". IJCV 2004



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

115

## DoG (SIFT) keypoint Detector

- DoG at multi-octaves
- Extrema detection in scale space
- Keypoint location
  - Interpolation
  - Removing instable points
- Orientation Assignment




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

116

116

## DoG (SIFT) Detector

- DoG at multi-octaves




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

117

117

## DoG (SIFT) Detector

- Scale-Space Extrema Choose all extrema within 3x3x3 neighborhood



X is selected if it is larger or smaller than all 26 neighbors  
(its 8 neighbors in the current image and 9 neighbors  
each in the scales above and below)





SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

118

118

## DoG (SIFT) Detector

- Orientation assignment
  - Create histogram of local gradient directions at selected scale
  - Assign canonical orientation at peak of smoothed histogram
- Each key specifies stable 2D coordinates  
**(x, y, scale,orientation)**



If 2 major orientations, use both.

## Example of keypoint detection



(a)



(b)




(c)



(d)

- (a) 233x189 image
- (b) 832 DOG extrema
- (c) 729 left after peak value threshold
- (d) 536 left after testing ratio of principle curvatures (removing edge responses)

## DoG (SIFT) Detector



A SIFT keypoint : { $x, y, \text{scale}, \text{dominant orientation}$ }



Source: [Distinctive Image Features from Scale-Invariant Keypoints](#) – IJCV 2004

121


121

## Scale Invariant Detectors

- Experimental evaluation of detectors w.r.t. scale change

Repeatability rate:

$$\frac{\# \text{ correspondences}}{\# \text{ possible correspondences}}$$



K.Mikolajczyk, C.Schmid. "Indexing Based on Scale Invariant Interest Points". ICCV 2001



Slide credit: CS131 -Juan Carlos Niebles and Ranjay Krishna

122

## Many existing detectors available

- Hessian & Harris [Beaudet '78], [Harris '88]
- Laplacian, DoG [Lindeberg '98], [Lowe '99]
- Harris-/Hessian-Laplace [Mikolajczyk & Schmid '01]
- Harris-/Hessian-Affine [Mikolajczyk & Schmid '04]
- EBR and IBR [Tuytelaars & Van Gool '04]
- MSER [Matas '02]
- Salient Regions [Kadir & Brady '01]
- Others...
  
- *Those detectors have become a basic building block for many recent applications in Computer Vision.*



Slide credit: Bastian Leibe

123

## Feature extraction

- Global features
- Local features
  - Interest point detector
  - Local descriptor
  - Matching



124


124

## Local Descriptor

- Compact, good representation for local information
- Invariant
  - Geometric transformations: rotation, translation, scaling,..
  - Camera view change
  - Illumination
- Exemples
  - SIFT, SURF([Speeded Up Robust Features](#)), [PCA-SIFT](#), ...
  - LBP, BRISK, MSER and FREAK, ...

## Invariant local features

- Image content is transformed into local feature coordinates that are invariant to translation, rotation, scale, and other imaging parameters



Following slides credit: CVPR 2003 Tutorial on **Recognition and Matching Based on Local Invariant Features** David Lowe

## Advantages of invariant local features



- **Locality:**
  - features are local, so robust to occlusion and clutter (no prior segmentation)
- **Distinctiveness:**
  - individual features can be matched to a large database of objects
- **Quantity:**
  - many features can be generated for even small objects
- **Efficiency:**
  - close to real-time performance
- **Extensibility:**
  - can easily be extended to wide range of differing feature types, with each adding robustness



127


## Becoming rotation invariant

- We are given a keypoint and its scale from DoG
- We will select a **characteristic orientation** for the keypoint (based on the most prominent gradient there)
- We will describe all features **relative** to this orientation



128

## SIFT descriptor formation



- Use the blurred image associated with the keypoint's scale
- Take image gradients over the keypoint neighborhood.
- To become rotation invariant, rotate the gradient **directions AND locations** by (-keypoint orientation)
  - Now we've cancelled out rotation and have gradients expressed at locations **relative** to keypoint orientation  $\theta$
  - We could also have just rotated the whole image by  $-\theta$ , but that would be slower.


Source: Distinctive Image Features from Scale-Invariant Keypoints – IJCV 2004  
[http://campar.in.tum.de/twiki/pub/Chair/TeachingWs13TDCV/feature\\_descriptors.pdf](http://campar.in.tum.de/twiki/pub/Chair/TeachingWs13TDCV/feature_descriptors.pdf)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

129

## SIFT descriptor formation



- Using precise gradient locations is fragile. We'd like to allow some "slop" in the image, and still produce a very similar descriptor
- Using Gaussian filter : to **avoid sudden changes** in the descriptor with small changes in the position of the window, and to give **less emphasis to gradients that are far** from the center of the descriptor, as these are most affected by misregistration errors
- Create array of orientation histograms (a 4x4 array is shown)

SIFT: Distinctive Image Features from Scale-Invariant Keypoints – IJCV 2004


Image: Ashish A Gupta, PhD thesis 2013



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

130

## SIFT descriptor formation



- Put the rotated gradients into their local orientation histograms
  - A local orientation histogram has  $n$  bins (e.g. 8 as shown).
  - To avoid all boundary affects in which the descriptor **abruptly changes** as a sample shifts smoothly from being within one histogram to another or from one orientation to another
    - interpolation is used to distribute the value of each gradient sample into adjacent histogram bins
    - Also, scale down **gradient contributions** for gradients far from the bin center: a weight of  $1-d$
- The SIFT authors found that best results were with **8 orientation** bins per histogram and **and a 4x4 histogram array** → a SIFT descriptor: vector of 128 values



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Image: Ashish A Gupta, PhD thesis 2013

131

## SIFT descriptor formation

- Adding robustness to **illumination changes**:
  - The descriptor is made of gradients (differences between pixels)
    - **already invariant to changes in brightness** (e.g. adding 10 to all image pixels yields the exact same descriptor)
  - A higher -contrast photo will increase the magnitude of gradients linearly
    - to correct for contrast changes, **normalize the vector** (scale to length 1.0)
  - Very large image gradients are usually from unreliable 3D illumination effects (glare, etc)
    - to reduce their effect, **clamp all values** in the vector to  $b \leq 0.2$  (an experimentally tuned value). Then normalize the vector again.
- Result is a vector which is fairly invariant to illumination changes



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

SIFT: Distinctive Image Features from Scale-Invariant Keypoints – IJCV 2004

Image: Ashish A Gupta, PhD thesis 2013

132

# SIFT

- Extraordinarily robust matching technique
  - Can handle changes in viewpoint: up to about 60 degree out of plane rotation
  - Can handle significant changes in illumination
    - Sometimes even day vs. night (below)
  - Fast and efficient—can run in real time



Steve Seitz



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

133

## Sensitivity to number of histogram orientations




Figure 8: This graph shows the percent of keypoints giving the correct match to a database of 40,000 keypoints as a function of width of the  $n \times n$  keypoint descriptor and the number of orientations in each histogram. The graph is computed for images with affine viewpoint change of 50 degrees and addition of 4% noise.




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

134

## Feature stability to noise

- Match features after random change in image scale & orientation, with differing levels of image noise
- Find nearest neighbor in database of 30,000 features



David G. Lowe, "Distinctive image features from scale-invariant keypoints," IJCV, 60, 2 (2004), pp. 91-110



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

135

## Feature stability to affine change

- Match features after random change in image scale & orientation, with 2% image noise, and affine distortion
- Find nearest neighbor in database of 30,000 features




Figure 9: This graph shows the stability of detection for keypoint location, orientation, and final matching to a database as a function of affine distortion. The degree of affine distortion is expressed in terms of the equivalent viewpoint rotation in depth for a planar surface.




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

136

## Distinctiveness of features


- Vary size of database of features, with 30 degree affine change, 2% image noise
- Measure % correct for single nearest neighbor match



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

137

## SIFT Keypoint Descriptor: summary



Source: [Distinctive Image Features from Scale-Invariant Keypoints](#) – IJCV 2004  
[http://campar.in.tum.de/twiki/pub/Chair/TeachingWs13TDCV/feature\\_descriptors.pdf](http://campar.in.tum.de/twiki/pub/Chair/TeachingWs13TDCV/feature_descriptors.pdf)

138

138

## Other detectors and descriptors

Popular features: SURF, HOG, SIFT

[http://campar.in.tum.de/twiki/pub/Chair/TeachingWs13TDCV/feature\\_descriptors.pdf](http://campar.in.tum.de/twiki/pub/Chair/TeachingWs13TDCV/feature_descriptors.pdf)

Summary some local features:

[http://www.cse.iitm.ac.in/~vplab/courses/CV\\_DIP/PDF/Feature\\_Detectors\\_and\\_Descriptors.pdf](http://www.cse.iitm.ac.in/~vplab/courses/CV_DIP/PDF/Feature_Detectors_and_Descriptors.pdf)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

139

139

## Feature extraction

- Global features
- **Local features**
  - Interest point detector
  - Local descriptor
  - Matching



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

140

140

## Feature matching

Given a feature in  $I_1$ , how to find the best match in  $I_2$ ?

1. Define distance function that compares two descriptors
  - Use L1, L2, cosine, Mahalanobis,... distance
2. Test all the features in  $I_2$ , find the one with min distance

OpenCV:

- Brute force matching
- Flann Matching: Fast Library for Approximate Nearest Neighbors  
[Muja and Lowe, 2009]

*Marius Muja and David G Lowe. Fast approximate nearest neighbors with automatic algorithm configuration. In VISAPP (1), pages 331–340, 2009*



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

141

## Feature matching

- How to define the difference between two features  $f_1, f_2$ ?
  - Simple approach: use only distance value  $d(f_1, f_2)$ 
    - → can give good score to very ambiguous matches
  - Better approaches: add additional constraints
    - Radio of distance
    - Spatial constraints between neighborhood pixels
    - Fitting the transformation, then refine the matches (RANSAC)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

142

## Feature matching

- Simple approach: use distance value  $d(f_1, f_2)$   
→ can give good score to very ambiguous matches



 SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

143

## Feature matching

- Better approaches: ratio of distance =  $d(f_1, f_2) / d(f_1, f_2')$ 
  - $f_2$  is best match to  $f_1$  in  $I_2$ ;
  - $f_2'$  is 2nd best SSD match to  $f_1$  in  $I_2$
  - An ambiguous/bad match will have ratio close 1
  - Look for unique matches which have low ratio



144

## Ratio of distances reliable for matching




Figure 11: The probability that a match is correct can be determined by taking the ratio of distance from the closest neighbor to the distance of the second closest. Using a database of 40,000 keypoints, the solid line shows the PDF of this ratio for correct matches, while the dotted line is for matches that were incorrect.




David G. Lowe, "Distinctive image features from scale-invariant keypoints," IJCV, 60, 2 (2004), pp. 91-110

145

## Feature matching

- Better approaches: Spatial constraints between neighborhood pixels



146

## Feature matching

- Better approaches: fitting the transformation (RANSAC alg.)

- Fitting 2D transformation matrix

- Six variables

- Each point give two equations
- → at least three points

- Least squares

$$H = \begin{bmatrix} h_{11} & h_{12} & h_{13} \\ h_{21} & h_{22} & h_{23} \\ 0 & 0 & 1 \end{bmatrix}$$

- RANSAC: refinement of matches

- Compute error:


$$\left\| \begin{bmatrix} x_2 \\ y_2 \\ 1 \end{bmatrix} - H \begin{bmatrix} x_1 \\ y_1 \\ 1 \end{bmatrix} \right\|_2$$



147


## Evaluating the results

How can we measure the performance of a feature matcher?



148

## True/false positives



The distance threshold affects performance

- True positives = # of detected matches that are correct
  - Suppose we want to maximize these—how to choose threshold?
- False positives = # of detected matches that are incorrect
  - Suppose we want to minimize these—how to choose threshold?



149

## Image matching



- How to define the distance between 2 images  $I_1, I_2$ ?
  - Using global features: easy
 
$$d(I_1, I_2) = d(\text{feature of } I_1, \text{feature of } I_2)$$
  - Using local features:
    - Voting strategy
    - Solving an optimization problem (time consuming)
    - Building a "global" feature from local features: BoW (bag-of-words, bag-of-features), VLAD, ..



150

150

## Voting strategy



- Distance faible  $\leq \varepsilon$
- Distance plus élevée  $\leq \varepsilon$
- Distance  $> \varepsilon$

The similarity between 2 images is based on **the number of matches**

Source: Modified from slides of Valérie Gouet-Brunet



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

151

151

## Optimization problem

- *Transportation problem*

$I_1 : \{(r_i, w_i), i=1, N\}$  Provider

$I_2 : \{(r'_j, w_j), j=1, M\}$  Consommateur


$d(I_1, I_2) = ???$

$$d(I_1, I_2) = \min \sum_i \sum_j f_{ij} \times d(r_i, r'_j)$$

$$f_{ij} \geq 0$$

$$\sum_i f_{ij} \leq w_j, \sum_j f_{ij} \leq w_i$$

$$\sum_i \sum_j f_{ij} = \min(\sum_i w_i, \sum_j w_j)$$



$$d_{EMD}(I_1, I_2) = \frac{\sum_i \sum_j f_{ij}^* \times d(r_i, r'_j)}{\sum_i \sum_j f_{ij}^*}$$



<http://vellum.cz/~mikc/oss-projects/CarRecognition/doc/dp/node29.html>

152

152

## Bag-of-words

- Local feature ~ a word
- An image ~ a document
- Apply a technique for textual document representation: vector model



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


153

153

## Visual Vocabulary ...



1. Extracting local features from a set of images



2. Building visual vocabulary (dictionary) using a clustering method



3. An image is represented by a bag of words  
→ can be represented by tf.idf vector




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

154

154

## Bag of words: outline

1. Extract features
2. Learn “visual vocabulary”
3. Quantize features using visual vocabulary
4. Represent images by frequencies of “visual words”



155



156