

1

A white slide with a thin black border. At the top, the word "Content" is written in blue. Below it, a bulleted list in black text includes "Segmentation" and "Object detection". At the bottom, there is a small logo on the left with the text "ĐẠI HỌC" and "BÁCH KHOA" above "SOICT", and "25" to its right. To the right of the logo, the text "SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY" is written in red. A horizontal red line is positioned at the bottom of the slide.

2



Introduction

- Purpose:
 - to partition an image into meaningful regions with respect to a particular application
- Goal:
 - to cluster pixels into salient image regions, i.e., regions corresponding to individual surfaces, objects, or natural parts of objects.
- The segmentation is based on the feature measurements taken from the image:
 - grey level, color, texture, depth or motion...



3

Introduction



Source : Jean-Christophe Baillie, ENSTA, uei.ensta.fr/baillie/assets/E5322%20-%20Segmentation.ppt



4

4

Introduction

- Entity can be extracted from images using mask



Source : Pascal Bertolino, Cours de Traitement d'images. LIS, INPG (France)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

5

Approaches for image segmentation

- Segmentation is usually based on:
 - discontinuities: edges
 - sudden changes, borders (frontiers) between regions...
 - homogeneous zones: regions
 - same color, texture, intensity, ...




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

6

6

Approaches for image segmentation

- Pixel-based approach
- Region-based approach:
 - look for **homogeneous** areas in the image
- Edge-based approach :
 - look for **discontinuities** in the image
 - **A closed edge is equivalent to a region**
- Hybrid (Dual) approach (region + edge)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

7

7

Examples

Original images



Segmented images



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

8

8

Pixel-based approach

- Pixel-based approach
 - Thresholding
 - Clustering
- It is not a region segmentation technique
 - But we often in segmentation looking for regions
 - Need some post-processing

Thresholding


- Thresholding is a *simple and popular* method for object segmentation in digital images
- Thresholding can be
 - *Global*: one threshold for the whole image
 - *Local*: one threshold for a part of the image
 - *Adaptive*: one threshold adjusted according to each image or each image part

Basic global thresholding

- Basic thresholding (2 classes) – main idea :
 - IF value(pixel) \geq threshold THEN value(pixel) = 1 (or 255)
 - IF value(pixel) $<$ threshold THEN value(pixel) = 0
- The result is a binary image
- It is also possible to use n thresholds to split the image in $n+1$ classes
- Problem: choosing the threshold(s)!

Basic global thresholding



- Find the threshold on histogram of gray level intensity (histogram thresholding)



$$g(x, y) = \begin{cases} 0, & f(x, y) < T \\ 1, & f(x, y) \geq T \end{cases}$$

Basic global thresholding

- Threshold value: not difficult if
 - Controled environment
 - Industrial applications




Multi-thresholds

- **n thresholds** to split the image in **n+1** classes:
 - IF $\text{value(pixel)} < \text{threshold_1}$
 - THEN $\text{value(pixel)} = 0$
 - IF $\text{value(pixel)} \geq \text{threshold_1} \ \&\& \text{value(pixel)} < \text{threshold_2}$
 - THEN $\text{value(pixel)} = 1$
 - ...
 - IF $\text{value(pixel)} \geq \text{threshold_n}$
 - THEN $\text{value(pixel)} = n$
- Problems: **How many thresholds?**

Multi-thresholds

$$g(x,y) = \begin{cases} 0, & f(x,y) < T_1 \\ 1, & T_2 > f(x,y) \geq T_1 \\ 2, & f(x,y) \geq T_2 \end{cases}$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

15

15

Threshold value

- Global thresholding: How to find the value of the threshold **T** ?
 - Value obtained by tests
 - The mean value of gray values
 - The median value between the min gray level and the max one
 - One value balancing both sections of the histogram
 - automatic thresholding




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

16

16

Choice of thresholds (optimal)

- 2 surfaces (background and object) in an image
 - We suppose mathematical models for distributions ([gaussians](#), etc.)
 - We determine the probability of error in the classes 1 and 2 (surfaces 1 et 2)
 - We search for a threshold **T** resulting in a minimum error
 - Several methods for achieving this



Source : www.iro.umontreal.ca/~dift2730/

SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

17

17

Example: Global automatic thresholding

- One possible algorithm:
 - Choose an [initial value for the threshold T](#) (mean, median, ...)
 - We obtain 2 groups of pixels
 - G_1 where $f(x,y) \geq T$ and G_2 where $f(x,y) < T$
 - Compute the gray level means for G_1 and $G_2 \rightarrow \mu_1$ and μ_2
 - Compute a new value for T
 - $T = 1/2 (\mu_1 + \mu_2)$
 - Repeat until T is ~ constant
- There exist many other global automatic methods
 - Otsu, Kittler, K-means, ...
 - No solution on which one to use
 - Must be tested for each new application



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

18

18

Example: Otsu algorithm

- Sweep all possible threshold value for T

- For each value of T :

- Compute the mean and variance for each class


- We look for the intraclass variance

- Means: μ_1, μ_2

- Variances: σ_1^2, σ_2^2

- Intra-class variance:

$$\sigma_w^2 = P_1 * \sigma_1^2 + P_2 * \sigma_2^2$$



$$\sigma_1^2 = \frac{1}{T} \sum_{i=0}^{T-1} (h(i) - \mu_1)^2$$

$$\sigma_2^2 = \frac{1}{256-T} \sum_{i=T}^{255} (h(i) - \mu_2)^2$$

$$\mu_1 = \frac{1}{T} \sum_{i=0}^{T-1} h(i) \quad P_1 = \frac{1}{N \cdot M} \sum_{i=0}^{T-1} h(i)$$

$$\mu_2 = \frac{1}{256-T} \sum_{i=T}^{255} h(i) \quad P_2 = \frac{1}{N \cdot M} \sum_{i=T}^{255} h(i)$$

- The optimal threshold is the one with the minimum value for σ_w^2

- It is based on the idea that classes are well defined and well grouped

Source : www.iro.umontreal.ca/~dift2730/



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


19

19

Example: Otsu algorithm

- Threshold found by the algorithm:

- $T = 125$




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

20

20


Global threshold: problem

- Problem:
 - Global thresholding cannot be used in that case
 - Solution: adaptive local thresholding




Example of adaptive thresholding

- Split the image in sub-images and process each sub-image with its own threshold
- The main decision is to choose the size of the sub-images
- Before processing each sub-image, check the variance to make sure that the sub-image contains two regions, and not only one.
 - Example: no thresholding for a sub-image if variance<100



Example of adaptive thresholding



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


23

23

Example of adaptive thresholding

a
b

FIGURE 10.37
 (a) Original image. (b) Image segmented by local thresholding.
 (Courtesy of IBM Corporation.)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

24

24

Clustering-based segmentation

- Image is considered as a set of N image pixels.
- Attributes (property) of the pixels
 - gray level of single-band gray tone images,
 - color values of three-band color images: (r, g, b)
 - values of multi-band images, ...
- Based on the similar attribute, pixels classification operators partition an image into homogeneous regions.
 - Clustering provides a grouping of the pixels that is dependent on their values in the image but not necessarily on their locations in the image unless location is a specified property
 - Classifier provide the pixel classes which should be homogeneous regions.



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

25

25

Clustering algorithms

- **Image segmentation approaches including:**
 - Feature space clustering approaches
 - Graph-based approaches
- **Clustering algorithms:**
 - K-Means clustering
 - Mean-Shift Clustering
 - Expectation-Maximization Clustering
 - Watershed Segmentation
 - Graph Cuts (Spectral clustering)
 - Normalized cuts
 - ...




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

26

26


K-means Clustering

- Let $X = \{p_1, \dots, p_N\}$ be a set of N image pixels:
 - $V(p_i)$: the property vector associated with pixel p_i
 - The clustering algorithm is to partition the image into K clusters (K regions)
- The **K-means** algorithm:
 - Initialization step: An initial property vector of each class C_k is chosen randomly from the set of all property vector, note $\mu_k(0)$
 - Interactive step: Assignment of image pixels to K clusters



27


27



28

28

K-means Clustering



Input image

K-means on gray level

K-means on color

Source : D.A. Forsyth and J. Ponce. Computer Vision : A Modern Approach. Prentice-Hall, 2002.




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

29

K-means Clust

K-means on color for
11 groups



Source : D.A. Forsyth and J. Ponce. Computer Vision : A Modern Approach. Prentice-Hall, 2002.




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


30

30

Example



Example



Pixel-based approach: Pros & cons

- Pros
 - Simple, fast
- Cons: thresholding is mainly an operation on pixels
 - It does **not give connected regions** → can add more features
 - we need to « clean » the results
 - erase **lonely pixels**, keep regions
- Other segmentation methods exist
 - that can keep the integrity of regions (connected pixels)



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

33

Features for segmentation

- Intensity, Color?
- Position
- Texture
- ...



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

34

34

Segmentation as clustering

Depending on what we choose as the *feature space*, we can group pixels in different ways.

Grouping pixels based on **intensity** similarity



Feature space: intensity value (1-d)




Slide credit: Kristen Grauman

35

Segmentation as clustering

Depending on what we choose as the *feature space*, we can group pixels in different ways.

Grouping pixels based on **intensity+position** similarity



Both regions are black, but if we also include **position (x,y)**, then we could group the two into distinct segments; way to encode both **similarity & proximity**.





36

Segmentation as clustering

Depending on what we choose as the *feature space*, we can group pixels in different ways.

Grouping pixels based on **texture** similarity



Feature space: filter bank responses (e.g., 24-d)

Slide credit: Kristen Grauman



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

37

Segmentation with texture features

- Find “textons” by **clustering** vectors of filter bank outputs
- Describe texture in a window based on *texton histogram*

Image Texton map




Malik, Belongie, Leung and Shi. IJCV 2001.
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Adapted from Lana Lazebnik

38

Image segmentation example



Slide credit: Kristen Grauman



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

39

Region-based segmentation

- Finding region based on the criterion of **homogeneity** and **connectivity** of pixels (region)
 - Each region is homogeneous (i.e., uniform in terms of the pixel attributes such as intensity, color, range, or texture, etc.)
 - and connected
- **Algorithms:**
 - Region growing
 - Split and merge algorithm
 - Hierarchical clustering
 - ...



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

40

40

Region-based segmentation

- Region-based approaches provide :
 - All pixels must be assigned to regions
 - Each pixel must belong to a **single region** only
 - Each region must be **uniform**
 - Any **merged pair of adjacent regions must be non-uniform**
 - Each region must be **a connected set of pixels**
- Region-based approaches:
 - Different methods
 - Common point: **homogeneity criteria**



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

41

41

Region growing

- Start from a point (seed) and add neighbor pixels following a **given criteria**
- The seeds can be manually or automatically chosen
 - automatic seeds in very homogeneous zones for example



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

42

42

Region growing algorithm

- Algorithm:
 - Choose K random pixels in K regions
 - Use 8-connected and threshold to determine
 - Repeat a and b until almost points are K classified.
- Example illustrated:

1	1	9	9	9
1	1	9	9	9
5	1	1	9	9
5	5	5	3	9
3	3	3	3	3

1	1	9	9	9
1	1	9	9	9
5	1	1	9	9
5	5	5	3	9
3	3	3	3	3

1	1	9	9	9
1	1	9	9	9
5	1	1	9	9
5	5	5	3	9
3	3	3	3	3




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

43

43

Region growing with multi-seeds



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

44

44

Example

Simulation
of region
growing
(90% pixels)





SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

45

45

Split-and-merge

- Split (step 1)
 - Recursively split all non-homogeneous regions following a given criteria
 - variance, max-min, ...
 - Dividing one region gives 4 subregions
 - Subregion attributes are re-computed
- Merge (step 2)
 - Group all homogeneous adjacent regions following a given criteria



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

46

46

Split-and-merge: split

0	1	0	0	7	7	7	7
1	0	2	2	7	7	7	7
0	2	2	2	7	7	7	7
4	4	2	2	7	7	7	7
0	0	1	1	3	3	7	7
1	1	2	2	3	7	7	7
2	4	3	0	5	7	7	7
2	3	3	5	5	0	7	7

0	1	0	0	7	7	7	7
1	0	2	2	7	7	7	7
0	2	2	2	7	7	7	7
4	4	2	2	7	7	7	7
0	0	1	1	3	3	7	7
1	1	2	2	3	7	7	7
2	4	3	0	5	7	7	7
2	3	3	5	5	0	7	7

0	1	0	0	7	7	7	7
1	0	2	2	7	7	7	7
0	2	2	2	7	7	7	7
4	4	2	2	7	7	7	7
0	0	1	1	3	3	7	7
1	1	2	2	3	7	7	7
2	4	3	0	5	7	7	7
2	3	3	5	5	0	7	7

0	1	0	0	7	7	7	7
1	0	2	2	7	7	7	7
0	2	2	2	7	7	7	7
4	4	2	2	7	7	7	7
0	0	1	1	3	3	7	7
1	1	2	2	3	7	7	7
2	4	3	0	5	7	7	7
2	3	3	5	5	0	7	7

Image initiale

Split1

Split 2

split 3

*Homogeneity = criteria on the variance
(or max-min <= 1)*

Source : Jean-Christophe Baillie. Cours de segmentation. ENSTA ParisTech (France).

47

Split-and-merge: merge

Phase 1: Create homogeneous zones (split)
Phase 2: Group homogeneous zone (merge)

Quadtree

Connect homogeneous adjacent regions

Source : Jean-Christophe Baillie. Cours de segmentation. ENSTA ParisTech (France)

48

Split-and-merge



49

Edge-based segmentation

- Finding region based on edges




- **Algorithms:**

- Basic Edge Detection
- The Marr-Hildreth edge detector (LoG)
- Short response Hilbert transform (SRHLT)
- Watersheds


50

Watershed segmentation

- We consider the image as a 3D shape using the gray level as the third dimension



2D image





Visualization in 3D

Source : <http://www.gpa.etsmtl.ca/cours/gpa669/>

51


Watershed segmentation

- After we reverse (upside down) the values to create « holes » in the shape



Watershed segmentation

- Next we fill in the holes with water




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

53

53


Watershed segmentation




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

54

54



55



56

Segmentation – advices

- Image segmentation
 - No method works for all images
 - No miracle, no warranty!
- One of the main problem is to define the **goal of segmentation**:
 - What exactly are we looking for in the image?
 - Global regions or small details?
 - Presence or not of persons details in the face?
- It is good to think in advance **what we will do with this segmentation results**
 - This helps to define the level of precision needed

Segmentation – advices

- Image Pre-processing:
 - **good selection** of sensors and energy source, and controlled image acquisition conditions help to make segmentation easier and more efficient
- For some applications, we realize today that we can **avoid to segment** the image. It is often better like this.

Limits of segmentation

Image segmentation alone cannot find all image objects as we can interpret them



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

59

Object detection




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

60

60

Object Detection

- **Problem:** Detecting and localizing generic objects from various categories, such as cars, people, etc.
- **Challenges:**
 - Illumination,
 - viewpoint,
 - deformations,
 - Intra-class variability



Window-based generic object detection


Basic pipeline

Generic category recognition: basic framework

- Build/train object model
 - Choose a representation
 - Learn or fit parameters of model / classifier
- Generate candidates in new image
- Score the candidates

Window-based models Building an object model

Given the representation, train a binary classifier



Window-based models

Generating and scoring candidates



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide: Kristen Grauman

65

65

Window-based models

Generating and scoring candidates

- Slide through the image and check if there is an object at every location



YES!! Person match found



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

66

66

Window-based models

Generating and scoring candidates

- But what if we were looking for buses?

No bus found!




- We will never find the object if we don't choose our window size wisely!

Bus found



Multi-scale sliding window

- Work with multiple size windows
- Create a feature pyramid




Window-based object detection: recap

Training:

1. Obtain training data
2. Define features
3. Define classifier

Given new image:

1. Slide window
2. Score by classifier



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Slide: Kristen Grauman


69

69

Features

70

- HOG



- Bags of visual words

Bag of 'words'



- Haar features, ...




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


70

Discriminative classifier construction


Nearest neighbor




Neural networks




Support Vector Machines



Boosting



Conditional Random Fields




71

71

Boosting classifiers

Boosting intuition

Weak
Classifier 1



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


Slide credit: Paul Viola

73

73

Boosting illustration

Weights
Increased




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

74

74

Boosting illustration




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

75

75

Boosting illustration

Weights
Increased




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

76

76

Boosting illustration




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

77

77

Boosting illustration

Final classifier is
a combination of weak
classifiers



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

78

78

39

Boosting: training

- Initially, weight each training example equally
- In each boosting round:
 - Find the **weak learner** that achieves the lowest *weighted* training error
 - **Raise weights of training examples misclassified** by current weak learner
- Compute final classifier as linear combination of all weak learners
 - (weight of each learner is directly proportional to its accuracy)
- Exact formulas for re-weighting and combining weak learners **depend on the particular boosting scheme** (e.g., AdaBoost)



Slide credit: Lana Lazebnik

79

Object proposals




80

Object proposals

Main idea:

- Learn to generate category-independent regions/boxes that have **object-like** properties.
- Let object detector **search over “proposals”**, not exhaustive sliding windows





Alexe et al. Measuring the objectness of image windows, PAMI 2012

81

81

Object proposals



Multi-scale
saliency



Color
contrast



Alexe et al. Measuring the objectness of image windows, PAMI 2012

82

82

Object proposals

Edge density



(a)



(b)


Superpixel straddling




(a)



(b)



(a)



83




Alexe et al. Measuring the objectness of image windows, PAMI 2012

83

Object proposals

Yellow box: object detected
Cyan box: groundtruth




Alexe et al. Measuring the objectness of image windows, PAMI 2012

84

Deformable Part Model (DPM)


- Represents an object as a **collection of parts** arranged in a deformable configuration
- Each part represents **local appearances**
- Spring-like connections between certain pairs of parts



Fischler and Elschlager, Pictorial Structures, 1973



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY




Felzenszwalb et al., PAMI 2010

86


86

Deformable Part Model (DPM)

high scoring true positives



high scoring false positives



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

87

87

Deformable Part Model (DPM)

- References

- [Pedro F. Felzenszwalb](#) & [Daniel P. Huttenlocher](#), Pictorial Structures for Object Recognition, IJCV 2005
 - <https://www.cs.cornell.edu/~dph/papers/pict-struct-ijcv.pdf>
- P. F. Felzenszwalb, R. B. Girshick, D. McAllester, and D. Ramanan. Object detection with discriminatively trained part based models. IEEE Transactions on Pattern Analysis and Machine Intelligence, 32(9):1627–1645, 2010



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

—

88

88

Object detection: Evaluation



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY


—

89

89

Object Detection Benchmarks


- PASCAL VOC Challenge
- ImageNet Large Scale Visual Recognition Challenge (ILSVR)
 - 200 Categories for detection



- Common Objects in Context (COCO)
 - 80 Object categories



How do we evaluate object detection?



— predictions

— ground truth

True positive:


- The overlap of the prediction with the ground truth is **MORE** than a threshold value (0.5)

How do we evaluate object detection?




- predictions
- ground truth
- True positive:**
- False positive:**
- The overlap of the prediction with the ground truth is **LESS** than a threshold value (0.5)

How do we evaluate object detection?



- predictions
- ground truth
- True positive:**
- False positive:**
- False negative:**
- The objects that our model doesn't find

How do we evaluate object detection?



— predictions
— ground truth

True positive:

False positive:

False negative:

- The objects that our model doesn't find

What is a **True Negative**?



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

94

94

		Predicted 1	Predicted 0
		true positive	false negative
True 1	Predicted 1	true positive	false negative
	Predicted 0	false positive	true negative

		Predicted 1	Predicted 0
		TP	FN
True 1	Predicted 1	TP	FN
	Predicted 0	FP	TN

		Predicted 1	Predicted 0
		hits	misses
True 1	Predicted 1	hits	misses
	Predicted 0	false alarms	correct rejections

$$precision = \frac{TP}{TP + FP}$$

$$recall = \frac{TP}{TP + FN}$$




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

95

95

How do we evaluate object detection?



— predictions
— ground truth

True positive: 1
False positive: 2
False negative: 1

So what is the
- precision?
- recall?



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

96

96

Precision versus recall

- Precision:

- how many of the object detections
are correct?

$$\text{precision} = \frac{TP}{TP + FP}$$

- Recall:

- how many of the ground truth objects
can the model detect?
- True Positive Rate (TPR)

$$\text{recall} = \frac{TP}{TP + FN}$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

97

97

- In reality, our model makes a lot of predictions with varying scores between 0 and 1




— predictions
— ground truth

Here are all the boxes that are predicted with **score > 0**.

This means that our

- **Recall is perfect!**
- But our **precision is BAD!**

How do we evaluate object detection?




— predictions
— ground truth

Here are all the boxes that are predicted with **score > 0.5**

We are setting a **threshold** of 0.5

Precision – recall curve (PR curve)




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

100

100

Which model is the best?




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

101

101

Which model is the best?



- **Area under curve (AUC), average precision (AP)**
- **F1-score** (highest value at optimal confidential score)




SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

102

102

Which model is the best?



AP: The metric calculates the average precision (AP) for each class individually across all of the IoU thresholds

$$AP = \frac{1}{11} \sum_{r \in \{0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1\}} p_{inter,p}(r)$$

$$\text{mAP: the average of AP} = \frac{1}{11} (1 + 1 + 1 + 1 + 0.67 + 0.67 + 0.67 + 0.67 + 0.5 + 0.5 + 0.5) \\ \approx 0.728$$



SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

103

103

Summary

- Object recognition as classification task
 - Boosting (face detection ex)
 - Support vector machines and HOG (human detection ex)
 - Sliding window search paradigm
 - Pros and cons
 - Speed up with attentional cascade
 - Object proposals, proposal regions as alternative



104

104

DAU HOC
BACH KHOA

25
SOICT

VIEN CONG NGHE THONG TIN VÀ TRUYỀN THÔNG
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Thank you for
your attention!

soict.hust.edu.vn/ fb.com/groups/soict

105