

Flash Sale Platform

v1 API Contract

Generated: 2026-09-26 20:32

Overview

The v1 API provides endpoints for waiting room management, ticket reservation, payment processing, and status tracking. All endpoints require authentication (Bearer token) except for webhooks. Responses use JSON. Money is represented in paise (1/100th of currency unit).

Base URL

<https://api.flashsale.example.com/v1>

Authentication

All endpoints require an **Authorization** header with a Bearer token. Exception: **POST /payments/webhook** uses signature verification instead.

Idempotency

Mutation endpoints (POST) accept **Idempotency-Key** header. Same key + same body = original response. Different body + same key = 422.

REST Endpoints

1. Join Queue

POST /events/{eventId}/queue

Join waiting room. Returns queue position and estimated wait time.

Response (201): queueTicket, position, estimatedWaitMinutes

Errors: 409 (already queued), 410 (sale ended), 401 (unauthorized)

2. Poll Queue Position / Get Admission Token

GET /events/{eventId}/queue/{queueTicket}

Check queue position or retrieve admission token when your turn comes.

Response (200): position, admissionToken (null if waiting), tokenExpiresAt

Errors: 404 (invalid ticket), 410 (sale ended)

3. Reserve Tickets

POST /events/{eventId}/reservations

Create a hold on tickets. Hold lasts 10 minutes. Requires valid admission token.

Body: { qty: number }

Response (201): reservationId, qty, status (HELD), holdExpiresAt, totalAmountPaise
Errors: 401 (no token), 409 (sold out), 429 (rate limited), 422 (bad qty)

4. Get Reservation Status

GET /reservations/{reservationId}

Check status of hold or order.

Response (200): reservationId, status, orderId, qty, holdExpiresAt, totalAmountPaise

Errors: 404 (not found), 401 (not your reservation)

5. Initiate Payment

POST /reservations/{reservationId}/payments

Start payment. Returns redirect URL to payment gateway.

Response (202): paymentId, status (INITIATED), redirectUrl

Errors: 409 (hold expired, already paid), 404 (not found)

6. Payment Webhook

POST /payments/webhook

Payment gateway callback (no auth). Signature verified via X-Signature header (HMAC-SHA256).

Body: paymentId, status, reservationId, amountPaise, gatewayRef, occurredAt

Response (200): { ok: true } (idempotent)

Errors: 400 (bad signature), 422 (malformed)

7. Health Checks

GET /healthz/live | GET /healthz/ready

K8s probes (no auth). Returns 200 if healthy, 503 if draining.

HTTP Status Codes

Code	Meaning	Retry?
200 OK	Request succeeded	No
201 Created	Resource created	No
202 Accepted	Processing async	No
400 Bad Request	Malformed request	No
401 Unauthorized	Invalid/missing token	No
404 Not Found	Resource missing	No
409 Conflict	Sold out / duplicate	Maybe
410 Gone	Sale ended	No
422 Unprocessable	Semantic error	No
429 Too Many Requests	Rate limited	Yes, backoff
500 Internal Error	Unexpected error	Yes, backoff
503 Unavailable	Draining	Yes