

DECLARATION OF PERFORMANCE

N.º DoP-AISOL-ICB-01-Rev1-14

Unique identification code of the product-type: 1.

ICB - Expanded Insulation Cork Board

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): 2.

See the label product

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the 3. manufacturer:

For use as thermal insulation for buildings (see EN 13170) according to the manufacturer's specifications

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Amorim Isolamentos, S.A. Rua da Corticeira, nº 66 4535-173 Mozelos - Portugal

- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: 6. System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard: 7. Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).
 - CSTB Centre Scientifique et Technique du Bâtiment, notified test laboratory nº 0679 (France), report nº HO 04-005 and nº HO 05-053
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: 8 not applicable
- Declared performance: ICB EN 13170 L2 W2 T2 CS(10)100 TR50 WS MU20 CC(0,8/0,4/10)5 9.

Essential characteristics	Performance	Harmonised technical specification		
Reaction to fire, Euroclass characteristics	Reaction to fire	Euroclass E		
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD		
Acoustic absorption index	Sound absorption	NPD		
Impact noise transmission index (for floors)	Dynamic stiffness	NPD		
	Thickness, d _L	NPD		
	Compressibility	NPD		
	Air flow resistivity	NPD		
Direct airborne sound insulation index	Air flow resistivity	NPD		
Continuous Glowing combustion	Continuous Glowing combustion	NPD		
Thermal resistance	Thermal resistance	see Table A		
	Thermal conductivity	0,040 W/m.K	EN 13170:2012	
	Thickness, d _L	T1 - T2 (d _L > 50 mm)	LIN 13170.2012	
Water permeability	Water absorption WS			
Water vapour permeability	Water vapour transmission	MU20		
Compressive strength	Compressive stress at 10% deformation	CS(10)100		
	Point load	NPD		
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	satisfy		
Durability of thermal resistance against heat,	Thermal resistance and thermal conductivity	satisfy		
weathering, ageing/degradation	Durability characteristics	satisfy		
Tensile/Flexural strength	Tensile strength perpendicular to faces	TR50		
Durability of compressive strength against ageing/degradation	Compressive creep	CC(0,8/0,4/10)5		

UNIDADE DE DISTRIBUIÇÃO: Rua da Corticeira, 66 4535-173 MOZELOS VFR – PORTUGAL Telef: +351 22 741 9100

Fax: +351 22 741 9101 Email: geral.aisol@amorim.com

UNIDADE INDUSTRIAL DE SILVES: Vale de Lama - Apartado 27 8300-999 SILVES - PORTUGAL Telef: +351 282 440 720

Fax: +351 282 440 721

UNIDADE INDUSTRIAL DE VENDAS NOVAS - SEDE: Capital Social: EUR 100.000,00 Estrada de Lavre, Km 6 – Apartado 7 7084-909 VENDAS NOVAS – PORTUGAL

Telef: +351 265 809 220 Fax: +351 265 809 221

Registo na C.R.C.P. de Vendas Novas NIF N° PT 502 863 145





Amorim Isolamentos, S.A.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

AMORIM/ISQLAMENTOS, S.A.

Administração

Carlos Manuel, Managing Director

Mozelos, July 2014

(signature)

Table A: Thermal resistance (R) in accordance with EN 13170:2012

Thickness, d _L [mm]	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
Thermal resistance [m².K/W]	0,50	0,60	0,75	0,85	1,00	1,10	1,25	1,35	1,50	1,60	1,75	1,85	2,00	2,10	2,25	2,35
Thickness, d _L [mm]	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250
Thermal resistance [m².K/W]	2,50	2,75	3,00	3,25	3,50	3,75	4,00	4,25	4,50	4,75	5,00	5,25	5,50	5,75	6,00	6,25

