Bootstrap Enhanced Scenario Optimization, a Case Study in Two-Echelon Logistics

Livio Fenga[1†] and Vittorio Maniezzo[2*†]

[1]Center for Simulation, Analytics and Modelling, University of Exeter, Exeter, EX4 4PU, UK.
[2*]Department of Computer Science, University of Bologna, Cesena, 47521, Italy.

*Corresponding author(s). E-mail(s): vittorio.maniezzo@unibo.it;
Contributing authors: L.Fenga@exeter.ac.uk;
†These authors contributed equally to this work.

Abstract

We propose a data-driven robust optimization framework for logistics, where bootstrapped forecasts define the ambiguity set to achieve improved worst-case performance.} We introduce the Bootstrap Enhanced Scenario Optimization (BESO) framework, a novel methodology for prescriptive analytics under uncertainty. BESO addresses the challenge of generating reliable demand scenarios from volatile, short, and non-stationary time series data. The core innovation lies in delegating the modeling of uncertainties to the Maximum Entropy Bootstrap (MEB) integrated with bagging, a technique that preserves the complex autocorrelation structure of empirical time series forecasts, enabling the generation of statistically coherent scenarios. We further extend MEB through an objective-augmented formulation that incorporates downstream recourse elements into the resampling mechanism. These statistically rich scenarios are then integrated into a deterministic equivalent model to derive accountable and optimized prescriptions. We demonstrate the framework's power using a real-world case study in tactical inventory allocation. Our findings, also validated against an extensive set of artificial benchmark instances, demonstrate the effectiveness of MEB-enhanced forecasting in optimization. BESO establishes a new, generalizable paradigm for robust decision-making derived from noisy univariate data series.

Keywords: Stochastic programming, Distributionally Robust Optimization, Forecasting, Maximum Entropy Bootstrap, Two-echelon logistics

1 Introduction

Decision-making under uncertainty is a pervasive challenge in operations research, particularly in complex systems such as logistics networks. Scenario-based optimization has long been used to address this challenge by capturing the variability of future events through a finite set of possible outcomes. However, the reliability of such methods depends heavily on how accurately these scenarios represent the underlying stochastic processes.

In this paper, we propose a novel method —- *Bootstrap Enhanced Scenario Optimization* (BESO) —- that integrates bootstrap-based forecasting with scenario-based linear optimization to enhance the robustness and realism of stochastic modeling. The approach can be framed within the Distributionally Robust Optimization (DRO) paradigm; however, unlike mainstream moment- or ambiguity-set-based formulations, it leverages statistical models fitted to empirical data to generate optimization-ready scenarios.

BESO introduces a twofold, decision-aware extension of the Maximum Entropy Bootstrap (MEB). First, the bootstrap objective is augmented with optimization cost components, allowing scenario generation to internalize downstream decision criteria. Second, we explicitly account for the effect of bootstrap-set cardinality on the resulting optimization outcomes, recognizing scenario size as a structural parameter shaping the effective ambiguity set. Together, these mechanisms create a feedback loop between the optimization model and the statistical resampling phase: the ambiguity set remains statistically coherent while its geometry and dispersion are partially shaped by optimization-relevant considerations. The framework is particularly suited to predictive settings where reliable historical time series are available.

The resulting data-driven methodology for empirically estimating the distribution of stochastic variables and embedding it in scenario generation for robust and stochastic optimization may offer significant advantages over standard distribution-aware approaches. Traditional methods often rely on strong assumptions about the underlying probability distribution — typically normality or other parametric forms — which may not accurately reflect the true behavior of real-world uncertainties. In contrast, data-driven techniques directly leverage historical or observed data to construct empirical distributions, capturing nuances such as asymmetry, multimodality, or heavy tails that standard models might overlook. This increased fidelity can lead to more realistic and effective scenario generation, improving both the robustness and relevance of the resulting optimization solutions. Furthermore, by adapting to the structure present in the data, data-driven approaches are naturally more flexible

and can better accommodate nonstationarities or structural changes in the stochastic environment, providing better alignment with real operational environments.

To demonstrate the practical value and performance of BESO, we apply it to a real-world two-echelon logistics network problem. In this setting, uncertain outbound freight demands must be satisfied across multiple depots. By using BESO to define demand scenarios and solve for optimal allocation decisions and related inventory requests, we show how the method improves the solution robustness compared to conventional techniques, while remaining conceptually transparent, computationally efficient and straightforward to implement.

The remainder of the paper is structured as follows: Section 2 reviews previous works related to the different research areas intersected by this study. Section 3 describes the case study that motivated our research. Section **??** and **??** present the BESO methodology in detail. Section 6 discusses the computational results, and Section 7 concludes with key insights and future research directions.

2 Literature review

The paper intersects different research threads, both in terms of the theoretical contribution and the application use case.

2.1 Predictive Prescriptions and Distributionally Robust Optimization

Stochastic programming has long served as a fundamental framework for modeling decision-making under uncertainty, primarily through expected-value models and recourse formulations (Dantzig 1955; Beale 2018). As the field matured, methods evolved to address model robustness. Robust optimization (Bertsimas and Sim 2004) proposes a deterministic reformulation considering worst-case outcomes within a defined uncertainty set. A major development is *Distributionally Robust Optimization* (DRO), which seeks decisions that are robust against the worst-case probability distribution of the uncertain parameters within a prescribed *ambiguity set* (Delage and Ye 2010).

The ambiguity set ($\mathcal{U}$) in DRO is a carefully constructed family of probability distributions that is assumed to contain the true, but unknown, distribution of the uncertain parameters. The core idea is to optimize the worst-case expected performance over all distributions within this set, thereby providing robustness against distributional uncertainty. Different DRO methodologies differ primarily in the way

this ambiguity set is defined. Delage and Ye (2010) propose ambiguity sets characterized by known moment information, such as bounds on the mean vector and covariance matrix of the uncertain parameters. Ben-Tal et al. (2013) instead consider ambiguity in probability distributions characterized through ϕ-divergence-based uncertainty regions, which can be constructed as statistical confidence regions around estimated probability vectors. More recently, Esfahani and Kuhn (2018) define the ambiguity set as a Wasserstein ball around the empirical distribution, obtaining tractable convex reformulations while providing finite-sample performance guarantees. Despite their differences, these approaches share the common characteristic that the ambiguity set is designed independently of the forecasting process that generates the uncertain parameters.

A primary technique for applying both stochastic programming and DRO is *Scenario-Based Optimization*. This approach discretizes the continuous probability distribution of uncertain parameters into a finite set of representative scenarios. The *Sample Average Approximation* (SAA) method is a cornerstone of this paradigm (Shapiro and Homem-de Mello 1998), approximating the unknown distribution by the empirical distribution obtained from a sample of independent and identically distributed realizations. Extending this idea, Bertsimas and Kallus (2019) replace the uniform scenario weights of SAA with covariate-dependent weights derived from nonparametric learning methods, yielding predictive prescriptions that approximate the conditional distribution of the uncertain parameters given observed side information.

The integration of forecasting and scenario-based optimization—often referred to as *predict-then-optimize*—has recently attracted considerable attention. The traditional workflow follows a two-stage paradigm in which a forecasting model (e.g., SARIMA, GARCH, or LSTM) first predicts future uncertain parameters, after which a separate scenario generation phase constructs the optimization input from the predictive distribution. This sequential approach has been questioned because prediction errors that are statistically small may nevertheless induce substantial degradation in the quality of the downstream decision. To address this limitation, Elmachtoub and Grigas (2022) propose the *Smart Predict-then-Optimize* (SPO) framework, in which the prediction model is trained using a loss function that measures the resulting decision regret rather than conventional prediction error. Consequently, the learned predictor is optimized for its usefulness to the downstream optimization problem rather than solely for predictive accuracy. Unlike DRO approaches, however, SPO does not model uncertainty through ambiguity sets nor optimize against worst-case probability distributions, but remains an empirical risk minimization framework with a decision-aware loss.

Unlike these traditional DRO and predict-then-optimize approaches, our work introduces a novel framework that fundamentally links the statistical modeling of input data to the generation of the uncertainty set. Our *Bootstrap Enhanced Scenario Optimization* (BESO) framework leverages bootstrapped time series to generate future scenarios. This approach is conceptually aligned with DRO, as it seeks robustness across a set of statistically plausible distributions. However, rather than specifying the ambiguity set *a priori* through moment constraints, statistical divergences, or Wasserstein distances, BESO induces it directly from the bootstrap distribution generated by the Maximum Entropy Bootstrap (MEB), preserving the autocorrelation structure, non-stationarity, and other empirical characteristics of the historical time series. Moreover, scenarios are not generated as a post-processing step following forecasting, but emerge directly from the statistical model itself. Finally, we extend the MEB objective function by incorporating a downstream optimization component, thereby making the forecasting process explicitly aware of the optimization objective while simultaneously preserving the distributional robustness inherent in the bootstrap-generated scenario set. In this sense, our approach combines the complementary strengths of DRO, which emphasizes robustness to distributional uncertainty, and decision-aware learning methods such as SPO, which emphasize the quality of downstream decisions.

ZZZ includere Summers and Kamgarpour (2021)

2.2 2-echelon logistics networks

Multi-echelon inventory management is a supply chain control strategy that coordinates inventory across multiple levels, called "echelons," of the chain (Clark and Scarf 1960). The objective is to optimize inventory and routing costs across all levels of the supply chain rather than addressing each level in isolation. The literature on this strategy has expanded significantly, covering various aspects such as inventory control policies, replenishment strategies, and inventory risk management.

The successful implementation of effective management policies hinges on sound forecasting and optimization processes. Specifically, in the context of 2-echelon logistics, prescriptions grounded in predictive analytics are essential for refining demand forecasting, inventory allocation, and transportation planning (Aviv 2001). Considerable attention has been paid to demand forecasting (Ma et al. 2015; Shenstone and Dekker 2001), however, precise demand forecasting, especially within the context of dynamic retail environments characterized by fluctuating trends and seasonal variations, remains a significant obstacle. Multi-echelon demand forecasting commonly

incorporates a variety of models that frequently rely on assumptions of stationarity and specific parametric distributional characteristics that are often violated in dynamic retail environments characterized by short-horizon, non-stationary demand series, leading to model mismatch and suboptimal prescriptions.

The application of prescriptive analytics in 2-echelon logistics systems thus faces a critical challenge: how to robustly model the underlying uncertainty to support efficient management decision processes. Most documented multi-echelon inventory policies in the literature rely on instances with generic demand, often generated according to parametric distributions (Escorcia-Caballero et al. 2020). Our work addresses this methodological gap.

By introducing the BESO framework, we provide a statistically-grounded approach to tactical logistics planning. BESO leverages the MEB to generate demand scenarios that accurately preserve the complex autocorrelation and non-stationary structure of empirical demand data. This novel method directly counters the limitations of traditional approaches that fail to capture the nuances of real-world volatility, enabling the distribution centers (DCs) to update their market forecast and anticipate the structural attributes of the model, ultimately providing valuable management insights (Papier 2016). We demonstrate this capability using a comprehensive real-world case study where all instance elements, from demand series to network configurations, are derived from actual records. This application provides a validation of how BESO improves both solution robustness and operational efficiency in multi-echelon inventory management.

3 The 2-echelon test case

The test case, that makes use of data that comes from an LSRT company that manages multiple retail stores in a large city in northern Italy, originally proposed in Maniezzo and Zhou (2023) for a different application. In this case, 52 stores provided aggregate sales time series data spanning at least 45 months prior to the forecast period, which is set at a three-month horizon, as detailed in the following. Each store maintains a small inventory, replenished by deliveries from one of four different distribution centers (DCs) in the area. The products are categorized into three lines: fresh, dry, and household. In this context, the focus has been exclusively on the logistics of dry and household goods, including product categories ranging from personal care items to basic electronics, from household goods to holiday decorations. For this product line, DCs are required to maintain an aggregate inventory sufficient to cover a demand for a period of two weeks.

The supply chain consists of a large distribution center (DC) in the northern suburbs of the city, a smaller DC in the south, and two small satellite facilities closer to the city center. The satellites have limited storage capacity, but they offer lower-cost and more timely service to the majority of the city's stores. Each store must be allocated to a distribution center (DC), ensuring that the total requests made to a DC do not exceed its storage capacity. It is assumed that the handling and transportation capacities will always be sufficient. Both storage capacities and requests are quantified in terms of pallets, with no further granularity at this level. The cost of servicing a store from a DC is assessed based on the travel time required to transport goods between the two entities. Notably, the three smaller DCs are owned by the company, whereas the fourth DC is situated in a leased facility.

The ultimate goal of the analysis is to determine how much space to rent during the next peak demand period, the Christmas season. To achieve this, we first optimize the allocation of stores to DCs, taking into account transportation and storage costs, and from the solution it is immediate to derive the space required in each DC, therefore the space to rent in the largest one.

Another requirement characterizes the problem we are addressing: large stores located near small DCs often lead to rapid saturation of the capacity of central DCs. This forces nearby stores to be served by comparatively distant DCs. Therefore, it has been proposed to allow tentative split service for certain selected stores to facilitate what-if analysis. The problem we address thus involves a parametric number of possible assignments for each store, where which store should be allowed multiple (double) assignments is an input parameter, not a decision variable.

The analysis was conducted during the summer of 2022 in preparation for the subsequent Christmas season. At the time of the analysis, the anticipated demand requests were unknown and required forecasting. The analysis underwent iterative refinements throughout the summer, culminating in the final forecast produced in September. Consequently, the data presented in this paper correspond to a three-month forecasting case.

All codes and data are available in an anonymized format from the project repository *(public upon acceptance)*. Specifically, the file containing the request time series can be downloaded from the repository, where all series are complete up to the most recent actual values. However, it should be noted that the last three values were unknown at the time the final forecast was generated.

4 Bootstrap Enhanced Scenario Oprimzation

The framework we propose by the acronym of BESO integrates forecasting and optimization by including in the former elements from the latter and by formalizing the latter upon elements of the former. The two componeents can be integrated at different lavels, giving rise to different two different models, BESO-SAA and BESO-DRO.

4.1 The predictive component

Data-driven approaches to estimating the distribution of stochastic variables have gained increasing attention as alternatives to classical parametric modeling, particularly in settings where assumptions of stationarity or known distributional forms are invalid. Unlike traditional techniques that rely on a priori specification of distribution families (e.g., Gaussian or Poisson), data-driven methods infer distributional characteristics directly from historical or observed data, making them especially suited for real-world applications with complex, noisy, or limited information.

Among the most prominent techniques are resampling-based methods such as the Bootstrap (Efron 1979), which generates empirical distributions by repeatedly sampling from the data with replacement. The Maximum Entropy Bootstrap (MEB) (Vinod and Kourentzes 2006) extends this idea by producing replicates that preserve dependence structures in time series data, making it particularly valuable for short or non-stationary sequences.

Recent work has explored the integration of these empirical distribution estimates into stochastic and robust optimization pipelines. Notable contributions include nonparametric scenario generation (Bayraksan and Morton 2011), distributionally robust optimization using empirical Wasserstein distances (Esfahani and Kuhn 2018).

In our proposal, we utilize the MEB methodology in conjunction with the ensemble learning technique known as *bagging* (Bootstrap Aggregating). This combination enhances the accuracy and robustness of predictive models through the generation of multiple bootstrapped datasets from the original data. By training individual models on these datasets and aggregating their predictions through averaging, we adhere to MEB's principles while capturing the underlying statistical variability. Maximizing entropy under empirical constraints allows the integration of bagging with MEB to produce more robust models. In more details, each model trained on distinct bootstrapped samples incorporates uncertainty characteristics from the original data, allowing for a comprehensive representation of its variation.

Furthermore, this approach allows for dealing with noisy datasets and mitigating overfitting, as bagging inherently provides a mechanism to increase the robustness

of the predictive model by leveraging the diversity across the bootstrapped samples. Since MEB generates bootstrapped datasets based on the maximum entropy principle, the resulting models avoid being overly sensitive to any one particular realization of the data.

4.1.1 Resampling techniques

In recent years, bootstrap resampling has become a valuable tool for overcoming limitations of conventional forecasting methods (Hasni et al. 2019). By generating simulated time series from observed data, it helps mitigating issues related to small sample sizes (Davison and Hinkley 1997) and model uncertainty (Sarris et al. 2020). Bootstrap methods have also proven effective in model selection. Fenga and Politis (2011) proposed a bootstrap-based approach for ARMA order selection, improving accuracy in finite samples, and later for high-dimensional sparse autoregression (Fenga and Politis 2017), highlighting the relevance of bootstrap techniques in modern statistical modeling.

However, standard bootstrap assumes independent and identically distributed (i.i.d.) data, which is inappropriate for time series characterized by dependence, autocorrelation, and structural patterns. This limitation is particularly critical for short series, where resampling can distort temporal structure and underestimate variability. In this context, Maximum Entropy Bootstrap (MEB) provides several advantages, including *i*) *Preservation of dependence structure*: maintains autocorrelation, trend, and seasonality through rank-based reordering and interpolation; *ii*) *Suitability for short series*: preserves local features and generates plausible data paths under limited observations; *iii*) *Model-free approach*: avoids parametric assumptions and tuning choices such as block length or ARMA specification; *iv*) *Smooth pseudo-series generation*: produces continuous series suitable for inference and forecasting; *v*) *Maximum entropy principle*: generates least-biased samples consistent with observed data; *vi*) *Flexibility*: applicable to both stationary and non-stationary series.

The Maximum Entropy Bootstrap (MEB) introduced by Vinod and Kourentzes (2006) is not a parametric entropy–maximization model, but a multi–step resampling algorithm specifically designed for short and non–stationary time series. For clarity, we summarize the essential components of the classical MEB procedure:

1. construction of order statistics and interval endpoints;
2. definition of a piecewise–uniform maximum–entropy density over the intervals;
3. sampling of random quantiles from this density;

4. restoration of the temporal ordering to preserve dependence structure.

This algorithm produces bootstrap replicates that preserve local dependence patterns without requiring parametric assumptions. In our framework, MEB is used *as originally defined* to generate a set of candidate future trajectories.

Entropy–tilting layer. The bootstrapped trajectories will be used to define probability distributions and ultimately scenarios in the prescriptive component. To this end, they are assigned probability weights whose values are influenced by the downstream optimization function whose fomalization they enter into (see section 6.2). These weights used in the optimization model are not part of the classical MEB algorithm. Instead, they represent an additional *entropy–tilting* step applied *after* the MEB replicates have been generated. Given a set of MEB–generated scenarios $\{s_i\}_{i=1}^{N}$ and associated features f_i (and optionally g_i), we define scenario weights as

$$p_i \propto \exp(\mu f_i)\,, \tag{1}$$

or, as in our use case where the objective function is madeup by two components,

$$p_i^{\mathrm{OA}} \propto \exp(\mu f_i + \gamma g_i)\,. \tag{2}$$

Equations (1)–(2) therefore do *not* represent the classical MEB formulation, but a post–processing layer that adjusts scenario weights according to decision–relevant features. This distinction is important: MEB provides the empirical distributional structure, while entropy–tilting provides a mechanism to emphasize or down–weight specific trajectories within the optimization model.

In particular, the weighted empirical measure $\widehat{\mathbb{P}}_N^{\mathrm{OA}} = \sum_i p_i^{\mathrm{OA}} \delta_{s_i}$ is a cost-aware reference distribution, not an unbiased estimate of the data-generating distribution. To avoid ambiguity, throughout the paper we refer to this combined approach as *OA–MEB*: MEB–generated scenarios equipped with entropy–tilted weights.

Under mild regularity conditions on the cost function and the scenario–generation mechanism, empirical scenario–based optimization using MEB replicates provides a stable approximation of the underlying stochastic program. The consistency properties of MEB for short dependent series have been documented in Vinod and Kourentzes (2006), and our numerical results confirm that the OA–MEB scenario sets lead to stable and robust optimization outcomes.

4.2 The prescriptive component

The set of bootstrap trajectories admits two related but conceptually distinct interpretations. BESO uses bootstrap resampling to construct a data-driven family of plausible predictive distributions. This family naturally induces a bootstrap-based ambiguity set. A scenario-based formulation corresponds to optimization under the empirical mixture of these distributions, while a worst-case formulation over the induced ambiguity set provides the corresponding DRO extension.

In the **first**, the trajectories are regarded as alternative realizations of a single predictive distribution. Given N trajectories ρ^s, $s \in S = \{1, \ldots, N\}$, assigning equal probability to each of them yields the empirical distribution

$$\widehat{\mathbb{P}}_N = \frac{1}{N} \sum_{s \in S} \delta_{\rho^s}.$$

The expected downstream cost is consequently approximated by its average over the bootstrap trajectories, leading to a standard sample average approximation (SAA) model. Under this interpretation, the bootstrap procedure represents uncertainty within one estimated predictive distribution.

A **second** interpretation uses bootstrap resampling at the distributional level. Repeated resamples, or suitably constructed groups, of the available trajectories define a collection of empirical distributions

$$\widehat{\mathbb{P}}^{\,k} = \sum_{s \in S} p_{ks} \delta_{\rho^s}, \qquad k \in K,$$

where the weights p_{ks} reflect the composition of resample k. These distributions are then treated as alternative plausible descriptions of the uncertain demand process and used to construct an ambiguity set, for example

$$\mathcal{U} = \operatorname{conv} \left\{ \widehat{\mathbb{P}}^{\,k} : k \in K \right\}.$$

The resulting formulation minimizes cost under the worst-case distribution in $\mathcal{U}$, thereby yielding a fully distributionally robust model. Thus, while both constructions rely on the same underlying pool of bootstrap trajectories, the first averages uncertainty across trajectories within a single empirical distribution, whereas the second exploits resampling variability to represent ambiguity about the distribution itself. The two formulations are detailed in the following subsections.

The bootstrap does not merely produce arbitrary scenarios. Each bootstrap replication represents a statistically plausible empirical realization of the unknown data-generating process. The collection of bootstrap empirical distributions therefore

provides a data-driven approximation to a family of plausible probability distributions, rather than a single assumed distribution.

More in detail, we can construct several empirical distributions from resamples of the predictive trajectories and take their convex hull as the ambiguity set. The construction is:

1. Retain the K complete joint trajectories ρ^s, $s = 1, \ldots, K$.
2. Compute their cost-aware base probabilities p_s^{OA}.
3. For each ambiguity vertex $k = 1, \ldots, K$, draw L trajectories with replacement according to p_s^{OA}.
4. Treat that resample as an empirical distribution $\widehat{P}^{(k)}$.
5. Define the ambiguity set as the convex hull of these distributions.

Formally, let $I_{k1}, \ldots, I_{kL}$ be series indices sampled from $\{1, \ldots, K\}$ according to p^{OA}. Then we can define empirical distributions, using the Dirac delta function, as

$$\widehat{P}^{(k)} = \frac{1}{L} \sum_{\ell=1}^{L} \delta_{\rho^{I_{k\ell}}}, \qquad k = 1, \ldots, K,$$

and the related ambiguity set as $\mathcal{U}_{K,L} = \mathrm{conv}\left\{\widehat{P}^{(1)}, \ldots, \widehat{P}^{(K)}\right\}$. Equivalently, let N_{ks} be the number of times series s appears in resample k. Define $w_{ks} = \frac{N_{ks}}{L}$. Then $\widehat{P}^{(k)} = \sum_{s=1}^{K} w_{ks} \delta_{\rho^s}$.

We have $\Psi_m(x) = \sup_{P \in \mathcal{U}_m} E_P[c(x, \xi)]$ for the convex hull of bootstrap empirical distributions.

Because the expected cost is linear in the probability distribution,

$$\sup_{P \in \mathcal{U}_m^{\mathrm{OA}}} \mathbb{E}_P[C(x, \xi)] = \max_{k=1,\ldots,m} \sum_{s=1}^{n} p_{ks}^{\mathrm{OA}} C(x, \xi_{ks}).$$

The fully DRO objective becomes $\min_x \max_{k=1,\ldots,K} \sum_{s=1}^{K} w_{ks} Q(x, \rho^s)$. Note that the p_{ks}^{OA} are computed before the final optimization and passed to a solver as fixed numerical coefficients.

The construction for BESO becomes hierarchical: historical data $\longrightarrow$ $\widehat{P}_1, \widehat{P}_2, \ldots, \widehat{P}_m$(bootstrap predictive distributions) $\longrightarrow$ scenarios within each $\widehat{P}_k$(forecast realizations).

Then we take the expectation *within* each bootstrap distribution, and the worst case *across* bootstrap distributions:

$\min_x \max_{k=1,\ldots,m} \mathbb{E}_{\widehat{P}_k}[c(x, \xi)]$

This means that uncertainty within a bootstrap distribution is handled stochastically through expected recourse, while uncertainty about which bootstrap distribution best represents the unknown data-generating process is handled distributionally robustly.

Because expectation is linear in (P), the supremum over that convex hull occurs at an extreme point. Consequently, $\sup_{P \in \mathcal{U}_m} E_P[c(x,\xi)] = \max_{k=1,\dots,m} E_{\widehat{P}_k}[c(x,\xi)]$.

Suppose bootstrap replication k induces an empirical distribution $\widehat{P}_k$, and let

$$C_k(x) = \mathbb{E}_{\widehat{P}_k}[c(x,\xi)]$$

denote the expected optimized cost associated with that bootstrap distribution.

Then

$$\min_x \sup_{P \in \mathcal{U}_m} E_P[c(x,\xi)]$$

with

$$\mathcal{U}_m = \operatorname{conv}\{\widehat{P}_1, \dots, \widehat{P}_m\}$$

is equivalent to

$$\min_x \max_{k=1,\dots,m} C_k(x).$$

And that max is trivial to linearize. It is sufficient to introduce one continuous variable, say z, and write

$$\min z$$

subject to

$$z \geq C_k(x), \qquad k = 1, \dots, m.$$

As long as each $C_k(x)$ comes from an existing linear/MILP recourse structure, the resulting model remains a MILP.

Uncertainty within a bootstrap distribution is handled stochastically through expected recourse, while uncertainty about which bootstrap distribution best represents the unknown data-generating process is handled distributionally robustly.

Assuming bootstrap replication k induces an empirical distribution $\widehat{P}_k$, let $C_k(x) = \mathbb{E}_{\widehat{P}_k}[c(x,\xi)]$ denote the expected optimized cost associated with that bootstrap distribution and take its convex hull as the ambiguity set.

Then $\min_x \sup_{P \in \mathcal{U}_m} E_P[c(x,\xi)]$ with $\mathcal{U}_m = \operatorname{conv} \widehat{P}_1, \dots, \widehat{P}_m$ is equivalent to $\min_x \max_{k=1,\dots,m} C_k(x)$. which permits to define the following DRO formulation:

We therefore finally have three models:

1. Deterministic: $min_x c(x, \hat{\xi})$,
2. Bootstrap stochastic (SAA): $min_x \frac{1}{m} \sum_{k=1}^{m} E_{\hat{P}_n^{b(k)}}[c(x, \xi)]$,
3. Bootstrap distributional (DRO):$min_x max_{k=1,\ldots,m} E_{\hat{P}_n^{b(k)}}[c(x, \xi)]$.

==========

DRO

You write

$$\Psi_m(x) = \sup_{P \in \mathcal{U}_m} E_P[c(x, \xi)]$$

for the convex hull of bootstrap empirical distributions.

One methodological caveat remains: this is formally DRO, but L and K determine the ambiguity-set conservativeness and require empirical calibration. A random grouping does not by itself provide a coverage guarantee. Existing bootstrap-DRO work likewise treats ambiguity-set size or radius as a central calibration issue rather than an arbitrary implementation detail; see [Summers and Kamgarpour, "Distributionally Robust Bootstrap Optimization"](https://arxiv.org/abs/2112.13932). Summers and Kamgarpour (2021)

5 BESO for 2-echelon optimization

The predictive module provides a structural component of the prescriptive module, which aims to optimize the allocation of stores to distribution centers (DCs), thereby enabling the quantification of space to rent in third-party DCs. The results of the optimization are in turn used to evaluate the modeled *scenario*, where scenarios are defined for specific what-if analyses. For example, the objective of the what-if analyses could be to examine the effect of freezing some allocations while leaving free the others, or possibly accepting some multiple – double in the test case – allocations for some selected stores.

The core optimization problem is a *split allocation problem*. This variant of the basic allocation problem has already received attention in the optimization literature, mainly in the context of survivable communication network design (Mokhtar et al. 2019), and more generally as the splittable capacitated multiple allocation hub location problems (Marín 2005). It finds applications in fiber optic access networks (Youngjin et al. 2011), split delivery routing (Dror and Trudeau 1989), and even in school timetabling Beyrouthy et al. (2007). The problem we are interested in is related

to one that is presented in Zhu et al. (2021), but it is modelled in a very different way. The mathematical model we use is a direct extension of the standard model for allocation problems. As our proposed framework is valid beyond the specific case study described in the paper, we will refer to the application elements (stores and data centers) using standard allocation terminology in what follows. To emphasize the generality of the analysis, we will use the more generic term 'clients' to denote the stores and 'servers' to denote the centers. In our context, the constraints can accept a parametric number of assignments, enabling requests to be serviced across multiple servers.

$$(FD) \qquad z_{FD} = \textbf{min} \sum_{i\in I}\sum_{j\in J}(c_{ij}x_{ij} + d_i q_{ij}) \tag{3}$$

$$\textbf{subject to} \sum_{i\in I} q_{ij} = req_j \qquad j \in J \tag{4}$$

$$\sum_{j\in J} q_{ij} \leq Q_i \qquad i \in I \tag{5}$$

$$\sum_{i\in I} x_{ij} = b_j \qquad j \in J \tag{6}$$

$$q_{ij} \leq req_j x_{ij} \qquad i \in I, j \in J \tag{7}$$

$$x_{ij} \in \{0,1\}; \quad q_{ij} \in \mathbb{Z}_0^+ \qquad i \in I, j \in J \tag{8}$$

The notation used in the model is as follows: n: number of clients (stores), J: index set of clients, $J = \{1, \ldots, n\}$, m: number of servers (DCs), I: index set of servers, $I = \{1, \ldots, m\}$, c_{ij}: global cost for allocating client $j \in J$ to server $i \in I$, Q_i: storage capacity of server $i \in I$, d_i: unit storage cost of server $i \in I$, req_j: total request of client j, b_j: maximum number of servers (DCs) client j can be assigned to, x_{ij}: binary decision variable equal to 1 iff client j is allocated to server i, $i \in I$ and $j \in J$, q_{ij}: integer decision variable representing the amount (number of pallets) of request of client j provided from server i.

In the final test case, the amount requested by each client was always set to equal the corresponding predicted value. However, in some scenarios, some clients' requests could be split between two servers, meaning the requested q_{ij} amounts could vary. The mathematical model used for this problem is as in formulation (FD).

The constraints in equation 6 are formulated as equalities due to the need to impose specific splits in 'what if' scenarios. However, if this is not of particular interest, these constraints could be replaced by $1 \leq \sum_{i\in I} x_{ij} \leq b_j$ inequalities. Note that when $b_j = 1$ for all clients, i.e., when each client $j \in J$ can be served by only one server, constraints 8 and 4 force the entire quantity requested by client j, req_j, to be supplied by a single

server. The constraints 8 thus become equations, the constraints 4 become redundant, and the constraints 5 can be expressed by replacing $\sum_{j \in J} q_{ij}$ with $\sum_{j \in J} req_j x_{ij}$. Problem P reduces to the standard GAP and can be solved by any of the methods described in Maniezzo et al. (2021). However, we are interested in the general case that allows for multiple assignments. Since the cost is derived from these assignments, the problem can be considered a fixed-cost split-assignment allocation problem.

Furthermore, as future client requests can only be forecast, it is more convenient to formulate the problem as a stochastic optimization problem, where the future requests are random variables ρ_j, $j \in J$, whose distributions are derived from the forecast results. The resulting stochastic problem is formulated as in formulation (FS), where the values $R(\rho_j)$ in the constraints 10 and 14 refer to any same realization of the random variable ρ_j.

$$(FS) \qquad z_{FS} = \textbf{min} \sum_{i \in I} \sum_{j \in J} (c_{ij} x_{ij} + d_i q_{ij}) \tag{9}$$

$$\textbf{subject to} \sum_{i \in I} q_{ij} = R(\rho_j) \qquad j \in J \tag{10}$$

$$\sum_{j \in J} q_{ij} \leq Q_i \qquad i \in I \tag{11}$$

$$\sum_{i \in I} x_{ij} = b_j \qquad j \in J \tag{12}$$

$$q_{ij} \leq R(\rho_j) x_{ij} \qquad i \in I, j \in J \tag{13}$$

$$x_{ij} \in \{0,1\}; \quad q_{ij} \in \mathbb{Z}_0^+ \qquad i \in I, j \in J \tag{14}$$

Different methods can be used to deal with this case (Shapiro et al. 2009). We transformed the formulation (FS) into its *deterministic equivalent* (Dantzig 1955) using the forecasts computed on the bootstrap sets. We generated multiple scenarios each containing a realization of the stochastic variable ρ, which is defined as a forecast of one series from the bootstrap set in use. For each scenario s, we thus created a version of the constraint with b_i^s as the right-hand side. The final solution must satisfy these constraints across all scenarios. The objective function now incorporates the quantities to be delivered to each client in different scenarios. Therefore, we consider the expected cost as a weighted average across these scenarios and include it in the objective function.

SAA

The resulting formulation is in formulation (DE). The random variables ρ_j are sampled in a finite number of scenarios. Let ρ_j^s denote the realization of ρ_j in scenario s, $s \in S$, and let $p_s = \frac{1}{|S|}$ be the probability associated with scenario $s \in S$. The

variables ϵ_{js} are slack variables for the customer service constraints.

$$(DE) \quad z_{DE} = \textbf{min} \quad \sum_{s\in S}\left(p_s \sum_{j\in J}\left(\sum_{i\in I}(c_{ij}x_{ij} + d_i q_{ij}^s) + M\epsilon_{js}\right)\right) \tag{15}$$

$$\tag{16}$$

$$\textbf{s.t.} \sum_{i\in I} q_{ij}^s + \epsilon_{js} = \rho_j^s \qquad j \in J, s \in S \tag{17}$$

$$\sum_{j\in J} q_{ij}^s \leq Q_i \qquad i \in I, s \in S \tag{18}$$

$$\sum_{i\in I} x_{ij} = b_j \qquad j \in J \tag{19}$$

$$q_{ij}^s \leq \rho_j^s x_{ij}; \quad q_{ij}^s \in \mathbb{Z}_0^+ \qquad i \in I, j \in J, s \in S \tag{20}$$

$$x_{ij} \in \{0,1\} \qquad i \in I, j \in J \tag{21}$$

$$\epsilon_{js} \in \mathbb{Z}_0^+ \qquad j \in J, s \in S \tag{22}$$

In this formulation, since each variable ρ_j^s derives from a specific realization of the corresponding random variable ρ_j, the amounts to be delivered to each store $j \in J$ are scenario-specific. However, it is required to determine a unique allocation that allows to serve all stores in any proposed scenario. This last requirement may be infeasible, so the slack variables ϵ_{js} are needed in the formulation. They are lexicographically penalized in the objective function by appropriately high costs, implementing the primary concern of achieving feasibility. Optimizing formulation (DE) determines the total quantity that each server must handle. In terms of our logistical application, since each DC must maintain sufficient inventory to meet the anticipated demand during the designated period, the optimization of the client (retailer) allocation translates directly into a quantification of the DC inventory and therefore of its required minimum size. Thus, solving the allocation problem also solves the dimensioning question that motivated this research.

DRO

Formulation DE treats each forecast realization as a scenario assigning equal probability weights to each of them.

Formulation DE minimizes the equally weighted expected cost over bootstrap scenarios, with one common allocation (x_{ij}) and scenario-dependent recourse variables (q_{ij}^s) and (ϵ_j^s). The common (x) across all scenarios provides the basis for a two-stage robust/stochastic formulation.

Yes. For each demand scenario ξ_i, you could solve a simplified transportation problem

$$g_i = \min_{z_i} \left\{ c^\top z_i : z_i \in \mathcal{T}(\xi_i) \right\},$$

and use its optimal value as the cost-exposure score in

$$p_i^{\mathrm{OA}} = \frac{q_i \exp(\gamma \widetilde{g}_i)}{\sum_j q_j \exp(\gamma \widetilde{g}_j)}.$$

This is often better than a crude analytical formula because it captures network structure: origins, destinations, transport costs, capacities, and demand geography.

The resulting pipeline would be:

MEB scenario $\xi_i \to$ transportation LP $\to g_i \to p_i^{\mathrm{OA}} \to$ final DRO model.

The transportation problems are only preprocessing. They are independent LPs and should normally be very fast. The final probabilities are then passed to Gurobi as fixed coefficients within each bootstrap distribution; Gurobi subsequently solves the convex-hull worst-case model.

$$(DRO) \quad z_{DRO} = \min z \tag{23}$$

$$\textbf{s.t.} \quad z \geq \sum_{s \in S_k} p_{ks} \left[\sum_{j \in J} \left(\sum_{i \in I} (c_{ij} x_{ij} + d_i q_{ij}^{ks}) + M \epsilon_j^{ks} \right) \right], \quad k = 1, \ldots, m \tag{24}$$

$$\sum_{i \in I} q_{ij}^{ks} + \epsilon_j^{ks} = \rho_j^{ks} \qquad j \in J, s \in S, k = 1, \ldots, m \tag{25}$$

$$\sum_{j \in J} q_{ij}^{ks} \leq Q_i \qquad i \in I, s \in S, k = 1, \ldots, m \tag{26}$$

$$\sum_{i \in I} x_{ij} = b_j \qquad j \in J \tag{27}$$

$$q_{ij}^{ks} \leq \rho_j^{ks} x_{ij}; \quad q_{ij}^{ks} \in \mathbb{Z}_0^+ \qquad i \in I, j \in J, s \in S, k = 1, \ldots, m \tag{28}$$

$$x_{ij} \in \{0, 1\} \qquad i \in I, j \in J \tag{29}$$

$$\epsilon_j^{ks} \in \mathbb{Z}_0^+ \qquad j \in J, s \in S, k = 1, \ldots, m \tag{30}$$

In Gurobi, this is represented by

$$z \geq \sum_{s=1}^{125} w_{ks} Q(x, \rho^s), \qquad k = 1, \ldots, K.$$

Here:

* $s = 1, \ldots, 125$ indexes your original predictive trajectories; * $k = 1, \ldots, K$ indexes candidate distributions—the vertices of the ambiguity set; * L is the number of trajectory draws used to construct each distribution.

My concrete recommendation

For your 125 trajectories, I would initially use

$$L = 25, \qquad K = 50.$$

Thus, generate 50 empirical distributions, each based on 25 draws from the 125 trajectories. Because sampling is with replacement, you are not restricted to five disjoint groups.

I would then perform sensitivity tests with

$$L \in \{10, 25, 50\}.$$

Their interpretation is:

* $L = 10$: dispersed empirical distributions and relatively strong robustness; * $L = 25$: reasonable intermediate specification; * $L = 50$: distributions closer to the cost-aware reference distribution and milder robustness.

I would use $L = 5$ only as a deliberately conservative stress test. With five atoms, the worst of many group averages can be dominated by accidental composition.

The number K controls how thoroughly you explore the space of plausible distributions. Values around 25–50 should be adequate for an initial implementation; increasing K makes it more likely that an adverse empirical distribution is included.

Computationally, this need not create KL separate recourse models. You retain only the 125 original scenario-specific recourse blocks $Q(x, \rho^s)$; the K distributions merely give you K different vectors of coefficients w_{ks} and hence K epigraph constraints.

6 Computational results

This section reports on the results of validating the predictive and prescriptive modules in accordance with the specifications previously described.

6.1 Predictive module tests

The objective of the predictive module is to forecast demand for each store, asking for a forecast three months ahead. The available data consists of a time series for each of the 52 stores. Each series contains 45 values corresponding to four years of monthly data on relevant requests for each store. The values for the last three months of the last year are missing, as these are to be forecast.

The core approach set out in this paper is the bootstrap method, which is described in Section **??**. The results obtained using this method were validated against those

obtained using several alternative forecasting algorithms: SARIMAX, Holt-Winters, MLP, RNN (LSTM), Random Forest and Gradient Boosting (XGBoost). The relevant hyperparameters were determined by grid search for algorithms with integer-valued parameters, such as SARIMAX, and by Hammersley sampling (Hammersley 1960) for real-valued parameters.

Python version 3.11 was used for all implementations and the codes were run on a Windows PC workstation equipped with four Intel Core i7-4790 CPUs running at 3.60 GHz and with 32 GB of RAM.

The focus of this part of the research is on the bootstrap method. To this end, we tested the approach with the following settings: 1) bootstrap sets containing 75, 125 and 175 series; 2) bootstrap sets generated by simple autoregressive AR(p) with p=5 model (the default in python's statsmodels), where parameters are estimated using Yule-Walker equations (Brockwell and Davis 1991), and by ARIMA, where autoarima is run on each of the seed series and the optimized orders are then applied to each boosted series; 3) the forecasting of all the boosted series generated as above to obtain the boosted forecasts was tested with AR(p), Random Forest or ARIMA. In the case of ARIMA, autoarima was only repeated on the first series of each bootstrap set. In the case of AR, the parameter p was set for each series after a loop on different p values, keeping the one that maximized the corresponding AIC value.

We also attempted to generate bootstrap sets with and without backcasting, as well as with simple extraction and repetitions among the residuals of the seed series, and compared these with their scrambling. We did not report the results of these tests because backcasting worsened the results, while scrambling the residuals showed no difference compared to extraction with repetitions. Therefore, in line with the literature, we decided to use the latter approach.

The forecasts were compared using three cost functions: mean absolute error (MAE), mean squared error (MSE) and bias. The results are reported by ranking the corresponding forecasts for each series according to the quality of the considered function to emphasize how the algorithms perform relative to each other. Then, the rank of each function is averaged over all series. Appendix A of the Electronic Companion reports the absolute values of the error measures, rather than the rank-based values, for all boostset sizes. Table 1 presents the results of comparing the forecasts obtained using standard algorithms with those obtained using boosting. The boosted series were computed using an AR(5) model based on Yule-Walker equations. The forecasts of these series were obtained using a simple autoregressive model. The boosted sets consisted of 75, 125, and 175 series, which are labelled YW_AR_75

	YW_AR_75			YW_AR_125			YW_AR_175		
	MAE	MSE	bias	MAE	MSE	bias	MAE	MSE	bias
fcast_avg	2.67	2.67	0.08	2.58	2.58	0.05	3.83	3.83	0.04
fcast_50	3.04	3.04	0.06	3.19	3.19	0.04	2.50	2.50	0.03
yhw	5.42	5.42	0.08	6.06	6.06	0.04	5.88	5.88	0.03
yarima	5.73	5.73	0.05	6.04	6.04	0.03	6.08	6.08	0.02
ysvm	5.88	5.88	0.08	5.50	5.50	0.05	5.50	5.50	0.03
ylstm	6.02	6.02	0.06	5.52	5.52	0.04	6.27	6.27	0.02
yar	6.06	6.06	0.04	6.54	6.54	0.02	6.79	6.79	0.02
ymlp	6.38	6.38	0.05	5.98	5.98	0.03	6.17	6.17	0.02
yrf	6.46	6.46	0.11	6.31	6.31	0.06	5.48	5.48	0.04
yxgb	7.33	7.33	0.12	7.29	7.29	0.07	6.50	6.50	0.05


Table 1: Average rankings for different boostset size.

(standing for Yule-Walker, AutoRegressive, 75 series bootstrap set), YW_AR_125, and YW_AR_175, respectively.

The columns show the average ranking of each cost function (MAE, MSE or bias) for each boostset size, while on the rows we report: $fcast_avg$: boost forecast obtained as the average of the corresponding ranks; $fcast_50$: boost forecast obtained as the median of the corresponding ranks; yar: non-boost forecast obtained by an AR model; $yarima$: non-boost forecast obtained by an ARIMA model; yhw: non-boost forecast obtained by a Holt and Winters model; $ymlp$: non-boost forecast obtained by a multi-layer perceptron model; $ysvm$: non-boost forecast obtained by a SVM model; $ylstm$: non-boost forecast obtained by a LSTM model; yrf: non-boost forecast obtained by a random forest model; $yxgb$: non-boost forecast obtained by a XGboost model. The table shows that boosting is consistently the most reliable method for minimizing forecast errors, even when forecasts are obtained from a model as simple as AR(p), while ARIMA produces the least bias.

Figure 1 shows two examples of forecast distributions obtained for two different series. The green bars correspond to the distribution of the results obtained by the AR[p] model over the differently recolored alternatives of a series. The distribution is superimposed with lines representing the results of other forecasting algorithms applied to the original series.

The relative merits of the different forecasting approaches are better highlighted by critical difference diagrams based on the non-parametric Friedman test followed by a post-hoc Nemenyi test. These diagrams allow for a visual comparison of performance ranks and indicate whether the differences between classifiers are statistically significant (Demšar 2006). In our case, the graphs were generated using the SciKit version (Scikit 2024) and plot the average rank across all series for each algorithm along the x-axis. Horizontal bars connect those that could not be considered statistically different.



(a) 75 bootset *(b) 125 boostset*

Fig. 1: Distribution of bootstrap forecasts.




Fig. 2: Average ranks for MAE on instance res_YW_AR_75




Fig. 3: Average ranks for MSE on instance res_YW_AR_175

Figures 2 and 3 show a comparison of the ranks on MAE for the 75 series boostset and on MSE for the 175 series boostset. In both cases, as with all those tested, the accuracy of the boost forecasts is significantly higher than that obtained with alternative models. The tables in A confirm that the comparison yields consistent results across all boostset sizes and cost functions, except for bias. The bias rankings are in fact unrelated to those obtained with the other cost functions. This is because the bias is very small in all cases, less than 1% of the average of the empirical values, which ensures that all the forecasting models are free of systematic errors on our data and makes the difference in the rankings insignificant.

Our relatively short time series require a forecasting approach that can handle both limited data and non-stationarity. Although sophisticated machine learning models such as recurrent neural networks (RNNs) and gradient boosting machines (GBMs) have become more popular in recent years, they can perform less well when there is limited data available, particularly when the data has non-stationary properties. This can lead to overfitting. The autoregressive (AR) model combined with MEB offers a powerful and promising alternative. This technique performed excellently in the context of this study, consistently outperforming more complex machine learning models. It offers an approach based on robust statistical principles that mitigates the risk of overfitting inherent in many AI approaches. Moreover, the AR model combined with the bootstrap methodology provides reliable forecasts ideally suited to integration into the subsequent optimization module.

In our case, the choice of an autoregressive (AR) model not only offers superior accuracy, but also several crucial advantages over more complex machine learning approaches. Firstly, the AR model's inherent simplicity makes it easy to implement and interpret. Unlike many machine learning algorithms, which operate as 'black boxes', the parameters of the AR model have clear statistical interpretations that provide insight into the underlying dynamics of the time series data. Secondly, the well-established theoretical framework of the AR model and the readily available diagnostic tools allow for robust validation and assessment of model performance.

6.2 Prescriptive module tests

The bootstrap forecasts results reported in section 6.1 provided the basis for instantiating the optimization phase. The prescriptive module was first run in a deterministic setting, to define a benchmark solution, then extended to the stochastic setting described in section **??**.

When the problem is modelled using the (FD) formulation and the average predictions obtained by boosting are used as deterministic data, it can be easily solved by any state-of-the-art MILP solver. This demonstrates the feasibility of dealing with a significant deterministic equivalent of the stochastic formulation (FS). The optimal deterministic value of $z_{FP} = 15553$ is used as a benchmark in the following tests. We moved on to the (DE) formulation generating a value for each of the stochastic variables ρ_j in correspondence to each bootstrap forecast. Given these input data, we ran experiments to assess the impact of the variation of the remaining sets of parameters of the formulation, i.e., cardinality of the boostsets, number of splittable clients, and assumptions on inventory costs.

All reported tests were run on the same machine as in subsection 6.1, a Windows PC workstation equipped with four Intel Core i7-4790 CPUs running at 3.60 GHz and 32 GB of RAM, but in this case the implementation language was C++ to allow finer control over the MILP solver used, which was CPLEX v. 22.11. These test reports on the sensitivity of the solution to variations in the instance coefficients. Appendix B of the Electronic Companion provides an initial study of the fitness landscape for the split-assignment problem, using a set of artificial benchmark instances.

Test case solution

ZZZ

The WEK alternative implements a finite-support Wasserstein DRO model. The empirical distribution initially assigns probability $1/N$ to each demand scenario, but we introduce ambiguity by transporting probability mass among the observed scenarios, subject to a Wasserstein transportation budget. Unlike the usual Wasserstein ball of Esfahani and Kuhn, which may contain distributions supported outside the N observed scenarios, WEK restricts them to the available finite support.

For the validation, we use the same AR predictor adopted in BESO, but without bootstrap resampling, which is an integral part of our proposal. We do not center the ambiguity set directly on the 45 raw monthly observations, since the series are short and nonstationary, and demand at the target seasonal period cannot be regarded as exchangeable with that of arbitrary historical months.

For each historical rolling forecast origin t and each store j, we compute the three-step-ahead empirical forecast error $e_{t,j}^{(3)} = y_{t+3,j} - \hat{y}_{t+3|t,j}$. Using a minimum training length of 24 observations for the AR recursions yields 18 admissible forecast origins. The errors associated with each origin are retained jointly across stores and combined with the current three-step-ahead forecasts, thereby generating $N = 18$ predictive demand scenarios ρ^s, $s \in S$. These scenarios provide a non-bootstrap empirical representation of predictive uncertainty and define the finite support of the Wasserstein benchmark. Let $\Xi_N = \{\rho^1, \ldots, \rho^N\}$ denote this support.

Distances are computed between normalized three-step-ahead demand scenarios using the L_1 ground metric, $D_{st} = \frac{1}{|J|} \sum_j \left|\tilde{\rho}_j^s - \tilde{\rho}_j^t\right|$, $\tilde{\rho}_j^s = \frac{\rho_j^s}{\bar{\rho}_j}$, where $\bar{\rho}_j$ is the store-specific mean demand computed from the training sample.

Using the Dirac delta function, the corresponding empirical distribution is $\widehat{P}_N = \frac{1}{N} \sum_{t=1}^{N} \delta_{\xi^t}$. The finite-support Wasserstein ambiguity set is defined as $\mathcal{U}_\alpha^{FS} = \left\{ P : \text{supp}(P) \subseteq \Xi_N,\ W_1(P, \widehat{P}_N) \leq \alpha \right\}$. To obtain a scale-free parametrization of the Wasserstein radius, we define D_0 as the median pairwise distance between the empirical demand scenarios and set $D_\alpha = \alpha D_0$, where α is a dimensionless robustness parameter.

Defining the first-stage allocation cost as $F(x) = \sum_{i,j} c_{ij} x_{ij}$ and the scenario-specific recourse cost as $R_s = \sum_{i,j} d_i q_{ij}^s + M \sum_j \epsilon_j^s$, while retaining the DE constraints on q^s, ϵ^s, and x, the WEK model solves $\min_x \left\{ F(x) + \sup_{P \in \mathcal{U}_\alpha^{FS}} \mathbb{E}_P[R] \right\}$.

For the finite support above, LP duality turns the worst-case expectation into $\min \quad F(x) + \lambda D_\alpha + \frac{1}{N} \sum_{s=1}^{N} \eta_s$, subject to $\eta_s \geq R_t - \lambda D_{st}$, $s, t = 1, \ldots, N$, $\lambda \geq 0$. This formulation is consistent with the Wasserstein-DRO dual reformulations in Esfahani and Kuhn (2018); Gao and Kleywegt (2023). The complete WEK model is




Fig. 4: Comparison of distributions on 75 bootstrapped series

$$
\begin{aligned}
(WDRO) \quad \min \quad & \sum_{i,j} c_{ij} x_{ij} + \lambda D_\alpha + \frac{1}{N} \sum_{s} \eta_s && && (31)\\
\text{s.t.} \quad & \eta_s \geq \sum_{i,j} d_i q_{ij}^t + M \sum_{j} \epsilon_j^t - \lambda D_{st} && s,t \in S, && (32)\\
& \sum_{i} q_{ij}^s + \epsilon_j^s = \rho_j^s && j \in J, s \in S, && (33)\\
& \sum_{j} q_{ij}^s \leq Q_i && i \in I, s \in S, && (34)\\
& q_{ij}^s \leq \rho_j^s x_{ij} && i \in I, j \in J, s \in S, && (35)\\
& \sum_{i} x_{ij} = b_j && j \in J, && (36)\\
& x_{ij} \in \{0,1\}, && && (37)\\
& q_{ij}^s, \epsilon_j^s \in \mathbb{Z}_0^+, && && (38)\\
& \lambda \geq 0. && && (39)
\end{aligned}
$$

Figure 4 shows the distributions of the forecasts of the 75 boostset obtained by BESO and by ETS. Note that the BESO distribution, given its MEB foundation, spans a wider range of values than the ETS distribution. The wider distribution has an impact on the proposed allocation. We had empirical proof of this when we tested the BESO and ETS solutions on the validation data obtained by the end of the year.

Table 2 presents a comparison of solutions in the first two columns when no rental cost was added for the use of leased floor space and in the last two columns when the rental cost was included in the objective function. As expected, given that the constraints were less restrictive, the ETS solution is less expensive in both cases. However, in both cases, the solution was infeasible as it did not provide all the goods requested by one of the retailers. This result was obtained in a single instance; therefore, it may

	No rental cost		With rental cost	
	BESO	ETS	BESO	ETS
Assign. Cost	17781	15423	5446720	4378380
Optimality gap%	0	0	16.07	0.69
Infeasibilities	0	1	0	1
t.Cpu	33	29	3600	3600

Table 2: Solution cost with and without rental cost

	No rental cost		With rental cost	
	BESO	ETS	BESO	ETS
DC 0	67 / 120	119 / 120	82 / 120	116 / 120
DC 1	571 / 1000	430 / 1000	532 / 1000	428 / 1000
DC 2	257 / 300	301 / 300	257 / 300	303 / 300
DC 3	128 / 180	173 / 180	152 / 180	176 / 180

Table 3: DC usage with and without rental cost

not have happened. However, it is significant that, even in the first instance in which we tested our model, its robustness proved important in dealing with a limit case.

Table 3 details the proposed usage of the DCs in the different cases. It appears that DC 2, the biggest owned one, is the overloaded one in both cases, even though by small amounts.

Finally, we note that Table 2 shows that including the rental cost makes otherwise identical instances much harder to solve. In fact, the time limit of 3600 CPU seconds was too short to reach optimality, and a duality gap was left in the proposed solutions, a substantial one in the case of the BESO instance.

Increasing boostset size

The size of the boostset helps to stabilize the results during forecasting, as introduced in subsection **??**, but it also has a deep impact on the optimization. In fact, the number of variables and constraints in the DE formulation do not depend on the size of the boostset, larger boostsets are more likely to contain unusual values or combinations thereof. This makes the constraints in equation (17) progressively harder to satisfy, which increases the cost and may render the instance infeasible. To ascertain this, we conducted experiments using 75, 125 and 175 series boostsets, with a time limit of 600 seconds on the optimization process. Figure 5 shows a boxplot diagram depicting the distribution of the optimized cost over a number of tests equal to 1/5 of the number of series in the boostset, i.e., 15, 25, 35, respectively.

Figure 5 has a red horizontal line at the cost value for the deterministic case. Therefore, the increase in cost can be considered a quantification of the value of




Fig. 5: Allocation cost for increasing boostset size

information about storage requests. We observe that the cost remains relatively stable for the 75 and 125 series sets, but increases significantly for the 175 boostset. This is due to the increased difficulty of the larger boostset instances, which meant that some could only be solved heuristically within the time limit. While all instances were feasible, seven out of 35 still had a gap between the lower and upper bounds after 600 seconds of CPU time.

Finally, we note that, as expected, taking the optimal solution obtained with the coefficients imposed by the 75 series and evaluating it with the coefficients of the 125 series results in a more costly solution than that computed with the 125 series coefficients. More interestingly, however, this solution is not feasible with the 175 series coefficients.

Increasing number of splittable clients

A defining feature of the problem we face is the possibility of accepting split service for some clients. This is unusual for allocation problems and results from the requirement to perform specific what-if analyses on the results. The number of clients allowed to split, and which ones they are, is given in input. In the actual case, the service to a client, if splittable, could be split between at most two servers, and the quantities delivered had to be integers, as specified in all formulations.

The clients to be split are chosen from the most requesting clients. We ran a series of tests based on 75 series boostsets, allowing the 0, 4, 8, and 12 most requesting clients to be split. Figure 6 shows the corresponding boxplots.

Allowing a service to be split for a client is a partial relaxation of the corresponding assignment constraint, so the expected optimal cost is lower. This can indeed be seen in figure 6, where the more clients that are permitted to split, the lower all distribution




Fig. 6: Allocation cost for increasing number of splittable clients

moments become. However, the marginal decrease becomes smaller as the number of clients who can split increases, since splitting a small client may result in only a small contribution, if any.

Impact of different inventory cost assumptions

A further set of tests was conducted to determine the impact of inventory costs d_i, $i \in I$ on the search process. Recall that in the original case study, one of the objectives was to determine how much space should be rented in the only DC not owned by the company, where storage space needs to be leased. The data of the case study proposed in Maniezzo and Zhou (2023) did not report storage costs. Here, we consider storage costs that are inversely proportional to the average distance of the DC from the stores. We consider three settings, one with no storage costs, one where only the most distant DC incurs costs, and one where all DCs need to lease space. Costs are proportional to the quantities stored and are therefore influenced by the allocation policy.

All the tests were performed using the 75-series boost set. The focus of the analysis is not on the increase in optimal costs, since an increase in the costs of the decision variables clearly leads to an increase in the total costs. Rather, the focus is on the variation in the complexity of the search, as reflected in the CPU time required to reach the final result, and on the optimality or feasibility of the solutions. To evaluate the effectiveness of increasingly lengthy searches, we present results after 600, 1200, and 3600 seconds of CPU time. The results are summarized in the table 4. All results are based on 15 repetitions, and the columns show: n: number of clients (stores); m: number of servers (DCs); n_{boost}: number of series in the boostset; n_q: number of servers incurring leasing costs; n_{inf}: number of infeasible solutions at the end of the search; *GAP lin*: average gap between the linear bound and the best solution at the end of

n	m	n_{boost}	n_q	n_{inf}	GAP lin	GAP fin	t.CPU
52	4	75	0	0	0.01	0.00	333.95
52	4	75	1	1	0.18	0.17	600
52	4	75	1	0	0.15	0.14	1200
52	4	75	1	0	0.14	0.13	3600
52	4	75	2	0	0.04	0.04	600
52	4	75	2	0	0.01	0.03	1200
52	4	75	2	0	0.01	0.03	3600
52	4	75	3	0	0.01	0.00	211.03
52	4	75	4	0	0.01	0.00	13.00

Table 4: Gap and CPU time for increasing number of leased servers.

the search; *GAP fin*: average gap between the best lower bound and the best solution at the end of the search; *t.CPU*: average CPU time (in sec) of the search process.

Table 4 illustrates an interesting feature of the fitness landscape of this split-cost allocation problem: the complexity of the search is not monotonic with respect to the number of leased servers. In fact, CPLEX was able to solve all instances to optimality for 0, 3 and 4 leased servers. However, for 1 or 2 leased servers, it was never able to prove the optimality of the best solution found within the time limit of 3600 seconds. Furthermore, instances with one leased server are more challenging than those with two, as demonstrated by the gap between the lower and upper bounds, both between the linear relaxation bound and the best solution found and between the best final lower bound and the best solution. This feature is discussed further in Appendix B of the Electronic Companion.

As a final note, we point out that the objective function was structured to lexicographically first strive for feasibility and then optimize within the feasible domain. In fact, all instances have always resulted in feasible solutions. Reducing the cost coefficient of the request slack variables allows us to explore the trade-off between solution cost and the probability of reaching an infeasible solution. However, we did not explore this further.

7 Conclusions and future directions

This paper introduces Bootstrap Enhanced Scenario Optimization (BESO), a framework for deriving predictive prescriptions from relevant data series. It integrates statistically grounded forecasting with scenario-based optimization by generating future scenarios via bootstrapped autoregressive time series, while incorporating feedback from the optimization stage. A two-echelon logistics case study illustrates how BESO forecasts retailer demand and supports DC allocation, enabling decisions on inventory, capacity, and assignment that reflect both cost structures and uncertainty.

A central contribution of BESO is providing a credible alternative to traditional Distributionally Robust Optimization (DRO). Standard DRO methods rely on predefined ambiguity sets (e.g., moment bounds, Wasserstein metrics, ϕ-divergences), which may fail to capture complex empirical features such as nonstationarity or heavy tails. BESO instead constructs empirical scenario distributions via Maximum Entropy Bootstrap (MEB), avoiding explicit ambiguity sets. It also allows an objective-aware extension, where optimization-related costs inform the resampling process, producing scenarios aligned with decision quality. The bootstrap size further acts as a transparent control over robustness, replacing exogenous parametric design.

Experiments on real and synthetic data show that BESO yields robust, interpretable prescriptions and adapts well to varying uncertainty structures, achieving performance comparable to classical scenario generation and DRO approaches. Overall, integrating forecasting and optimization within a unified empirical loop enhances both stability and operational effectiveness.

Future research may further explore bootstrap-based ambiguity representations, positioning BESO as a data-driven DRO alternative. Extensions could include hybrid schemes incorporating prior knowledge or Bayesian elements, as well as broader applicability to settings where reliable forecasting models are not available.

References

Aviv Y (2001) The effect of collaborative forecasting on supply chain performance. Management Science 47(10):1326–1343

Bayraksan G, Morton DP (2011) A sequential sampling procedure for stochastic programming. Operations research 59(4):iii–1058

Beale EML (2018) On minimizing a convex function subject to linear inequalities. Journal of the Royal Statistical Society: Series B (Methodological) 17(2):173–184

Ben-Tal A, den Hertog D, De Waegenaere A, et al (2013) Robust solutions of optimization problems affected by uncertain probabilities. Management Science 59(2):341–357

Bertsimas D, Kallus N (2019) From predictive to prescriptive analytics. Management Science 66(3):1025–1044

Bertsimas D, Sim M (2004) The price of robustness. Operations Research 52(1):35–53

Beyrouthy C, Burke EK, et al. (2007) The teaching space allocation problem with splitting. In: Burke EK, Rudová H (eds) Practice and Theory of Automated Timetabling VI. Springer, Heidelberg, pp 228–247

Brockwell PJ, Davis R (1991) Time Series: Theory and Methods. Springer

Clark A, Scarf H (1960) Optimal policies for a multi-echelon inventory problem. Management Science 6(4):475–490

Dantzig G (1955) Linear programming under uncertainty. Management Science 1(3-4):197–206

Davison AC, Hinkley DV (1997) Bootstrap Methods and Their Application. Cambridge University Press

Delage E, Ye Y (2010) Distributionally robust optimization under moment uncertainty with application to data-driven problems. Operations Research 58(3):595–612

Demšar J (2006) Statistical comparisons of classifiers over multiple data sets. The Journal of Machine learning research 7(1):1–30

Dror M, Trudeau P (1989) Savings by split delivery routing. Transportation Science 23(2):141–145

Efron B (1979) Bootstrap methods: Another look at the jackknife. The Annals of Statistics 7(1):1–26

Elmachtoub AN, Grigas P (2022) Smart "predict, then optimize". Management Science 68(1):9–26

Escorcia-Caballero J, Amaya-Mier R, Soto-Ferrari M, et al (2020) Multi-echelon inventory management policies: A case study for a two-echelon supply chain. In: proc. International Conference on Industrial Engineering and Operations Management, pp 165–175

Esfahani MP, Kuhn D (2018) Data-driven distributionally robust optimization using the wasserstein metric: performance guarantees and tractable reformulations. Math Programming 171:115–166

Fenga L, Politis D (2011) Bootstrap-based arma order selection. Journal of Statistical Computation and Simulation

Fenga L, Politis DN (2017) Lasso order selection for sparse autoregression: a bootstrap approach. Journal of Statistical Computation and Simulation 87(2):319–334

Gao R, Kleywegt A (2023) Distributionally robust stochastic optimization with wasserstein distance. Mathematics Operations Research 48(2):603–655

Hammersley J (1960) Monte carlo methods for solving multivariable problems. Annals of the New York Academy of Sciences 86(3):844–874

Hasni M, Aguir M, Babai MZ, et al (2019) Spare parts demand forecasting: a review on bootstrapping methods. International Journal of Production Research 57(15-16):4791–4804

Hyndman R, Koehler A, Ord J, et al (2008) Forecasting with Exponential Smoothing: The State Space Approach. Springer, Switzerland

Ma Z, Li H, Wang Y (2015) Combining forecasts in supply chain forecasting. Omega

Maniezzo V, Zhou T (2023) Integrated forecast and optimization for retailer allocation in a two-echelon inventory system. In: Bringas P, et al. (eds) proc. of 18th Int. Conf. on Soft Computing Models in Ind. and Envir. Appl., Lecture Notes in Networks and Systems, vol 749. Springer, pp 279 – 289

Maniezzo V, Boschetti M, Stützle T (2021) Matheuristics, algorithms and implementations. EURO Advanced Tutorials on Operational Research, Springer, New York

Marín A (2005) Formulating and solving splittable capacitated multiple allocation hub location problems. Computers & Oper Research 32(12):3093–3109

Mokhtar H, Krishnamoorthy M, Ernst AT (2019) The 2-allocation p-hub median problem and a modified benders decomposition method for solving hub location problems. Computers & Operations Research 104:375–393

Papier F (2016) Supply allocation under sequential advance demand information. Operations Research 64(2):341–361

Sarris D, Spiliotis E, Assimakopoulos V (2020) Exploiting resampling techniques for model selection in forecasting: an empirical evaluation using out-of-sample tests. Operational Research 20(2):701–721

Scikit (2024) posthocs critical difference diagram. Https://scikit-posthocs.readthedocs.io/en/latest/generated/scikit_posthocs.critical_difference_diagram.html

Shapiro A, Homem-de Mello T (1998) A simulation-based approach to two-stage stochastic programming with recourse. Mathematical Programming 81:301–325

Shapiro A, Dentcheva D, Ruszczyński A (2009) Lectures on Stochastic Programming: Modeling and Theory. SIAM

Shenstone AG, Dekker R (2001) A literature review on approaches to the forecasting of intermittent demand. Journal of the Oper Research Society

Summers T, Kamgarpour M (2021) Distributionally robust bootstrap optimization. URL https://arxiv.org/abs/2112.13932, arXiv:2112.13932

Vinod HD, Kourentzes N (2006) Maximum entropy bootstrap for predictive inference. Jou of Forecasting 25(1):49–63

Youngjin K, Youngho L, Junghee H (2011) A splitter location–allocation problem in designing fiber optic access networks. Eur Journal of Operational Research 210(2):425–435

Zhu S, Hu X, Huang K, et al (2021) Optimization of product category allocation in multiple warehouses to minimize splitting of online supermarket customer orders. Eur Jou of Oper Research 290(2):556–571

A Appendix A: Cost function values

This section reports the absolute values of the various cost functions, which were calculated using the forecast errors obtained by averaging the corresponding errors for each of the 52 test case series described in the paper.

The functions reported in the columns are: bias, Means Absolute Percentage Error (MAPE), Mean Error (ME), Mean Absolute Error (MAE), Mean Percentage Error (MPE) and Root Mean Square Error (RMSE). Table 5 gives the cost values for the

model	bias	MAPE	ME	MAE	MPE	RMSE
fcast_50	-0.27	0.09	-1.02	1.63	-0.05	2.12
fcast_avg	0.02	0.07	0.07	1.25	0.01	1.68
yar	0.36	0.34	1.36	5.86	0.07	9.75
yhw	0.63	0.34	2.41	5.99	0.13	10.59
ysvm	0.69	0.36	2.66	6.20	0.14	10.99
ylstm	0.56	0.35	2.13	6.01	0.11	10.41
ymlp	0.47	0.36	1.79	6.26	0.09	10.60
yrf	1.50	0.44	5.73	7.79	0.31	13.54
yxgb	2.28	0.58	8.74	10.12	0.49	17.05
yarima	0.44	0.34	1.67	5.80	0.09	9.77

Table 5: Error costs for the 75 series boostset.

model	bias	MAPE	ME	MAE	MPE	RMSE
fcast_50	-0.56	0.09	-1.08	1.59	-0.06	2.25
fcast_avg	0.02	0.07	0.05	1.18	0.01	1.65
yar	-0.59	0.25	-1.13	4.36	-0.07	6.31
yhw	-0.13	0.24	-0.26	4.33	-0.02	6.39
ysvm	-0.06	0.24	-0.11	4.18	-0.01	6.39
ylstm	-0.30	0.24	-0.58	4.15	-0.04	6.34
ymlp	-0.47	0.24	-0.90	4.22	-0.05	5.99
yrf	1.27	0.28	2.44	5.01	0.14	7.48
yxgb	2.52	0.38	4.85	6.52	0.28	9.46
yarima	-0.40	0.25	-0.76	4.44	-0.05	6.83

Table 6: Error costs for the 125 series boostset.

model	bias	MAPE	ME	MAE	MPE	RMSE
fcast_50	-0.04	0.07	-0.07	1.22	0	1.51
fcast_avg	0.99	0.12	1.90	2.04	0.12	2.76
yar	-0.22	0.35	-0.42	5.84	-0.03	7.64
yhw	0.25	0.34	0.48	5.75	0.02	7.90
ysvm	0.30	0.33	0.58	5.66	0.03	7.76
ylstm	0.10	0.34	0.20	5.76	0	7.74
ymlp	-0.19	0.34	-0.36	5.69	-0.02	7.57
yrf	1.72	0.37	3.31	6.39	0.18	9.66
yxgb	3.01	0.46	5.78	7.96	0.33	11.83
yarima	-0.04	0.34	-0.08	5.69	-0.01	7.63

Table 7: Error costs for the 175 series boostset.

case of a boost set composed of 75 series, table 6 for the 125 series and table 7 for the 175 series sets.

All tables show significantly consistent results across all boost set sizes.

B Appendix B: Extended deterministic benchmark set

All analyses reported in sections 6.1 and 6.2 refer to the case study at the heart of this paper, but the interest of the method is not limited to this particular case study as it can be effective on any instance of this 2-echelon supply chain problem. To test the generality of the results, we generated a benchmark set with varying dimensions and coefficients. The study was conducted only with respect to the deterministic setting, and is therefore significant for assessing the computational complexity of the split-allocation problem as a deterministic combinatorial optimization problem.

We generated 5 instances for each configuration of number of clients (n), number of servers (m), and number of splittable clients. The travel costs were obtained by randomly selecting m rows and n columns from a large distance matrix, whose values were computed as the actual road distances between points located in the same area as the test case. Server inventory costs were inversely proportional to the average travel cost from the server to the clients and client requests were inversely proportional to the average travel cost from the client to the servers. Note that the distance matrix is asymmetric, as it was computed within a city area. The number n_b of splittable clients was progressively increased as the number n_q of servers with nonzero inventory costs. Specifically, the range of the defining parameters were: n: {50, 52, 100, 200, 300}, m: {4, 5, 10, 25, 50}, n_b: {0, 4, 5, 10, 25, 50}, n_q: {0, 1, 2, 3, 4, 5}.

Not all combinations of values were generated, the larger values were used only for instances with higher number of clients. In particular, the values 4 and 52 were only used to generate instances with the same dimensionality as the case study, in order to check the generality of the results obtained. The first instance of this set was kept to be the case study one.

The computational results in the case of no costly server, reported as averages over the 5 generated instances, are summarized in table 8, whose columns show:

- n, m: number of clients and number of servers;
- n_b: maximum number of splittable clients;
- $ncols$, $nrows$: number of columns and number of rows in formulation FD;
- $gaplb$: average percentage gap between the linear relaxation lower bound and the cost of the best solution found;
- $gapfinal$: average percentage gap between the best lower bound at the end of the search (smallest cost of an unexpanded node) and the cost of the best solution found;

n	m	n_b	$ncols$	$nrows$	$gaplb$	$gapfinal$	$ninf$	$nopt$	$tcpu$
52	4	0	416	316	0.21	0.01	0	5	0
50	5	0	500	355	0.39	0.00	0	5	3
50	5	5	500	355	0.40	0.00	0	5	4
50	10	0	1000	610	1.32	0.00	0	5	383
50	10	5	1000	610	1.34	0.00	0	5	378
50	10	10	1000	610	1.35	0.13	0	4	1150
100	10	0	1000	1210	0.50	0.12	0	2	1920
100	10	5	1000	1210	0.54	0.05	0	3	1514
100	10	10	1000	1210	0.57	0.09	0	3	2063
100	50	0	10000	5250	5.23	3.06	0	0	3600
100	50	5	10000	5250	4.77	2.70	0	0	3600
100	50	10	10000	5250	4.55	2.42	0	0	3600
100	50	25	10000	5250	4.52	2.61	0	0	3600
200	10	0	4000	2410	0.17	0.05	0	2	2369
200	10	5	4000	2410	0.17	0.09	0	1	2893
200	10	10	4000	2410	0.18	1.01	0	0	3600
200	50	0	20000	10450	1.66	1.26	0	0	3600
200	50	10	20000	10450	1.68	1.29	0	0	3600
200	50	25	20000	10450	1.71	1.37	0	0	3600
300	10	0	6000	3610	0.09	0.03	0	3	1798
300	10	5	6000	3610	0.09	0.07	0	0	3600
300	10	10	6000	3610	1.02	0.47	0	0	3600
300	50	0	30000	15650	0.94	0.73	0	0	3600
300	50	10	30000	15650	0.93	0.76	0	0	3600
300	50	25	30000	15650	0.96	0.84	0	0	3600

Table 8: Extended benchmark set, deterministic case, no costly server

- $ninf$: number of instances for which no feasible solution was found;
- $nopt$: number of instances solved to proven optimality;
- $tcpu$: average CPU time for solving the instance, time to optimality or 3600 if optimality could not be proven;

The table shows two trends. One, with respect to instance size, shows an expected increase in complexity. While instances the size of our test case are easily solved to optimality by modern solvers, increasing the size, as defined by the number of variables and the number of constraints, quickly leads to instances that could not be solved to optimality within the 3600-second time limit. The number of splittable clients has an important effect on the complexity of the instance. Instances of the same absolute size, but with more splittable clients, usually have a looser linear relaxation (LP) bound and have more difficulty reaching optimality, as can be seen by the decreasing number of instances out of the 5 from each group that could be solved to optimality.

Note that the optimality gap of the LP bound is usually small, except for the n=100 and m=50 instances, but the search still struggles to close this gap. Interestingly, the LP bound gets tighter as n increases, but this does not make the search any easier. The least-cost solution when optimality was not proven was usually found within the first 600 seconds of CPU time. However, we note that designing efficient heuristics

n	m	ncols	nrows	lb0	t0	lb1	t1	lb2	t2	lb3	t3	lb4	t4	lb5	t5
52	4	416	316	0.86	0.2	0.17	0.81	0.08	0.22	0.01	0.02	0.00	0.02	-	-
50	5	500	355	1.33	0.06	2.77	0.06	1.46	0.13	0.11	14.31	0.06	7	0.05	0.93
100	5	1000	705	0.41	0.24	0.09	6.39	0.06	3.2	0.01	0.06	0.02	4.8	0.02	2.71
200	5	2000	1405	0.14	1.43	0.01	1.79	0.01	0.25	0.01	0.17	0.01	0.11	0.01	7.84
52	4	416	316	0.86	0.36	0.24	0.22	0.22	0.14	0.26	0.09	0.05	1.9	-	-
50	5	500	355	1.33	0.16	0.52	0.07	0.50	5.8	0.13	10.11	0.05	1.37	0.02	0.22
100	5	1000	705	0.41	0.33	0.19	8.58	0.04	6.14	0.02	0.41	0.02	0.58	0.02	3.78
200	5	2000	1405	0.14	1.55	0.07	39.07	0.04	9.44	0.01	0.12	0.02	4.48	0.01	6.66

Table 9: Extended benchmark set, deterministic case, increasing number of costly servers

for this problem is beyond the scope of this research. We could have tweaked the solver configuration to favor heuristic search at the expense of efficiency in proving optimality, or designed custom heuristics, but the focus here is on assessing the fitness landscape when road network costs are involved.

Table 9 reports results about tests varying the number of costly servers, the columns show:

- n, m: number of clients and number of servers;
- $ncols$, $nrows$: number of columns and number of rows in formulation FD;
- lb0, t0: linear relaxation bound and CPU time in the case of no costly servers;
- lb1, t1: linear relaxation bound and CPU time in the case of 1 costly server;
- lb2, t2: linear relaxation bound and CPU time in the case of 2 costly servers;
- lb3, t3: linear relaxation bound and CPU time in the case of 3 costly servers;
- lb4, t4: linear relaxation bound and CPU time in the case of 4 costly servers;
- lb5, t5: linear relaxation bound and CPU time in the case of 5 costly servers;

The table reports results on two sets of instances. The top 4 rows contain aggregate results on a set of instances, 5 for each configuration, where inventory costs are directly proportional to average distances, while the bottom 4 rows have costs inversely proportional to average distances.

The complexity of solving instances increases non-monotonically with the number of costly servers, for both increasing and decreasing inventory costs. While the 0-cost instances are comparatively easy to solve, the CPU time required to prove optimality increases with the addition of the first costly servers and then decreases as more servers are paid to store inventory. However, this is not true of the gap between the linear relaxation bound and the cost of the optimal solution, where the instances with no costly servers always have the largest gap. As expected, the CPU time required to prove optimality increases with the dimension, and an inverse correlation between storage cost and travel cost is more difficult to solve than the case with a positive correlation.