

Interface-Scoped Dispatch: Independent Components with $O(1)$ Self-Calls

R. SCOTT MCKINNEY, Manifold Systems, USA

Object composition under static typing forces a trade: independent components, or self-calls through the composite. Forwarding-based constructs compose independent components, but a component's self-calls do not dispatch through the composite. Trait/mixin composition preserves self-call dispatch at the expense of independent components. Neither delivers both. Achieving both at the cost of ordinary dispatch is the open problem.

We present *Parts*, realized as a compiler plugin for Java 8–26. A *part* is an independent component, supplied as a runtime object at construction, whose self-calls route through the composite; the enabling mechanism, *interface-scoped dispatch* (ISD), assigns composite identity per interface rather than per object. Self-calls route through the correct composite in arbitrary DAG compositions. The dispatch cost is $O(1)$, empirically equivalent to a vtable call.

1 INTRODUCTION

Object composition is the standard prescription for avoiding implementation inheritance [1]. Two properties make it a genuine replacement: *independent components* (unrestricted late-bound objects fixed at construction) and *open recursion* (self-calls through the composite). Static typing is what makes the two hard to combine: dynamically-typed object models have had both for decades, yet to our knowledge no available statically-typed language provides them together—and none at the cost of ordinary dispatch.

Forwarding-based composition (Kotlin by [23], Lombok @Delegate [24]) supplies independent components but does not support open recursion: a component's self-calls resolve within the component because the composite is never on the dispatch path. This is the *self* problem [3, 8].

Trait composition (Scala with [9], mixins [4]) inverts the trade. Self-calls dispatch through this in the linearized class, so composite overrides are visible. But traits are fused into the class hierarchy at compile time, not supplied as runtime objects. Components cannot be constructed independently or supplied externally; composition is static.

Parts provides both. @part marks a class as a *part*, an independent object supplied at construction. @link marks a field through which a composite delegates one or more interfaces to a part. When a composite is constructed, a compiler plugin wires composite identity into each part, so self-calls in the part dispatch through the composite. A link field accepts all implementations of its interface: forwarding works with any object; part objects bring open recursion. *Parts* thus subsumes forwarding rather than replacing it. The enabling mechanism is *interface-scoped dispatch* (ISD): assigning composite identity per interface rather than per object enables open recursion in all *Parts* compositions.

The core contributions are:

- **Parts:** a model for object composition in which components are independent runtime objects, self-calls dispatch through the composite, and interface contracts are statically enforced. The model is defined over standard interface hierarchies with a central dispatch invariant (Invariant 1) and composite-scoped encapsulation (@internal).
- **Interface-scoped dispatch (ISD):** the mechanism that assigns composite identity per interface rather than per object, enabling open recursion in *Parts* compositions, including partial delegation (where a composite claims a proper subset of a part's interfaces) and arbitrary DAG compositions.

- **An implementation:** a compiler plugin for Java 8–26 realizing the model at $O(1)$ dispatch cost, with open-source release [26] and IDE integration.

2 OVERVIEW

Consider a minimal example that shows `@part` and `@link` working in a concrete single-rooted composite.

```
interface Formatter {
    String prefix();
    String format(String msg);
}

@part class LogFormatter implements Formatter {
    public String prefix() { return "INFO"; }
    public String format(String msg) { return "[" + prefix() + "] " + msg; }
}

class AppFormatter implements Formatter {
    @link Formatter fmt;
    AppFormatter(Formatter fmt) { this.fmt = fmt; }
    @Override public String prefix() { return "APP"; }
}

new AppFormatter(new LogFormatter()).format("started"); // "[APP] started"
```

When `AppFormatter` is constructed, the compiler wires `LogFormatter`'s composite identity for `Formatter` to `AppFormatter`. A call to `format("started")` dispatches to `LogFormatter.format()`, and the self-call `prefix()` within `format()` dispatches back through `AppFormatter`, invoking `AppFormatter.prefix()`, not `LogFormatter.prefix()`.

Because the `link` field accepts any `Formatter` at construction time, the `part` is a real late-bound object, not fused into the class hierarchy. A different `Formatter` implementation can be substituted without changing `AppFormatter`.

Interface contracts are enforced at compile time: the `link` field has type `Formatter`, and the compiler verifies that `AppFormatter` implements the delegated interface. `Part` identity may not escape the composite dispatch path: passing or assigning `this` as the concrete `part` type is a compile error; interface types are required.

This example is single-rooted: `AppFormatter` is the sole composite for `LogFormatter`, and one composite identity suffices. The following section exposes the limit of the single-identity model and the per-interface generalization that resolves it.

3 THE MODEL

Motivating example

The following example shows a `part` whose interfaces are rooted at different composites. `Track` implements both `Streamable` and `Classifiable`; in the composed graph, `Streamable` is rooted at `Playlist` and `Classifiable` at `Library`. From one `Track` instance, `codec()` must route through `Playlist` and `genre()` through `Library`; a single composite identity cannot serve both. Assigning a separate composite identity per interface resolves this. Figures 1 and 2 show the structure.




Fig. 1. DAG composition structure. Arrows show link fields labeled by the delegated interface. Playlist is the root for Streamable dispatch; Library is the root for Classifiable dispatch.

```

interface Streamable {
    String codec();
    void stream(String audio);
}

interface Classifiable {
    String genre();
    String classify(String title);
}

@part class Track implements Streamable, Classifiable {
    public String codec() { return "wav"; }
    public String genre() { return "unknown"; }
    public void stream(String audio) {
        System.out.println "[" + codec() + " ] " + audio;
    }
    public String classify(String title) {
        stream("indexing: " + title); // Streamable dispatch
        return genre() + ":" + title; // Classifiable dispatch
    }
}

@part class Playlist implements Streamable, Classifiable {
    @link Streamable streamable;
    @link Classifiable classifiable;
    Playlist(Track t) { this.streamable = t; this.classifiable = t; }
    @Override public String codec() { return "mp3"; }
}

class Library implements Classifiable {
    @link Classifiable classifiable;
    Library(Classifiable c) { this.classifiable = c; }
    @Override public String genre() { return "jazz"; }
}

Playlist playlist = new Playlist(new Track());
Library library = new Library(playlist);
String result = library.classify("Autumn Leaves");
out.println(result);
// Streamable dispatch rooted at Playlist -> codec() -> "mp3"
// Classifiable dispatch rooted at Library -> genre() -> "jazz"
// prints: "[mp3] indexing: Autumn Leaves"
// returns: "jazz:Autumn Leaves"

```

Fig. 2. DAG composition with multiple composite roots per part. Track carries distinct composite identities for Streamable (rooted at Playlist) and Classifiable (rooted at Library).

Definitions

We define Parts over a standard typed object model where classes implement interfaces and method dispatch is defined by the receiver's runtime type.

Definition 1 (Part). A *part* is a class annotated with `@part`. Parts implement one or more interfaces. A part may also be a composite.

Definition 2 (Link). A *link* is a field annotated with `@link`. Its declared type is an interface or an abstract part class. A link claims the interfaces common to its field type’s interface hierarchy and the enclosing composite’s. The plugin enforces `private` and `final` on link fields; explicit modifiers are redundant.

Definition 3 (Composite). A *composite* is a class containing one or more link fields. A composite implements all interfaces claimed by its links.

Definition 4 (Delegation surface). The *delegation surface* of a part is its interface hierarchy, excluding any interfaces marked `@internal` in its implements clause.

Definition 5 (Composite identity). When a part is wired to a composite, it receives a *composite identity*: a reference to the composite object. Self-calls within the part (calls to methods on the part’s delegation surface) dispatch through a composite identity rather than `this`.

Definition 6 (Interface-scoped dispatch). *Interface-scoped dispatch* is the dispatch mechanism by which the receiver for a self-call is determined by the interface of the called method, not by `this`. Each interface in a part’s delegation surface is assigned an independent composite identity; self-calls route through the composite for that interface.

Definition 7 (Transitive propagation). A part may itself contain link fields. When such a part is wired to an outer composite, composite identity propagates transitively: the outer composite becomes the dispatch root for each interface it claims throughout the delegation chain. Interfaces not claimed by the outer composite retain the dispatch roots established by inner composites. Propagation traverses part links only: it terminates at any non-part link, which is a forwarding leaf whose self-calls remain local to the delegate. A composition may freely mix parts and non-part delegates: each part routes, each non-part forwards, with no interaction between them.

Definition 8 (Diamond resolution). When two links in a composite share a common interface, exactly one must declare `@link(share=T.class)` for the shared interface. That link is authoritative; the other delegates only its non-shared interfaces, and the shared interface is excluded from propagation when the non-authoritative link is wired. Unresolved diamonds are compile errors.

Two practical extensions, composite-scoped encapsulation (`@internal`) and abstract parts with deferred linkage (`asLink()`), are defined and implemented (Section 4).

Dispatch rule. Traditional object-oriented dispatch resolves a call through the receiver’s object identity:

$$\text{call } m() \text{ on } o \longrightarrow \text{vtable}(o, m)$$

Interface-scoped dispatch replaces the single object identity with a per-interface composite identity. A self-call $m()$ in part P where $m \in I$ resolves through the composite identity for I :

$$\text{self-call } m() \in I \text{ in } P \longrightarrow \$\text{selfesp}[I].m()$$

For self-calls within a part’s methods, the dispatch triple is (*part*, *interface*, *method*) rather than the conventional (*object*, *method*). Figure 3 contrasts this per-interface routing with a single shared composite identity. This is *open recursion*: a method’s self-calls late-bind to the most-derived receiver. Here the receiver resolves from the interface of the self-call. Forwarding is the closed case: a component’s self-calls stay in the component, and the composite never enters the recursion.




Fig. 3. Object-scoped vs. interface-scoped dispatch. In both panels C_2 (impl I_2) delegates I_2 to C_1 (impl I_1, I_2), which delegates both interfaces to part P . *Left*: a self-call $m() \in I_1$ inside P routes through $\$self = C_2$, the wrong composite for I_1 . *Right*: $\$selves[I_1]$ routes to C_1 ; $\$selves[I_2]$ routes to C_2 ; each self-call reaches its correct composite root.

INVARIANT 1. For any part P in a delegation chain for interface I rooted at composite C : a self-call $this.m()$ within P where $m \in I$ dispatches to C .

This invariant presumes each interface has a single composite root. The model maintains this precondition for every composition it admits but does not statically enforce it; the lone exception is treated in Section 5.4.

The invariant is established by construction. When composite C establishes a link to part P for interface I , the plugin-generated `$linkPartToSelf` sets $\$selves_P[I] \leftarrow C$ and recurses into P 's own links, propagating C 's identity for each interface C claims and leaving all other slots unchanged. Each interface of a part resolves through a single $\$selves$ slot. Wiring an outer composite that claims I re-roots this slot to that composite and leaves the slots for interfaces it does not claim unchanged, so the slot holds exactly one root at any time and stabilizes once the outermost composite claiming I is wired; C denotes that final root. Each write occurs during the wiring composite's construction. Wiring happens solely as link field assignment, and the plugin enforces `final` on link fields, so writes are confined to construction: the $\$selves$ slots are never written after the outermost composite claiming I is constructed.

Visibility follows from safe publication: once the composite root is safely published, the Java Memory Model guarantees that any thread observing it sees all writes that happened-before publication, the wired slots included. The role of `final` here is write-confinement, not the JMM's final-field freeze: array-element writes are not covered by freeze semantics, so the guarantee rests on write-confinement together with safe publication of the root, not on the finality of the slots.

Self-calls in P where $m \in I$ are rewritten by the plugin to $((I) \$selves[IDX_I]).m()$; when m belongs to multiple interfaces (the diamond case), I is determined at compile time by diamond resolution (Section 4). For self-calls through the delegation surface, there is no code path in a part method that dispatches through anything other than the indexed slot. Because the slot holds C

once the composition is constructed and is not written thereafter, the invariant holds at every point a self-call can execute. Before wiring, each slot is initialized to `this`; an unwired part dispatches on itself, consistent with standard object-oriented dispatch, and the invariant is vacuously satisfied (no delegation chain exists). A full mechanized proof in a Featherweight Java subset is a natural direction for follow-on work (Section 6.4).

4 IMPLEMENTATION

The implementation is a javac plugin operating on the compiler's AST during two phases. In `ENTER`, the plugin generates structural scaffolding: the `$selves` composite identity array and `$linkPartToSelf` wiring method for each part, delegation forwarding method for each composite class, and (for abstract parts) the `$Impl` subclass and `asLink()` factories. In `ANALYZE`, after type resolution, self-calls in part methods are rewritten, link field assignments are rewritten to invoke wiring, and `@internal` visibility is enforced. No bytecode manipulation is performed; all transformation is at the AST level and subject to standard type checking.

4.1 Part Transformation

Each part holds a `$selves` array whose compile-time-determined ordinals cover the part's interfaces.

```
private final Object[] $selves = {this, ..., this};  
// after wiring: $selves[IDX_I] = composite identity for interface I
```

Before wiring, every `$selves` slot holds `this`, so the part dispatches on itself. Wired at link assignment via `$linkPartToSelf`, dispatch routes through the composite defining the link. `$linkPartToSelf` updates each relevant slot and recurses through link fields in the part whose delegation surface includes the interface being propagated, with cycle detection at each assignment.

Within a part method, every call `this.m(args)` where `m` is declared in interface `I` is rewritten to:

```
((I) $selves[IDX_I]).m(args)
```

The cast to `I` selects the dispatch interface explicitly; when diamond resolution has assigned `m` to a specific authoritative link, `I` is that link's interface, determined at compile time.

The ordinal `IDX_I` is assigned per part over its own delegation surface, so it is local to that class: the rewritten self-calls and the generated `$linkPartToSelf` both reside in the part and share its indexing, and no index agreement across separately-compiled classes is required.

4.2 Composite Transformation

A composite implements every interface claimed by its links. For each method of a claimed interface that the composite does not implement directly, the plugin generates a delegating method that forwards through the corresponding link field:

```
R m(args) { return link.m(args); }
```

When two links share an interface, the forwarders for the shared methods route through the authoritative link (Definition 8). Wiring corresponding with the authoritative link is established by sharing the link's part instance between the links sharing the interface.

In composite classes, each link field assignment `this.link = expr` is rewritten to invoke `$linkPartToSelf`, propagating the composite identity into the part. An `instanceof` check guards the call so that non-part assignments pass through unchanged.

4.3 Abstract Part Support

A part may be abstract, deferring some interface methods to the composite. Linking an abstract part obligates the composite to implement those methods or to be declared abstract, enforced at compile time: the plugin generates a delegating method for every interface method the part implements and none for a method it leaves abstract, so a concrete composite is missing exactly those methods and javac rejects it unless they are supplied directly. This is the compositional analog of the rule that a concrete class must implement its inherited abstract methods.

To make an abstract part instantiable for linking, the compiler generates a private `$Impl` subclass whose stubs throw `DelegationLinkageError`, and an `asLink()` factory per non-private constructor:

```
private static final class $Impl extends Foo {
    $Impl(/* ctor args */) { super(/* ctor args */); }
    @Override public T m(Params p) {
        throw new DelegationLinkageError(
            "abstract method called on an unlinked part");
    }
}
public static Foo asLink(/* ctor args */) { return new $Impl(/* same */); }
```

Once wired, the stubs are unreachable: self-calls dispatch through `$selves` to the composite, whose implementation the compile-time obligation guarantees. The stubs remain only as a runtime guard for an `asLink()` instance invoked before it is wired.

4.4 Default Methods

A part inherits self-calling behavior from the default methods of the interfaces it implements. If neither the composite nor the part overrides a default, it runs with the part as receiver, not the composite, resulting in incorrect self-call dispatch.

No bytecode instruction directly invokes a default with a receiver other than the current `this`, but a method handle bound to an invokedynamic call site can. When a part does not override a default, the plugin generates an override that invokes the interface's default implementation through such a site, with the receiver taken from the interface's slot in `$selves`, so the default's self-calls dispatch through that receiver. An explicit `I.super.m()` in part code is rewritten the same way.

```
interface Foo {
    void bar();
    // default self-calls bar()
    default void foo(P p) { bar(); }
}

@part class FooPart implements Foo {
    public void bar() { ... }

    // generated
    // calls Foo.super.foo() with composite in $selves as receiver
    // Foo's bar() self-call dispatches through the composite
    public void foo(P p) {
        invokedynamic Foo::foo((Foo) $selves[IDX_Foo], p);
    }
}
```


The site's bootstrap links it once to a fixed target (the default implementation), with the receiver as its only varying argument. Being monomorphic, it is inlined by the JIT to the same type of array-indexed invocation as in Section 5.

4.5 Safety Guarantees

Cycle detection. If a part is wired to itself directly or transitively, `DelegationLinkageError` is thrown at assignment time during the recursive `$linkPartToSelf()` call.

Deferred method access. The obligation that a wired composite implement an abstract part's deferred methods is enforced at compile time; an `asLink()` instance invoked before wiring throws `DelegationLinkageError` from the `$Impl` stub, the compositional analog of `AbstractMethodError`.

@internal enforcement. `@internal` may annotate an interface method or an interface type literal in a class's `implements` clause, with distinct effects. A marked method has its calls confined to the composite, the intent behind protected in implementation inheritance, but more cleanly scoped for composition. A marked interface type literal in a class's `implements` clause removes that interface from the class's delegation surface: no composite may claim it via a link field.

Self-preservation. Inside a part, this use is guarded. Field access, private calls, and callbacks through the part's own link fields (the compositional analog of `super`) are all permitted. Passing or assigning this as the concrete part type is not: that is a compile error, since a caller holding the bare part could invoke methods outside the composite dispatch path and violate Invariant 1. The only this that can leave is therefore interface-typed, and the reference that crosses is the `$selves` slot for that interface: the part's composite identity for it, which may be the part itself. A client receiving it reaches the composite's overrides; recovering some other interface by reflection or downcast can still reach a lower root (Section 5.4).

5 EVALUATION

5.1 Dispatch Performance

The dispatch path for a self-call through a composite is:

- (1) Load `$selves[IDX_I]`, an array-indexed load with compile-time constant index
- (2) Cast to `I`
- (3) `invokeinterface m`, standard JVM virtual dispatch

This is $O(1)$. The parallel to `vtable` dispatch is direct: a `vtable` call is an indexed slot load followed by an indirect call. Call sites in typical compositions are monomorphic or bimorphic, the JIT's most aggressively optimized scenarios. Composite dispatch adds at most one additional virtual dispatch over direct delegation.

Benchmark. We verify this empirically using JMH [25] in average-time mode. Each scenario calls `compute()` through a composite root at chain depth d (1–6). The *baseline* traverses d `@link` delegation hops to a leaf that returns directly, with no self-call. The *concrete* variant traverses the same hops but the leaf issues a self-call (`$selves[IDX_I].scale()`) from a concrete part method, dispatching through the composite root. The *default* variant issues the same self-call from an inherited interface default method the leaf does not override, routed through the generated `invokedynamic` override of Section 4.4. The delta (concrete minus baseline) isolates the cost of the self-call dispatch mechanism alone. All runs: 10 JVM forks, 5 warmup iterations, 10 measurement iterations per fork (100 data points per cell); errors are $\pm$ half-width of the 99.9% confidence interval.

A separate single-dispatch calibration run (`invokeinterface` on a monomorphic call site, same harness) yields 0.43 ns/op; the delta values in Table 1 are therefore roughly 1–2 $\times$ a single virtual dispatch.

Choice of baseline. The delta is measured against Parts’s own forwarding path, which is the right baseline: that path is semantically equivalent to Kotlin by and Lombok `@Delegate` (Section 7), so the delta prices exactly the self-call routing those mechanisms cannot express, against their own dispatch cost. To our knowledge no other model satisfies all three criteria with a runnable implementation, so there is no cross-system benchmark to run; that comparison is analytic (Section 7).

Table 1. Self-call dispatch cost by delegation depth (JMH, average-time mode; ns/op, $\pm$ 99.9% CI half-width). *Baseline* traverses the delegation hops with no self-call; *Concrete* and *Default* add one self-call through the composite, issued from a concrete part method and from an inherited interface default (via `invokedynamic`) respectively. The delta (Concrete minus Baseline) isolates the self-call dispatch cost over plain delegation. Values are rounded from the measured means and intervals; the delta combines the Baseline and Concrete cells (difference of means, half-widths in quadrature) and may differ from the rounded column difference by 0.01 ns.

Depth	Baseline (ns)	Concrete (ns)	Default (ns)	Delta (ns)
1	0.62 $\pm$ 0.02	1.16 $\pm$ 0.03	1.18 $\pm$ 0.03	0.55 $\pm$ 0.03
2	0.91 $\pm$ 0.03	1.56 $\pm$ 0.04	1.55 $\pm$ 0.04	0.65 $\pm$ 0.05
3	1.18 $\pm$ 0.03	1.93 $\pm$ 0.05	1.92 $\pm$ 0.05	0.75 $\pm$ 0.06
4	1.64 $\pm$ 0.03	2.30 $\pm$ 0.06	2.23 $\pm$ 0.06	0.66 $\pm$ 0.07
5	1.93 $\pm$ 0.06	2.70 $\pm$ 0.06	2.76 $\pm$ 0.07	0.77 $\pm$ 0.09
6	2.37 $\pm$ 0.06	3.21 $\pm$ 0.09	3.23 $\pm$ 0.08	0.84 $\pm$ 0.11

Across depths 1–6 the delta remains bounded, on the order of a single virtual dispatch (the 0.43 ns calibration above), consistent with one array-indexed load (`$selves[IDX_I]`) followed by `invokeinterface`. The self-call routes through a dynamically wired `$selves` slot, so its receiver is not statically known and the dispatch does not fold away: the delta is one genuine virtual dispatch, with the array indexing on top (confirmed free below). The $O(1)$ claim is structural: one dispatch per self-call, independent of depth, with the per-call cost pinned by the isolation measurement below. The small upward drift in the delta across depths (0.55 to 0.84 ns) stays well under a second dispatch and plausibly reflects less complete inlining of the dispatch site within the larger compiled method at greater depth. The *default* column tracks the *concrete* column within $\pm 3\%$ at every depth, with the sign of the difference varying; the two are indistinguishable at this resolution. The interface-default template, dispatched through `invokedynamic`, thus carries no measurable cost over the concrete part template, confirming the equivalence claimed in Section 4.4. The comparison is steady-state: the one-time bootstrap that links each `invokedynamic` site is absorbed during warmup and is not measured here.

Isolating the array index. The depth-series delta is essentially one virtual dispatch; to confirm the `$selves` array indexing adds nothing on top, we isolate the dispatch. Holding a target method non-inlinable so a real call occurs, we compare three depth-0 forms over the same receiver: a `vtable` call (`invokevirtual`), the `invokeinterface` it compiles to, and the plugin’s emitted form (`((I) $selves[IDX_I]).m()` (an `Object[]` element load, a cast, and `invokeinterface`). Over 10 JVM forks (JDK 21) the three are statistically indistinguishable: the ISD form differs from the bare `invokeinterface` it emits by 0.03 ± 0.09 ns, and from `invokevirtual` by 0.10 ± 0.05 ns, both within the fork-to-fork variance of the measurement. The array-element load is thus not separately

observable; it overlaps with the dispatch. The self-call costs one virtual dispatch and no more, the empirical content of the vtable-equivalence claim.

Construction cost. The result above is the steady-state call cost; wiring is paid once, at construction. Building a composite invokes `$linkPartToSelf` at each link assignment, which sets the relevant `$selves` slots and recurses through the part's own link fields, propagating composite identity for each interface the composite claims. Cycle detection adds only a constant-time check per claimed interface, an aaload and a compare, so each part node costs $O(1)$ per propagated interface and the whole traversal is linear in the size of the delegation graph reachable through link fields. None of it lies on the dispatch path, so the per-call cost is unchanged, and the traversal is proportional to the object graph the program constructs in any case. The cost is therefore a bounded, one-time increment to composite construction, amortized over every subsequent self-call.

5.2 Example: Teaching Assistant

The following example exercises DAG composition, diamond dispatch resolution, and self-call routing through the composite. A teaching assistant is both a student and a teacher; both roles share a common `Person` base.

```
interface Person {  
    String getName(); String getTitle(); String getTitledName();  
}  
interface Student extends Person { String getMajor(); }  
interface Teacher extends Person { String getDept(); }  
interface TA extends Student, Teacher {}
```

Forwarding (Kotlin) [23, 24]. Forwarding-based mechanisms inject the implementation as a real object at construction time; components are independent. But self-calls remain within the component: the composite is invisible. Delegating `Student` by `s` and `Teacher` by `t` creates a diamond: the compiler forces a manual override of every shared `Person` method. The deeper problem is that `getTitledName()`, the template method worth sharing, cannot be safely delegated: whichever branch receives it calls `getTitle()` on its own `this`, bypassing `TaImpl.getTitle()`.

```
class TaImpl(val s: Student, val t: Teacher) : TA,  
    Student by s, Teacher by t {  
    // Diamond: every shared Person method must be manually resolved  
    override fun getName() = s.getName()  
    override fun getTitle() = "TA"  
    // Without this override, getTitledName() forwards to s.getTitledName(),  
    // which calls s.getTitle() = "Student" -- self stays in the delegate:  
    // TaImpl(...).getTitledName() -> "Student Milton" (wrong)  
    override fun getTitledName() = "${getTitle()} ${getName()}"  
    // TaImpl(...).getTitledName() -> "TA Milton" (correct, but forced)  
}
```

Every composite must re-implement `getTitledName()`. Adding a new template method to `Person` requires a matching override in every composite class; the maintenance cost grows with the number of composites. Lombok's `@Delegate` generates equivalent forwarders in Java; the self-call semantics are identical.

Parts. `PersonPart` holds the template once. Its self-call to `getTitle()` dispatches through the composite at each level of the delegation chain.

```

@part class PersonPart implements Person {
    private final String name;
    public PersonPart(String name) { this.name = name; }
    public String getName()      { return name; }
    public String getTitle()     { return "Person"; }
    public String getTitledName() { return getTitle() + " " + getName(); }
}

@part class StudentPart implements Student {
    @link Person person;
    private final String major;
    public StudentPart(Person p, String major) {
        this.person = p; this.major = major;
    }
    public String getTitle() { return "Student"; }
    public String getMajor() { return major; }
}

@part class TeacherPart implements Teacher {
    @link Person person;
    private final String dept;
    public TeacherPart(Person p, String dept) {
        this.person = p; this.dept = dept;
    }
    public String getTitle() { return "Teacher"; }
    public String getDept() { return dept; }
}

@part class TaPart implements TA {
    @link(share=Person.class) Student student;
    @link Teacher teacher;
    public TaPart(Student s) {
        this.student = s;
        this.teacher = new TeacherPart(s, "Math");
    }
    public String getTitle() { return "TA"; }
}

TA ta = new TaPart(new StudentPart(new PersonPart("Milton"), "CS"));
ta.getTitledName(); // "TA Milton" -- getTitle() dispatches through TaPart

```

getTitle() is defined once in PersonPart and overridden nowhere. Diamond resolution is handled statically: @link(share=Person.class) designates student as the authoritative delegate for Person, so Person is excluded from propagation when teacher is wired, leaving the identity established through student intact.

5.3 Case Study: Stream Decoration

A pattern common in the JDK, exemplified by `java.io.InputStream` [1], is a bulk operation implemented as a loop over a finer one: `read(byte[], int, int)` calls the single-byte `read()` repeatedly. Decorators override `read()` to add behavior; the template is supposed to propagate it to bulk calls automatically. The Readable interface below captures this contract directly. Under forwarding, the propagation breaks.

A `CountingStream` that tracks bytes consumed overrides `read()` to increment a counter. With Lombok's `@Delegate`, `read(byte[], int, int)` is forwarded to the delegate, which calls `read()` on itself, not on `CountingStream`. The override is never reached for bulk calls.

Forwarding [24].

```
interface Readable {
    int read();
    int read(byte[] buf, int off, int len);
}

class BaseStream implements Readable {
    private final byte[] data;
    private int pos;
    BaseStream(byte[] data) { this.data = data; }
    public int read() {
        return pos < data.length ? (data[pos++] & 0xff) : -1;
    }
    public int read(byte[] buf, int off, int len) {
        for (int i = 0; i < len; i++) {
            int b = read(); // self-call
            if (b == -1) return i == 0 ? -1 : i;
            buf[off + i] = (byte) b;
        }
        return len;
    }
}

class CountingStream implements Readable {
    @Delegate private final Readable delegate;
    private int count;
    CountingStream(Readable r) { this.delegate = r; }
    @Override public int read() {
        int b = delegate.read();
        if (b != -1) count++;
        return b;
    }
    public int count() { return count; }
}

CountingStream cs = new CountingStream(new BaseStream(data));
cs.read(buf, 0, 16); // -> delegate.read(byte[],int,int)
                    //   -> delegate.read() -- not cs.read()
cs.count();         // 0 -- bulk reads not counted
```

Parts. `BaseStream` is unchanged except for the `@part` annotation. The self-call in `read(byte[], int, int)` routes through `CountingStream` on every call path.

```
@part class BaseStream implements Readable { /* same as above */ }

class CountingStream implements Readable {
    @link Readable stream;
```

```

private int count;
CountingStream(Readable r) { this.stream = r; }
@Override public int read() {
    int b = stream.read();
    if (b != -1) count++;
    return b;
}
public int count() { return count; }
}

CountingStream cs = new CountingStream(new BaseStream(data));
cs.read(buf, 0, 16); // -> BaseStream.read(byte[],int,int)
                    // -> self-call read() -> CountingStream.read()
cs.count();         // 16 -- all bytes counted

```

A new decorator (buffering, decryption, rate limiting) requires only overriding `read()`; `BaseStream.read(byte[], int, int)` routes its self-call through whichever composite is the dispatch root, without modification.

5.4 Limitations

- Using `@link`, `@part`, and `@internal` requires configuring the `javac` plugin in the build system (Maven, Gradle, or similar).
- Composite dispatch semantics are not enforced against runtime introspection that reaches past a reference's supplied static type. A client that reflects on an escaped reference, or downcasts it to an interface it was not handed, can invoke that interface below its composite root, bypassing the overrides above it; type-directed clients, which use the interface they were handed, are unaffected.
- A part instance carries one composite root per interface (Section 6). Linking the same instance into two composites that each claim the *same* interface, with neither nesting the other, re-roots that interface to whichever is wired last, redirecting the first composite's self-calls. The contention is undetectable at the wiring step: re-rooting an already-wired slot is the model's normal operation during transitive propagation, so the two cases are observationally identical. One instance cannot be the composite root for a single interface in two places at once; separate part instances avoid it entirely.
- The plugin relies on internal `javac` APIs for AST rewriting, which may require adaptation across JDK releases. In practice the approach has proven stable: the Manifold project, on which this plugin is built, has tracked 18 JDK releases without API-driven breakage.

6 DISCUSSION

6.1 Implementation Identity and Dispatch Identity

A composition model that supports independent components must handle two structural scenarios:

- **Partial delegation:** a composite delegates a subset of a part's interfaces.
- **Multi-root:** a part's interfaces are claimed by separate composites, each requiring a distinct dispatch root from the same instance.

Multi-root requires a part to carry multiple simultaneous composite identities, one per interface. ISD resolves this by separating two notions of identity: *implementation identity*, the part object, from *dispatch identity*, the composite per interface. Within ISD, partial delegation and multi-root

are modeled the same way. Every interface has a single composite root: the composite that claims it, or the part itself when none does.

Multi-root arises naturally from partial delegation: when an outer composite claims a subset of a part's interfaces, transitive propagation assigns different roots to the remaining interfaces, producing multi-root at the part level. The Track example in Section 3 demonstrates this directly: Library claims only Classifiable from Playlist (partial delegation), which by propagation gives Track separate roots for Streamable and Classifiable (multi-root).

6.2 Language Design Implications

Parts resolves each known deficiency of implementation inheritance:

- **Fragile base class** [2]: a composite's dependency surface is the interface contracts it explicitly claims, not a part's internal implementation; changes to its encapsulated internals do not propagate. Partial delegation completes the isolation: a composite is unaffected by changes to interfaces it did not claim.
- **Forced IS-A semantics**: reuse does not require a type relationship; the composite is a subtype of the interface, not of the part.
- **The self problem**: a hazard in forwarding-based composition where self-calls remain within the component rather than routing through the composite; resolved by ISD.
- **Diamond ambiguity**: explicit `@link(share=T.class)` resolution; unresolved diamonds are compile errors, not silent merges.
- **Encapsulation breach**: a composite may implement a subset of its parts' interfaces; those it does not implement are absent from its API by construction. `@internal` strengthens this further: it provides composite-scoped visibility, preventing designated interfaces from being claimed by any composite.
- **Abstract behavior**: abstract parts with deferred linkage (`asLink()`) preserve the template-method capability of abstract classes without coupling the hierarchy.

Implementation inheritance's power is open recursion. Its fragility is the surface that power ranges over: every overridable member. Parts keeps the open recursion but bounds the surface to the declared interface contract; self-calls still reach the composite's overrides, while the internals that make base classes fragile stay off it entirely.

The interface contract—not implementation types—is what makes dispatch constant-time: a fixed, statically-known interface set lets each interface's composite root be an array-indexed slot. Restricting a part from exposing this as its concrete type is the static guarantee that makes the dispatch invariant hold.

Implementation inheritance and Parts are two bindings of the same open recursion: implementation inheritance binds it to the class hierarchy, where a subclass IS-A its superclass and inherits its entire implementation surface, while Parts binds it to a held object and a declared interface, where the composite HAS-A its parts and IS-A only their interfaces. That inheritance is open recursion, separable from subtyping, is Cook's [5, 6], and the reading of inheritance as composition is Bracha and Cook's [4]. Cook's model threads self as an explicit parameter; ISD keeps it implicit and per-interface. The missing piece was not theoretical but practical: independent runtime components, static interface contracts, and dispatch at the cost of a virtual call.

6.3 Concurrency

A constructed composition is safe to share across threads. Each interface's `$selves` slot is written only while its final composite root (Invariant 1) is under construction; once that root is safely published the slot is never written again, so the JMM makes all wired state visible to any thread

observing the root, with no synchronization on the dispatch path. The guarantee is thus scoped to a single composition, resting on the one-root invariant of Section 6. Parts may hold mutable state under the usual Java rules; dispatch adds no synchronization points.

6.4 Future Work

Per-interface composite roots as a general primitive. Assigning dispatch identity per interface rather than per object is a primitive that prior composition models do not expose. Problems that current statically-typed designs address through dynamic dispatch, AOP weaving, or collapsed component hierarchies may have cleaner solutions within this primitive. The extent of that solution space is an open question.

Formal verification. A mechanized proof of Invariant 1 in a small-step operational semantics would provide assurance beyond the construction argument in Section 3. The model maps cleanly to a subset of Featherweight Java, a natural starting point.

Domain model and persistence integration. IS-A relationships in normalized relational schemas map naturally to the Parts model: each type owns its interface and its data independently, composed at construction with open recursion available across the composed object. Transactional systems are designed for this normalized, per-type form. Much of the pressure to denormalize comes from the object model: the table-per-hierarchy strategy—a common ORM default for IS-A—collapses the hierarchy into one table, the storage shadow of the single object implementation inheritance produces. Mapping such a schema to objects has meant a choice between an inheritance hierarchy that couples the types and hand-wired composition that gives up open recursion. Parts needs neither, keeping the types independent with open recursion intact, aligning the domain model with the normalized schema the relational model already favors. How that mapping is realized in a persistence framework is an open question.

Parts as a complete compositional alternative. Parts does not argue that implementation inheritance is wrong, but that it is no longer the only practical option. Any codebase written with implementation inheritance can in principle be expressed purely in Parts compositions; whether the result is better depends on the codebase. What the model offers is a compositional foundation that delivers open recursion without hierarchy and fosters low coupling and high cohesion through its interface contracts and independent parts. A systematic study of implementation inheritance patterns in real codebases would identify any remaining gaps and clarify where the compositional model offers the most advantage.

7 RELATED WORK

Static typing is the baseline requirement; models without it are included where relevant.

Forwarding. Kotlin’s `by keyword` [23] generates forwarding methods at compile time; Lombok’s `@Delegate` [24] does the same in Java; Scala 3’s `export` keyword [22] generates forwarding methods for delegated members. In all cases, a component’s self-calls resolve within the component; the composite host is invisible. The mechanism is forwarding, not delegation. Scala provides both mechanisms in the same language: `export` for forwarding with independent components, and `traits` for correct self-call dispatch. Yet no combination of the two satisfies both requirements. Büchi and Weck’s generic wrappers [14] give the same forwarding choice a formal, soundness-proven treatment, and are the closest prior analysis of the identity-escape hazard our self-preservation constraint prevents (Section 4), though they decline the disciplines we adopt as too restrictive for arbitrary legacy objects.

Scala traits / abstract type members. Odersky and Zenger [9] introduced statically-typed mixin composition with abstract type members. Scala's `with` clause linearizes traits into the target class at compile time, so self-calls dispatch through the outermost class in the linearized hierarchy. This gives open recursion, but it also fuses the component into the class: the trait's implementation is resolved at compile time, not supplied as an independent component at construction. A component implementation therefore cannot be chosen or replaced, and a single instance cannot be shared across composites. The fusion and the open recursion are inseparable: linearization is the single mechanism behind both, so in statically-typed languages fusing the component into the class became standard, and remains so in recent precisely-typed mixin systems [10]. Interface-scoped dispatch shows the fusion was never necessary: it obtains the same open recursion without abandoning independent components.

Prototype-based delegation. Lieberman [3] introduced *open delegation*: an object may delegate unanswered messages to a prototype, with *self* remaining the original receiver throughout the chain. Self [8] realized this in a working language. These systems support open recursion with late-bound components in arbitrary delegation graphs. Static type guarantees are absent by design.

Mixins. Bracha and Cook [4] formalized mixins as parameterized abstract subclasses. Mixins extend through linearization: the mixin is applied to a chain at class definition time, not supplied as an independent component at construction. Self-calls dispatch through this in the linearized result.

Traits. Schärli et al. [7] proposed traits as stateless, composable units of behavior. Trait composition is a compile-time operation: methods are flattened into the target class, not supplied as independent components at construction. Self-calls dispatch through this in the composed class.

Multiple inheritance. Stroustrup [11] introduced virtual base classes and virtual inheritance in C++ to handle diamonds. The result is a single linearized object with a merged vtable; components are not preserved as independent objects.

Kniesel / Lava. Kniesel's "type-safe delegation" [12, 13] is the closest predecessor and frames the problem this paper inherits: components are real runtime objects supplied at construction, types are statically enforced, and DARWIN binds *self* to the original receiver so self-calls route through the composite rather than staying in the component. The difference from Parts is not in capability but in practice. DARWIN routes each self-call through forwarding adapters and a reflective walk up the parent-pointer chain (`Lava.parentCast`); that walk is a search, not a constant-time step. The typical configuration `@link` targets is an abstract or interface parent with a concrete-subtype instance. For exactly that case, Kniesel's own analysis is candid that dispatch "can be slowed down significantly" [13, §7.4.2]. The component is never present in the composition as itself—widened to Object or adapter-wrapped—where Parts holds it directly and dispatches through an array index. He explored mitigations, leaving their evaluation open [13, §7.5.5]; the system was realized in Lava, a research language. Kniesel also weighed the static alternative of storing the composite identity in the component, and his objections to it are sound: "sharing of one parent by multiple delegating children cannot be expressed at all," and recursive delegation could be simulated only "with significant run-time and software maintenance costs" [12]. Each objection holds for a single per-object identity wired at run time. Interface-scoped dispatch answers them with two mechanisms: indexing the stored identity by interface lets multiple composites claiming disjoint interfaces of a shared part each hold their own root, and transitive propagation wires recursive delegation chains at construction, so dispatch stays constant-time and the chain adds no per-call cost or maintenance burden.

Delegation Layers. Ostermann’s delegation layers [15] (ECOOP 2002) combine delegation with virtual classes to compose collaborations dynamically at runtime; self-calls route correctly within a composed collaboration. The unit composed is the collaboration (a layer of virtual nested classes bound to a common enclosing type), not the individual object; participants are members of that collaboration.

Virtual classes and family polymorphism. The virtual-class lineage (gbeta [18], CaesarJ [19], Object Teams/Java [20], and J& [17]) achieves open class composition through virtual nested classes within a common enclosing family type; Ernst, Ostermann, and Cook [16] provide the definitive formal treatment. Components are runtime instances of virtual classes, but they are bound to an enclosing family type and cannot be independently supplied from outside. Self-calls dispatch correctly within the family. The dispatch scope is the enclosing family.

Dynamic composition. Newspeak [21] treats classes as first-class late-bound arguments, enabling runtime composition of first-class module objects with open recursion. Static type checking is absent by design.

8 CONCLUSION

In static typing, the *self* problem with independent components is a large part of why object composition never displaced implementation inheritance: a self-call that reaches the composite’s overrides is the one capability that made inheritance necessary rather than merely convenient. Parts resolves this by grounding identity in the interface rather than the object, recovering open recursion across independent components at ordinary dispatch cost—the two properties are not inherently in conflict, only unreconciled by prior models.

REFERENCES

- [1] E. Gamma, R. Helm, R. Johnson, and J. Vlissides. *Design Patterns: Elements of Reusable Object-Oriented Software*. Addison-Wesley, 1994.
- [2] L. Mihajlov and E. Sekerinski. A study of the fragile base class problem. In *Proceedings of ECOOP*, LNCS 1445, pages 355–382, 1998.
- [3] H. Lieberman. Using prototypical objects to implement shared behavior in object-oriented systems. In *Proceedings of OOPSLA*, pages 214–223, 1986.
- [4] G. Bracha and W. Cook. Mixin-based inheritance. In *Proceedings of OOPSLA/ECOOP*, pages 303–311, 1990.
- [5] W. Cook and J. Palsberg. A denotational semantics of inheritance and its correctness. In *Proceedings of OOPSLA*, pages 433–443, 1989.
- [6] W. R. Cook, W. Hill, and P. S. Canning. Inheritance is not subtyping. In *Conference Record of POPL*, pages 125–135, 1990.
- [7] N. Schärli, S. Ducasse, O. Nierstrasz, and A. Black. Traits: Composable units of behaviour. In *Proceedings of ECOOP*, LNCS 2743, pages 248–274, 2003.
- [8] D. Ungar and R. B. Smith. Self: The power of simplicity. In *Proceedings of OOPSLA*, pages 227–242, 1987.
- [9] M. Odersky and M. Zenger. Scalable component abstractions. In *Proceedings of OOPSLA*, pages 41–57, 2005.
- [10] A. Fan and L. Parreaux. super-charging object-oriented programming through precise typing of open recursion. In *Proceedings of ECOOP*, LIPIcs 263, pages 11:1–11:28, 2023. DOI: 10.4230/LIPIcs.ECOOP.2023.11.
- [11] B. Stroustrup. Multiple inheritance for C++. In *Proceedings of the EUUG Spring Conference*, 1987.
- [12] G. Kniesel. Type-safe delegation for run-time component adaptation. In *Proceedings of ECOOP*, LNCS 1628, pages 351–366, 1999. DOI: 10.1007/3-540-48743-3_16.
- [13] G. Kniesel. *Dynamic Object-Based Inheritance with Subtyping*. PhD thesis, University of Bonn, 2000.
- [14] M. Büchi and W. Weck. Generic wrappers. In *Proceedings of ECOOP*, LNCS 1850, pages 201–225, 2000.
- [15] K. Ostermann. Dynamically composable collaborations with delegation layers. In *Proceedings of ECOOP*, LNCS 2374, pages 89–110, 2002.
- [16] E. Ernst, K. Ostermann, and W. R. Cook. A virtual class calculus. In *Conference Record of POPL*, pages 270–282, 2006.
- [17] N. Nystrom, X. Qi, and A. C. Myers. J&: Nested intersection for scalable software composition. In *Proceedings of OOPSLA*, pages 347–366, 2006.

- [18] E. Ernst. Family polymorphism. In *Proceedings of ECOOP*, LNCS 2072, pages 303–326, 2001.
- [19] I. Aracic, V. Gasiunas, M. Mezini, and K. Ostermann. An overview of Caesar]. In *Transactions on Aspect-Oriented Software Development I*, LNCS 3880, pages 135–173, 2006.
- [20] S. Herrmann. Object Teams: Improving modularity for crosscutting collaborations. In *Proceedings of NetObjectDays*, LNCS 2591, pages 248–264, 2002.
- [21] G. Bracha, P. von der Ahé, V. Bykov, Y. Kishai, W. Maddox, and E. Miranda. Modules as objects in Newspeak. In *Proceedings of ECOOP*, LNCS 6183, pages 405–428, 2010.
- [22] EPFL. Exports — Scala 3 reference. <https://docs.scala-lang.org/scala3/reference/other-new-features/export.html>, 2024.
- [23] JetBrains. Delegation — Kotlin programming language. <https://kotlinlang.org/docs/delegation.html>, 2024.
- [24] Project Lombok. @Delegate — Lombok features. <https://projectlombok.org/features/Delegate>, 2024.
- [25] A. Shipilev and contributors. JMH: Java Microbenchmark Harness. <https://github.com/openjdk/jmh>, 2013–2024.
- [26] R. S. McKinney. manifold-delegation. <https://github.com/manifold-systems/manifold/tree/master/manifold-deps-parent/manifold-delegation>, 2026.