

```

1  /*In a bank there are n customers with attributes name, account_no, and balance. Write a program
2  to find out who has the highest balance in the bank.*/
3  #include <stdio.h>
4  #define N 100
5
6  struct Account
7  {
8      int account_no;
9      char name[20];
10     float balance;
11 };
12
13 int main()
14 {
15     struct Account customer[N];
16     int n;
17
18     // Input the number of customers
19     printf("How many customers: ");
20     scanf("%d", &n);
21
22     // Input data for each customer
23     for (int i = 0; i < n; i++)
24     {
25         printf("\nEnter data for customer %d:\n", i + 1);
26         printf("Enter account no: ");
27         scanf("%d", &customer[i].account_no);
28         printf("Enter name: ");
29         scanf(" %s", customer[i].name);
30         printf("Enter balance: ");
31         scanf("%f", &customer[i].balance);
32     }
33
34     // Find the customer with the highest balance
35     float max_balance = customer[0].balance;
36     int max_index = 0;
37
38     for (int i = 1; i < n; i++)
39     {
40         if (customer[i].balance > max_balance)
41         {
42             max_balance = customer[i].balance;
43             max_index = i;
44         }
45     }
46
47     // Display information about the customer with the highest balance
48     printf("\nCustomer with the highest balance:\n");
49     printf("Account number: %d\n", customer[max_index].account_no);
50     printf("Name: %s\n", customer[max_index].name);
51     printf("Balance: %.2f\n", customer[max_index].balance);
52
53     return 0;
54 }
55

```

```
manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!  
● $ cd "/home/manish/vs-code/bca-programming-repo/C/nestedStructure_and_Union/" && gcc ques  
question1  
How many customers: 4  
Enter data for customer 1.  
Enter account no: 1234  
Enter name: Ram  
Enter balance: 20000  
Enter data for customer 2.  
Enter account no: 21345  
Enter name: Shyam  
Enter balance: 40000  
Enter data for customer 3.  
Enter account no: 32154  
Enter name: Sima  
Enter balance: 65000  
Enter data for customer 4.  
Enter account no: 5412  
Enter name: Grishma\  
Enter balance: 100000  
  
Customer having highest balance:  
Account number: 5412  
Name: Grishma\  
Balance: 100000.00  
  
manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!  
○ $ █
```

```

1  /*Program to read 5 students record with following fields and display the record
2  of BCA faculty only.
3  Roll No.   |   Name   |   Faculty   |   DOB(date of birth)   |
4  |           |           |           |   dd | mm | yy       |
5  */
6  #include <stdio.h>
7  #include <string.h>
8  #define NUM 5
9
10 struct DOB
11 {
12     int dd;
13     int mm;
14     int yy;
15 };
16
17 struct Student
18 {
19     int roll_no;
20     char name[20];
21     char faculty[10];
22     struct DOB date_of_birth;
23 };
24
25 int main()
26 {
27     struct Student s[NUM];
28
29     // Input data for each student
30     for (int i = 0; i < NUM; i++)
31     {
32         printf("\nEnter data for student %d:\n", i + 1);
33         printf("Enter roll number: ");
34         scanf("%d", &s[i].roll_no);
35         printf("Enter name: ");
36         scanf(" %s", s[i].name);
37         printf("Enter faculty: ");
38         scanf(" %s", s[i].faculty);
39         printf("Enter day: ");
40         scanf("%d", &s[i].date_of_birth.dd);
41         printf("Enter month: ");
42         scanf("%d", &s[i].date_of_birth.mm);
43         printf("Enter year: ");
44         scanf("%d", &s[i].date_of_birth.yy);
45         printf("\n");
46     }
47
48     // Display the records of students in the BCA faculty
49     printf("Student records of BCA Faculty:\n");
50     for (int i = 0; i < NUM; i++)
51     {
52         if (strcmp(s[i].faculty, "BCA") == 0)
53         {
54             printf("Roll no: %d\n", s[i].roll_no);
55             printf("Name: %s\n", s[i].name);
56             printf("Faculty: %s\n", s[i].faculty);
57             printf("Date of birth: %d-%d-%d\n", s[i].date_of_birth.yy, s[i].date_of_birth.mm, s[i].date_of_birth.dd);
58         }
59     }
60
61     return 0;
62 }
63

```

```
manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!  
● $ ./question2
```

```
Enter data for student 1:  
Enter roll number: 13  
Enter name: Manish  
Enter faculty: BCA  
Enter day: 8  
Enter month: 6  
Enter year: 2002
```

```
Enter data for student 2:  
Enter roll number: 1  
Enter name: Benjamin  
Enter faculty: CSIT  
Enter day: 8  
Enter month: 8  
Enter year: 2000
```

```
Enter data for student 3:  
Enter roll number: 13  
Enter name: Grishma  
Enter faculty: CSIT  
Enter day: 9  
Enter month: 8  
Enter year: 2003
```

```
Enter data for student 4:  
Enter roll number: 14  
Enter name: Milan  
Enter faculty: Electrical  
Enter day: 2  
Enter month: 3  
Enter year: 2000
```

```
Enter data for student 5:  
Enter roll number: Bishal  
Enter name: Enter faculty: CSIT  
Enter day: 2  
Enter month: 2  
Enter year: 2002
```

```
Student records of BCA Faculty:  
Roll no: 13  
Name: Manish  
Faculty: BCA  
Date of birth: 2002-6-8
```

```

1 // Program to demonstrate the use of pointer to structure.
2 #include <stdio.h>
3
4 // Define the structure for Book
5 struct Book
6 {
7     char name[20];
8     int pages;
9     float price;
10 };
11
12 int main()
13 {
14     // Declare an array of Book structures and a pointer to Book
15     struct Book b[2], *ptr = b;
16
17     // Input details for each book
18     for (int i = 0; i < 2; i++)
19     {
20         printf("Enter name: ");
21         scanf("%s", (ptr + i)->name);
22
23         printf("Enter number of pages: ");
24         scanf("%d", &(ptr + i)->pages);
25
26         printf("Enter price: ");
27         scanf("%f", &(ptr + i)->price);
28
29         printf("\n");
30     }
31
32     // Display Book details
33     printf("\nBook Details:\n");
34     for (int i = 0; i < 2; i++)
35     {
36         printf("Name: %s\nTotal Pages: %d\nPrice: %.2f\n", (ptr + i)->name, (ptr + i)->pages, (ptr + i)->price);
37         printf("\n");
38     }
39
40     return 0;
41 }
42

```

```

manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!
● $ ./question3
Enter name: Think Like a Monk
Enter number of pages: 550
Enter price: 750.54

Enter name: The Monk Who Sold His Ferrahari
Enter number of pages: 320
Enter price: 340

Book Details:
Name: Think Like a Monk
Total Pages: 550
Price: 750.54

Name: The Monk Who Sold His Ferrahari
Total Pages: 320
Price: 340.00

```

```

1  /*Write a menu driven program which performs the following jobs:
2  * Create a structure named student with member variables: roll, name, grade, gender, age.
3  * Define ten structure variables of type student and using loop take input for all ten
4  structure variables.
5  * Display names of all male students.
6  * Exit.
7  */
8  #include <stdio.h>
9  #include <stdlib.h>
10
11 #define N 4
12
13 // Define the structure for Student
14 struct Student
15 {
16     int roll;
17     char name[20];
18     int grade;
19     char gender;
20     int age;
21 };
22
23 int main()
24 {
25     struct Student s[N];
26     char option, choice = 'y';
27
28     while (choice != 'n')
29     {
30         // Display menu options
31         printf("\nMenu Driven Program\n");
32         printf("1. Enter student information\n");
33         printf("2. Display names of all male students\n");
34         printf("3. Exit\n");
35         printf("Enter your option: ");
36         scanf(" %c", &option);
37
38         switch (option)
39         {
40             case '1':
41                 printf("Enter information for %d students\n", N);
42                 for (int i = 0; i < N; i++)
43                 {
44                     printf("\nInformation for student %d:\n", i + 1);
45                     printf("Roll: ");
46                     scanf("%d", &s[i].roll);
47                     printf("Name: ");
48                     scanf("%s", s[i].name);
49                     printf("Grade: ");
50                     scanf("%d", &s[i].grade);
51                     printf("Gender (M/F): ");
52                     scanf(" %c", &s[i].gender);
53                     printf("Age: ");
54                     scanf("%d", &s[i].age);
55                 }
56                 break;
57
58             case '2':
59                 printf("\nNames of all male students:\n");
60                 for (int i = 0; i < N; i++)
61                 {
62                     if (s[i].gender == 'M')
63                     {
64                         printf("%s\n", s[i].name);
65                     }
66                 }
67                 break;
68
69             case '3':
70                 exit(0);
71
72             default:
73                 printf("Invalid Option!\n");
74         }
75
76         // Ask user if they want to continue
77         printf("Do you want to continue? (y/n): ");
78         scanf(" %c", &choice);
79     }
80
81     return 0;
82 }
83

```

```
manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!  
● $ ./question4
```

```
Menu Driven Program  
1. Enter student information  
2. Display names of all male students  
3. Exit  
Enter your option: 1  
Enter information for 4 students
```

```
Information for student 1:  
Roll: 1  
Name: Benjamin  
Grade: 13  
Gender (M/F): M  
Age: 22
```

```
Information for student 2:  
Roll: 2  
Name: Grishma  
Grade: 14  
Gender (M/F): F  
Age: 22
```

```
Information for student 3:  
Roll: 3  
Name: Milan  
Grade: 16  
Gender (M/F): M  
Age: 23
```

```
Information for student 4:  
Roll: 4  
Name: Bibechana  
Grade: 4  
Gender (M/F): F  
Age: 10  
Do you want to continue? (y/n): y
```

```
Menu Driven Program  
1. Enter student information  
2. Display names of all male students  
3. Exit  
Enter your option: 2
```

```
Names of all male students:  
Benjamin  
Milan  
Do you want to continue? (y/n): y
```

```
Menu Driven Program  
1. Enter student information  
2. Display names of all male students  
3. Exit  
Enter your option: 3
```

```

1 // Program to demonstrate the use of union.
2 #include <stdio.h>
3
4 // Define a union named Student
5 union Student
6 {
7     char name[20];
8     int roll_no;
9     float marks;
10 };
11
12 int main()
13 {
14     // Declare a variable of type Student
15     union Student s;
16
17     // Input and display name
18     printf("Enter the name: ");
19     scanf("%[^\n]s", s.name);
20     printf("Name: %s\n", s.name);
21
22     // Input and display roll number
23     printf("Enter roll no: ");
24     scanf("%d", &s.roll_no);
25     printf("Roll no: %d\n", s.roll_no);
26
27     // Input and display marks
28     printf("Enter marks: ");
29     scanf("%f", &s.marks);
30     printf("Marks: %.2f\n", s.marks);
31
32     return 0;
33 }
34

```

```

manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!
● $ ./question5
Enter the name: Manish
Name: Manish
Enter roll no: 13
Roll no: 13
Enter marks: 99.99
Marks: 99.99

manish@fedora: ~/vs-code/bca-programming-repo/C/nestedStructure_and_Union main!
○ $

```