

11.16.3.21.1

EE24BTECH11013 - MANIKANTA D

Question:

In a class of 60 students, 30 opted for NCC, 32 opted for NSS, and 24 opted for both NCC and NSS. If one of these students is selected at random, find the probability that:

- 1) The student opted for NCC or NSS.

Theoretical Solution:

The total number of students in the class is:

$$|S| = 60 \quad (1.1)$$

The number of students who opted for NCC or NSS can be calculated using the formula for the union of two sets:

$$|A \cup B| = |A| + |B| - |A \cap B| \quad (1.2)$$

where:

$$|A| = 30 \quad (\text{students who opted for NCC}) \quad (1.3)$$

$$|B| = 32 \quad (\text{students who opted for NSS}) \quad (1.4)$$

$$|A \cap B| = 24 \quad (\text{students who opted for both NCC and NSS}). \quad (1.5)$$

Substituting these values, we get:

$$|A \cup B| = 30 + 32 - 24 = 38 \quad (1.6)$$

The probability of a student opting for NCC or NSS is:

$$P(A \cup B) = \frac{|A \cup B|}{|S|} = \frac{38}{60} = \frac{19}{30} \approx 0.6333 \quad (1.7)$$

Introduction

This task involves calculating the probability of a student opting for NCC or NSS using set theory and probability principles. The process is implemented in a C program, compiled into a shared object (.so) file, and then processed in Python to simulate the selection and visualize the results.

C Code Description:

The C program calculates the probability by simulating random selections of students and tracking how many belong to the union of the NCC and NSS groups. The program uses the `rand()` function to generate random samples and increments counters based on set membership.

Python Code Description:

The Python code performs the following steps:

- 1) Loads the shared object file generated by the C program using the `ctypes` library.

- 2) Simulates a specified number of trials (e.g., 1,000,000 selections).
- 3) Calculates the probability of selecting a student in $A \cup B$ using the formula:

$$P(A \cup B) = \frac{\text{frequency of students in } A \cup B}{\text{total trials}} \quad (3.1)$$

- 4) Plots the probability distribution using `matplotlib`.

Graphical Output:

The Python code generates a bar chart where:

- The x-axis represents the outcome: $A \cup B$ (students in NCC or NSS).
- The y-axis represents the probabilities, ranging from 0 to 1.
- The bar height corresponds to the calculated probability $P(A \cup B) \approx 0.6333$.

Stemplot Distribution:

The stemplot shows a single vertical line at $A \cup B$ on the x-axis with a height corresponding to its probability (0.6333).

Probability Mass Function (PMF):

The PMF represents the probability of selecting a student in $A \cup B$:

$$P(X = x) = \begin{cases} \frac{38}{60}, & x \in A \cup B, \\ \frac{22}{60}, & x \notin A \cup B, \\ 0, & x \notin S. \end{cases}$$

Cumulative Distribution Function (CDF):

The CDF represents the cumulative probability of outcomes up to a given value x , defined as:

$$F(x) = P(X \leq x) = \sum_{k \in S, k \leq x} P(X = k).$$

For the class of students:

$$F(x) = \begin{cases} 0, & x < \text{Not in } A \cup B, \\ \frac{22}{60}, & x = \text{Not in } A \cup B, \\ 1, & x \geq \text{In } A \cup B. \end{cases}$$

Simulation Process:

The simulation process is as follows:

- 1) The set of students is represented as:

$$S = \{\text{In } A \cup B, \text{Not in } A \cup B\},$$

with 38 students in $A \cup B$ and 22 not in $A \cup B$.

- 2) For each simulated selection, a random integer X is generated such that:

$$X \in \{1, 2, \dots, 60\}.$$

- 3) If $X \leq 38$, it corresponds to a student in $A \cup B$; otherwise, it corresponds to a student not in $A \cup B$.
- 4) The number of occurrences of each outcome is tracked over N trials.

Calculation of Probabilities:

Probability of Selecting a Student in $A \cup B$ (PMF): The probability is calculated as:

$$P(A \cup B) = \frac{\text{Number of students in } A \cup B}{\text{Total students}} = \frac{38}{60} \approx 0.6333.$$

Cumulative Probability (CDF):

The cumulative probability is:

$$F(x) = \begin{cases} P(\text{Not in } A \cup B), & x = \text{Not in } A \cup B, \\ P(\text{Not in } A \cup B) + P(\text{In } A \cup B), & x = \text{In } A \cup B. \end{cases}$$

For the class of students:

$$F(\text{Not in } A \cup B) = \frac{22}{60}, \quad F(\text{In } A \cup B) = 1.$$

Probability of Selecting $X \notin S$:

Since all students belong to the set $S = \{\text{In } A \cup B, \text{Not in } A \cup B\}$, the probability of selecting $X \notin S$ is:

$$P(X \notin S) = 0.$$

Output Representation:

The computed probabilities are represented in two forms:

- PMF: The probability of selecting a student in $A \cup B$ or not in $A \cup B$.
- CDF: The cumulative probabilities up to each outcome.

Conclusion:

This task demonstrates the use of C and Python for probabilistic simulations and visualizations. The probability of selecting a student in $A \cup B$ is calculated as **0.6333**, matching the theoretical value.




Fig. 4.1: Probability for opting NCC or NSS