Prepare Lab Codes

10/30/2026 23:48:28

Install MongoDB and configure ATLAS

PROGRAM 12 (a): Install MongoDB and Configure ATLAS

FSD-2 Lab Record | Pages 81–83

AIM

To install MongoDB and configure MongoDB Atlas.

Introduction

MongoDB is a NoSQL, document-oriented database that stores data in JSON-like documents instead of traditional rows and columns.

MongoDB can be used in two ways:

1. **Local Installation:** Installing MongoDB software on your system.
2. **Cloud-based Atlas:** Using MongoDB Atlas, a fully managed cloud database service.

Part 1: Install MongoDB locally (Windows)

Step 1: Download MongoDB

- Go to: MongoDB Community Server.
- Choose Windows.
- Select the MSI installer.

Step 2: Install MongoDB

1. Run the downloaded installer.

2. Select Complete Installation.
3. Make sure **Install MongoDB as a Service** is checked.
4. Select Run service as Network Service or Local System.
5. Check Install MongoDB Compass (GUI tool).
6. Click Next and Finish.

Step 3: Add MongoDB to PATH

1. Open Environment Variables.
2. Select System Variables → Path → Edit.
3. Click New.
4. Add the MongoDB bin path:

```
C:\Program Files\MongoDB\Server\6.0\bin
```

Note: The version number may differ.


Step 4: Verify installation

Open Command Prompt:

```
mongod --version
```

If installed correctly, it displays the MongoDB version.

Part 2: Configure MongoDB Atlas (Cloud)



Step 1: Create Atlas Account

- Go to MongoDB Atlas.
- Sign up using Google, GitHub or email.

Step 2: Create a Cluster

1. Click Build a Database.
2. Choose Free Tier (M0 – 512 MB storage, as mentioned in the record).
3. Select a cloud provider (AWS, Azure or GCP).
4. Select a region closest to you.
5. Click Create Cluster.

Step 3: Create a Database User

1. Go to Database Access.
2. Click Add New User.
3. Set username and password.
4. Save credentials.

Step 4: Configure Network Access

1. Go to Network Access.
2. Click Add IP Address.
3. Choose Allow Access from Anywhere (`0.0.0.0/0`) or add your local machine IP.

Step 5: Connect to Cluster

1. Click Connect.
2. Select Connect your application.
3. Get the connection string.

Example:

```
mongodb+srv://username:password@cluster0.abcd.mongodb.net/myDatabase
```

Step 6: Connect using MongoDB Shell

```
mongosh "mongodb+srv://cluster0.abcd.mongodb.net/myDatabase" --username myUser
```

Benefits of MongoDB Atlas

1. No need to install or maintain servers.
2. Provides automatic scaling and backups.
3. Accessible from anywhere with an internet connection.
4. Secure access control with authentication and IP whitelisting.

MongoDB Atlas vs MongoDB Compass

MongoDB Atlas	MongoDB Compass
Hosts database in cloud	GUI tool to manage database
Handles server maintenance	Used for viewing and querying
Cloud service	Desktop application

Result

MongoDB was installed locally and MongoDB Atlas was configured successfully for cloud database connectivity.

Important viva questions

1. What is MongoDB?

MongoDB is a NoSQL, document-oriented database that stores data in JSON-like documents.

2. What is MongoDB Atlas?

MongoDB Atlas is a fully managed cloud-based MongoDB database service.

3. What is MongoDB Compass?

MongoDB Compass is a GUI tool used to view, query and manage MongoDB databases.

4. What is a cluster?

A cluster is a group of database servers that store and manage data.

5. What is the default MongoDB port?

6. What is the difference between local MongoDB and Atlas?

Local MongoDB runs on our computer, whereas Atlas runs on cloud infrastructure.

7. What is the purpose of `mongod --version`?

It verifies the installed MongoDB server version.

8. What is a connection string?

It is a URL used by applications to connect to a MongoDB database.

Exam tip Remember these five important terms: `mongod`, MongoDB Compass, Atlas, Database Access, Network Access.

Write MongoDB queries to perform CRUD operations on document using insert(), find(),
update(), remove().

PROGRAM 12 (b): MongoDB CRUD Operations

FSD-2 Lab Record | Page 84 onwards

AIM

To write MongoDB queries to perform CRUD operations on documents using `insert()`, `find()`, `update()` and `remove()`.

Introduction

CRUD stands for:

1. **Create** – Insert new documents.
2. **Read** – Retrieve documents.
3. **Update** – Modify existing documents.
4. **Delete** – Remove documents.

Procedure

1. Open MongoDB Compass.
2. Click on Add New Connection.
3. Verify the MongoDB URL and port number.
4. Give a connection name and click Save & Connect.
5. Select a database.
6. Open MongoDB Command Shell.
7. Execute the following queries.

MongoDB Queries

1. Show Databases

```
show databases
```

Or

```
show dbs
```

2. Create / Switch Database

```
use school
```

Output:

```
switched to db school
```

3. Create Collection

```
db.createCollection("students")
```

4. CREATE – Insert Documents

Insert a single document:

```
db.students.insert({
    rollno: 1,
    name: "Ravi",
    department: "CSE",
    age: 20
})
```

Insert multiple documents:

```
db.students.insert([
    {rollno: 2, name: "Anita", department: "CSE", age: 21},
    {rollno: 3, name: "Kiran", department: "ECE", age: 20},
    {rollno: 4, name: "Sita", department: "CSE", age: 19}
])
```

5. READ – Find Documents

Display all documents:

```
db.students.find()
```

Find a specific document:

```
db.students.find({department: "CSE"})
```

6. UPDATE – Update Documents

Update one document:

```
db.students.update(
    {rollno: 1},
    {$set: {age: 22}}
)
```

7. DELETE – Remove Documents

Remove one document:

```
db.students.remove({rollno: 1})
```

Remove all documents:

```
db.students.remove({})
```

Output

The MongoDB queries are executed successfully to insert, retrieve, update and delete documents in the students collection.

Result

Thus, MongoDB CRUD operations using `insert()`, `find()`, `update()` and `remove()` were performed successfully.

Important Viva Questions

1. What is CRUD?

CRUD stands for Create, Read, Update and Delete.

2. Which command is used to insert documents?

`insert()`

3. Which command is used to retrieve documents?

`find()`

4. Which command is used to update documents?

`update()`

5. Which command is used to delete documents?

`remove()`

6. What is a collection?

A collection is a group of related documents in MongoDB, similar to a table in SQL.

7. What is a document?

A document is a single record stored in JSON-like BSON format.

8. What is `$set`?

`$set` is an update operator used to modify specified fields in a document.

Important for exam

Operation	Query
Create	`db.students.insert()`
Read	`db.students.find()`
Update	`db.students.update()`
Delete	`db.students.remove()`

Remember these four commands perfectly. They are the core of this experiment.

Note: These are the legacy methods used in your lab record. Modern MongoDB applications commonly use `insertOne()`, `findOne()`, `updateOne()` and `deleteOne()` instead. For your examination, follow the methods prescribed in your record.