Skill – Week10

Session 19:

1. To Register Handlers, Configure Signal Actions, Handle Interrupts, Manage Signal Context, Verify Stability, Test Signal Events

```
  GNU nano 8.7.1                    signal_handler.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <string.h>

volatile sig_atomic_t interrupt_count = 0;
volatile sig_atomic_t terminate_requested = 0;
volatile sig_atomic_t user_signal_count = 0;


/* Handle Ctrl+C */
void handle_sigint(int sig)
{
    (void)sig;
    interrupt_count++;
}

/* Handle termination signal */
void handle_sigterm(int sig)
{
    (void)sig;
    terminate_requested = 1;
}

/* Handle user-defined signal */
void handle_sigusr1(int sig, siginfo_t *info, void *context)
{
    (void)sig;
    (void)context;

    user_signal_count++;

    if (info != NULL)
        user_signal_count += 0;
}
```



Report: Signal handlers were registered using sigaction(). The program demonstrates interrupt handling, signal actions, signal context through SA_SIGINFO, and safe termination using signal flags.

2. To Capture SIGINT, Forward Signals, Protect Shell Process, Terminate Foreground Jobs, Update Job States, Test Interrupt Handling

```
  GNU nano 8.7.1                    interrupt_shell.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <errno.h>
#include <termios.h>

#define MAX_JOBS 10

struct Job
{
    pid_t pid;
    int status;   // 0 = Running, 1 = Stopped, 2 = Completed
};

struct Job jobs[MAX_JOBS];
int job_count = 0;

pid_t shell_pgid;
int terminal_fd = STDIN_FILENO;

void add_job(pid_t pid)
{
    if (job_count < MAX_JOBS)
    {
        jobs[job_count].pid = pid;
        jobs[job_count].status = 0;
        job_count++;
    }
}

void update_jobs()
{
    int status;
    pid_t pid;
```

```
manikanta@Hemu:~$ nano interrupt_shell.c
manikanta@Hemu:~$ gcc -Wall -Wextra interrupt_shell.c -o interrupt_shell
manikanta@Hemu:~$ ./interrupt_shell
Shell PID: 1469
Shell process group: 1469

--- MINI SHELL ---
1. Run Foreground Job
2. Run Background Job
3. Show Job Table
4. Resume Stopped Job
5. Exit
Enter choice: 1
Foreground job started. Press Ctrl+C to interrupt.
Child PID 1470 started.
Job 1470 running: 1
Job 1470 running: 2
Job 1470 running: 3
Job 1470 running: 4
^C
Foreground job terminated or completed.

--- MINI SHELL ---
1. Run Foreground Job
2. Run Background Job
3. Show Job Table
4. Resume Stopped Job
5. Exit
Enter choice: 3

--- JOB TABLE ---
Job 1 | PID: 1470 | Completed
```

```
--- MINI SHELL ---
1. Run Foreground Job
2. Run Background Job
3. Show Job Table
4. Resume Stopped Job
5. Exit
Enter choice: Job 1471 running: 10
Job 1471 running: 11
Job 1471 running: 12
Job 1471 running: 13
Job 1471 running: 14
5
Shell exited safely.
```

Report: The program demonstrates signal handling and job control by protecting the shell from SIGINT, transferring terminal control to foreground jobs, and tracking stopped, running, and completed processes.

Session 20:

1. To Capture SIGTSTP, Suspend Processes, Update Job Table, Preserve State, Resume Later, Test Suspension Workflow

```
  GNU nano 8.7.1                        suspend_jobs.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <errno.h>

#define MAX_JOBS 10

struct Job
{
    pid_t pid;
    int status;  // 0 = Running, 1 = Stopped, 2 = Completed
    int progress;
};
struct Job jobs[MAX_JOBS];
int job_count = 0;
pid_t shell_pgid;
int terminal_fd = STDIN_FILENO;
/* Add a process to the job table */
void add_job(pid_t pid)
{
    if (job_count < MAX_JOBS)
    {
        jobs[job_count].pid = pid;
        jobs[job_count].status = 0;
        jobs[job_count].progress = 0;
        job_count++;
    }
}
/* Update job states using waitpid */
void update_jobs()
{
    int status;
    pid_t result;
    for (int i = 0; i < job_count; i++)
```

```
manikanta@Hemu:~$ nano suspend_jobs.c
manikanta@Hemu:~$ gcc -Wall -Wextra suspend_jobs.c -o suspend_jobs
manikanta@Hemu:~$ ./suspend_jobs
Shell PID: 1528

--- JOB CONTROL SHELL ---
1. Create Foreground Job
2. Show Job Table
3. Resume Stopped Job
4. Exit
Enter choice: 1
Foreground job started. Press Ctrl+Z to suspend.
Child PID 1529: Progress = 0
Child PID 1529: Progress = 1
Child PID 1529: Progress = 2
Child PID 1529: Progress = 3
^Z
SIGTSTP received. Job suspended.
```

```
--- JOB CONTROL SHELL ---
1. Create Foreground Job
2. Show Job Table
3. Resume Stopped Job
4. Exit
Enter choice: 2

------ JOB TABLE ------
Job 1 | PID: 1529 | Progress: 0 | Status: Stopped
```

```
--- JOB CONTROL SHELL ---
1. Create Foreground Job
2. Show Job Table
3. Resume Stopped Job
4. Exit
Enter choice: 3

------ JOB TABLE ------
Job 1 | PID: 1529 | Progress: 0 | Status: Stopped
Enter job number to resume: 1
Job resumed. Press Ctrl+Z to suspend again.
Child PID 1529: Progress = 4
Child PID 1529: Progress = 5
Child PID 1529: Progress = 6
Child PID 1529: Progress = 7
Child PID 1529: Progress = 8
Child PID 1529: Progress = 9
^Z
Job suspended again.
```

Report: The program captures terminal suspension through SIGTSTP, detects stopped processes using waitpid() and WUNTRACED, maintains job states, and resumes processes using SIGCONT while preserving their execution progress.

2. To Create Process Groups, Assign Group IDs, Transfer Terminal Control, Restore Ownership, Coordinate Signals, Validate Behavior.

```
  GNU nano 8.7.1                    process_groups.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <errno.h>

#define MAX_JOBS 10

struct Job
{
    pid_t pid;
    pid_t pgid;
    int status;  // 0 = Running, 1 = Stopped, 2 = Completed
};
struct Job jobs[MAX_JOBS];
int job_count = 0;
pid_t shell_pgid;
int terminal_fd = STDIN_FILENO;
/* Add a job to the job table */
void add_job(pid_t pid, pid_t pgid)
{
    if (job_count < MAX_JOBS)
    {
        jobs[job_count].pid = pid;
        jobs[job_count].pgid = pgid;
        jobs[job_count].status = 0;
        job_count++;
    }
}
/* Display jobs and their process groups */
void show_jobs()
{
    printf("\n------ JOB TABLE ------\n");
    for (int i = 0; i < job_count; i++)
    {
```

```
manikanta@Hemu:~$ nano process_groups.c
manikanta@Hemu:~$ gcc -Wall -Wextra process_groups.c -o process_groups
manikanta@Hemu:~$ ./process_groups
Shell PID: 1626
Shell PGID: 1626

--- PROCESS GROUP MENU ---
1. Create Foregrund Process Group
2. Show Job Table
3. Resume Stopped Job
4. Send SIGTERM to Job Group
5. Exit
Enter choice: 1

Created child PID: 1627
Assigned process group ID: 1627
Terminal transferred to foreground job.
Press Ctrl+C to terminate or Ctrl+Z to suspend.

Child PID: 1627
Child PGID: 1627
Child process running: 1
Child process running: 2
Child process running: 3
Child process running: 4
^Z
Child process stopped.
Terminal control restored to shell.
```

```
--- PROCESS GROUP MENU ---
1. Create Foreground Process Group
2. Show Job Table
3. Resume Stopped Job
4. Send SIGTERM to Job Group
5. Exit
Enter choice: 3

------ JOB TABLE ------
Job 1 | PID: 1627 | PGID: 1627 | Stopped
Enter job number to resume: 1
SIGCONT sent to process group 1627.
Child process running: 5
Child process running: 6
Child process running: 7
Child process running: 8
Child process running: 9
Child process running: 10
^ZJob suspended again.
Terminal restored to shell.
```

Report: Process groups were created using setpgid(), terminal control was transferred and restored using tcsetpgrp(), and group signals were coordinated using kill() with negative PGIDs. Process states were verified using waitpid().