

Chat API integration guide

How to call 'POST /chat' (the "Any Questions?" popup)

'/chat' cannot be used on its own: every question is answered against a

session created by 'POST /summary', so the flow is always

'/summary' -> keep the 'session_id' -> '/chat' (up to 5 times).

Base URL

<https://agent.dtpay.digital/>.

1. Create a session with 'POST /summary'

```http

POST /summary

Authorization: Bearer <jwt>

Content-Type: application/json

```
{
 "uid": 122,
 "start_date": "2026-07-28",
 "end_date": "2026-08-01",
 "cp_product_id": null
}
```

```

| field | type | required | notes |

|---|---|---|---|

| 'uid' | int | yes | must match the JWT's own uid row |

| 'start_date' | date 'YYYY-MM-DD' | yes | inclusive |

| 'end_date' | date 'YYYY-MM-DD' | yes | inclusive |

| 'cp_product_id' | int | null | no | omit for "everything this uid may see" |

The range is inclusive of both ends and may not exceed

'MAX_DATE_RANGE_DAYS' (default 7) & otherwise '400'.

Response (trimmed):

```json

```
{
 "session_id": "2fda4486-f5b2-4d6a-a649-ecdb0793a4e6",
 "date_range": { "start": "2026-07-28", "end": "2026-08-01" },
 "overall": { "total_resolved": 18432, "completed": 14120, "conversion_rate_pct": 76.6 },
 "products": [{ "product_id": 41, "product_name": "...", "summary": "...", "daily": [], "hourly": [] }],
 "generated_at": "2026-08-03T09:41:22.104512+00:00"
}
```

```

Store 'session_id'. A session is created on every '/summary' call

whether or not the user ever opens the chat, and it is the only handle

'/chat' accepts. Its stored grounding data is exactly the 'overall' +

'products' payload above & the chat answers from that frozen snapshot,

never from a fresh query.

2. Ask a question with 'POST /chat'

```http

POST /chat

Authorization: Bearer <jwt>

Content-Type: application/json

```
{
 "uid": 122,
 "session_id": "2fda4486-f5b2-4d6a-a649-ecdb0793a4e6",
 "message": "Why did DRC dip on the 25th?"
}
```

```

| field | type | required | notes |

|---|---|---|---|

| 'uid' | int | yes | same uid that created the session, or an 'ADMIN' |

| 'session_id' | string (uuid) | yes | from the '/summary' response |

| 'message' | string | yes | the user's question, free text |

All three are required; a missing or wrongly-typed field is a

'422', not a '400'. The 'Authorization' header is also required & a

missing header is a '422' as well.