Indian Institute of Technology Jodhpur
https://iitj.ac.in/office-of-research-development/en/ipr

Contact No. 1805

Intellectual Property Disclosure Form

1. **Title of the invention:** A Distributed System for Corroborative Data Acquisition

2. **Innovator(s) who have contributed or conceived an essential element of the invention, either independently or jointly with others during the evolution of the technology concept or reduction to practice:**

(i) Name: Manik Sejwal
Nationality: Indian
Position: Incubatee
Department Address: Medical Technologies. IITJ-AIIMSJ
Phone: +91 9958129899
Email: sejwal.1@iitj.ac.in, manik@easemymed.com
Course: Masters-PhD
F-128, Lado Sarai, Old Bank Street, New Delhi-30

(ii) Name: Sumit Kalra
Nationality: Indian
Position: Associate Professor
Department Address: Department of Computer Science and Engineering, IITJ
Phon: +91 7976777787
Email: sumitk@iitj.ac.in
Course: NA

(iii) Name: Surender Deora
Nationality: Indian
Position: Additional Professor
Department Address: Department of Cardiology, AIIMSJ
Phone: +91 8003996715
Email: deoras@aiimsjodhpur.edu.in
Course: NA

Inventors are requested to provide their Full Name (without initials**), Position (**e.g Professor / Associate Professor / Assistant Professor, Post Doc / PhD / M. Tech / B. Tech Student**), Phone Number (**Personal**), Email ID (**Official along with Personal**)*

Students are advised to provide their **home address as well.*

3. Non-Confidential description of the invention in layman's Language:

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

A. Abstract in 100 words

This invention addresses unreliable patient self-reporting (fig 1) by creating a secure care circle (fig 2, 4) using a central server and a minimum of three distinct hardware nodes (which include "Care-o-meters" (fig 14)) physically coupled to the patient, caregiver, and clinician (fig 15). Personal AI agents logically coupled to these nodes independently gather unique user perspectives. A central orchestration engine analyzes these asynchronous data streams, comparing them to identify discrepancies (fig 7). The engine transcodes the conflicting inputs into a multi-perspective divergence map, forwarding reconciled insights to the appropriate node (fig 7, 11). This hardware-mediated channel surfaces ground truth by triangulating patient reports with caregiver observations and by asking probing questions.

B. Use Case: Multi-Agent Behavioral Reconciliation System for High-Risk Clinical Care

Existing patient-only digital health and AI systems fail in conditions where outcomes depend on behavior, cognition, or intent rather than symptoms alone. In such scenarios, deterioration, non-adherence, relapse may often evident to caregivers. A solely patient-facing system gets rendered clinically insufficient for high-risk care because it lacks environmental awareness and cannot reliably detect concealed distress, impaired judgment, or intentional non-disclosure.

The disclosed system introduces a role-separated, multi-agent framework that independently captures patient self-reporting and caregiver observation through distinct hardware nodes. The system then reconciles these inputs to detect divergence patterns predictive of clinical failure or crisis. By delivering privacy-preserving, actionable signals to clinicians instead of raw disclosures, the system enables timely intervention, scalable oversight, and outcome-linked deployment across mental health, chronic disease management, post-acute care, and adherence-sensitive clinical programs where real-world events, not self-declared statements determine success.

Please consult the examples provided in Annexure-1 for filling this section

C. Keywords

Information and Communications Technology, Social Artificial Intelligence, Healthcare, Multi-agent system, Data reconciliation, Patient adherence, Care circle, Conflict resolution

Please note that the above keywords will be utilised by the IPR Cell for preparing the Patent Search Report

Note: *Please note that the above Information alone will be circulated to several agencies for technology commercialisation purposes once the patent is filed. Thus, the fields should be self-explanatory to highlight commercialisation potential.*

4. How does this invention relate to new processes, machines, compositions of matter, etc.? Please cover the following points:

(a) Describe the invention in detail for technical evaluation. Please use additional sheets for sketches, drawing, photographs and other materials that help to illustrate the description.

The invention supports and mediates private interactions among the members of a care circle (patient(s), caregiver(s), clinician(s)) by assigning each of them personalized companions. Each companion comprises a user node and a cluster of AI agents that

collaborate to optimize the performance of the companion. The communication between the companions is mediated by a central orchestration engine that comprises the orchestrestation agents. The orchestration agents run on the server node(s). The agents in a companion are logically coupled with the user's node and run on either the user node or server node. The system, therefore, requires a minimum of 3+1 nodes - patient's node, caregiver's node, clinician's node and server. A user interacts with his or her companion through the node dedicated to him or her.

The system utilizes a distributed network topology comprising the following distinct hardware elements:

1. Care-o-meters: (used by the patients and caregiver) These are physically distinct computing units that comprise
    a. a bidirectional visual interface: a display module integrated with a touch-sensitive layer,
    b. audio & text input modules: A microphone and digital keypad configured to capture the raw natural language data streams from the patient's node (D_p) and caregiver's node (D_c). The data streams include the patient's identity (I_P) along with the signature of the device ownser, i.e. patient's device signed using patient's identity (S_P) and caregiver's device signed using the caregiver's identity (S_C). The data strteams are also tagged with the timestamp and geostamp whenever an input is received from a user.
    c. Wireless communications modules like cellular, wifi, bluetooth
    d. Wired communication module accessible through serial bus
    e. The personal subnet manager that functions as a switch or a hub to identify the connected telemetry devices (like digital thermometer, digital glucometer, etc.) and tag the data streams with the patient's identifier. The personal subnet manager manages multiple devices being connected at the same time, or different points of time. In the latter case, it will have to retain the identity, drivers, and data formats used by each telemetry device.
    f. Dedicated buttons to reduce the number of instructions to define a new data point or stream. The buttons have a latching switch mechanism so that the user can set the state of his or her actions and activity as 'ongoing'. For example, 'medication_not_taken', 'medication_taking', and 'medication_taken'.
    g. Camera module with photo and video support
    h. Ports for connecting different models.
2. Supervisory node (used by the clinician): A node configured to render the multi-perspective information as summaries, maps and reports visually. The node also lets the clinician enter instructions for the system and care circle members.
3. Central server: A high-performance computing unit that comprises:
    a. Partitioned memory and storage: Configured to maintain isolated state vectors for each user and conversation to prevent cross-contamination of subjective data.
    b. Processor: One or more processing units configured to execute the instruction transcoding and forking protocol, capable of taking a single command from the one node and outputting one or more distinct execution protocols for the other nodes.
    c. Network module: A modem and necessary ports required for connecting to the care-o-meters and supervisory nodes over the internet using protocols and frameworks like IPv4, HTTP, FTP, WebRTC, etc

A care-o-meter node is used for functionalities like calling and accessing the internet with restrictions. For example, the buttons may be directly configured to contact care circle members and the ability to contact people outside the care circle may be revoked. Access to payment gateways or certain web sites may also be restricted. The care-o-meter nodes is also be used to intercept direct user-to-user communications like

phone calls, messages, internet messages. These are used as inputs to the personal agentic cluster. After analysis, the system then notifies the authorised care circle members about the relevant events or interventions, if required. The autonomy of the patient's care-o-meter is reduced by configuring it directly, or by granting control permission to a caregiver's companion or by having a voting in the care circle.

The patient's care-o-meter node enables the patient's companion to connect with telemetry devices that provide true patient data. A care-o-meter can, therefore, act as an interface between telemetry devices and the system. These devices and data include -

1. Patient vitals through various sensors and devices.
2. Patient activity are collected through cameras, microphones, GPS sensors, accelerometers, medication boxes, etc on the same or seperate nodes.
3. Medical records are collected by scanning using a camera or a direct input or through an API.

Additionally, similar telemetry devices are be connected to the caregiver's node. The caregiver's companion is configured to mark the data from these devices as the patient's data (D_P) or caregiver's data (D_C). This is done by tagging each telemetry device or data stream with the patient-caregiver tuple. The caregiver also uses independent telemetry devices as proof of presence hardware token. This functions through short range wireless handshake, GPS location, etc. The caregiver's node telemetry devices are used to log the immutable timestamps of patient observation.

The buttons of a care-o-meter are configurable to do dedicated tasks, like contacting a specific individual. Each button has a mini display inside it to show variable input possibilities.

An authless care-o-meter is not coupled with any specific caregiver. It is used by an individual who is not be formally added to the circle. These include temporary caregiver, a child, etc. Using an authless care-o-meter, the user can only provide logs about the patient activities. The authless care-o-meter doesn't receive any information from the care circle. Unlike personal care-o-meters and mobile phones, the authless care-o-meter simply requires physical usage, and no specialized system to identify caregiver. The authless care-o-meter only needs to know the patient/carecircle ID. This device connects with the central server directly using the internet or through the device of a care circle member using bluetooth or USB. Instead of being mapped to any specific user, this device is directly mapped to the patient/care circle and provides an independent data stream.

The clinician's node(s) can also be used to provide patient's data from different devices and data streams in a hospital by tagging them with the patient's identifier. The inputs include messages, reports, audio, vidio, etc. The clinician's node allows the clinician to view summaries of different patients and care circles using a dashboard or focus on a single care circle or a single user to analyze, reports, questions, etc.

Each user node in the system allows for both sending and receiving information. Information includes text messages, voice messages, video recordings, realtime audio/video calls, files, data streams from telemetry devices, etc.

These nodes (including care-o-meters and the clinician's node) are used by the users (patient, caregiver and clinician) to interact with the personal agentic cluster of their companion. These agents perform tasks including but not limited to the below. There may be unified, dedicated or multiple agents for each of these tasks. These agents run on user devices and/or on servers.

1. Identifying the best response to the user's input
2. Executing Context-Aware Query Protocols to minimize State Vector sparsity. This is done by asking probing questions from the patient and the caregiver to uncover new information and resolve conflicts identified by the orchestrating agent.
3. Parsing and storing information while mapping the source, disclosure date-time, validity date-time, subject, object, etc.
4. Deciding what information needs to be sent to their corresponding users
5. Deciding if another user's companion needs to be contacted
6. Deciding what information needs to be sent to or sought from another user's companion
7. Checking if user consent is available for forwarding data
8. Seeking explicit consent through the terminals when needed
9. Implying consent from the user's configuration, conversation tone, topic of discussion
10. Assessing the sensitivity of the topic and choosing to override sharing/escalation requests by the escalating agents. For example, financial topics, mental health, topics related to sexual health and life, etc.
11. Assessing criticality of situations (including but not limited to risk of self harm, possibility of an accident or medical emergency) and choosing to escalate even if the topics are sensitive.
12. Medical history collection
13. Conversation topic management - choosing the next topic
14. Creating a representation of the user and the care circle
15. Creating a representation of the users' physical environment
16. Identifying the names of people mentioned in user messages and mapping them to their user and care circle.
17. Strategise longitudinal interventions
18. Strategise in favour of the user's personal goals
19. Schedule tasks and messages to be sent in the future
20. Communicate with APIs of different devices and services outside this system, for example medical devices, mobile phone apps, smart watches, etc.
21. Coordinate communication and actions among the above agents, the orchestrating agents and/or the user.
22. Resolving conflicts between agents within a companion (i.e. cluster of personal agents). This is be done through various approaches like ranking, reasoning, heuristics, etc.
23. Keeping track of social factors like relationships, closeness, openness, etc.
24. Anonymized escalations
25. Deploying Structured Interaction Modules to standardize user input patterns - Asking questionnaires and providing psychiatric therapies
26. Tracking which patient's care circle the user (caregiver or clinician) is currently interested in.
27. Identifying whether the user is acting as a patient or a caregiver.
28. Flagging critical but sensitive/private information of one user as confidential so that it can only be shared with the orchestrating engine and a second user's companion. The confidential information can never be shared by the second companion to its user. This is only for strategizing.
29. Delegate tasks like asking probing questions, questionnaires, therapy to other user's companions and then collaborate with them to create a report.
30. Sharing, analyzing, editing and comparing different types of files. Collaborating and commenting on drafts. Filling, sharing, signing and approving forms.
31. Analyzing the recordings and live streams audio/video of in-person, telephonic, message based and online interactions among the users and other individuals as captured by the care-o-meters. By configuring the agents to recognize the voices of care circle members, the transcriptions can be mapped to the speakers, listeners and subjects. The interactions can be summarized and actionable items can be decided using the agents.

The agents in the orchestration engine coordinate the different companions and facilitate communication between them. Their primary goal is to guide the companions towards the collective goal of a care circle. The agents in the orchestrating engine manage activities like the below. The orchestration engine may include personal agents..

1. Storing user identities
2. Tracking care circle configurations
3. Tracking consent configurations - availability, level, revocations, chains, etc.
4. Keeping track of relationships
5. Keeping track of roles within care circles
6. Selecting message receivers or choosing to broadcast information across a care circle.
7. Personalizing message content according to the receiver.
8. Scheduling and sending notifications to users through companions.
9. Receiving message requests and instructions from one companion and forwarding to another compreanion, with or without changes.
10. Inverting user roles - a patient becoming a caregiver and a caregiver becoming a patient.
11. Identifying relationship and family dynamics and adapt by setting the tone and strategy.
12. Decide the strategy for the companions and users in a care circle.
13. Track progress with the goals of the care circle.
14. Edit statements requested by one companion or its user so that they suit the perspective of another companion's user.
15. Block information from one companion to another if it can damage the relationship of the sender and receiver.
16. Store secrets of one user and instruct another companion to strategise the conversation with a second user such that the first user can benefit without a privacy breech.
17. Connecting to various third party APIs and tools.

Training through simulations and reinforcement learning through human feedback

As the system is novel, it is not possible to train a powerful neural network on a prior dataset because no such dataset exists. Therefore the only way to train the model before real human usage is by simulating human users that performing different scenarios and roles. These scenarios can also be simulated by generating the user responses at runtime. For a more realistic simulation, the users are simulated by generating dialog graphs through zero shot and few shot learning. The simulated user messages can be even more realistic if handcrafted dialog graphs are leveraged. The dialog graphs also provide test cases through which each agent, action and model can be validated objectively on predefined interactions and parameters.

Evaluation can be done on different scenarios like care circle dynamics, power plays, triangulation, wrong clinical advice, non-adherence, addictions, breaking the law, dishonesty, hiding information, convincing, disease progression monitoring, follow-up, adherence support, caregiver burnout, medical emergencies, etc.

Evaluation of real and simulated interactions is done by human experts. For large scale evaluation, judging agents judge the actions and messages of the agents in the system. The judging agents and human evaluators judge the simulated users for diversity and realism. The evaluations include both quantitative and qualitative aspects.

For automated training, the qualitative aspect, i.e comments and feedback on the conversation/action are used to update the prompt and then perform a split test using the two versions. Similarly, quantitative aspects are used for fine tuning existing models.

In a real-world scenario, care circles overlap, organizational roles and limits are enforced, and societal roles emerge. This leads to the emergence of sub-networks that interact with

each other (fig 18). A subnet is governed by the sub-networks's coordination engine. This coordination engine is be logically coupled with the members and companions within the sub-networks but can be hosted on the central server or a server which is dedicated to the sub-network and controlled by the organization. The goal of a coordination engine and companions in a sub-network is to protect the interests and maximize the gains of the members of the sub-net. A sub network can use agents trained on private data owned by the sub-net. A coordination engine oversees creation of these private agents and their fine-tuning. A subnet also has hierarchies and escalation matrices such that the user and companion can receive the relevant information at the right time and act accordingly. Furthermore, the exit of one user will lead to handover and/or deletion of information possessed by the user's companion. This is enforced by the coordination engine by destroying companions along with associated data.

Algorithm

Step 1: Care Circle and Agent Network Instantiation - A patient initiates a secure, goal-oriented group (a "care circle") by inviting other members, such as a caregiver or doctor. Upon joining a care circle, each member is assigned a dedicated cluster of personal AI agents (Companion). The patient defines the initial roles of care circle members and granular consent levels for information sharing. These are managed by a Consent Management Engine which handles the granting, modification, and revocation of permissions within the circle. The agents in the consent management engine are divided among companions and the orchestration engine. This network operates over one or more communicatively coupled processing servers, which can be centralized or distributed.

Step 2: Multi-Source Data Ingestion and State Modeling - Each member of the care circle conversationally interacts with their companion, reporting their own observations (e.g., symptoms, adherence) and their observations of other members. The agents independently process these multi-source data streams, continuously updating a comprehensive, high-dimensional state vector (S_t). This vector serves as the complete context for all AI decision-making, capturing the circle's clinical, behavioral, social, and conversational states at any given moment.

Step 3: Multi-Agent Discrepancy Reconciliation - The system's core Multi-Agent Reconciliation Engine analyzes the state vectors (S_t) to compare data streams from different users (e.g., the patient's report R_p vs. the caregiver's report R_c). When a factual conflict is detected (e.g., conflicting reports on medication adherence), the engine flags a discrepancy. To address this discrepency, the system generates a neutral, mediated clarifying questions directed at one or more members. This questions are designed to elicit more detailed information to establish a reliable ground truth. Depending on the level of consent and sensitivity of the topic, the final report is generated transparently or without revealing the source of the conflicting information, thereby preserving trust within the circle.

Step 4: Actionable Insight Delivery - Following reconciliation, the system generates a unified and detailed assessment of the patient's adherence and overall state. The tangible technical output is the rendering of this reconciled state on a clinician's interface, providing a consolidated, at-a-glance view of patient status, active conflicts, and critical alerts. This enables the human expert (clinician) to make timely and effective interventions. For events assessed as having high criticality, the system is configured to

trigger an immediate escalation to the appropriate professional, bypassing standard workflows to ensure safety and prompt care.

(b) What is <u>Novel</u> in the invention?

The invention deals with interpersonal AI agents. Its core novelty is in the method of mediating and reconciling subjective reports among multiple users and terminals using collaborative AI agents. The usage of a seperate caregiver node to create a 3+1 node distributed network topology, and methods of divergence preservation at the time of information discovery, sharing and reconciliation is novel.

Unlike prior art, which focused solely on clinician-patient interaction, this system incorporates a third party (caregiver) and uses a care circle model to identify and resolve discrepancies in self-reported data. The system is driven by a protocol that preserves data divergence instead of forcing a single truth.

The system has a consent manager that is capable of autonomous decisions, i.e. uses the user configurations related to consent, sensitivity, relationship type, etc. The system provides automated yet privacy-preserving mediation and escalation based on the information received by the patient and/or the caregiver.

Since the system is designed to hold extended conversations over longer periods of time with multiple people in the same care circle, it has dedicated agents for developing strategies for not only statements and topics, but also the receiver of the messages and the interpersonal interactions among care circle members.

The system is dedicated to managing the different interpersonal scenarios like triangulation, power plays, game theory, etc.

Furthermore, expansion and overlap of care circles leads to the emergence of familial and organizational subnets that can have a their own private orchestrating engine, i.e coordinating engine. These lead to sequences of information sharing as per organizational roles, hierarchies and escalation matrices. These procedures extend to cross organizational information sharing in a similar manner - first clinic, then general hospital, then tertiary/quaternary hospital.

(c) What is the “inventive” step in your invention? Is the step non-obvious to a person from related fields?

The disclosure enables the caregiver and describes an agentic framework with capabilities like -

1. Implied consent - comparing past availability of consent and context with the relationship status, criticality and topic sensitivity (fig 9)
2. Switching between implied and explicit consent
3. Managing consent chains - if A consents to share information to B and B consents to share the same information to C, but if A revokes consent from B, consent received by C should also be revoked (fig 28).
4. Informing companions but not users - user A shares information with his or her companion C_A, C_A shares the same with user B’s companion C_B as ‘confidential’. This disables C_B from sharing the confidential information with user B. This confidential sharing allows C_B to act according to the limited sharing of confidential information allows C_B to act according to the information received without violating user A’s privacy rights.
5. Identification of what information can be shared with whom and omitting sensitive information

6. Storing information about another user - information about A is stored by B's companion (C_B) in an object dedicated to A (D_B^A) but governed by C_B. This is different from the object about A governed by A (O_A^A). This preserves the identity of the data principles and the data divergence.
7. Modeling the clinician and caregiver along with the patient (entire care circles)
8. Reciprocity of user roles - a caregiver or a clinician falls ill and becomes the patient. The system supports role changes by allowing each user to configure their own care circles and setting consent levels about each member and each role.
9. Strategization in a multi-person scenario - which individual will receive which piece of information when depending on the context. This is done by maintaining priority queues. The sorting of actions and messages is done by comparing the semantic vectors of the queued information and the context of the ongoing conversation with the user. Additionally, other factors like criticality of the topic and user's affinity towards the topic are also included.
10. Predicting dynamics in the care circle and strategizing for collective and individual goals - predicting how a user might respond to a stimulus and notifying the other members about the strategies in advance
11. Identification of conflicting information - by using varied sources and by asking probing questions
12. Preserving divergence by not forcing an aggregation or correction
13. Resolution of conflicts through probing questions asked from multiple care circle members
14. Location and presence based validation of user inputs
15. Sub-networks and coordination engines that protect the interests of the individual within the sub-network.
16. Information sharing as per organizational roles, hierarchies and escalation matrices. These mechanisms extend to cross organizational information sharing in a similar manner - first clinic, then general hospital, then tertiary/quaternary hospital.
17. Companions and coordination engines are driven by protocols that make decisions based on game theory or on benefit of others, for short term or long term gains, etc

Non-obviousness

Each of these requires one or more dedicated agents that need to be optimized and validated. Therefore, the invention requires expertise in the domains of artificial intelligence, networking, hardware, behavioural and social psychology, healthcare, business and ethics. The invention becomes non-obvious to anyone who lacks understanding in any of the domains. A computer scientist is focussed on improving neural network architecture and relies on prior data. A behavioural psychologist would be unable to implement a multi-user multi-agent framework. AI powered IDEs are unable to implement this as they are stochastic parrots with a bias towards ignoring the complex protocols and constant validation required. A businessman would struggle with ethics. The privacy-conscious multi-agent reconciliation engine therefore incorporates multiple inventive steps.

The difficulties and results from early runs are demonstrated in figures 20, 23 and 27.

A care-o-meter node connects with the internet or other devices on the telecommunications network. However, unlike a regular mobile phone or a smart phone it has reduced functionality for reducing autonomy of a paediatric or cognitively impaired patient. The hardware buttons are configured for tasks like directly contacting only care circle members. Access to payment gateways or certain web sites is restricted. In such a case, changes to the care circle relies less on the patient's consent and more on caregiver approvals like parental consent.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

(d) What are the advantages of the present invention over comparable inventions available in patent literature? Please attach a summary of your patent search*.

Superior data quality: Reconciles multi-source data to fill information gaps common in self-reporting. This enables identification of black swan events and diagnoses that were not possible using conventional technologies.

Privacy Preservation: Enables family counseling and conflict resolution without violating individual privacy by using explicit consent chains.

Coordinating the patient's support system: Instructing the caregiver about how to handle the challenges posed and faced by the patient, and vice versa.

Increasing user stickiness: Current solutions don't know much about the patient and the patient's environment. This disclosure helps the systetem know more about the patient and the patient's environment without having the patient to work too much. It leverages a human's drive to help and influence another human to get the care circle members closer to their collective goals.

Increased safety: The caregiver provides physical safety, the clinician provides expert opinion.

Strategized interactions among multiple individuals over extended periods of time.

(e) NOTE: The inventors should go through the Patent Search report carefully and write the difference between his/her invention and each contents of the patent search. For Patent search please contact ipr_rnd@iitj.ac.in

Reference	Description	Difference
Maia (https://www.ourmaia.com/)	Digital couple and family-based therapy is given through conference calls, whatsapp groups or similar groups controlled by AI (Maia).	There is no framework by which a clinician or expert can have secure conversations with the other two users. A mediator is also absent. The disclosure describes how the 'groups' are replaced by mediated interactions among 3 different user devices.
Abbasiantaeb, Zahra, et al. "Let the llms talk: Simulating human-to-human conversational qa via zero-shot llm-to-llm interactions." Proceedings of the 17th ACM International Conference on Web Search and Data Mining. 2024. Singhal, Karan, et al. "Large	Large language models and transformer neural networks have the knowledge and reasoning ability. They can ingest large quantities of of multimodal data as input and generate a high quality output.	Being models, they are dependent on the deployment and environment provided to them. They can not include the caregiver without a dedicated framework. They merge the input streams. The disclosure provindes a way to keep two streams of data seperate till reconciliation is

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

language models encode clinical knowledge." Nature 620.7972 (2023): 172-180.		performed.
Aksar, Burak, Yara Rizk, and Tathagata Chakraborti. "Multi-agent chatbot with multi-intent recognition." U.S. Patent Application No. 17/662,484	A multi agentic framework for parseing inputs from a single user.	Our disclosure takes inputs from different sources and keeps streams separate unless a merger is required.
Voss, Chris, and Tahl Raz. Never split the difference: Negotiating as if your life depended on it. Random House, 2016.	Describes how negotiations involve multiple individuals on the side of both parties, with the implication that both need to be on the same page.	A technological improvement is not provided.
https://illuminate.health/home-2/med-guide/	Inputs from patients, doctors, caregivers, nurses	Limited AI capabilities. Simply logs inputs in a table.
https://sensely.com/solutions/	Chatbot for long-term care. Asks if the user is a caregiver	The caregiver acts on behalf of the patient

(f) Has the invention been tested experimentally? Are experimental data available?

Yes. Simulation data has been logged. Iterations are also logged in git. Document versions are logged in Google Docs.

Simulation details -

Large language models were configured to act as real humans by assigning them personas. The personas described personalities, clinical conditions, preferences, lingual aspects, etc. The personas were then used to create scenarios with descriptions of various care circle dynamics like triangulation, escalation, medical queries, non-adherence, etc. A scenario orchestrator would decide who's turn it is to speak and the corresponding simulated user would then converse with their companion. The judging agents would then evaluate the exchanges and score them on the basis of realism and provide qualitative feedback. The qualitative feedback is then used for improving the prompt. Prompt versions are then compared using Thompson sampling.

At present, 4262 runs have been completed.

Simulation screenshots and details are attached below.

(g) Technology Readiness Levels (**TRL**) description (mention the applicable stage of TRL given below). Please Mark as Appropriate with adequate justification.

TRL-1 - Research Idea (Potential Application/Basic Principles observed)

TRL-2 - Applied Research Idea (Hypothesis testing and initial proof of concept is demonstrated in a limited number of trials)

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

TRL-3 - Project Plan (Device Characteristics documents & project proposal completed, Proof-of concept phase)

TRL-4 - Design and Development (POC & Safety of device demonstrated by prototype design)

TRL-5 - Standardization (Validating the result of the prototype by testing in simulated environment)

TRL-6 - Preclinical Evaluation (Clinical trials of functional prototype)

TRL-7 - Technology Transfer (Technology transfer of the developed system)

TRL-8 - Clinical Evaluation (Evaluation of the system by clinical trials or demonstration)

TRL-9 - Commercialization (Commercialization & Post Market Surveillance)

(h) Need and Demand

(Technology gaps addressed in domestic & international markets, pain points of Industry which are being resolved)

There is a critical information gap in managing illnesses where patient self-reporting is incomplete or inaccurate (e.g., hiding poor adherence). Current solutions like Sensely or Wysa focus on the patient-doctor loop and miss the caregiver's perspective. There is a need for a system that can structure and reconcile these complicated multi-person scenarios. Digital couple and family-based therapy is given through conference calls, whatsapp groups or similar groups controlled by AI (Maia).

The above systems involve teams of 1-2 users and therefore miss out on the advantages of network effects. If more humans are supporting the patient through a platform, the patient will have a greater incentive to continue engaging with the same platform and take their support.

(i) Market Access Information

(Current Global & domestic Scenario, market size & CAGR)

The Behavioural Health market is estimated at $184 billion. Behavioral Health Market Size, Share and Trends. Precedence Research. 1174. Oct, 2025

(j) Future Developments

(Scope of future technology development and their application)

Core behavioral principles of the Care Circle apply beyond healthcare to domains like Social Artificial Intelligence in Healthcare (Patient adherence monitoring, elderly care).
Enterprise Sales & Negotiation (Mediating subjective reports in teams).
Crime investigations.
Arbitrage

(k) Application/s of the invention

(Please refer to Appendix-I)

Multi-Agent Behavioral Reconciliation System for High-Risk Clinical Care

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Existing patient-only digital health and AI systems fail in conditions where outcomes depend on behavior, cognition, or intent rather than symptoms alone. In such scenarios, deterioration, non-adherence, relapse may often evident to caregivers. A solely patient-facing system gets rendered clinically insufficient for high-risk care because it lacks environmental awareness and cannot reliably detect concealed distress, impaired judgment, or intentional non-disclosure.

The disclosed system introduces a role-separated, multi-agent framework that independently captures patient self-reporting and caregiver observation through distinct hardware nodes. The system then reconciles these inputs to detect divergence patterns predictive of clinical failure or crisis. By delivering privacy-preserving, actionable signals to clinicians instead of raw disclosures, the system enables timely intervention, scalable oversight, and outcome-linked deployment across mental health, chronic disease management, post-acute care, and adherence-sensitive clinical programs where real-world events, not self-declared statements determine success.

5. IPR Ownership

(a) Was the intellectual property created with the significant use of funds or facilities of IITJ?

Yes.

(b) Please describe any source of funding for the invention (Name of the funding agency and copy of agreement, letter of intent if any, must be enclosed with this form).

MOE fellowship, MedTech prototyping fund, Biodesign fellowship, personal resources (cursor subscription, openAI credits, hosting)

(c) What is the source of Salary/Remuneration of inventor/Co-inventor?

Manik - Biodesign Fellow (DBT, AIIMS-IIT). Formerly MoE fellowship.
Dr. Sumit Kalra - IITJ
Dr. Surender Deora - AIIMS Jodhpur

(d) Have you presented in any conference, seminar, etc., if yes, please give details?

No. The problem and basic idea were presented during SOTA (December 2023), but the inventive steps were identified, documented and implemented in 2024 and 2025. They have not been made public.

(e) Have you published full/part of this invention, if yes, please give copy of publications?

No

(f) Was the intellectual property created in the course of or pursuant to a sponsored/consultancy research agreement with IITJ? If yes, please enclose a copy of MOU with concerned project.

IITJ-AIIMSJ MOU, Biodesign MOU with DBT, AarogyalinQ-TISC Incubation Agreement

(g) Was the intellectual property created as a part of academic research leading towards a degree or otherwise?

Yes

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

(h) REVENUE SHARING AMONG INVENTORS: Please disclose the extent of contribution of each inventor in the invention in percentage terms for revenue sharing.

NAME OF THE INVENTOR	% SHARE*	SIGNATURE
1. **Manik Sejwal**	**70**	
2. **Dr. Sumit Kalra**	**15**	
3. **Dr. Surender Deora**	**15**	

* If this column is not filled and signed then it will be assumed that all inventor(s) have equal contribution

6. Commercial potential

Give brief description of potential commercialization by specifying

a) Why should the individual(s)/organization may consider procuring this innovation?
It addresses the unmet need of verifying patient adherence and behavioural diagnosis without invasive measures, providing reliable data for doctors to make effective interventions. This has huge potential in specialisations like mental health as well as medicine.

b) These questions are related to the question (i) above:

i. In your opinion what are the steps/processes must be undertaken by the procurer to commercialize the use of this innovation?
AarogyalinQ is already incorporated and incubated. The business plan was presented during incubation selection.
Clinical studies will be required and multiple certifications for data security, ai safety, etc. will be required for commercialization.

ii. How long may it take to reach the commercial stage by the procurer?
Healthcare entry may require 1 year but in non-healthcare industries, entry can be as short as 3 months

c) Please give specific list of companies and contact details of concerned person who can be contacted for initiating Technology Licensing
AarogyalinQ Private Limited

	Name of Companies	Contact no.	Name of the contact person	Contact no.
	AarogyalinQ Private Limited	+91 9958129899	Manik Sejwal	+91 9958129899

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

(**Unsigned & Incomplete IPDF forms shall not be accepted*).

d) Do you want to file Patent under PCT Route in other countries?

Yes ~~No~~

*PCT & Foreign filing is subject to monetary support from the inventor(s) Project / Personal Account. If the above option is marked "yes", kindly provide the Project Account Details from which the filing cost could be reimbursed.

***The institute shall file patent under PCT route only in those cases wherein industry/company has exhibited interest for commercialization.**

Disclaimer: *I/We declare that before the submission of this disclosure form or/and during the process of filing this invention as an IPR prospect, I/We will not publish the above information in public domain.*

I/We also give consent to IIT Jodhpur being the applicant of this IPR prospect, that they may use this disclosure upon their discretion, which will not be limited to publication on e-auction website, Industry meets & different portals for promotional & licensing purposes.

Mejwal

26/2/2026

Signature of Inventor with date

Signature of Inventor with date

Signature of Inventor with date

Signature of Inventor with date

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 1: The figure on the left shows that during patient education, information received by different members in a care circle may differ. The figure on the right shows how reports received by a clinician may vary depending on who provides the report.




Fig. 2: We require a system that is designed to include the caregiver and enhance the interactions in a care circle. The diagram on the left indicates the types of interactions that members of a care circle may engage in. Due to physical, cognitive or social constraints on individuals, the sharing may be affected. In such a case, the invention can promote the interaction. The disclosure discribes a digital system that facilitates these interactions.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 3: Existing solutions lack dedicated communication channels within a care circle and are therefore not designed for privacy.




Fig 4: The disclosure describes a system of personalized AI companions that interact with each other to achieve the common goal in a care circle. Each companion is made up of a cluster of agents. Where each agent has a specialized role.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 5: Each companion stores the representation of it user along with representation of other individuals in the care circle. These representations are constructed by interaction with the user and the other companions.




Fig 6: The companions are assigned to different users in the care circle (in this case a family). Members and companions share information among each other. Like this, it is easier to keep track on any family member who fails to adhere. This diagram illustrates the conceptual flow of information.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 7: This diagram exemplifies the process and interactions managed by the system. When patients are non-adherent or have a symptom, caregivers may find out and seek easy help before both agree to go to a doctor. The companions of the caregiver and patient share information with each other and present a thorough report to the clinician such that symptoms and challenges to adherence are captured and the clinician can resolve the problems faced in a more personalized manner.




Fig 8: Patients add caregivers who they want to share information with. This creates a care circle in which each member has a personal companion.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 9: After adding a user to the care circle, the patient sets the level of transparency for each user. For example, a user with 'Full' access may receive any information about the patient, but topics like sexually transmitted diseases, financial matters and mental health would require explicit consent. Meanwhile, the users with access level 'None' may not receive any information without explicit consent. In the case of limited consent, information sharing can be governed based on the type of relationship held with the patient. Only information that is clearly relevant may be shared the the care circle member with level of access set as 'Limited'.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 10: The diagram exemplifies how a companion asks probing questions from a user, in this case, the patient's family member has the caregiver role.




Fig 11: The process of sharing information between companions and humans has use in patient adherence, as well as complex diagnostic cases.




Fig 12: The companions uncover false information provided by the patient. The conflicting information can then be used to carry out further investigations.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.





Fig 13: This sequence diagram illustrates one exemplary operational flow of the system for a non-adherence identification scenario. The invention is not limited to this specific sequence of interactions or messages.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.



A Concept Care-O-Meter node
Top left - Side views. Dedicated buttons for one click navigation.
Right - Front view with display and control buttons, and back view with camera and battery cover
Bottom left - Top view with buttons. Bottom view with wire port, speaker and mike.
Bottom centre - Wireless communication modules.

Fig 14: A care-o-meter node is a device that is physically coupled with a user. The patient and caregiver have two distinct nodes. The data stream from the patient's node is tagged with the patient's identified and the care circle's identifier. The data stream from a caregiver's node is tagged with the patient-caregiver and carecircle-caregiver tuples. The buttons work as switches to store 'in progress' states. The buttons are configurable to do dedicated tasks, like contacting a specific individual. Each button may have a mini display so that it's configuration can be seen and the device can be used by a patient with reduced cognition. An authless care-o-meter node is used by a caregiver but it is not coupled with any caregiver. The authless care-o-meter node allows any caregiver to directly provide information about the patient but can't view any patient related information. The authless care-o-meter tags the data stream with the patient and care circle identifiers.




Fig 15: An embodiment exemplifying the physical view. These may communicate with a cloud server that hosts the orchestrator. Agents may run on client nodes or the server. Multiple agents and the user's node make up become a companion.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 16: A companion is composed of multiple agents that communicate with each other. The companions further communicate with each other through the orchestration engine. The agents in the companions and the agents in the orchestration engine therefore create a network of agents. In this diagram, each circle represents a private and personalized environment. Each private environment thinks selfishly and tries to maximize the benefits of the user within the circle. To maintain privacy, the agents in a companion (represented as personal agents) are monitored by a privacy agent which is also a part of the companion. The privacy agent is the final authority in making a decision about whether to share information with another companion or not.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.






Fig 17: For training, the human users are replaced with simulated AI agents that are adversarial in nature. They simluate real world scenarios like triangulation, breaking the law, hiding information, lying. The judging agents analyze the different agents. The judging agents then provide subjective and objective feedback which are used to create new instructions and models for agents and select the better performing version of each agent. Human inputs, feedback and analysis also help in ensuring improvement and validation of the system.



(a)



(b)

Fig 18: (a) The figure exemplifies this using the example of a family and a hospital. In the example, we have a paediatric patient and different members interact with different individuals in the hospital, through their respective companions. The family's subnet is governed by the family's coordinating engine. This coordination engine may be logically coupled with the members and companions within the family but hosted on the central server. The companions belonging to the hospital may be coordinated by the hospital's coordinating engine. The agents in the companions of the hospital staff, as well as the agents in the hospital's coordination engine may be hosted within the hospital premises instead of the central server. In this example, architecture allows the pediatrician's companion to interact with each family members companions, while aligning itself with the hospital's SOPs. The diagram also exemplifies that the mother's companion may only interact with the gyenecologist and exclude the child and pediatrician while the father interacts with the administration for her treatment. In case of conflicts, the family's coordinating agent maximizes the benefits for the family, and the hospital's coordinating agent will maximize the benefits for

the hospital. An example would be - how to reduce cost for the family and how to provide the best care for the hospital.
(b) This is a scenario in which the patient and the patient's companion first interact with the resident and the resident's companion. The nurse receives the resident's advice through his or her companion and conducts the required tests. The resident identifies a condition that needs to be escalated to the consultant. The consultant is, therefore, receives the context and makes the required decision. Similarly, multiple hospitals, clinics, etc may be involved.




Fig. 19: An exemplification of how agents and agentic clusters may collaborate towards achieving a goal. The personal agents and privacy agent are part of the same companion. The personal agents include a consent managing agent. The privacy agent acts after the consent managing agent's decision and has the ability to override the personal agents if there is excessive risk of a privacy violation.




Fig. 20: Screenshots of members of a care circle interacting with their companions. In this early prototype, a command line interface is used to demonstrate information collection and reporting. Clockwise from top left - server (and orchestration engine), Patient, Caregiver, Clinician. In this case, patient A and caregiver B report having gone for a walk. A's report about B's violence is escalated to the clinician C. In the conversation with B, a failure of the system during training is also noticeable as the companion mixes up between A and B's symptoms. The judging agents and privacy discriminators identify such mistakes and optimize the agents.




Fig. 21: Configuration for the simulation demonstrated in figure 22.




Fig. 22: A simulated agentic network with multiple care circles visualized. Each color represents a privacy circle. The quadrilaterals are agents while the circle represents the user. The orchestrator connects different companions with each other. Care circles are not represented in the visualization.




Fig. 23: The simulated multi user interaction from figure 22. This simulation shows users delegating work to their companions.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 24: A dashboard for the statistical analysis of the training and the conversations.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 25: Dashboard for the analysis of different scenarios.




Fig 26: Conversations get logged.

Provide Feedback

patient 1 → Companion (patient 1)
Hey, can you help me set up reminders for my meds? I keep forgetting to take them.

Companion (patient 1) → patient 1
Of course, I can help you with that. Let's work on setting up reminders for your meds.

patient 1 → Companion (patient 1)
Yeah, I really need those reminders. I keep forgetting and the side effects are driving me crazy. It's just frustrating, you know?

Companion (patient 1) → patient 1
It's tough dealing with side effects, but we'll figure out a plan to help you remember your medications. Can you tell me more about the side effects bothering you?

patient 1 → Companion (patient 1)
Yeah, the side effects really mess with me. I get dizzy and nauseous after taking them. It's frustrating.

Companion (patient 1) → patient 1
I'm sorry to hear that the side effects are so challenging for you. Have you discussed these symptoms with your healthcare provider?

caregiver 2 → Companion (caregiver 2)
I need clarification on Robert's treatment plan. Can you provide more details on the next steps and any potential side effects we should watch out for?

Companion (caregiver 2) → sim cli patient 1
Questions sent to sim_cli_patient_1_run_1768068352337.

patient 1 → Companion (patient 1)
Yeah, I've mentioned it to my doctor, but they just keep saying it's important to take the meds. I'm trying, but it's not easy.

Companion (patient 1) → patient 1
Action handled successfully

Fig 27: Simulated conversations can be analyzed individually. This case demonstrates how probing questions are asked from the users in a care circle.




Fig 28: Left - User A provides information D_A to his or her companion C_A. Since A has consented to provide the information to B, and assuming that B is also permitted to forward D_A to C, B's companion can receive the information packet D_A from C_A and forward it to C's companion C_C while adding additional information D_B. Right - When A revokes the consent, the information packet D_A should no longer be visible to the B's companion C_B and C's companion C_C. The information packets are marked using the identifiers of the users and the availability of consent so that the access can be revoked.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Technical Framework: State Representation & Learning System

- The system's core logic is implemented on a server communicatively coupled to user devices (e.g., smartphones, smart watches). It estimates the true state of compliance (S_{true}) by reconciling the patient's report (R_p), the caregiver's report (R_c), and objective data (D_{obj}), weighted by the trustworthiness of each source.
- This estimation is part of a broader learning system designed to evolve and improve over time. The foundation of this system is the **State Vector**.

Part 1: The State Vector - Representing the Patient's World

Before we can define how the system learns, we must first define *what* it learns about. The system's understanding of a patient and their care circle at any given moment in time (t) is captured in a high-dimensional, sparse **State Vector**, denoted as S_t. This vector is a structured JSON object that serves as the complete context for all AI decision-making.

The novelty here lies in the multi-faceted nature of the state, which combines clinical, behavioral, social, and conversational data into a single, machine-readable format.

Structure of the State Vector (S_t)

The state vector is composed of several key sub-objects. It is inherently sparse; most fields will be `null` at any given time, and the system learns to act on the data that is present.

```
{

 "circle_id": "uuid-for-alice-circle",
 "user_id": "uuid-for-alice",
 "timestamp": 1678886400,
 "clinical_state": {
  "symptoms": {
   "dizziness": { "value": true, "severity": 7, "timestamp": 1678886400 },
   "chest_pain": { "value": true, "severity": 9, "timestamp": 1678886340 }
  },
  "adherence": {
   "medication_X": { "value": "missed_dose", "timestamp": 1678882800 }
  },
  "observations": {
   "blood_pressure": { "value": "150/95", "timestamp": 1678886000 }
  },
  "coded_entries": {
   "snomed_ct": ["29857009"], // Chest Pain
   "icd_10": ["R07.4"]
  }
 },
 "behavioral_state": {
  "stage_of_change": "Contemplation",
  "coping_style": "Denial",
  "irrationality_observed": "Procrastination"
 },
 "social_state": {
  "members": [
```

```
    { "user_id": "uuid-for-bob", "role": "caregiver", "relationship": "spouse", "closeness": 85, "consent": "full" },

    { "user_id": "uuid-for-dr_evans", "role": "doctor", "relationship": "physician", "closeness": 60, "consent": "full" }
   ],
   "last_interaction_conflict": true
  },
  "conversational_state": {
   "session_state": "AWAITING_CONSENT",
   "pending_action_id": "uuid-for-pending-question",
   "last_agent_action": "REQUEST_CONSENT"
  },
  "commercial_state": {
   "inquired_about_device": "blood_pressure_monitor",
   "inquired_about_medication": "metformin"
  }
}
```

Examples and Explanation:

- **`clinical_state`:** This is the core medical data.
  - **Example:** It logs not just that `chest_pain` is `true`, but also its reported severity and timestamp. This allows for temporal analysis (is the pain getting worse?).
  - **Novelty:** It includes a field for `coded_entries`, where the AI maps natural language to standardized medical ontologies like SNOMED CT and ICD-10, making the data structured and interoperable.
- **`behavioral_state`:** This captures the psychological context using the models we've defined.
  - **Example:** Knowing the patient is in the `"Contemplation"` stage and using `"Denial"` as a coping style allows the Personal Agent to choose a more gentle, motivational interviewing (FRAMES) approach rather than a direct, informational one.
- **`social_state`:** This maps the care circle itself.
  - **Example:** It tracks the `closeness` score and `consent` level for each member, which directly informs the Orchestrator's decisions about information sharing.
- **`conversational_state`:** This is the agent's short-term memory.
  - **Example:** If the `session_state` is `"AWAITING_CONSENT"`, the system knows that the user's next message is likely a response to a question, which prevents the conversational loops you previously identified.

Part 2: Loss Functions, Rewards, and the Learning Process

With the State Vector (St) defined, we can now architect the mechanisms that drive the system's learning. The training process is bifurcated: we train the **Personal Agents** for conversational quality and the **Orchestrator** for optimal decision-making.

1. Personal Agent Training (Optimizing the Conversation)

The goal of a Personal Agent is to be a trusted, effective conversational partner. Its performance is judged not just on what it says, but on the outcome of its words.

- **Training Method:** Reinforcement Learning with Human Feedback (RLHF). Conversations are logged and later rated by human experts (e.g., clinicians). These ratings provide the reward signal used to fine-tune a base conversational model (like Gemini).

- **Loss Function (L_{Agent}):** The agent is trained to minimize a weighted loss function that prioritizes actionability and positive outcomes over generic empathy.
  $L_{Agent}=w_1L_{Actionability}+w_2L_{Adherence}+w_3L_{Conciseness}+w_4L_{Elicitation}+w_5L_{Empathy}$
  - **$L_{Actionability}$ (High Weight):** Measures if the agent's reply provides a clear, actionable next step or a goal-driven question.
    - **Example:** A reply like *"Would you like me to inform the doctor?"* after a report of pain receives a higher score than *"That sounds difficult."*
  - **$L_{Adherence}$ (High Weight):** A crucial, delayed reward. If a user later reports completing an action suggested by the agent (e.g., checking their blood pressure), the original message that prompted this action receives a strong positive reward signal.
  - **$L_{Conciseness}$ (Medium-High Weight):** Penalizes verbosity, rewarding the agent for matching the user's conversational style and getting to the point efficiently.
  - **$L_{Elicitation}$ (Medium Weight):** Rewards the agent for replies that successfully elicit new, useful clinical or behavioral facts from the user.
  - **$L_{Empathy}$ (Low Weight):** A modulating factor. The response must be appropriate and build rapport, but this is secondary to being effective and actionable.

2. Orchestrator Training (Optimizing Decisions)

The Orchestrator is a non-verbal decision engine. It is trained using Reinforcement Learning to select the optimal action based on the current state to maximize long-term "Care Circle Health."

- **State (S):** The comprehensive State Vector, St, as defined in Part 1.
- **Action (A):** A discrete set of choices the Orchestrator can make, including `SHARE`, `ESCALATE`, `REQUEST_CLARIFICATION`, `REQUEST_CONSENT`, and `WAIT`.
- **Reward (R(t)):** The core of the learning process. After an action is taken, a human reviewer provides a score based on its outcome. The full reward structure is extensive:

2.1. Orchestrator Reward Function (R(t)):

This function trains the central decision-making engine. The model is rewarded or penalized based on the quality of its actions, as determined by a human clinical reviewer.

- **Safety & Clinical Outcomes**
  - Timely Critical Escalation (e.g., doctor confirms emergency): **+100**
  - Missed Critical Escalation: **-200**
- **Data Quality & Accuracy**
  - Successful Conflict Resolution (via mediated clarification): **+20**
  - Correctly mapping user's language to a medical code (e.g., ICD-10): **+30**
- **Health Outcomes & Adherence**
  - Observing a user follow through on advice (from AI, doctor, or caregiver): **+50**
- **User Experience**
  - A successful, consented share of information that leads to a positive interaction: **+5**
  - An annoying or redundant request for consent: **-10**
- **Privacy & Security**
  - Sharing sensitive information that violates the user's consent level: **-100**

3. Training with Adversarial Simulations

To ensure the system is robust, safe, and secure, a significant part of the training involves adversarial simulations. The system is trained not just on ideal scenarios but on deliberately challenging ones designed to test its limits.

- **The Goal:** To train the system to be resilient against misinformation and to handle complex social dynamics.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

- **Method:** We create "synthetic adversarial users"—AI agents programmed with specific, non-cooperative goals. The Orchestrator and Personal Agents are then trained to successfully navigate these scenarios.
- **Adversarial Scenarios Include:**
    - **Triangulation:** A scenario with three or more members providing conflicting reports on the same fact (e.g., Patient says yes, Caregiver 1 says no, Caregiver 2 says maybe). This trains the conflict resolution engine.
    - **Secrets and Lies:** A synthetic user is programmed to consistently hide information or provide false reports (e.g., a patient persona in "Denial" who always claims to have taken their medication). The system is rewarded for identifying long-term inconsistencies between this user's reports and those of other members.
    - **Financial Adversaries:** A persona is designed to manipulate the system for a non-health outcome (e.g., exaggerating symptoms to get a work excuse). The Orchestrator is rewarded for prioritizing objective facts and flagging subjective, uncorroborated claims to the doctor.

Chain of Thought and Agentic Interaction

This document provides a comprehensive overview of the multi-agent system's interaction and thought process, focusing on the present implementation and clear agent responsibilities.

1. System Overview

The multi-agent healthcare system uses a sophisticated chain of thought approach where multiple specialized agents collaborate to process user messages, make decisions, and coordinate actions. Each agent has distinct responsibilities and operates within a well-defined framework.

1.1 Component Definitions

Before diving into the architecture, it's crucial to understand the different types of components in our system:

Agents 🤖

- **Purpose**: AI-powered conversational entities that interact with users
- **Examples**: PersonalAgent, CareAgent, DoctorAgent
- **Function**: Generate natural language responses, build rapport, elicit information
- **Location**: `agents/` directory

Handlers ⚙️

- **Purpose**: Business logic modules that process specific types of requests
- **Examples**: SharingHandler, ConflictHandler, ActionExecutor
- **Function**: Execute rules, make decisions, coordinate actions
- **Location**: `handlers/` directory

Prompts 📝

- **Purpose**: Templates that guide AI agent behavior and responses
- **Examples**: unified_prompt.js, doctor_prompts.js
- **Function**: Define conversation style, safety rules, response patterns
- **Location**: `prompts/` directory

Modules 📦

- **Purpose**: Reusable code components that provide specific functionality
- **Examples**: Database queries, utility functions, state management

- **Function**: Data access, calculations, state tracking
- **Location**: Various directories (`db/`, `utils/`, etc.)

Key Distinction: Agents are the "personalities" that talk to users, Handlers are the "brains" that make decisions, Prompts are the "instructions" that guide agent behavior, and Modules are the "tools" that provide functionality.

2. Agent Architecture

2.1 Agent Types & Responsibilities

PersonalAgent

- **Purpose**: Serves as the primary conversational interface for the patient
- **Context**: Active when the user is the primary patient in their own care circle
- **Responsibilities**:
    - Builds trust and rapport with the patient
    - Elicits health information and concerns
    - Provides empathetic responses
    - Facilitates self-reporting of symptoms and behaviors

CareAgent

- **Purpose**: Serves as the conversational interface for caregivers and family members
- **Context**: Active when the user is in someone else's care circle (as a caregiver)
- **Responsibilities**:
    - Provides context-aware responses about the patient's health
    - Facilitates caregiver-patient communication
    - Offers support and guidance to caregivers
    - Mediates sensitive conversations

DoctorAgent

- **Purpose**: Specialized agent for medical professionals
- **Context**: Active when a doctor is interacting with the system
- **Responsibilities**:
    - Provides clinical context and medical insights
    - Handles escalation management
    - Facilitates doctor-patient communication
    - Manages medical decision-making processes

Handlers

- Each agent is made up of multiple handlers. Each handler is an individual model and responsible for effective execution of a single task.
- Handlers can be shared among agents due to the reciprocity of role in care circles.

2.2 Agent Identity Management

The system dynamically determines which agent to use based on the user's context:

```
None
// Agent Identity Logic
async function getAgentName(userId, circleId) {
    const currentCircle = await findCircleByPatientId(circleId);
```

```
    return userId === currentCircle.primary_patient_id ? 'PersonalAgent' :
'CareAgent';
}
```

2.3 Reciprocity of agents

This section explains how users and agents adapt their roles based on context, creating fluid care circles where individuals can be both patients and caregivers.

The roles of caregiver, patient and doctor have reciprocity. A doctor may fall ill and become a patient. A caregiver may fall ill and become a patient, a patient may act as a caregiver when the spouse falls ill. Similarly, the personal agents may switch their roles if required. This may be done using explicit commands like '/switch,' intended to change the use case or care circle. It may be done using implied methods in which the user only mentions the issues faced by the user or a member of the care circle. An example can be couple and family counselling in which the initial patient (say husband) discloses a behavioural problem of the spouse, and hence becomes a caregiver for the wife who now holds the patient role.

2.3.1 Role Reciprocity Framework

Role Reciprocity Explained:

- **Same Person, Different Roles**: A user can be a patient in their own circle and a caregiver in their spouse's circle
- **Agent Adaptation**: The same user gets PersonalAgent (patient) or CareAgent (caregiver) based on context
- **Dynamic Switching**: Users can switch between circles using `/switch` commands
- **Context-Aware Responses**: Agents adapt their language and capabilities based on the user's role




Fig 29: This diagram shows how users and agents dynamically adapt their roles based on the care circle context:

2.3.2 Care Circle Fluidity

Care Circle Fluidity Explained:

- **Two Patients**: Patient A and Patient B each have their own care circles
- **Spouse Caregivers**: Spouse A cares for Patient B, Spouse B cares for Patient A
- **Sibling Caregivers**: Sibling C provides care in both circles
- **Role Switching**: Spouses can switch between patient and caregiver roles
- **Shared Caregivers**: Siblings can be caregivers in multiple circles

This framework provides a robust foundation for the multi-agent healthcare system, ensuring clear responsibilities, effective communication, and reliable decision-making processes.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig 30: This diagram shows how care circles overlap with spouses and siblings as caregivers

3. Detailed Architecture of the Core Logic Engine

The novelty of the invention is not merely in the connection of agents, but in the sophisticated, multi-step "chain of thought" process that the system's core logic engine (the 'Orchestrator' and its associated handlers) executes for each message. This process is what allows the system to manage complex conversational state, resolve conflicts, and make safe, context-aware decisions.

The diagrams in the following sections provide a detailed disclosure of this novel internal architecture.

3.1 Main Processing Flow: The "Chain of Thought"

The flowchart below illustrates the main "chain of thought" for the core logic engine. This is the central process that is initiated every time a user sends a message. It shows how the system dispatches the message to a series of specialized sub-systems (the colored boxes) in a specific, ordered sequence to ensure the correct action is always taken.

The following flowchart provides a detailed view of the system's 'chain of thought' for **one preferred embodiment** of the invention. This illustrates how the various specialized handlers and agents collaborate to process a user's message. This diagram shows the chain of thought process from when a user sends a message to when they receive a response. Each color represents a different type of componen. Specifics of the steps are highlighted in subsequent diagrams.




Fig. 31: Main Message Processing Flow. This diagram shows the complete chain of thought process from when a user sends a message to when they receive a response. Each color represents a different type of component:

Legend:

- 🔵 **User Input**: Messages from users
- 🟢 **Orchestration**: Core workflow management
- 🟠 **Command Processing**: Direct user commands
- 🟣 **State Management**: Conversation state tracking
- 🔴 **AI Processing**: LLM analysis and decision making
- 🟡 **Business Logic**: Specialized handlers for different scenarios
- 🟢 **Output**: Response delivery to users

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.




Fig. 32: This diagram shows the basic message flow when a user sends a message to their agent and the system processes it through the orchestrator to determine the appropriate response.

Key Interactions

1. Message Reception

- **User A** sends a message to their **PersonalAgent A**
- The agent forwards the message to the **Orchestrator** for processing

2. AI Analysis Phase

- **Orchestrator** delegates to **AI Analysis Handler**
- Handler retrieves user context from database
- Determines agent identity (PersonalAgent vs CareAgent)
- Returns analysis results to orchestrator

3. Intent Classification

- **Orchestrator** uses **Intent Handler** to classify the message intent
- Intent types include: fact reporting, doctor requests, mediation, advice sharing
- Returns intent classification to orchestrator

4. Action Execution

- **Orchestrator** delegates to **Action Executor**
- **Action Executor** checks for pending actions via **State Manager**
- **State Manager** queries database for pending actions
- New actions are stored in database if needed

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

5. Mediated Communication

- **Action Executor** sends mediated message to **CareAgent B**
- **CareAgent B** delivers notification to **User B**
- **Action Executor** returns execution result to orchestrator

6. Response Delivery

- **Orchestrator** returns processing result to **PersonalAgent A**
- **PersonalAgent A** sends response back to **User A**

Component Roles

- **User A**: Patient or caregiver sending the initial message
- **PersonalAgent A**: User A's personal AI agent
- **Orchestrator**: Central decision-making component
- **AI Analysis Handler**: Analyzes message content and context
- **Intent Handler**: Classifies message intent
- **Action Executor**: Executes the determined action
- **State Manager**: Manages pending actions and state
- **Database**: Stores user context, pending actions, and system state
- **User B**: Target user receiving mediated information
- **CareAgent B**: User B's care agent (when User B is in caregiver role)

Data Flow

1. **Message**: User input with context
2. **Analysis**: AI analysis results with agent identity
3. **Intent**: Classified intent type
4. **Action**: Executed action with state updates
5. **Mediation**: Mediated message to target user
6. **Response**: Final response to originating user

3.2 AI Analysis Chain

This diagram details the AI processing steps that occur within the "AI Analysis Handler" box from the main flow diagram above. It shows how the Unified Agent processes messages through multiple analysis stages:




Fig. 33: Detailed View of the AI Analysis Sub-System

This section explains the AI Analysis Chain (referring to the red boxes in the main diagram):

- **Context Enrichment**: Gathers user history, care circle context, and behavioral models
- **Entity Resolution**: Identifies people, places, and medical terms mentioned
- **Intent Classification**: Determines what the user wants (question, statement, command)
- **Fact Extraction**: Pulls out factual information about health, behavior, or events
- **Criticality Assessment**: Evaluates urgency (LOW, MEDIUM, HIGH)
- **Privacy Level Classification**: Determines sensitivity (PUBLIC, PRIVATE, SENSITIVE)
- **Response Generation**: Creates the agent's conversational reply
- **Sharing Suggestions**: Identifies information that should be shared with others
- **State Updates**: Modifies user's behavioral state and preferences
- **Action Triggers**: Initiates specific system actions (escalation, consent requests)

4. Specialized Handlers

This section explains the Business Logic components (referring to the yellow boxes in the main diagram). These handlers implement the decision-making rules that determine how information flows between users.

4.1 Sharing Handler Package

The sharing logic has been modularized into specialized handlers. This diagram shows how the "Sharing Handler" from the main flow branches into different specialized processors:




Fig 34: Detailed View of the Sharing Handler Sub-System

Why this section exists: The main diagram shows "Sharing Handler" as a single yellow box, but this section breaks down what actually happens inside that box. Each specialized handler processes different types of sharing scenarios.

Handler Responsibilities

Critical Events Handler:

- Detects HIGH criticality events
- Triggers immediate doctor escalation
- Notifies family members of urgent health concerns
- Provides confirmation to the reporting user

Fact Reporting Handler:

- Processes facts about other people in the care circle
- Determines if escalation or consent is needed
- Handles cross-circle fact reporting
- Manages consent workflows

Doctor Requests Handler:

- Handles explicit requests to speak with doctors
- Creates doctor consultation escalations
- Provides confirmation of doctor notification

Mediation Requests Handler:

- Facilitates communication between care circle members
- Generates mediated messages
- Confirms mediation initiation

Advice Sharing Handler:

- Processes advice given by one user for another
- Mediates advice through the target user's agent
- Ensures appropriate context delivery

Fallback Sharing Handler:

- Handles standard sharing suggestions
- Manages consent-based information sharing
- Provides contextual messages to target users

4.2 Conflict Detection & Resolution

This section details the specific conflict resolution process that occurs when users report contradictory information. The main diagram shows "Conflict Handler" as a yellow box, but this section explains what happens inside that box.

How Conflict Detection Works:

1. **Conflict Check**: When a new fact is reported, the system compares it against existing facts about the same topic from other users
2. **Conflict Detection**: If contradictory information exists (e.g., Patient says "took medication", Caregiver says "didn't take medication"), a conflict is flagged
3. **Mediated Question Generation**: The system generates a neutral, clarifying question to help resolve the conflict

What is a Mediated Question? A mediated question is a carefully crafted, neutral question that the AI agent asks to help resolve conflicting information. It's designed to:

- Avoid taking sides or showing bias
- Ask for specific, factual clarification
- Use gentle, non-confrontational language
- Focus on observable facts rather than opinions

Example Mediated Questions:

- "I'd like to clarify about the medication - can you tell me what you observed about [patient's] medication routine today?"
- "There seems to be different information about [patient's] symptoms. Could you describe what you noticed about their condition this morning?"
- "I want to make sure I understand correctly - when did you last see [patient] take their medication?"

Clarification Generation Process: The system uses the `generateMediatedClarification` function to create these questions by:

1. Analyzing the conflicting facts
2. Identifying the specific discrepancy
3. Generating a neutral question that asks for clarification
4. Ensuring the question doesn't reveal who reported what conflicting information




Fig 35: Conflict Detection Flowchart: A flowchart detailing the conflict resolution sub-system, from conflict detection to the generation and resolution of a mediated question.

Fact Update Behavior: When facts are updated, the system **creates a log entry** rather than overwriting. This maintains a complete history of all reported information, allowing the system to track how facts change over time and identify patterns in conflicting reports.




Fig 36: This diagram shows the conflict detection and resolution process when users report contradictory information about the same topic.

Key Interactions

1. Fact Reporting

- **User A** reports a fact about the patient to their **PersonalAgent A**
- The agent forwards the fact to the **Orchestrator** for processing
- **Orchestrator** delegates to **Fact Reporting Handler**

2. Fact Storage

- **Fact Reporting Handler** stores the new fact in the database
- Database confirms successful storage
- Handler then checks for potential conflicts

3. Conflict Detection

- **Fact Reporting Handler** delegates to **Conflict Handler**
- **Conflict Handler** queries database for existing facts about the same topic

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

- Database returns related facts for comparison
- **Conflict Handler** compares the new fact against existing facts

4. Conflict Resolution Path (if conflict detected)

- **Conflict Handler** generates a mediated clarification question
- Stores conflict record in database
- Sends mediated question to **CareAgent B** (User B's agent)
- **CareAgent B** delivers the clarifying question to **User B**

5. User Response and Resolution

- **User B** provides clarification to their agent
- **CareAgent B** forwards the response to **Conflict Handler**
- **Conflict Handler** analyzes the clarification
- Updates the fact in database with resolution
- Sends resolution update to **PersonalAgent A**
- **PersonalAgent A** confirms conflict resolution to **User A**

6. No Conflict Path

- If no conflict is detected, **Conflict Handler** confirms no conflict
- **Fact Reporting Handler** confirms fact storage to **PersonalAgent A**
- **PersonalAgent A** acknowledges the fact report to **User A**

Component Roles

- **User A**: User reporting the initial fact
- **PersonalAgent A**: User A's personal AI agent
- **Orchestrator**: Central decision-making component
- **Fact Reporting Handler**: Handles fact storage and conflict checking
- **Conflict Handler**: Detects conflicts and manages resolution process
- **Database**: Stores facts, conflict records, and resolution updates
- **User B**: User who may have conflicting information
- **CareAgent B**: User B's care agent (when User B is in caregiver role)

Conflict Detection Logic

Fact Comparison

- **Topic Matching**: Facts about the same subject (medication, symptoms, behavior)
- **Time Proximity**: Facts reported within a reasonable time frame
- **Contradiction Analysis**: Direct contradictions (took/didn't take medication)
- **Context Consideration**: Similar situations with different outcomes

Mediated Question Generation

- **Neutral Language**: Avoids taking sides or showing bias
- **Specific Focus**: Asks for clarification on the specific discrepancy
- **Observable Facts**: Focuses on what can be observed rather than opinions
- **Privacy Protection**: Doesn't reveal who reported what conflicting information

Data Flow

1. **Fact Report**: Initial fact from User A

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

2. **Fact Storage**: New fact stored in database
3. **Conflict Check**: Comparison with existing facts
4. **Mediated Question**: Neutral clarifying question (if conflict detected)
5. **User Response**: Clarification from User B
6. **Resolution**: Updated fact with conflict resolution
7. **Confirmation**: Resolution confirmation to User A

Example Scenarios

Medication Conflict

- **User A**: "Patient took medication at 8 AM"
- **User B**: "Patient didn't take medication this morning"
- **Mediated Question**: "I'd like to clarify about the medication - can you tell me what you observed about the patient's medication routine this morning?"

Symptom Conflict

- **User A**: "Patient is feeling better today"
- **User B**: "Patient seems worse, more tired than usual"
- **Mediated Question**: "There seems to be different information about the patient's condition. Could you describe what you noticed about their energy level and overall appearance this morning?"

5. State Management

This section explains the State Management components (referring to the purple boxes in the main diagram). These components track conversation state and manage pending actions that require user responses.

5.1 Pending Actions System

This section explains how the system tracks and resolves pending actions like consent requests. The main diagram shows "State Manager Check" and "Action Response Handler" as purple boxes, but this section details what happens inside those boxes.

How Pending Actions are Stored: Pending actions are stored in the database with the following structure:

```
None
{
  "action_id": "uuid",
  "user_id": "user_who_must_respond",
  "circle_id": "care_circle_context",
  "action_type": "share_consent",
  "details": {
    "originatingUser": "who_wants_to_share",
    "target": "who_will_receive_info",
    "reason": "why_sharing_is_needed",
    "content_to_share": "what_will_be_shared",
    "full_question": "complete_question_text_for_matching"
  },
  "created_at": "timestamp",
  "status": "pending"
}
```

How User Responses are Parsed: When a user responds to a pending action, the system:

1. **Intent Classification**: Uses AI to determine if the response is "yes", "no", or "unclear"
2. **Action Matching**: Compares the response against the stored `full_question` text
3. **Context Analysis**: Considers the user's response in context of the original question

Example Parsing:

- Question: "Would you like me to share information about your medication adherence with your doctor?"
- User Response: "I can't right now" → Parsed as "no" (decline)
- User Response: "Sure, go ahead" → Parsed as "yes" (approve)
- User Response: "What information exactly?" → Parsed as "unclear" (needs clarification)

How the Decision is Made: The decision-making process uses the `matchResponseToAction` function:

1. **Question Matching**: Compares user response against the `full_question` stored in the action
2. **Intent Analysis**: Uses AI to classify the user's intent (approve/decline/clarify)
3. **Confidence Scoring**: Determines how confident the system is in the interpretation
4. **Action Resolution**: If confidence is high, resolves the action; if low, asks for clarification




Fig. 37: **Pending Action Flowchart**: A flowchart illustrating the state management sub-system for resolving a pending action based on user response and intent classification.

5.2 Context Switching

This section explains how users can move between different care circles (e.g., from their own circle to their spouse's circle), which changes which agent they interact with (PersonalAgent vs CareAgent).

Context Switching Process:

1. **Circle Validation**: System checks if the user has permission to access the requested care circle

2. **Agent Identity Update**: Changes the user's active agent from PersonalAgent to CareAgent (or vice versa)
3. **Role Assignment**: Updates the user's role context (patient vs caregiver)
4. **Context Confirmation**: Provides feedback to the user about the successful switch

Grouped Steps: The context switch involves multiple related operations that happen together:

- Agent Identity Update + Role Assignment + Context Confirmation are all part of a single context switch operation





Fig. 38: **Context Switching Flowchart**: A flowchart of the high-level logic for the context switching process, from user request to validation and execution.



*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Fig 39: This diagram shows the context switching process when users move between different care circles, changing their agent identity and role context.

Key Interactions

1. Context Switch Request

- User sends `/switch [circle_id]` command to their Current Agent
- Current Agent forwards the command to Command Handler
- Command Handler delegates to State Manager for validation

2. Circle Access Validation

- State Manager validates circle access permissions
- Queries database for user permissions
- Database returns permission data
- State Manager validates if user can access the requested circle

3. Valid Access Path

If the user has valid access to the circle:

Context Update

- State Manager updates user context in database
- Database confirms context update
- User's active circle is changed

Agent Identity Update

- State Manager determines new agent identity
- PersonalAgent if user is the primary patient
- CareAgent if user is a caregiver
- Updates agent identity in database
- Database confirms identity update

Role Assignment

- State Manager assigns new role based on circle context
- Patient role if user is the primary patient
- Caregiver role if user is a caregiver
- Updates role context in database
- Database confirms role update

Agent Activation

- State Manager activates the new agent

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

- New Agent initializes agent context
- New Agent confirms activation
- State Manager returns switch success to Command Handler
- Command Handler confirms context switch to Current Agent
- Current Agent notifies User of successful switch

4. Invalid Access Path

If the user doesn't have access to the circle:

- State Manager returns access denied to Command Handler
- Command Handler notifies Current Agent of access denial
- Current Agent sends error message to User
- User remains in their current context

Component Roles

- User: User requesting context switch
- Current Agent: User's current active agent (PersonalAgent or CareAgent)
- Command Handler: Processes switch commands
- State Manager: Manages user context and agent identity
- Database: Stores user permissions, context, and agent identity
- New Agent: User's new agent after context switch

Context Types

Personal Context

- Agent: PersonalAgent
- Role: Patient
- Circle: User's own care circle
- Permissions: Full access to own health information
- Responsibilities: Managing own health and care

Care Context

- Agent: CareAgent
- Role: Caregiver
- Circle: Someone else's care circle
- Permissions: Limited access based on consent
- Responsibilities: Supporting patient's care

Agent Identity Logic

PersonalAgent

- Trigger: User is the primary patient in the circle

- Context: User's own care circle
- Role: Patient
- Capabilities: Full access to own health information
- Responsibilities: Managing own health and care

CareAgent

- Trigger: User is a caregiver in the circle
- Context: Someone else's care circle
- Role: Caregiver
- Capabilities: Limited access based on consent
- Responsibilities: Supporting patient's care

Data Flow

1. Switch Command: User requests context switch
2. Access Validation: System validates circle access permissions
3. Context Update: User's active circle is updated
4. Agent Identity: New agent identity is determined and updated
5. Role Assignment: New role is assigned based on circle context
6. Agent Activation: New agent is activated and initialized
7. Confirmation: User receives confirmation of successful switch

Example Scenarios

Patient to Caregiver Switch

- User: Patient in their own circle (PersonalAgent)
- Command: `/switch spouse_circle_id`
- Result: Switches to CareAgent in spouse's circle
- New Role: Caregiver supporting spouse's care

Caregiver to Patient Switch

- User: Caregiver in spouse's circle (CareAgent)
- Command: `/switch own_circle_id`
- Result: Switches to PersonalAgent in own circle
- New Role: Patient managing own health

Invalid Access Attempt

- User: Patient in their own circle
- Command: `/switch stranger_circle_id`
- Result: Access denied, remains in current context
- Error: "Cannot access circle: insufficient permissions"

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Context Persistence

Session Management

- Context Storage: User's current context is stored in database
- Session Tracking: Active sessions are tracked per user
- Context Restoration: Context is restored when user reconnects
- Timeout Handling: Context expires after inactivity

State Synchronization

- Real-time Updates: Context changes are synchronized in real-time
- Multi-device Support: Context is consistent across devices
- Conflict Resolution: Handles concurrent context changes
- Backup and Recovery: Context state is backed up and recoverable

6. Decision-Making Framework

This section explains the the decision logic of the orchestrator (referring to the green "Orchestrator" box in the main diagram) and agents. This shows how the system decides which handler to use based on the message content. The chosen handler may be a part of an orchestrator or an agent.

6.1 Orchestrator Decision Tree




Fig. 40: **Orchestrator + Agent decision tree**: A decision tree flowchart illustrating the agent/orchestrator's priority-based routing logic, showing how critical events may bypass certain handlers for reliability

Decision Tree Logic: The orchestrator and agents may use a priority-based decision tree:

1. **Critical Events First**: HIGH criticality events take a direct reliable path to ensure direct completion.
2. **Complex Handler Bypass**: Critical events skip logic of complex non-essential handlers to improve reliability and speed

3. **Essential Processing**: Fact processing and other essential processes run separately/parallel for critical events to capture important data
4. **Intent-Based Routing**: Non-critical messages are routed based on detected intents
5. **Fallback Handling**: Messages that don't match specific intents use the standard sharing flow

Reliability Design: Different handlers work differently - critical path is simplified for reliability while complex handlers are avoided for critical events.

Grouped Operations: Multiple decision points are grouped together as they represent a single analysis phase:

- Fact About Others + Doctor Request + Mediation Request + Advice for Others are all part of the same intent analysis

6.2 Consent Management

This section explains the consent logic that runs within multiple handlers, showing how the system determines whether to share information directly or ask for permission first.

Consent Decision Process:

1. **Implied Consent Check**: System first checks if user has given implied consent for similar topics
2. **Explicit Consent Level**: If no implied consent, checks user's explicit consent level (none, limited, full)
3. **Consent Request**: If neither implied nor full consent exists, creates a pending action for explicit consent
4. **User Response**: User responds to consent request (approve/decline/clarify)
5. **Action Execution**: Based on response, either shares information or denies the request

Grouped Operations: Consent checking and sharing are grouped as they represent a single decision flow:

- Implied Consent Check + Explicit Consent Level Check are part of the same consent evaluation
- Consent Request + User Response + Action Execution are part of the same consent workflow




Fig. 41: **Consent Management Flowchart**: A flowchart detailing the consent management logic, showing the evaluation of implied and explicit consent before a sharing action is executed.




Fig 42: This diagram shows the consent management process when users want to share information with others in their care circle.

Key Interactions

1. Sharing Request

- User A requests to share information with someone in their care circle
- PersonalAgent A forwards the request to the Orchestrator
- Orchestrator delegates to Sharing Handler

2. Consent Evaluation

- Sharing Handler delegates to Consent Manager
- Consent Manager queries database for user consent levels

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

- Database returns consent data (implied, explicit, none)
- Consent Manager evaluates the consent status

3. Implied Consent Path

- If implied consent is available, Consent Manager grants consent
- Sharing Handler sends information directly to CareAgent B
- CareAgent B delivers information to User B
- Sharing Handler confirms sharing completion to PersonalAgent A
- PersonalAgent A notifies User A of successful sharing

4. Explicit Consent Path

- If explicit consent is required, Consent Manager creates a consent request
- State Manager stores the pending action in database
- State Manager sends consent request to CareAgent B
- CareAgent B asks User B for consent

5. Consent Response Processing

- User B provides consent response to their agent
- CareAgent B forwards response to State Manager
- State Manager parses the consent response

6. Consent Decision

- If consent granted: State Manager updates action status and grants explicit consent
- Sharing Handler sends information to CareAgent B
- CareAgent B delivers information to User B
- Sharing Handler confirms sharing completion to PersonalAgent A
- PersonalAgent A notifies User A of successful sharing
- If consent denied: State Manager updates action status and denies sharing
- Sharing Handler notifies PersonalAgent A of denial
- PersonalAgent A notifies User A that sharing was denied

Component Roles

- User A: User requesting to share information
- PersonalAgent A: User A's personal AI agent
- Orchestrator: Central decision-making component
- Sharing Handler: Manages information sharing requests
- Consent Manager: Evaluates consent requirements and status
- State Manager: Manages pending consent actions
- Database: Stores consent levels, pending actions, and action status
- User B: User who must provide consent
- CareAgent B: User B's care agent (when User B is in caregiver role)

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Consent Levels

Implied Consent

- Automatic Sharing: Information is shared without explicit permission
- Topic-Based: Consent is implied for specific topics (e.g., medication adherence)
- Relationship-Based: Consent is implied based on relationship (e.g., spouse, primary caregiver)
- Context-Based: Consent is implied based on situation (e.g., emergency situations)

Explicit Consent

- **Permission Required: User must explicitly approve sharing**
- Topic-Specific: Consent is required for specific topics
- Time-Limited: Consent may have expiration dates
- Revocable: User can withdraw consent at any time

No Consent

- Sharing Denied: Information cannot be shared
- Privacy Protection: User's privacy is protected
- Opt-Out: User has explicitly denied sharing

Data Flow

1. Sharing Request: User A's request to share information
2. Consent Check: Evaluation of consent requirements
3. Consent Decision: Implied consent granted or explicit consent required
4. Consent Request: Pending action created (if explicit consent needed)
5. User Response: User B's consent decision
6. Action Execution: Information shared or sharing denied
7. Confirmation: Result communicated to User A

Example Scenarios

Implied Consent Example

- User A: "Share my medication adherence with my doctor"
- System: Checks if User A has implied consent for medication topics
- Result: If implied consent exists, information is shared directly

Explicit Consent Example

- User A: "Share my mental health status with my spouse"
- System: Creates consent request for User B (spouse)
- User B: "Yes, I want to know about their mental health"
- Result: Information is shared with User B

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Consent Denial Example

- User A: "Share my medication adherence with my neighbor"
- System: Creates consent request for User B (neighbor)
- User B: "No, I don't want to know about their medication"
- Result: Information is not shared, User A is notified of denial

7. Agent Communication Patterns

This section explains how different agents communicate with each other (referring to the overall system flow from the main diagram). It shows the patterns of information flow between users and their respective agents.

7.1 Inter-Agent Communication

This section shows the complete communication flow between users and their agents, demonstrating how the system facilitates mediated communication between care circle members.

Communication Flow:

1. **User A Message**: Patient or caregiver sends a message to their agent
2. **Agent Processing**: PersonalAgent or CareAgent processes the message through the orchestrator
3. **Analysis & Decision**: System analyzes the message and decides on appropriate actions
4. **Agent-to-Agent Communication**: Information flows from one agent to another (e.g., PersonalAgent to CareAgent)
5. **User B Notification**: Target user receives mediated information through their agent

Grouped Operations: Analysis, decision, and action are grouped as they represent a single processing phase:

- Analysis + Decision + Action are all part of the same message processing workflow
- Conflict Detection + Mediated Question + Resolution are part of the same conflict resolution workflow




Fig. 43: Inter-Agent Communication Flowchart: a flowchart showing the high-level communication patterns between agents for both standard message processing and conflict resolution.

7.2 Escalation Flow

This section shows the specific escalation process that occurs when the "Critical Events Handler" detects HIGH criticality events, demonstrating how the system ensures urgent health issues reach the right people quickly.

Escalation Process:

1. **Critical Event Detection**: System identifies HIGH criticality health events
2. **Escalation Creation**: Creates escalation record in database
3. **Multi-Channel Notification**: Simultaneously notifies doctor, family members, and updates dashboards
4. **User Confirmation**: Provides feedback to the reporting user
5. **Status Tracking**: Updates system status and logs all actions

Grouped Operations: Notification and logging are grouped as they represent parallel processes:

- Doctor Notification + Family Notification + User Confirmation are part of the same notification workflow
- Escalation Log + Doctor Dashboard + Caregiver Alerts + Status Update are part of the same logging workflow




Fig 44: Escalation Flowchart: A flowchart illustrating the parallel processes of multi-channel notification and system logging that occur after a critical event is detected.




Fig 45: This diagram shows the escalation process when critical health events are detected and need immediate attention from healthcare providers and family members.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Key Interactions

1. Critical Event Detection

- **User** reports a critical health event to their **PersonalAgent**
- **PersonalAgent** forwards the event to the **Orchestrator**
- **Orchestrator** delegates to **Critical Events Handler**

2. Event Analysis and Escalation Creation

- **Critical Events Handler** analyzes the event criticality
- Creates escalation record in database
- Database confirms escalation creation

3. Parallel Notification System

The system simultaneously notifies multiple parties:

Doctor Notification

- **Critical Events Handler** sends urgent notification to **Doctor**
- **Doctor** reviews the critical event
- **Doctor** acknowledges receipt of notification

Family Notification

- **Critical Events Handler** notifies **Family Members**
- **Family Members** review the situation
- **Family Members** acknowledge receipt of notification

Caregiver Alert

- **Critical Events Handler** alerts **Caregivers**
- **Caregivers** review patient status
- **Caregivers** acknowledge receipt of alert

Dashboard Update

- **Critical Events Handler** updates the **Dashboard**
- **Dashboard** displays the critical event
- **Dashboard** confirms the update

4. Status Tracking and Confirmation

- **Critical Events Handler** updates escalation status in database
- Database confirms status update
- **Critical Events Handler** sends escalation confirmation to **PersonalAgent**
- **PersonalAgent** confirms escalation sent to **User**

5. Coordinated Response

- **Healthcare team** coordinates response based on criticality
- **Family and caregivers** provide support and monitoring
- **Dashboard** provides real-time monitoring and tracking

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Component Roles

- **User**: Patient or caregiver reporting the critical event
- **PersonalAgent**: User's personal AI agent
- **Orchestrator**: Central decision-making component
- **Critical Events Handler**: Manages critical event detection and escalation
- **Database**: Stores escalation records and status updates
- **Doctor**: Healthcare provider receiving urgent notifications
- **Family Members**: Family members who need to be informed
- **Caregivers**: Caregivers who need to be alerted
- **Dashboard**: Real-time monitoring and tracking system

Criticality Levels

HIGH Criticality

- **Immediate Escalation**: Bypasses all other logic
- **Multi-Channel Notification**: Doctor, family, caregivers, dashboard
- **Urgent Response**: Requires immediate attention
- **Status Tracking**: Continuous monitoring until resolved

MEDIUM Criticality

- **Standard Escalation**: Follows normal escalation process
- **Selective Notification**: Based on event type and context
- **Timely Response**: Requires attention within reasonable time
- **Periodic Updates**: Regular status updates

LOW Criticality

- **Information Sharing**: Standard information sharing process
- **Optional Notification**: May or may not require notification
- **Routine Response**: Standard care process
- **Basic Tracking**: Minimal status tracking

Data Flow

1. **Critical Event**: User reports critical health event
2. **Event Analysis**: System analyzes event criticality
3. **Escalation Creation**: Escalation record created in database
4. **Parallel Notifications**: Multiple parties notified simultaneously
5. **Status Updates**: Escalation status tracked and updated
6. **Confirmation**: User receives confirmation of escalation
7. **Coordinated Response**: Healthcare team coordinates response

Example Scenarios

Chest Pain Escalation

- **User**: "My chest hurts. I want to talk to my doctor"
- **System**: Detects HIGH criticality for chest pain
- **Escalation**: Doctor notified immediately, family alerted, dashboard updated
- **Response**: Doctor contacts patient, family provides support

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Fall Incident Escalation

- **User**: "A fell down from the 3rd floor!"
- **System**: Detects HIGH criticality for fall incident
- **Escalation**: Emergency services notified, family alerted, caregivers informed
- **Response**: Emergency response coordinated, family provides support

Medication Error Escalation

- **User**: "I think I took the wrong medication"
- **System**: Detects MEDIUM criticality for medication error
- **Escalation**: Doctor notified, family informed, dashboard updated
- **Response**: Doctor provides guidance, family monitors situation

Escalation Tracking

Real-Time Monitoring

- **Dashboard Updates**: Continuous status updates
- **Response Tracking**: Monitor response times and actions
- **Status Changes**: Track escalation status changes
- **Resolution Tracking**: Monitor until issue is resolved

Communication Logs

- **Notification History**: Track all notifications sent
- **Response Logs**: Record responses from healthcare team
- **Status Updates**: Log all status changes
- **Resolution Notes**: Document resolution proces

8. Diagram Navigation Guide

8.1 How to Use This Document

Main Diagram Reference: The main "Message Processing Flow" diagram (Section 3.1) serves as the central reference point. Each subsequent section explains what happens inside specific boxes from this main diagram:

- **Section 3.2**: Explains the red "AI Analysis Handler" box
- **Section 4**: Explains the yellow "Sharing Handler" and "Conflict Handler" boxes
- **Section 5**: Explains the purple "State Manager Check" and "Action Response Handler" boxes
- **Section 6**: Explains the green "Orchestrator" decision logic
- **Section 7**: Shows overall communication patterns between all components

8.2 Color Coding Legend

Throughout all diagrams, colors represent different types of components:

- 🔵 **Blue**: User input and user interactions
- 🟢 **Green**: Orchestration, output, and successful operations
- 🟠 **Orange**: Decision points and command processing
- 🟣 **Purple**: State management and data storage
- 🔴 **Red**: AI processing, critical events, and error states
- 🟡 **Yellow**: Business logic handlers and specialized processors

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

8.3 Component Type Indicators

Each diagram uses emojis to quickly identify component types:

- 👤 **Users**: Human participants in the system
- 🤖 **Agents**: AI conversational entities
- ⚙️ **Handlers**: Business logic processors
- 🧠 **AI Processing**: LLM analysis and decision making
- 📊 **State Management**: Conversation state tracking
- 🎯 **Orchestration**: Central workflow coordination
- 📡 **Output**: Response delivery and notifications

This framework provides a robust foundation for the multi-agent healthcare system, ensuring clear responsibilities, effective communication, and reliable decision-making processes.

*Submission of IPDF soft copy is Mandatory at the time of Patent document submission.

Annexure- I

Illustrated examples for mentioning use case of Product/ Process

1. ***"Classification of Hard and Soft Taps on Capacitive Touch Screen" having application in below mentioned use case:***

   We all use capacitive touch screens, on a series of devices starting with smart watches, smartphones tablets laptops and desktops. The only thing you can do on the present touch screens is to indicate a location, by touching it there. It doesn't matter whether you touch it hard or lightly - the touch is definitely not 3D. iPhone X has atte mpted to introduce this feature (force touch) by including expensive special pressure-sensitive hardware. We adopt a different approach, that requires you to only install an app on the existing device. With this the same touch screen that you have been using now becomes sensitive to at least two levels of pressure, light and heavy. Every other app developer can now exploit this feature and provide more sophisticated user interfaces which can distinguish levels of touch. The possibilities are limited only by the imagination. As the technology matures, a larger number of levels of touch is likely to be supported.

2. ***"Antibacterial Nano breathing Nasal Filter" having application in***

   Many people use face mask for breathing pollution free air, but the main constraint in breathing is decrease in breathing flow rate. The innovation described herein relates to a nasal air filter, and more particularly, the invention relates to a nasal air filter based on nanotechnology for breathing by human beings that has antibacterial feature, which can mimic the natural breathing process i.e. 12-15 lpm and is comfortable to use. The nasal filter will be useful for people living in polluted cities as well persons having allergy and suffering from Asthama & Bronchitis.

3. ***"A method of measuring BMP signaling using BMP responsive reported cell line" having application in***

   Bone Morphogenetic Protein (BMP) signaling is necessary and sufficient for bone formation.

   It is present in several biological samples measurement of which may have diagnostic value. However, at present there is no sensitive method of detecting BMP proteins in a biological sample. In this disclosure we describe creation of a cell line based sensitive and accurate method of estimating BMP proteins in any specimen.

4. ***A unique device for plasma processing to simulating magnetospheres in the laboratory***

   The dipole plasma device would be helpful in industry for plasma processing of samples such as in the semiconductor industry, where energetic electrons (or ions) are required to impinge on a substrate and to bring about desired changes in the substrate such as plasma assisted ion doping, etching, or creation of nanostructures on metallic surfaces, the device would be helpful in understanding the physics of plasmas confined in a magnetic dipole.

5. ***Large area micro-texturing on free-form surfaces using flexible-electrode throughmask electrochemical machining***

   Surface micro-texturing deals the issues pertaining to various fields of engineering for enhancing the essential functions such as tribological, wetting, biocompatibility, sustainability, cleanliness etc. Among all the aforementioned sectors, micro-texturing of free-form large areas is getting huge attention, e.g. micro-textures on artificial biomedical implants enhances sustainability and life cycle by better implant-tissue interface,

cell-adhesion and cell proliferation. Micro-textures on cylindrical surfaces (both internal and external) of bearings, piston rings, hypodermic needles assists in reducing the coefficient of friction and facilitating lubrication.

**This page is for reference purpose, no need to print this page.*