

GENERAL ABSTRACT

Name of work : Construction of New Rural Police Station Building for Perungavalathan Police Station in Thiruvarur District

SI.No.	Qty	Description	Rate	Unit	Amount		
	-	BUILDING WORKS	AS PER	PWD SR	2020-2021		
1	1.00	Rural Poice station Main Building (G + 1)	7253739.33	1 unit	7253739.33		
		SUB - TOTAL - I Rs.			7253739.33		
2		GST at 12.0% (GST at 6% + CGST 6%)			870448.72		
		SUB - TOTAL - II Rs.			8124188.05		
.3		Provision for Soil Investigation	LS		LS		25000.00
		SUB - TOTAL - III Rs.			8149188.05		
4		Labour Welfare fund @ 1.0%	As pr PWD Norms		81491.88		
5		Unforeseen, Contingencies & PS charges @2.5%	As pr PWD Norms		204130.97		
6		Supervision Charges @ 7.5%	-		611189.10		
		SUB - TOTAL - IV Rs.			9046000.00		
7		Advertisement charges	LS	3	25000.00		
8		Provision for EB Deposits	LS		LS		70000.00
9		Provision for planning permission & payment to other department	LS		20000.00		
10		Structural Design / Consultancy charges	LS		25000.00		
		GRAND TOTAL Rs.			9186000.00		

16/2/201

JE

(Algion)

X

DO



GENERAL ABSTRACT

Name of work : Construction of New Rural Police Station Building for Perungavalathan Police Station in Thiruvarur District

SI.No.	Qty	Description	Rate	Unit	Amount		
	-	BUILDING WORKS	AS PER	PWD SR	2020-2021		
1	1.00	Rural Poice station Main Building (G + 1)	7253739.33	1 unit	7253739.33		
		SUB - TOTAL - I Rs.			7253739.33		
2		GST at 12.0% (GST at 6% + CGST 6%)			870448.72		
		SUB - TOTAL - II Rs.			8124188.05		
.3		Provision for Soil Investigation	LS		LS		25000.00
		SUB - TOTAL - III Rs.			8149188.05		
4		Labour Welfare fund @ 1.0%	As pr PWD Norms		81491.88		
5		Unforeseen, Contingencies & PS charges @2.5%	As pr PWD Norms		204130.97		
6		Supervision Charges @ 7.5%	-		611189.10		
		SUB - TOTAL - IV Rs.			9046000.00		
7		Advertisement charges	LS	3	25000.00		
8		Provision for EB Deposits	LS		LS		70000.00
9		Provision for planning permission & payment to other department	LS		20000.00		
10		Structural Design / Consultancy charges	LS		25000.00		
		GRAND TOTAL Rs.			9186000.00		

16/2/201

JE

(Algion)

X

DO

TAMIL NADU POLICE HOUSING CORPORATION LIMITED No: 132 E.V.R. Salai, Kilpauk, Chennai-10.

Memo No: CE/DB/275/2021 Date:19.02.2021.

Sub: TNPHC -HO/DB - SC - Trichy Dn. - Construction of New Rural Police Station building for Perugavalathan in Thiruvarur District - Estimate Technically Sanctioned -Intimation - Regarding.

Ref: SE's Lr.No.DB/SC/363/2021, Dt.09.02.2021

With reference to the above, it is informed that the estimate submitted by the Superintending Engineer / South Circle for the above work is technically sanctioned by the Undersigned for ₹91,86,000/- and registered as CER.No.196/ 2020-2021. Also the above work should be completed within the sanctioned fund and the interest of the organization should be safe guarded while awarding the above work.

The Superintending Engineer/South Circle is requested to depute a person to this office to take a copy of the above estimate.

The receipt of the memo should be acknowledged

Yours faithfully,

for Chief Engineer/TNPHC

To
The Superintending Engineer/South Circle
TNPHC Ltd, Madurai.

wal21222

Copy to the Executive Engineer / Trichy Dn. TNPHC Ltd., Trichy.

CE/DB / 275 /2021

TAMIL NADU POLICE HOUSING CORPORATION LIMITED No. 132 EVR Salai, Kilpauk, Chennai – 600 010.

Technical Sanction Slip

Name of work: Construction of New Rural Police Station Building for Perungavalathan Police Station in Thiruvarur District

Perungavarathan Tonce Station in				
A.S. for Buildings	-	₹ 91.86	Lakhs	
G.O.Ms.No.553 Home (Police –X) Dept, Dt:31.12.2020		₹	Lakhs	
Total		₹ 91.861	_akhs /	
Total Administrative Sanction		₹ 91.86	Lakhs	
Estimate Sanctioned so for	-	₹	Lakhs	
	-	₹ 91.86	Lakhs	
Technically sanctioned for Rs. 91, 86, 000 One lakes and Eighty Only) Only) and register Only JE HDO	Si red in C		96 12020 - 2021	



Name of work : Construction of New Rural Police Station Building for Perungavalathan Police Station in Thiruvarur District

Inir	uvarur District			
No. Description	Rate (M Sand)	Unit	Main building	(G+2)
			Qty	Amount
1.1 Earth work excavation in all soils (including infil	ling)			
a. 0 to 2 mt.	177.	77 /Cum.	168.000	29865.36
2.1 Filling sand	2090.	60 Cum.	31.800	66481.08
3 1 C.C.1:5:10 for Foundation & Basement	4874.	34 Cum.	13.000	63366.42
6.5 Brick work in C.M. 1:5 (F& B) using Kiln Burnt Co of size 22 x 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4")	intry bricks 6000.	77 Cum.	38.600	231629.72
9.5 Brick work in C.M. 1:6 using Kiln Burnt Country size 22 x 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4")	y iricks of			
a. In Ground Floor	5990	.37 Cum.	66.300	397161.53
b. In First Floor	6109	.67 Curn.	26.100	159462.39
c. In Second Floor	6228	.97 Cum.	19.600	122087.81
10.5 Brick partition work in C.M. 1:4 Kiln Burnt Count size 22 x 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4") 110 m	ry broks of nm * . (B.P.)	/		
b. In Ground Floor	714	1.50 Sqm.	50.000	35725.00
c. In First Floor	72	7.62 Sqm.	92.600	67377.61
d. In Second Floor	74	0,74 Sqm.	26.600	19703.68
11.5 Brick work in C.M. 1:4 Kiln Burnt Country briks 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4") 70 mm tk 3.P	of size 22 x .)			
a. In Ground Floor	48	2.64 Sqm.	14.200	6853.49
b. In First Floor		0.99 Sqm.	12.600	6186.47
c. In Second Floor	. 49	9,34 Sqm.	3.800	1897.49
12.1 Brick partition in C.M. 1:4 using country brick x11x5cm 50 mm thick				
a. In Ground Floor	3:	53.55 Sqm.	7.400	2616.27
b. In First Floor		59.52 Sqm.	9.000	3235.68
c. In Second Floor	3	65.49 Sqm.	9.000	3289.41
13.1 Filling with Excavated Earth		29.30 Cum.	53.50	1567.55
21.2 Teak wood Wrought & Put up				
a. T.W. over 2 m & below 3 m	1218	75.00 Cum.	0.243	29615.63
b. T.W. below 2 m length.	1096	75.00 Cum.	0.101	11077.18
23.3 S&F of Magnetic door catches		52.00 Each	10.000	520.00
24.0 Manufacturing & supply of steel /indows (Weigh	nt basis)	61.50 Kg.	2007.000	123430.50
25 0 M.S Holdfast		9.60 Each	- 1.000	518.4
26.0 Flooring in C.C.1:5:10	41	74.34 Cum	10.000	48743.4
The second secon		-		1

Ren 1	
(50)	
-	

	11-11	Main building	
1.00	Rate Unit	Ar	nount
I. No. Description	(M Sand)	Qty	1217.71
	. cam	2.900/	9711.52
20 mm tk	419.90 Sqm	26.000	14801.89
28.0 Floor plastering in C.M. 1.4, 20 mm tk.	373.52 Sqm.	4.300	368084.22
30.0 Ellispattern	3442.30 Cum.	1761.000	9669.15
31.0 Weathering course	209.02 Sqm.	45.000	
33.0 Plastering in C.M. 1:5, 12 mm tk.	214.87 Sqm.	384.000	90236.16
34.0 Plastering in C.M. 1:4, 12 mm tk.	234.99 Sqm.		- 1
35.0 Spl. Ceiling plastering in C.M. 1:3,			5183.36
10 mm tk.	C123 Rmt	80.700	3349.05
10 mm tk. 36.0 Cement mortar Border in C.M. 1:5, 12 mm tk.	64.20	. 80.700	
a. 150 mm wide	41.07	80.700	2486.37
b. 75 mm wide	30.81 Rmt	384.000	13493.76
c. 50 mm wide	35.14 Sqm.	602.000	32809.00
37.1 White washing 3 coats (slaked)	54.50 Kg.	69.000	13633.02
39.0 M.s Grills	197.58 Sqm.	135.800	15936 13
40.0 Painting - New "wood work"	117.35 Sqm.	6.400	371.20
41.0 Painting - New "iron work"	58.00 Rmt		380.00
46.0 S & F 20 mm dia Alu. Hanger Rod	95.00 Each	4.000	440.00
47.0 S & F Alu Towel rail 75 cm long	55.00 Each	8.000	
48.0 S & F 5 pin Coat stand	1.50 Each	44.000	66.00
49.0 S & F chromium plated 8 guage Picture Hook	1	5.000	2065.70
50.3 Supply and planting avenue trees	410.0	5.000	3788.15
	757.63 Each	1.000	15795.99
50.4 Providing Tree guard 50.5 Supplying. Fabricating and erection of M.S Scheme Name	15795.99 Each	1.000	
50.5 Supplying. Fabricating and eresting board			
52.0 PVC Water supply (ASTM)	209.32 Rmt	30.000	6279.60
a, 32 mm dia	1	89.000	17138.73
b. 25 mm dia	192.57 Rmt	9.000	1449531
59.5 Gully Trap using Kiln burnt country bricks 22 x 11 x 7 cm.	1610.59 Each		1230 30
60.0 PVC Nahani trap (4way/2way)	136.70 Each	9.000	1250
Electrical arrangements	129.00 Each	13.000	1677.0
69.0 15 Amp. Power plug	/	20.000	678.0
72.0 Box type Fibre Fan hook	33.90 Each	1.000	4017.0
73.10 6 way - D.B. Ao16 - 11	4017.00 Each		9340.0
74.0 Charges for fixing of "Fan"	467.00 - Each	20.000	315.
76.0 8 SWG wire	21.00 Rmt	15.000	836
77.3 S&F of TV/Telephone line Socket	76.00 Each	11.000	-
77.4 S&F of 20mm dia PVC pipe for TV/Telephone line	72.01 Rmt	65 000	4680
78.0 Earthing Station IS3043 (Type I)		1.000	2588
10.0 Letting Glebot 195045 (Type I)	2588.00 Each		99207

No. Description	Rate (M Sand)	Unit	Main building	j (G+2)
			Qty	Amount
81.0 Meter cupboard	2211.57	Sqm	0.700	1548.10
86.0 Anti termite treatment	34.00	Sqm.	168.000	5712.00
12.0 S & F of Exsaust Fan 300 mm dia	1919.00	Each	6.000	11514.00
ANNEXURE	/			
14.1 Precast Cupboard slab 20 mm tk.using standardised concrete mix M20 (annexure)				
a. In Ground floor	1166.67	Sqm.	27.000	31500.09
b. In First floor	1170.24	Sqm.	21.000	24575.04
c. In Second floor	1173.81	Sqm.	6.000	7042.86
14.II Precast cupboard slab 40 mm tkusing standardised concrete mix M20 (annexure)				
a. In Foundation & basement	1305.48	Sqm.	6.500	8485.62
4.1 Standardised concrete Mix M20 Grade Concrete				
a. In Foundation and basement	7506.43	Cum	35.900	269480.84
8.1 b. Ground Floor	7596.33	Cum	41.300	313728.43
c. In First Floor	7773.33	- Cum	33.200	258074.56
d. In Second Floor	7950.33	- Cum	23.500	186832.76
Plastering with CM 1:3, 12mm with WPC	232.99	_ Sqm	35.300	8224.55
Supplying and filling with Gravel	736.69	Cum	58.200	42875.36
18.1 Formwork using M.S.Sheet				
a.For Column footings,plinth beam,Grade beam,Raftbeam,Raft slab etc.,	664.30	Sqm	159.200	105756.56
b.Plain surfaces such as Roof slab,floorslab,Beams,lintels,lofts,sill slab,staircase,portico slab and other similar works	751.65	Sqm	848.000	637399.20
c.For Square and rectangular columns and small quantities	901.98	Sqm	315.700	284755.09
d.Vertical wall .	826.82	Sqm	27.700	22902.91
e.Circular column	1803.96	Sqm	13.000	23451.48
21.6 R.C.C.Door frames of size 100 x 75mm with one edge grocves size 't' x 20 mm using M20 grade (with out vibrating charges)	I			
a. 900 x 2100 mm	2217.470	Each	4.000	8869.88
c. 1000 x 2100 mm	2235.920	Each	8.000	17887.36
d. 750 x 2100 mm	2186.470	Each	1.000	
T.W. frame & TW styles & rails with BWR double leaf shutters for cup board/ ward robes including two coat enamel paint & one coat primer.	3849.810	Sqm	37.800	2186.4 145522.8
TW double leaves shutter of size with brass fittings a 1800 x 2100mm For PS	5361.17	Sqm	3.400	18227.

Sl. No. Description Rate (M Sand) Main builtiffing (4*2) Amount TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 1000 x 2100 mm TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 1000 x 2100 mm TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 1900 x 2100 mm TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 1900 x 2100 mm TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 1900 x 2100 mm TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 750 x 2100 mm TV styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 750 x 2100 mm 28.28.00 Sqm 11.500 32522 7 Sqm 21.5.2 Supply and Fixing Saild UPVC door Shutter with frame 28.28.00 Sqm 50.300 34616 8 Sqm 22.2.1 4mm thick pin headed Glass panels with Aluminum beedings 28.8 Glazed lifes using Grout (Tile Joint Filler) 28.8 Glazed lifes using Grout (Tile Joint Filler) 1016.55 Sqm 26.100 26564 1 Sqm 29.8 Glazed with exement for new walls and other similar works. 46.40 Sqm 1060.000 115324 Sqm 26.100 26564 1 Sqm 26.100 26762 1 Sqm 26.100 2744 N 27560 1 Sqm 2756	(54)			ala.	g (G+2)
St. No. Description (M Sand)				Main bulldin	
Same		Rate	Unit	7,014	amount
TW styles & rails with 9mm thick BVR single leaf shutters with brass across size of 1000 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters with brass across size of 900 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters with brass across size of 900 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters with brass across size of 750 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters with brass across size of 750 x 2100 mm 21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 22.2.1 4mm thick pin headed Glass panels with Aluminium beedings 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler). 1016.56 Sqm 26.100 26584.43 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 1016.56 Sqm 1600.000 51304.07 38.6 One cost white cement for new walls and other similar works. 48.40 Sqm 1600.000 51304.07 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) 68782.50 MT 14.725 10128223 or 10128223 or 10128223 or 10128223 or 10128223 or 1012823 or	SI. No. Description	(M Sand)		OW.	M. A. Company of the Company
TW styles & rails with 9mm thick BUVR single leaf shutters with brass screws size of 1000 x 2100 mm TW styles & rails with 9mm thick BUVR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BUVR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BUVR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BUVR single leaf shutters with brass screws size of 1750 x 2100 mm TW styles & rails with 9mm thick BUVR single leaf shutters with brass screws size of 1750 x 2100 mm 21.52 Supply and Fising Solid UPVC door Shutter with frame 223.2.1 4mm thick pin headed Glass panels with Aluminium beedings 28.6 Glazed tiles using Grout (Tile Joint Filler) 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 38.6 One cost white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304 to 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) 43.1 Fabrication of Mild steel / RTS grills (without cement sturry) 58.7 Fabrication of Mild steel / RTS grills (without cement sturry) 58.7 Fabrication of Mild steel / RTS grills (without cement sturry) 58.7 Fabrication of Mild steel / RTS grills (without cement sturry) 58.8 Fabrication of Mild steel / RTS grills (without cement sturry) 58.8 Fabrication of Mild steel / RTS grills (without cement sturry) 58.7 Fabrication of Mild steel / RTS grills (without cement sturry) 58.7 Fabrication of Mild steel / RTS grills (without cement sturry) 58.8 Fabrication of Mild steel / RTS grills (without cement sturry) 58.8 Fabrication of Mild steel / RTS grills (without cement sturry) 58.8 Fabrication of Mild steel / RTS grills (without cement sturry) 58.8 Fabrication of Mild steel / RTS grills (without cement sturry) 58.9 Fabrication of Mild steel / RTS grills (without cement sturry) 58.9 Fabrication of Mild steel / RTS grills (without cement sturry) 58.9 Fabrica				ALL THE CONTROL OF TH	529346
### TW styles & rails with 9mm thick BIVR single leaf shutters with brass screws size of 1000 x 2100 mm TW styles & rails with 9mm thick BIVR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BIVR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BIVR single leaf shutters with brass screws size of 750 x 2100 mm TW styles & rails with 9mm thick BIVR single leaf shutters with brass screws size of 750 x 2100 mm TW styles & rails with 9mm thick BIVR single leaf shutters with frame 2828.00 Sqm			- Sam	16.800	
with brass screws size of 1000 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters with brass screws size of 750 x 2100 mm TW styles & rails with 9mm thick BVR single leaf shutters 3683.20 Sqm 11,500 32522m 21,52 Supply and Fixing Solid UPVC door Shutter with frame 2828.00 Sqm 50,300 34616.60 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 1016.56 Sqm 26.100 25584.40 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 1016.56 Sqm 1060.000 513040 38.6 One coat white cement for new walfs and other similar works. 48.4.01 Sqm 1060.000 513040 43.0 Fabrication of Mild steel / RTS grills (without cement sfurry) 107.10 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.6 Sqm 108.000 513040 43.0 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.7 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.7 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.7 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.7 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.7 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 108.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 109.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 109.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 109.8 Fabrication of Mild steel / RTS grills (without cement sfurry) 109.8 Fabrication of Mild steel / RTS grills (without cement sfurry)	The state of soils with 9mm thick BWR single leaf shutters	3150.	87 5411	1 1 1 1 1 1 1 1 1	0.4000
TW styles & rails with firm thick BWR single leaf shutters with brass screws size of 900 x 2100 mm TW styles & rails with emm thick BWR single leaf shutters with brass screws size of 750 x 2100 mm TW styles & rails with emm thick BWR single leaf shutters with brass screws size of 750 x 2100 mm 21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 2828.00 Sqm 50.300 34616.e. 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 38.6 One cost white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304.ft 43.0 Fabrication of Mild steel RTS grills (without cement slurry) 43.0 Fabrication of Mild steel RTS grills (without cement slurry) 43.0 Fabrication of Mild steel RTS grills (without cement slurry) 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 188.78 Rmt 36.000 6832.61 walls) 53.4 SSF of C.I Manhole cover 60 x 60 cm (50kg weight) 53.4 SSF of C.I Manhole cover 60 x 60 cm (50kg weight) 54.5 SVR pipe (Soli line) with ISI mark - type 'B'. a. 10 mm dia. 55.4 Supplying Laying & Concealing the S0mm dia PVC (SWR) pipe with ISI mark (bye 'B'). 36.5 Uving with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 55.1 Wing with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 56.1 Wing with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 56.1 Wing with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 56.1 Wing with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 57.5 Cook Sqm 11.500 Sqm 11	with brass screws size of 1000 x 2100 mm		,	7 600/	24803.5
TW styles & rails with 9mm thick BWR single leaf shutters with briass screws size of 900 x 2100 mm TW styles & rails with 9mm thick BWR single leaf shutters with briass screws size of 750 x 2100 mm 21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 2828.00 Sqm 50.300 34616.42 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 28.8 Glazed tiles using Grout (Tile Joint Filler) 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 38.6 One coat white cement for new walls and other similar works. 43.0 Fabrication of Mild steel / RTS grills (without cement situry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement situry) for all sizes of rods. 44.6 FVC SWR 100 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in walls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 83.9 FVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. b. 75 mm dia. 54.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 134.00 Each 250.00 2744 No. 2506.00 Each 25	William of the Control of the Contro	-252	sa Sam	1.00	
with brass screws size of 900 x 2100 mm TW styles & rails with 6mm thick BWRs single leaf shutters with brass screws size of 750 x 2100 mm 21.5.2 Supply and Fixing Soild UPVC door Shutter with frame 2828.00 Sqm 50.300 34618 4 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.8 Glazed tiles using Grout (Tile Joint Filler) 1016.56 Sqm 77.500 111553 8 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 43.0 Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.76 Rmt 36.000 6832.61 walls) 53.4 S&F of C. I Manhole cover 60 x 60 cm (50kg weight) Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662.91 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. b. 75 mm dia. 58.4 Supplying, Laying & Concessing the S0mm dia PVC (SWR) pipe with ISI mark type - B' with relevant specials. Wiring with 1.5 sgmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 61.1 Uring with 1.5 sgmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 61.1 Uring with 1.5 sgmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 61.1 Uring with 1.5 sgmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 63.1 PVC SWR pipe (Soil Iming) with ISI mark confirming IS: 63.1 Syring with 1.5 sgmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 63.1 Syring with 1.5 sgmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 63.1 Syring with 1.5 sgmm PVC insulated sin	TW styles & rails with 9mm thick BWR single leaf shutters	3263.0	/		E000
TW styles & rails with emm thick BWR single leaf shutters with brass screws size of 750 x 2100 mm 21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304.6; 43.0 Fabrication of Mild stee! / RTS grills (without cement slurry) for all sizes of rods. 43.0 Fabrication of Mild stee! / RTS grills (without cement slurry) for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in walls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.0; Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662.51 Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662.51 Wiring with 1.5 sgmm PVC insulated single core multi strand fire retardant flow per capital with ISI mark confirming IS: 694:1990.6 Ordinary) a. Light point without ceiling rose 1344.00 Each 2.000 2744.00 55.1 Wiring with 1.5 sgmm PVC insulated single core multi strand fire retardant flow copper cable with ISI mark confirming IS: 694:1990.6 ordinary) a. Light point without ceiling rose 1344.00 Each 2.000 2744.00 55.1 Wiring with 1.5 sgmm PVC insulated single core multi strand fire retardant flow copper cable with ISI mark confirming IS: 694:1990.6 ordinary) a. Light point without ceiling rose 1344.00 Each 2.000 2744.00 55.1 Wiring with 1.5 sgmm PVC insulated single core multi strand fire retardant flow copper cable with ISI mark confirming IS: 695.000 Each 2.000 2744.00 55.1 Wiring with 1.5 sgmm PVC insulated single core multi strand fire retardant flow copper cable with ISI mark confirming IS: 695.000 Each 3.000 7518.00 55.1 Wiring with 1.5 sgmm PVC insulated single core multi stra	with brass screws size of 900 x 2100 mm			1.600	5093 1
TVX styles & rails with 9mm thick BWR single leaf shutters with brass screws size of 750 x 2100 mm 21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 2828.00 Sqm 21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 2828.00 Sqm 50.300 34616 sg 50.300 25584 sg 29.8 Glazzed tiles using Grout (Tile Joint Filler) 1018.55 Sqm 26.100 25584 sg 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 38.6 (One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304 tr 38.6 (One coat white cement for new walls and other similar works. 43.0 Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in walls) 53.4 SSF of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2943.82 Each 6.000 35550 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - B' with relevant specials. Wirting with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark fire relardant flexible copper cable with ISI mark confirming IS: 68.1 Single with 1.5 sqmm PVC insulated single core multi strand fire relardant flexible copper cable with ISI mark confirming IS: 68.1 Single with 1.5 sqmm PVC insulated single core multi strand fire relardant flexible copper cable with ISI mark confirming IS: 68.1 Single with 1.5 sqmm PVC insulated single core multi strand fire relardant flexible copper cable with ISI mark confirming IS: 68.1 Single with 1.5 sqmm PVC insulated single core multi strand fire relardant flexible copper cable with ISI mark confirming IS: 68.1 Single with 1.5 sqmm PVC insulated single core multi strand fire selardant flexible copper cable with ISI mark		3683.2	o sqm	/	
21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 1144.14 Sqm 97.500 1115538; 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 1018.56 Sqm 26.100 265844; 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 513040; 43.0 Flabrication of Mild steel / RTS grills (without cement slurry) 10 for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water 20 down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully conseated in walls) 53.4 SSF of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3658.00 Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17682 st 58.3 PVC SWR pipe (Soli line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 st 58.4 SUpplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark bype - B with relevant specials. 81.20 Rmt 9.000 73.05 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 1344.00 Each 2.000 2744 for retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 2.000 2744 for retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 2.000 2744 for retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 2.000 2744 for retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 3.000 7516 for retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 3.000 7516 for retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516 for retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516 for retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516 for retardant flexible copper cable w	TW styles & rails with 9mm thick BWR single leaf shutters	10		1.5-0.51	225224
21.5.2 Supply and Fixing Solid UPVC door Shutter with frame 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler) 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304.07 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 44.4 EVC With 10 mm dia with ISI mark type- A for Rain water 305.34 Rmt 305.00 305.34 Rmt 305.00 305.34 Rmt 305.00	with brass screws size of 750 x 2100 mm			11.500	323220
23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304 (X) 43.0 Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 35.000 6832 (X) walls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656 (X) Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662 (X) 58.3 PVC SWR pipe (Soil Iline) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 (SWR) pipe with ISI mark type - 3 with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 634:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point. Wiring with 1.5 sqmm PVC insulated single core multi strand GS4:1990 for Fan point.	24.5.2 Sweets and Fixing Solid LIBVC door Shutter with frame	2828.0	o Sqm		
23.2.1 4mm thick pin headed Glass panels with Aluminium beedings 1144.14 Sqm 97.500 111553 & 26.100 26584 & 26.100 26.100 26584 & 26.100 26584 & 26.100 26.	21.5.2 Supply and Fixing Solid OFVC door Strates with the same		02/202	50.300	3461645
29.8 Clazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304.0; 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304.0; 43.0 Fabrication of Mild stee! / RTS grills (without cement slurry) 68782.50 MT 14.725 1012822.3; 43.0 Fabrication of Mild stee! / RTS grills (without cement slurry) 68782.50 MT 14.725 1012822.3; 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832.6; walls) 53.4 SF of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.0; Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662.9; 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670.4; b. 75 mm dia. 610.45 Rmt 69.900 42670.4; b. 75 mm dia. 610.45 Rmt 9.000 75.600 37622.3; Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 (Ordinary) a. Light point with ceiling rose 1340.00 Each 2.000 37632.0° b. Light point with ceiling rose 1340.00 Each 2.000 2744.0° 55.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 67.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 148.400 Each 20000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.0000 27960.00000 27960.0000 27960.0000 27960.0000 27960.00000 27960.00000 27960.00000	22.2.4.4 mm thick his boarded Glass panels with Aluminium beedings	688.2	o Sqm		SH
29.8 Glazed tiles using Grout (Tile Joint Filler) 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304.07 43.0 Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rots. 44.6 FVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe (Tiley SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe (Tiley SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe (Tiley Consealed in walls) 53.4 SBF of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.07 Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662.51 58.3 FVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670.45 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 64.1990 (Ordinary) a. Light point with ceiling rose 1344.00 Each 2.000 37632.07 55.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Fan point. 67.5 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Staircase Light Point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694.1990 for Staircase Light Point.	23.2.1 4mm thick pin headed Glass panels wat room			07 500	111553 65
29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304 ft. 48.90 Sqm 1060.000 10686 ft. 48.90 Sqm 10 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832 ft. walls) 53.4 S8F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656 ft. Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662 ft. 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 ft. b. 75 mm dia. 497.65 Rmt 75.600 37622 ft. pipe with ISI mark type - B' with relevant specials. 497.65 Rmt 9.000 730 ft. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 (Ordinary) a. Light point with ceiling rose 1340.00 Each 2.000 2744 ft. I Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 81 mark confirming IS: 1398.00 Each 2.000 2744 ft. I Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 81 mark confirming IS: 450.00 Each 2.000 2746 ft. I Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 81 mark confirming IS: 450.00 Each 2.000 2746 ft. I Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 81 mark confirming IS: 450.00 Each 3.000 7518 ft. I Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.		1144.1	4 Sqm	. 97.500	
29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler). 38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.000 51304 (f) 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 35.000 6832 (f) 48.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832 (f) 48.6 PVC SWR 110 mm dia size 50 x 400 mm 2943.82 Each 6.000 17662 (f) 48.7 PVC SWR pipe (Soil line) with ISI mark - type 'B'. 48.8 PVC SWR pipe (Soil line) with ISI mark - type 'B'. 48.9 PVC SWR pipe (Soil line) with ISI mark - type 'B'. 48.10 mm dia. 610.45 Rmt 69.900 42670 (f) 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. 497.65 Rmt 75.600 37622 (f) 49.000 730 (f) 40.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 58960 (f) 40.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 58960 (f) 40.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 Fach 44.000 58960 (f) 40.000 7744 (f) 40.000 Fach 44.000 Fach 44.000 58960 (f) 40.000 Fach 44.000 Fach 44.	29.8 Glazed tiles using Grout (Tile Joint Filler)		Cam	26.100	26584 47
38.6 One coat white cement for new walls and other similar works. 48.40 Sqm 1060.0001 51304 0; 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) 68782.50 MT 14.725 1012822.31 43.0 Fabrication of Mild steel / RTS grills (without cement sturry) 68782.50 MT 14.725 1012822.31 44.6 FVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 35.000 10686.52. 44.6 FVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 35.000 10686.52. 52.4 20mm dia FVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832.03 walls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.00 Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662.91 58.3 FVC SWR pipe (Soli line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670.45 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type 'B' with relevant specials. 497.65 Rmt 75.600 37622.45 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 (Ordinary) a. Light point with ceiling rose 1340.00 Each 28.000 37632.01 b. Light point with ceiling rose 1340.00 Each 20.000 2744.02 c. Calling bell point with Buzzer/Calling bell 1372.00 Each 20.000 2744.02 694:1990 for Fan point. 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 694:1990 for Staircase	29.9 Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler).	1018.5	5 Sqm		/E
38.6 One coat white cement for new walls and other similar works. 43.0 Fabrication of Mild steel / RTS grills (without cement slurry) 68782.50 MT 14.725 1012822.31 for all sizes of rods. 43.0 Fabrication of Mild steel / RTS grills (without cement slurry) 68782.50 MT 35.000 10686.51 for all sizes of rods. 44.6 FVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe (fully consealed in 189.78 Rmt 35.000 6832.03 kg/lb) 52.4 20mm dia FVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832.03 kg/lb) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.01 kg/lb) 54.3 FVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 45 kg/lb) 55.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with eailing rose 1344.00 Each 28.000 37632 concerning the supple with ISI mark confirming IS: 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 66.1 Wiring with 1.5 sqmm PVC i			Sam	1060.000	51304.00
43.0 Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rods. 44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832 Grant walls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.00 Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662 Grant walls) Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662 Grant walls 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 Grant walls with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose 1340.00 Each 44.000 58950 Crant Grant fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 (Ordinary) 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand feet the copper cable with ISI mark confirming IS: 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	38.6 One coat white cement for new walls and other similar works.	48.40	Sqiii		· Carrie
43.0 Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rods. 46.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in 189.78 Rmt 36.000 6832 Gradualls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.00 Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662 St 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 St b. 75 mm dia. 497.65 Rmt 75.600 37622 St 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose 1340.00 Each 44.000 58950 N 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 (ordinary) 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 67.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.			NAT T	14.725	101282231
44.6 PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in walls) 53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight) Wash Hand Basin of size 550 x 400 mm Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17652 si 58.3 PVC SWR pipe (Soil tine) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 si 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 (Ordinary) a. Light point without ceiling rose b. Light point without ceiling rose 1340.00 Each 1372.00 Each 20.000 2744 co 27960 co Wiring with 1.5 sqmm PVC insulated single core multi strand fee retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand feet retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand feet retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand feet retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand feet retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand feet feet copper cable with ISI mark confirming IS: 696.00 Each 3.000 7518 columns for the copper cable with ISI mark confirming IS: 696.00 Each 3.000 7518 columns for the copper cable with ISI mark confirming IS: 696.00 Each 3.000 7518 columns for the copper cable with ISI mark confirming IS: 696.00 Each 3.000 7518 columns for the copper cable with ISI mark confirming IS: 696.00 Each 3.000 7518 columns f		68782.50	1011		,
44.6 PVC SWR 10 mm dia with ISI mark type- A for Rain water down fall pipe 52.4 20mm dia PVC water supply ASTM pipe (fully consealed in walls) 53.4 SSF of C.I Manhole cover 60 x 60 cm (50kg weight) 85.3 SSF of C.I Manhole cover 60 x 60 cm (50kg weight) 85.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 730 SS. PVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 7518 OVC SWR pipe (Soil line) with ISI mark type 'B'. 81.20 Rmt 9.000 7518 OVC SWR pipe (Soil line) with ISI mark type	for all sizes of rods.			35,000	10686 0
S2.4 20mm dia PVC water supply ASTM pipe (fully consealed in walls) 189.78 Rmt 36.000 6832.03		305.34	Rmt	35.000	10000.5.
Wash Same					***************************************
S3.4 S8F of C.I Manhole cover 60 x 60 cm (50kg weight) 1828.00 Each 2.000 3656.00		189.78	Rmt	36.000	6832.03
Wash Hand Basin of size 550 x 400 mm 2943.82 Each 6.000 17662 91 58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. 610.45 Rmt 69.900 42670 42 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990. (Ordinary) a. Light point with ceiling rose b. Light point with uith ceiling rose 1340.00 Each 1372.00 Each 28.000 37632 60 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	(walls)	_			-
58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. b. 75 mm dia. 610.45 Rmt 69.900 42670 42 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose b. Light point with ceiling rose 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	53.4 S&F of C.I Manhole cover 60 x 60 cm (50kg weight)	1828.00	Each	2.000	3656.00
58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'. a. 110 mm dia. b. 75 mm dia. 610.45 Rmt 69.900 42670 42 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose b. Light point with ceiling rose 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.				/	/
a. 110 mm dia. b. 75 mm dia. 497.65 Rmt 75.600 37622 34 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 1398.00 Each 2000 27960 00 Each 2000 27960 00 Each 2000 7518 00 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	Tradition Desir of Size 330 X 400 mm	2943.82	Each	6.000	17662.92
b. 75 mm dia. 610.45 Rmt 69.900 42670 25 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point without ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	58.3 PVC SWR pipe (Soil line) with ISI mark - type 'B'.				1900
b. 75 mm dia. 610.45 Rmt 69.900 42670 25 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point without ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	a 110 mm dia				
b. 75 mm dia. 58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multistrand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point. 65.1 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 1340.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 20.000 2744 00 66.1 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7516.00 Wiring with 1.5 sqmm PVC insulated single core multistrand figer	a. Tromin dia.	610.45	Rmt	69.900	4267045
58.4 Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials. Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose b. Light point with out ceiling rose c. Calling bell point with Buzzer/Calling bell 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS:	b. 75 mm dia.				42010
Social Supplying, Laying & Concealing the 50mm dia PVC (SWR) St. 20 Rmt 9.000 730 80	59 (10	497.65	Rmt	75.600	37622 34
Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark a. Light point with ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 1344.00 Each 28.000 37632 00 1372.00 Each 2.000 2744 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 1398.00 Each 20.000 27960 00 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	pine with ISI mark has a ISI with 50mm dia PVC (SWR)	94.20			- The state of
confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 1340.00 Each 28.000 37632 00 1372.00 Each 2.000 2744 00 694:1990 for Fan point. 1398.00 Each 20.000 27960 00 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	with relevant specials.	01.20	Rmt	9.000	730 80
confirming IS: 694:1990.(Ordinary) a. Light point with ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 1340.00 Each 28.000 37632 00 1372.00 Each 2.000 2744 00 694:1990 for Fan point. 1398.00 Each 20.000 27960 00 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point.	Wiring with 1.5 sqmm PVC insulated single core multi-				1
a. Light point with ceiling rose b. Light point without ceiling rose c. Calling bell point with Buzzer/Calling bell 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS:	strand fire retardant flexible copper cable with ISI mark				
b. Light point without ceiling rose 1340.00 Each 44.000 58960 00 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 2506.00 Each 3.000 7518.00 Wiring with 1.5 sqmm PVC insulated is mark confirming IS:	Comming is: 694:1990.(Ordinary)				
b. Light point without ceiling rose 1340.00 Each 44.000 58960 00 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 2506.00 Each 3.000 7518.00 Wiring with 1.5 sqmm PVC insulated is mark confirming IS:	a. Light point with ceiling ross	1			
ic. Calling bell point with Buzzer/Calling bell 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 694:1990 for Staircase Light Point. 695:1000 Each 20.000 27960 000 2506.00 Each 3.000 7518 000		1040			
c. Calling bell point with Buzzer/Calling bell 1344.00 Each 28.000 37632 00 65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 1398.00 Each 20.000 2744 00 27960 00 66.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 2506.00 Each 3.000 7518 00 Wiring with 1.5 sqmm PVC insulated is mark confirming IS:	b. Light point without ceiling rose	1340.00	Each	44,000	58960 00
65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 694:1990 for Staircase Light Point. 1372.00 Each 2.000 2744 00 27960 00 27		1344 00			00000
65.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Fan point. 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 694:1990 for Staircase Light Point. 1372.00 Each 2.000 2744 00 27960 00 27	c. Calling bell point with Buzzer/Calling bell	.014.00	Each	28.000	3763200
68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 1398.00 Each 20.000 27960 00 27960 00 Staircase Light Point. 2506.00 Each 3.000 7518.00	65 1 Wiring with 4 5	1372.00	Feet		
68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand 694:1990 for Staircase Light Point. 1398.00 Each 20.000 27960 00 27960 00 Staircase Light Point. 2506.00 Each 3.000 7518.00	fire retardant flexible copper cable with the		cach	2.000	2744.00
68.1 Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: Wiring with 1.5 sqmm PVC insulated single core multi strand 2506.00 Each 3.000 7518.00	1990 for Fan point.	1398.00	Each		New Comments
Wiring with 1.5 sqmm PVC insulated in Confirming IS: 2506.00 Each 3.000 7518.00/	68.1 William 111			20.000	27960
Wiring with 1.5 sqmm PVC insulated in Confirming IS: 2506.00 Each 3.000 7518.00/	fire retardant flexible copper and a single core multi-				-
fire rote 1.5 sqmm PVC insulated	1990 for Staircase Light Poles	2506.00			
fire role 1.5 Sqmm PVC insulated	William	35.00	Each	3.000	7518.00/
Board Itself. 694:1990 for 5 amps 5 pin plug socket point @ Switch 688.00 Each 15.000 10320 00	fire retardant to symm PVC insulated single	100			1,50,000
Goard Itself. Go	694:1990 for 5 among copper cable with ISI mark				
15.000 10320.00)	soard Itself. sinps 5 pin plug socket point @ confirming IS:	688.00	Each	The same of the same of the same	01
	- Switch	_	-4611	15.000	10320.00
				500	

19
3
-

SI No.	Description	Rate (M Sand)	Unit	Main building (G+2)
				Qty A	mount
fir 69	Firing with 1.5 sqmm PVC insulated single core multi strand e retardant flexible copper cable with ISI mark confirming IS: 94:1990 for 5 amps 5 pin plug socket point @ Convenient laces.	932.00	Each	16.000	14912.00
	upply and delivery of 48" (1200 mm) Fan with ISI mark with letronic Dimmer	1284.00	Each	20,000	25680.00
5	tun of 2 Wires of 4 sqmm PVC insulated single core multi trand fire retardant flexible copper cable with ISI mark onfirming IS: 694:1990.	219.00	. Rmt	57.500	12592.50
s	Run of 2 Wires of 2.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.	187.00	Rmt	62.000	11594.00
	4 x 4 Sq mm copper PVC insulated unsheathed single core cable for 3 phase EB service connection	221.00	Rmt	30.000	6630.00
	Rain water harvesting using defunct borewell and providing perforated cover slab (M20)				
	a). Providing pit	2020.70	Each	4.000	8082.80
	b) Augering 30cm dia	429.95	Rmt	16.000	6879.20
344.2	S&F of Bevelled edge mirror 500 x 400 x 5.5mm	375.700	Each	6.000	2254.20
71.2	Supplying and fixing of 32 AMPS Triple pole main switch	2007.000	Each	2.000	4014.00
80.1	450 x 375 x 20 mm thick TW plank	1170.000	Each	4.000	4680.00
	3 Nos. of 32Amps - Fuse Unit	725.000	Each	2.000	1450.00
87.1	Supplying and delivery of Three phase ELCB/RCCB	2870.000	Each	1.000	2870.00
-	Plastic Emulsion PAINT including primer for outer walls	190.31	Sqm	732.000	139306.92
38.4.1	Two coat of OBD over one coat white cement for inner walls	98.77	Sqm	1060.000	104696.20
448.2	Providing PVC Tee with end cap	109.75	Each	6.000	658.50
	Granite Tiles flooring (Ruby red) for PS	1428.42	Sqm	78.300	111845.29
	Providing wooden Melamine polish for new wood work	1204.68	Sqm	8.600	10360.25
	Vitrified Tiles flooring (Ivory)	1093.72	Sqm	131.900	144261.67
	Concrete designer tiles flooring	1269.56	Sqm	84.800	107658.69
	Supply & Fixing of MS door (for lockup door)	†*****************			
	MS door of Size 1000 x 2100mm (D2)	7463.70	each	2.000	14927.40
	Supply & Fixing of MS ventilator of size (lockup)	,	-		
	MS ventilator of size 1200 x 600 mm	3386.7	Sqm	1.500	5080.19
	MS Ventilator of Size 900 x 750mm	3548,7	4 Sqm	0.700	2484.12
	MS Ventilator of Size 600 x 600mm	4038.1	4 Sqm	0.400	1615.26
	Finshing the top of Terrace floor with one course of solar reflective Ceramic tiles with base concrete	1468.0	7 Sqm.	160.200	235184.81
-	UPVC Non Pressure pipe of SN8 SDR 34 (S 16.5) as per IS 15328/2003		1		1
-	a. 110 mm UPVC Non Pressure pipe	347.5	2 Rmt	49.000	17028.48

	à	-	-	
Po	Ş,	t	7	
1 %	r,	ь	1	

SI. No.	Description	Rate Unit (M Sand)	Main build	ing (G+2)
			Qty	Amount
	b. 160 mm UPVC Non Pressure pipe	574.83 Rmt	30.000	17244
	PVC Specials as per IS 10124/1982 Part II			
	a. 110 mm dia PVC bend (TWAD SR 20-21 P-19 S.No-4)	160.00 Each	2.000	320
	b. 160 mm dia PVC bend (TWAD SR 20-21 P-19 it-1.5, S.No-4)	510.00 Each	2.000	1020
	PVC Equal Tee as per BIS 7834/1975			
i	a. 110 mm dia PVC Equal tee(TWAD SR 20-21 P-19 S.No-9)	199.00 Each	2.000	398
	b. 160 mm dia PVC Equal tee(TWAD SR 20-21 P-19 S.No-9)	339.00 Each	. 2.000	678.
	S & F of Indian Water closet white glazed (Oriya type) of size 580 x 440mm with PVC SWR grade ' P' or "S' trap - in G.F.	2869.96 Each	2.000	5739.
27	S & F of Indian Water closet white glazed (Oriya type) of size 580 x 440mm with PVC SWR grade ' P' or "S' trap- Other than G.F.	4578.69 Each	2.000	9157.
	S & F of E.W.C. (White) 500 mm with PVC SWR grade "P" or "S" TRAP	6100.30 Each	2.000	12200.6
	S & F of 15mm dia half turn CP long body tap	452.00 Each	6.000	2712.0
	S & F of 15mm dia half turn CP short body tap	404.00 Each	8.000	3232.0
	9 watts LED bulb qtn	81.00 Each	28.000	2268.0
	18 watts LED Tube Light	635.00 Each	27.000	17145.0
-	Bulk Head fitting suitable for 12 watts for LED Bulb Supply and Fixing 25W LED Street light	462.00 Each	15.000	6930.00
- 10-14	Supply & fixing of 12 watts LED light (Qtn)	2991.00 Each	6.000	17946.0
	Supply and fixing of 20 A	170.00 Each	15.000	2550.00
10	enclosure with 32 A DP MCB in Flush with wall with earth connection (For AC Plug) Legrand (MDS) / Hager(L& T) Equivalent/ Superior variety Elec SD -140 /2020-21	1830.00 Each	2.000	3660.0
	Total			
	1912 221 0 1203			7253739.33

Po

16/03/30y

HD3/2/21

O.L.

SE/South Circle. Agt. No. 18/2021-2022

FILE No. DB/SC/363/2021

REPORT ACCOMPANYING SLIP FOR LUMPSUM AGREEMENT (FOR OFFICE USE ONLY)

TAMILNADU POLICE HOUSING CORPORATION LTD., SOUTH CIRCLE, MADURAI – 625 014.

NAME OF PROJECT : Announcem

Announcement made by the Hon'ble Chief Minister of Tamil Nadu during the Police

demand held on 24.03.2020

NAME OF WORK :

Construction of New Rural Police Station

building for Perugavalanthan Police Station in

Thiruvarur District X

ESTIMATE AMOUNT

₹. 91,86,000/-

ESTIMATE No.

CER No.196/2020-2021

ESTIMATE AMOUNT PUT IN TENDER

₹.81,24,187.95 (2020-2021)

(with GST @12%)

TENDER VALUE (with GST) : ₹.75,40,465.5

LESS AMOUNT

(-) ₹. 5,83,722.43

LESS PERCENTAGE

(-) 7.18%

TENDER ACCEPTED BY WHOM

The Chairman and Managing Director,

TNPHC Ltd., Chennai-10

NAME OF THE CONTRACTOR

Thiru. A. VELANI

No. OF ITEMS IN THE AGREEMENT

109 (One hundred and nine only)

No. OF PAGES IN THE AGREEMENT

106 (One hundred and six only)

No. OF CORRECTIONS IN THE AGREEMENT

.

145 (One hundred and forty five only)

SUPERINTENDING ENGINEER SOUTH CIRCLE, TNPHC LTD.,

//RPAD//

DB/F/01

TAMILNADU POLICE HOUSING CORPORATION LTD.,



(Government of Tamil Nadu Undertaking)
(ISO 9001-2015 CERTIFIED COMPANY)

SOUTH CIRCLE

No.1 Inspector Quarters, TSP 6th Battalion Campus, New Natham Road, Madurai - 625 014. email id: sesemdutnphcl@gmail.com

Phone: 0452 - 2538035 0452 - 2903019



Er.S.JAYAKUMAR B.E., Superintending Engineer

Lr.No.DB/SC/363/2021(2)

Date:18.06.2021

APPENDIX - HC NOTICE

To

Thiru. A. Velani, No:10A, Narikudi, Thondi(P.O) Thiruyadanai Taluk, Ramanathapuram district -623409

Sir,

Sub: TNPHC Ltd., - South Circle - Trichy Division - Construction of New Rural Police Station Building for Perugavalanthan Police Station in Thiruvarur District., - Tender accepted - Work order issued - Regarding.

Ref: 1) Your Tender dated: 22.03.2021

2) Your letter No.Nil Dated:27.05.2021

Your tender for the above work for a total value of ₹.75,40,465.52 (Rupees Seventy five lakhs forty thousand four hundred and sixty five and paise fifty two only) (Including GST @12%) has been accepted.

I request you to remit a sum of ₹.1,00,200/- (Rupees One lakh and two hundred only) towards the Security Deposit in addition to E.M.D. which will be retained as part of the Security Deposit amount for the due fulfilment of contract and to execute the agreement on stamp paper to a value of Rs.100.00 within one week. This written agreement between you and the Corporation will be the foundation of rights of both the parties and contract is not deemed to be completed until the agreement is first signed by you and then the officer authorise to enter into contract on behalf of the Corporation. You are also requested to remit the balance of the Security Deposit amount in the form of DD/NSC/KVP drawn in favour of the Executive Engineer/TNPHC Ltd.,/ Trichy Division.

Failure on your part to comply with the above requirements will entail it the cancellation of contract and forfeiture of your tender deposits.

Superintending Engineer, South Circle/TNPHC Ltd.,

Copy submitted to the CE/TNPHC Ltd.,/Chennai - 10 with reference to the

CE's memo No.CE/DB/275/2021 Dated: 14.06.2021

The Executive Engineer/TNPHC Ltd., Trichy Division, Trichy -12

SE/South Circle-102

15