SCHEDULE - A

NAME .VORK: SPECIAL REPAIR WORKS FOR THE OFFICE BUILDING OF DEPUTY INSPECTOR GENERAL OF POLICE AT RAMANATHAPURAM RANGE IN RAMANATHAPURAM DISTRICT

S.NO	QUANTITY 2	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS 4	UNIT IN FIGURES AND IN WORDS 5	AMOUNT 6
1	1243.80 Sq.M.	THOROUGH SCRAPPING OF OLD PLASTERED SURFACE AND WASHING OF PLASTERED SURFACE WITH SOAP, SODA AND WATER (OR WITH SODA LIME, BRUSH AND WATER) INCLUDING THE COST REQUIRED TOOLS AND PLANTS AND SCAFFOLDING IF NECESSARY AND CLEARING THE DEBRIS AWAY FROM SITE ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		1.Sq.M. (ONE SQUARE METRE)	4975.20
			No.		
2	202.00 Sq.M.	WHITE WASHING TWO COATS FOR OLD WALL USING CLEAN SHELL LIME SLAKED INCLUDING COST OF LIME, GUM, BLUE, BRUSHES, INCLUDING SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS.		1.Sq.M. (ONE SQUARE METRE)	7070.0
3	1.10 Cu.M.	BRICK WORK IN CM 1:5 (ONE OF CEMENT AND FIVE	Rs.6500.00	1.Cu.M.	7150.0
	A.	OF CRUSHED STONE SAND) USING KILN BURNT	(Rupees six thousand and five hundred only)	(ONE GUBIC METRE)	A
4		BRICK WORK IN CEMENT MORTAR 1:6 (ONE OF			
		CEMENT AND SIX OF CRUSHED STONE SAND) USING KILN BURNT COUNTRY BRICKS OF SIZE 8%"X4½"X2½" (22X11X7CM) FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDINGS, CURING ETC., COMPLETE IN ALL RESPECT COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.			
	0.30 Cu.M.	(a) IN GROUND FLOOR	√ Rs.7000.00	1.Cu.M.	2100.0
	1/2	(a) in Grooting (Eddin	(Rupees seven thousand only)	(ONE CUBIC METRE)	~ 1°
5	192.30 Sq.M.	CLEAN REMOVAL OF DAMAGED CEMENT PLASTERED SURFACE WITHOUT AFFECTING THE ADJACENT STRUCTURES, INCLUDING THE COST OF REQUIRED TOOLS AND PLANTS AND SCAFFOLDING IF NECESSARY AND CLEARING THE DEBRIS AWAY FROM THE SITE ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		1.Sq.M. (ONE SQUARE METRE)	1730.7
6	560.50 Sq.M.	PAINTING THE NEW WALLS WITH TWO COATS OF OIL BOUND DISTEMPER OVER THE EXISTING PRIMING COAT OF WHITE CEMENT OF APPROVED BRAND OVER NEW CEMENT PLASTERED WALL SURFACES INCLUDING COST OF PAINTS, PUTTY, BRUSHES, WATERING, CURING, ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (PAINTS AND ITS SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	(Rupees one hundred and thirty only)	1.Sq.M. (ONE SQUARE METRE)	72865.0
	N. BUILD	91			95890.9

Q. dury)

NO. OF CORRECTIONS

NO	QUANTITY	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN	UNIT IN FIGURES	
1	2	3	FIGURES AND IN WORDS 4	AND IN WORDS	TAUC
7	416.90 Sq.M.	The state of the s	Rs.240.00 (Rupees two hundred and forty only)	1.Sq.M. (ONE SQUARE METRE)	100056.0
8	64.60 Sq.M.	SPECIAL CEILING PLASTERING IN CEMENT MORTAR 1:3 (ONE OF CEMENT AND THREE OF CRUSHED STONE SAND) 10MM THICK FOR BOTTOM OF ROOF, STAIR, WAIST, LANDING AND SUNSHADES IN ALL FLOORS FINISHED WITH NEAT CEMENT INCLUDING HACKING THE AREAS, PROVIDING BAND CORNICE, SCAFFOLDING, CURING ETC., COMPLETE.	(Rupees two hundred and eighty	1.Sq.M. (ONE SQUARE METRE)	18411.0
9	33.20 Sq.M.	WHITE WASHING THREE COATS FOR EXISTING CLEANED CEILING SURFACES USING CLEAN SHELL LIME SLAKED INCLUDING COST OF LIME, GUM, BLUE, BRUSHES, INCLUDING SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS.	(Rupees forty five only)	1.Sq.M. (ONE SQUARE METRE)	1494.0
10	151.90 Sq.M.	PLASTERING WITH CM 1:5 (ONE OF CEMENT AND FIVE OF CRUSHED STONE SAND) 12MM THICK FINISHED WITH NEAT CEMENT INCLUDING PROVIDING BAND CORNICE, CEILING CORNICE, CURING, SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS AND COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	(Rupees two hundred and fifty six only)	1.Sq.M. (ONE SQUARE METRE)	38886.
11	0.08 Cu.M.	DISMANTLING CLEARING AWAY AND CAREFULLY STACKING MATERIALS USEFUL FOR RE-USE OF REINFORCEMENT CEMENT CONCRETE WITHOUT AFFECTING THE ADJACENT STRUCTURES, INCLUDING THE COST OF REQUIRED TOOLS AND PLANTS AND SCAFFOLDING IF NECESSARY ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	(Rupees two only)	1.Cu.M. (ONE CUBIC METRE)	0.
12	5.30 Sq.M.	DISMANTLING CLEARING AWAY AND CAREFULLY STACKING MATERIALS USEFUL FOR RE-USE OF CONCRETE MOSAIC-IN-SITU FINISH IN CEMENT MORTAR IN FLOORING AND IN WALL SURFACE	(Rupees fifty only)	1.Sq.M. (ONE SQUARE METRE)	265.
	Y		×	X .	
					255003

NO. OF CORRECTIONS

AND .	QUANTITY	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	AMOUNT
1	2	3	FIGURES AND IN WORDS 4	AND IN WORDS 5	6 255003.4
13	16.60 Sq.M.	SUPPLYING AND LAYING OF CERAMIC TILES (ANTI SKID) OF BEST APPROVED QUALITY FOR FLOORING AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE	(Rupees one thousand four hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	24070.0
	5.7	ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF CRUSHED STONE SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY, POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF TILES SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).	-	4	
14	7.90 Sq.M.	SUPPLYING AND FIXING OF COLOUR GLAZED TILES	Pc 500.00	1.Sq.M.	2050 (
14	7.90 34.11.	OF BEST APPROVED QUALITY (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT PLASTERING IN CM 1:2 (ONE OF CEMENT AND TWO OF	(Rupees five hundred only)	(ONE SQUARE METRE)	3950.0
		CRUSHED STONE SAND) 10MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY, POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF TILES SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).	*		
15	9 NOS.	SUPPLYING AND FIXING OF 9 WATTS LED BULB OF		1.NO.	1080.0
	×	BEST QUALITY INCLUDING COST OF MATERIAL AND FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY OF THE 9 W LED LAMP SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	only)	(EACH)	p.
16	10 NOS.	SUPPLYING AND FIXING OF 12 WATTS LED BULB FOR	Rs.150.00 ×	1.NO.	1500.0
	- 🔥	BULK HEAD FITTINGS OF BEST QUALITY INCLUDING COST OF MATERIAL AND FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICED SITE OF THE 12 WATTS LED LAMP SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	only)	(EACH)	37
17	35 NOS.	SUPPLYING AND FIXING OF 4'18 WATTS CRYSTAL LED TUBE LIGHT AND FIXING THE TUBE LIGHT	(Rupees eight hundred and forty	1.NO. (EACH)	29400.0
		FITTINGS ON TEAK WOOD ROUND BLOCKS OF 75MM DIA OR 40MM DEEP SUSPENDED FROM CEILING OR MOUNTED ON THE WALL INCLUDING COST OF ALL MATERIALS AND LABOUR FOR FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE ENTIRE TUBE LIGHT FITTINGS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	X		• \
					315003.
12-4	N. BUILD	EDS			0.5000

NO. OF CORRECTIONS

				1.1	
ò	all a rua	Neu les	DICent Poles	a Rangontuparan Ran	Bu

S.NO	QUANTITY	DESCRIPTION OF WORK	DATE		PAGE 1
1		3	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS 4	UNIT IN FIGURES AND IN WORDS 5	Гипо
18		SUPPLYING AND DELIVERY OF FOLLOWING ELECTRIC CEILING FAN WITH ISI MARK WITH BLADES AND DOUBLE BALL BEARING. CAPACITOR, ETC., COMPLETING WITH 300MM DOWN ROD, CANOPIES, CAPACITOR SHACKLE BLADES WITH ELECTRONIC DIMMERS SUITABLE FOR OPERATION ON 230 VOLTS 50 HT. SINGLE PHASE AC SUPPLY CONFORMING TO ISS NO.374/79 AND PROVIDED WITH INSULATION, (THE BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE SUPPLY MADE).	D E R Z		6 31500
	12 NOS.	(a) 48" ELECTRIC FAN 1200MM SWEEP	Rs.1100.00	1.NO.	
	×		(Rupees one thousand and one hundred only)	(EACH)	13200
			× ×		
19	12 NOS.	CHARGES FOR ASSEMBLING AND FIXING OF CEILING	Rs.200.00	1.NO	
	* X	FAN OF DIFFERENT SWEEP WITH NECESSARY CONNECTIONS AND FIXING OF FAN REGULATOR ON		(EACH)	2400
		THE EXISTING BOARD ETC., ALL COMPLETE (EXCLUDING COST OF FAN)	11	13	7)
20	1 NO.	SUPPLYING AND FIXING EWC (WHITE) SUPERIOR	Rs.7500.00	1.NO.	7500
	χ	VARIETY 500MM WITH PVC SWR GRADE 'P' OR 'S' TRAP INCLUDING COST AND FIXING OF DOUBLE FLAPPED PLASTIC SHEET COVER PVC FLUSHING CISTERN IN APPROPRIATE LEVEL AS DIRECTED BY THE	(Rupees seven thousand and five hundred only)	(EACH)	7500.
		DEPARTMENTAL OFFICERS AT A MAXIMUM LEVEL OF 5'6" AND OF APPROVED BRAND OF 10 LITRES CAPACITY INCLUDING FITTINGS SUCH AS CI BRACKETS, PVC CONNECTION GM WHEEL VALVE, HEX NIPPLE, ETC., COMPLETE (EWC AND PLASTIC COVER SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE FIXING).		4	2-)
11	3 NOS.				
		SUPPLYING AND FIXING OF PORCELIN WASH HAND F BASIN (WHITE WITHOUT PEDESTAL), SUPERIOR (VARIETY OF SIZE 550X400MM WITH ALL ACCESSORIES	Rs.4000.00 Kupees four thousand only)	1.NO. (EACH)	12000.0
	4	VARIETY OF SIZE 550X400MM WITH ALL ACCESSORIES SUCH AS POWDER COATED CAST IRON BRACKETS, 32MM DIA C.P. WASTE COUPLING, RUBBER PLUG AND ALUMINIUM CHAIN, 32MM DIA 'B' CLASS G.I. PVC WASTE PIPE, ANGLE VALVE, 15MM DIA NYLON CONNECTION, 15MM DIA BRASS NIPPLES, 15MM C.P. PILLAR TAP & REQUIRED GRATING ETC., COMPLETE IN ALL RESPECTS (WASH HAND BASIN SHALL BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE FIXING).	-\	1	.eY=
2	1118.30 KG.	SUPPLYING AND FIXING THE STATE OF THE STATE	V		
	iX (SUPPLYING AND FIXING MILD STEEL GRILLS AS PER RITHE DESIGN APPROVED TO VERANDAH ENCLOSURE OR GATE INCLUDING ONE COAT OF PRIMER AND LABOUR FIXING IN POSITION ETC. ALL COMPLETE.	s.5.00 Rupees five only)	1.KG. (ONE KILOGRAM)	5591.5
		ALL COMPLETE,	X	4	4
G.N.	. BUILDE	RS			355004.00
					355694.96
ĵ	BUILDE			1	

Jan O' and a manual destroyers

NO. OF CORRECTIONS

SUPERINTENDING ENGINEER/SOUTH CIRCLE.

CONTRACTOR

NC	QUANTITY	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN	LINUT IN SIGNE	
1	2	3	FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	TNUOMA
		·	4	5	6 355694.9
			V		000004.0
23	7.90 Sq.M.	PROVIDING AND FIXING OF FACTORY MADE UNPLASTICIZIED POLYVINYL CHLORIDE (UPVC) DOOR	Rs.4900.00	1.Sq.M.	38710.0
		FRAME OF SIZE 50X47MM WITH A WALL THICKNESS OF	hundred only)	(ONE SQUARE METRE)	
2		SMM, MADE OUT OF EXTRUDED 5MM RIGID UPVC FOAM SHEET, MITERED AT TWO CORNERS AND JOINED WITH	**	~	1/-
		2 NOS OF 150MM LONG BRACKETS OF 15X15MM M.S SQUARE TUBE. THE TWO VERTICAL AND HORIZONTAL			
		DOOR PROFILES ARE TO BE REINFORCED WITH 19X19MM M.S SQUARE TUBE OF 19 GAUGES WITH	× /		
		PRIMER COAT, THE DOOR FRAME SHALL BE FIXED TO THE WALL USING 65MM/100MM LONG M.S SCREW			
		THROUGH THE FRAME BY USING PVC FASTENERS, A			
		MINIMUM OF 4 NOS, SCREWS TO BE PROVIDED FOR EACH VERTICAL MEMBER AND MINIMUM 2 NOS, FOR	F.		
		HORIZONTAL MEMBER ETC., PROVIDING AND FIXING OF 30MM THICK FACTORY MADE DOOR SHUTTER WITH			
		UNPLASTICIZED POLYVINYL CHLORIDE (UPVC) SOLID PANEL FOAM SHEET, STRUCTURED WITH M.S.TUBE OF			
		19 GAUGE THICKNESS AND SIZE 19MM X 19MM FOR			
		STYLES AND 15MM X 15MM FOR TOP RAIL AND BOTTOM RAIL. PANELLING OF 5MM THICK UPVC ONE SIDE			
		PRINTED LAMINATION SINGLE SHEET TO BE FITTED IN THE M.S.FRAME WELDED / SEALED TO THE STYLES AND			
		RAILS COVERED WITH 5MM THICK HEAT MOULDED UPVC 'C' CHANNEL OF 30MMX50MM AND 5MM THICK			
		75MM WIDE UPVC SHEET FOR TOP RAIL, LOCK RAIL AND BOTTOM RAIL ON EITHER SIDE AND 10MM (5MM X 2			
		NOS.) THICK, 20MM WIDE CROSS UPVC SHEET AS GAP INSERT FOR TOP RAIL AND BOTTOM RAIL, AND JOINED			
		TOGETHER WITH PVC SOLVENT CEMENT ADHESIVE.			
		AN ADDITIONAL 5MM THICK UPVC STRIP OF 20MM WIDTH IS TO BE STUCK ON THE INTERIOR SIDE OF THE			
		C CHANNEL USING PVC SOLVENT CEMENT ADHESIVE, THE COST AND LABOUR CHARGES FOR FIXING OF 3		-	
		NOS. 4" SS BUTT HINGES AND ALUMINIUM FURNITURE FITTING SUCH AS 1 NO. 4" TOWER BOLT, 1 NO.5"			
		ALDROP, 2 NOS. 6" FLAT 'D' TYPE HANDLE, ETC ARE			
		INCLUDED. THE FITTING PROVIDED SHALL BEAR ISI MARKS, TO ENSURE THE GENUINITY OF PRODUCT, THE			
		DOOR SET SHOULD HAVE 4 NUMBERS OF MANUFACTURER'S LOGO HOLOGRAM OF APPROVED			
		BRAND, EACH AT FRAME, STYLE, RAIL AND INNER PANEL, (THE QUALITY AND BRAND OF DOOR SHUTTER			
		AND FURNITURE FITTINGS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)			
4		SUPPLYING AND FIXING OF BEST INDIAN TW SINGLE			
:		LEAF PANELLED DOOR SHUTTERS USING 9 MM THICK PHENOL BONDED BWR GRADE PLYWOOD			
		AS PER IS 303-1989 (GENERAL) WITH IS 5539-1969 (FOR PRESERVATIVE TREATMENT AND IS 848 -1974 (FOR			
		ADHESIVES) WITH RELEVANT IS SPECIFICATION AND ITS LATEST AMENDMENTS FOR SHUTTERS WITH			
		75MMX37,50MM TEAK WOOD STYLES AND 3 NOS. OF 150X37,50 MM TW RAILS (TOP, BOTTOM AND LOCK			
		RAILS) USING THE ABOVE PANELS INCLUDING LABOUR			
		CHARGES AND COST OF ALUMINIUM FURNITURE FITTINGS AS PER SCHEDULE 'E' WITH BRASS SCREWS			
		AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE QUALITY OF BWR GRADE PLYWOOD AND			
		ALUMINIUM FURNITURE FITTINGS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE			
		USC).			
	3.80 Sq.M.	SUITABLE FOR DOOR OF SIZE	Rs.4400.00	1.Sq.M.	16720.0
	1	(a) 900 X 2100MM	(Rupees four thousand and four	(ONE SQUARE	10720,0
	54\.		hundred only)	METRE)	1
1	\$ \$600 X 2 2 2 2 200	72.50	7	~\	
G.N	I. BUILE	ERS		-	44440
	Λ.				411124.9

NO. OF CORRECTIONS

S.NO	QUANTITY	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS 4	UNIT IN FIGURES AND IN WORDS 5	Contract of the second
1	Z	3	4		411124.96
25	41.00 Sq.M.	SUPPLYING AND FIXING UPVC (UN-PLASTICIZED POLYVINYL CHLORIDE) WINDOWS OF CASEMENT TYPE (OPEN) FROM THE PROFILE THE SIZE OF OUTER FRAME 60MM X 58MM AND SHUTTER PROFILE ARE REINFORCEMENT WITH GI/1MM 125GSM AND 100% CORROSION FREE, THE PROFILES ARE MULTI CHAMBERED SECTIONS WITH WALL THICK OF 2MM. THE EPDM RUBBER (BLACK COLOUR) COVERED WITH OVER ALL THE EDGES OF FRAME AND SHUTTER THE SHUTTER WILL BE PROVIDED WITH ESPAG MULTI POWER POINT LOCKS AND ALSO IT OPERATES AS HANDLE. THE CORNERS AND JOINTS SHOULD BE WELDED AND CLEANED. RADIATIONS FREE PIN HEADED PLAIN OR BROWN COLOUR GLASS 4MM THICK SHOULD BE PROVIDED TO THE SHUTTER AND IT SHOULD NOT ALLOW LEAKAGE OF WATER EVEN AT MOST RANGING STORMS AND SHOULD HAVE KEY LOCKABLE ACTION, SECURITY PROTECTIVE HINGES, STRONG LOCKING SYSTEMS AND AS PER SIZE FOR ARRESTING NOISE AND ENERGY LOSS. THE CONNECTING MECHANISM BETWEEN SASH AND OUTER FRAME THAT ENABLES OPENING OF THE WINDOW. THE WINDOW SHOULD BE FIXED TO THE	(Rupees nine thousand two hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	379250.00
26	1.50 Sq.M.	WALL WITH 100% PACKING WITH SCREWS AND SILICON PACKING ALL ROUND THE FRAMES, (THE WINDOW SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE ON WORK) SUPPLYING AND FIXING UPVC (UN-PLASTICIZED POLYVINYL CHLORIDE) LOUVERED VENTILATORS OF FROM THE PROFILE THE SIZE OF OUTER FRAME 60MM X 58MM AND SHUTTER PROFILE SIZE OF 60 X 78MM BOTH PROFILES ARE REINFORCED WITH GI/IMW 125GSM AND 100% CORROSION FREE, THE PROFILE ARE MULTI CHAMBERED SECTIONS WITH WALL THICK OF 2MM. THE EPDM RUBBER (BLACK COLOUR) COVERED WITH ALL OVER THE EDGES OF FRAME AND SHUTTER, THE CORNERS AND JOINTS SHOULD BE WELDED AND CLEANED, RADIATIONS PIN HEADED GLASS 4MM THICK SHOULD BE PROVIDED IN THE LOUVERS, THE WINDOW SHOULD BE FIXED TO THE WALL WITH 100% PACKING WITH SCREWS AND SILICON PACKING ALL ROUND THE FRAMES, THE VENTILATOR SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE ON WORK	Rs.9900.00 (Rupees nine thousand and nine hundred only)	1.Sq.M. (ONE SQUARE METRE)	14850.00
27	2 NOS.	SUPPLYING AND FIXING OF INDIAN WATER CLOSET WHITE GLAZED (ORIYA TYPE) OF SIZE	(Rupees four thousand only)	1.NO. (EACH)	8000.0
	580MMX440MM OF APPROVED MAKE WITH IS BE GOT APPROVED FROM THE EXECUTIVE BEFORE USE) WITH PVC SWR GRADE P C INCLUDING CONCRETE PACKING, FILLING WITH EARTH, FLOORING THE AREA WITH 7 BRICK JELLY CONCRETE IN CC 1:8:16 (ONE C EIGHT OF CRUSHED STONE SAND AND S BRICK JELLY) USING 40MM SIZE BRICK JELL LEFT ROUGH TO RECEIVE THE FLOOR PLAST INCLUDING ANTISYPHONAGE CONNECTION ETC. ALL COMPLETE AND AS DIRECTEI	BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE) WITH PVC SWR GRADE P OR S TRAF INCLUDING CONCRETE PACKING, FILLING PORTION WITH EARTH, FLOORING THE AREA WITH 75MM THICK BRICK JELLY CONCRETE IN CC 1:8:16 (ONE OF CEMENT EIGHT OF CRUSHED STONE SAND AND SIXTEEN OF BRICK JELLY) USING 40MM SIZE BRICK JELLY AND TOF LEFT ROUGH TO RECEIVE THE FLOOR PLASTERING BUT INCLUDING ANTISYPHONAGE CONNECTION, CURING ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (IN GROUND FLOOR)	X		d
or G.	N. BUILC	ERS			813224.9

NO. OF CORRECTIONS

	3	operative pair works pressure for the			PAGE - 7
5.NO	QUANTITY 2	DESCRIPTION OF WORK 3	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS 4	UNIT IN FIGURES AND IN WORDS 5	AMOUNT 6
28	7.30 Sq.M.	SUPPLYING, FABRICATING AND FIXING IN POSITION OF ALUMINIUM PARTITION WITH BOTTOM 2/3 PANELED 12MM THICK NOVAPAN	(Rupees eight hundred only)	1.Sq.M. (ONE SQUARE METRE)	813224.96 5840.00
	1	SHEET AND TOP 1/3 PLAIN GLASS 5.5MM THICK TO SUIT AGAINST THE PARTITION WALL. THE OUTER FRAME TOP AND BOTTOM USING RECTANGULAR BOX SECTION NO.9221 OF SIZE 101.50X44.450X2MM AT WEIGHT OF 1.975 KG/M VERTICAL AS WELL AS HORIZONTAL USING RECTANGULAR BOX SECTION NO.9222 OF 63.50X38.10X2MM AT WEIGHT OF 1.174 KG/M WITH ACCESSORIES INCLUDING COST OF MATERIALS RUBBER BEEDING "I" ANGLE REQUIRED CHROMIUM PLATED SCREWS ETC., AND POWER CONSUMPTION CHARGES REQUIRED FOR FABRICATION INCLUDING MAKING NECESSARY HOLES IN THE COLUMNS, BEAMS, MASONRY WITH POWER DRILL TO THE REQUIRED EXTENT AND REDOING THE MASONRY TO ORIGINAL CONDITIONS AFTER FIXING ETC., COMPLETE THE ALUMINIUM SECTION ANODIZIED WITH MATT FINISH UNDER ELECTRICALLY CONTROLLED CONDITIONS IN ACCORDANCE WITH IS SPECIFICATION 1863/1963 FOR ANODIC FILM THICKNESS OF NOT 15 MICRONS ALL THE CLIPS. (THE QUALITY AND BRAND OF THE MATERIALS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE IN WORK)			
			V		
29	3 NOS.	SUPPLYING AND FIXING OF 300 MM DIA SWEEP AC EXHAUST FAN OF APPROVED ISI QUALITY INCLUDING NECESSARY WALL OPENING, FIXING AND FINISHING THE WALL OPENING AND MAKING GOOD INCLUDING COST OF MATERIALS, LABOUR FOR FIXING, CHIPPING	(Rupees two thousand and three hundred only)	1 NO. (EACH)	6900.00
		AND REDOING NECESSARY INTER CONNECTION, SCAFFOLDING, HIRE CHARGES FOR TOOLS AND PLANTS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY OF THE 300 MM DIA SWEEP AC EXHAUST FAN SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	.4		
30	31.50 Sq.M.	SUPPLYING, FABRICATING, ERECTING AND	Rs.2100.00	1.Sq.M.	66150.00
	1	FIXING GYP BOARD FALSE CEILING UPTO A CEILING HEIGHT OF 4.5M FROM FLOOR LEVEL USING PLAIN SHEETS (10MM THICK) USING G.I PERIMETER CHANNEL OF SIZE 0.55MM THICK (HAVING ONE FLANGE OF 20MM THICK ANOTHER FLANGER OF 30MM AND WER	(Pungos two thousand and and	(ONE SQUARE METRE)	66150.00
		OF 27MM) ALONG WITH PERIMETER OF CEILING, SCREWS, FIXED BRICK WALL / PARTITION / RCC WORK WITH THE HELP OF NYLON SLEEVES AND SCREWS AT 610MM CENTRE TO CENTRE. THEN SUSPENDING G.I INTERMEDIATE CHANNELS OF 45MM (0.90MM THICK WITH TWO FLANGES OF 15MM EACH) FROM THE SOFFITS AT 1220MM CENTRE TO CENTRE WITH CEILING ANGLE OF WIDTH 25X10X0.55MM THICK FIXED TO SOFFITS WITH G.I CLEAT AND STEEL EXPANSION FASTENERS CEILING SECTION OF SIZE 0.55MM THICK HAVING KNURLED WEB OF 51.50MM AND TWO FLANGES OF 26MM EACH WITH LIPS OF 10.50MM ARE FIXED TO THE INTERMEDIATE CHANNEL WITH THE HELP OF CONNECTING CLIPS IN DIRECTION PERPENDICULAR FIXED TO THE INTERMEDIATE CHANNEL WITH THE HELP OF CONNECTING CLIPS IN DIRECTION PERPENDICULAR FIXED TO THE INTERMEDIATE CHANNEL WITH THE HELP OF CONNECTING CLIPS IN DIRECTION PERPENDICULAR TO THE INTERMEDIATE CHANNEL AT 457MM CENTER 10MM THICK TAPERED EDGE CALCIUM SILICATE BOARD DESIGNED AND PERFORATED (CONFIRMING TO IS 2035-1982) SCREW			
		FIXED TO CEILING SECTION WITH 25 MM DRY WALL SCREWS @ 230 MM CENTERS SCREW FIXING IS DONE MECHANICALLY EITHER WITH SCREW DRIVER OR DRILLING MACHINE WITH SUITABLE ATTACHMENT ETC ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICER. (THE MATERIALS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE).			
For	G.N. BUIL	DERS		/	
100		The time I Villy			

NO. OF CORRECTIONS

Special repair works DIG of Police of Ramanalegon on Range

					PAGE . 8
S,NO	QUANTITY	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	SUN IN
1	2	3	4	5	6 892114.9
31	6 NOS.	SUPPLYING AND FIXING OF 18W LED 3000K SQUARE TYPE RECESSED FITTING WITH LED INCLUDING COST OF MATERIALS AND LABOUR CHARGES ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAND OF THE MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	(Rupees nine hundred and fifty only)	1 NO. (EACH)	5700.0
32	59.50 Sq.M.	PAINTING THE NEW IRON WORK AND OTHER SIMILAR WORKS SUCH AS PVC / ASTM PIPES, KERB STONE AND GRILLS WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT OF APPROVED QUALITY AND BRAND, THE PAINT SHOULD BE SUPPLIED BY THE CONTRACTOR AT HIS OWN COST, (THE QUALITY AND THE BRAND OF PAINT SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE) COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS,	(Rupees one hundred and forty five only)	1.Sq.M. (ONE SQUARE METRE)	8627.5
33	55.50 Sq.M.	PAINTING THE OLD WOOD WORK WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT INCLUDING THOROUGH SCRAPPING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE QUALITY AND THE SHADE OF PAINT SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)	(Rupees one hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	8325.0
34	27.40 Sq.M.	DISMANTLING CLEARING AWAY AND CAREFULLY STACKING MATERIALS USEFUL FOR RE-USE OF PRESSED TILES AND WEATHERING COURSE IN CEMENT MORTAR AND WITHOUT AFFECTING THE ADJACENT STRUCTURES, INCLUDING THE COST OF REQUIRED TOOLS AND PLANTS AND SCAFFOLDING IF NECESSARY ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	(Rupees twenty only)	1.Sq.M. (ONE SQUARE METRE)	548.0
35	1.10 Cu.M.	WEATHERING COURSE WITH CONCRETE BROKEN BRICK JELLY 20MM GAUGE IN PURE BURNT LIME STONE SLAKED AND SCREENED (NO SAND) OVER RCC ROOF SLAB WITH PROPORTION OF BRICK JELLY TO LIME (FAT LIME) BEING 32: 12 1/2 BY VOLUME WELL BEATEN WITH WOODEN BEATERS FOR GIVING THE REQUIRED SLOPE AND THICKNESS COMPLYING WITH RELEVANT STANDARD SPECIFICATION AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	(Rupees four hundred only)	1.Cu.M. (ONE CUBIC METRE)	440.00
36	27.40 Sq.M.	SUPERIOR QUALITY OF SIZE 23CMX23CMX20MM THICK LAID OVER WEATHERING COURSE IN CM 1:3 (ONE OF CEMENT AND THREE OF CRUSHED STONE SAND) 12MM THICK MIXED WITH WATER PROOFING COMPOUND AT 2% BY WEIGHT OF CEMENT USED AND POINTED NEATLY WITH THE SAME CEMENT MORTER MIXED WITH WATER PROOFING COMPOUND INCLUDING CURING ETC., AS PER STANDARD SPECIFICATIONS, (THE QUALITY OF THE TILES SHALL BE GOT APPROVED	Rs.400.00 (Rupees four hundred only)	1.Sq.M. (ONE SQUARE METRE)	10960.00
		FROM THE EXECUTIVE ENGINEER BEFORE USE.)			

O. Jught

NO. OF CORRECTIONS

SUPERINA NDING ENGINEER/SOUTH CIRCLE.

CONTRACTOR

		NEADER ILLII SOLES DIEG OF CORRESPORTING	20		PAGE 9
1	QUANTITY 2	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS 4	UNIT IN FIGURES AND IN WORDS 5	6 926715.46
37	5 NOS.	SUPPLYING AND FIXING OF HALF TURN BRASS CORE CP LONG BODY TAP OF 15MM DIA OF BEST QUALITY INCLUDING COST OF HALF TURN CP TAP WITH REQUIRED SPECIALS AND LABOUR FOR FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		1.NO. (EACH)	2000.00
38	4 NOS.	SUPPLYING AND FIXING OF HALF TURN BRASS CORE CP SHORT BODY TAP OF 15MM DIA OF BEST QUALITY INCLUDING COST OF HALF TURN CP TAP WITH REQUIRED SPECIALS AND LABOUR FOR FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	(Rupees four hundred only)	1.NO. (EACH)	1600.00
39	2.60 Sq.M.	PROVIDING T.W. DOUBLE LEAF SHUTTERS FOR CUPBOARD/WARD ROBES WITH 9MM THICK PHENOL BONDED BWR GRADE PLYWOOD AS PER IS 303-1989 (GENERAL) WITH IS 5539-1969 (FOR ADHESIVE) WITH RELEVANT IS SPECIFICATIONS AND ITS LATEST AMENDMENT FOR SHUTTERS. THE ALL ROUND FRAME MADE UP OF T.W SCANTLING OF 75MMX37,50MM AND THE STYLES MADE UP OF T.W.	(Rupees four thousand only)	1.Sq.M. (ONE SQUARE METRE)	10400.00
		SCANTLINGS OF 75MM X 37,50MM AND SHUTTER MIDDLE RAIL (HORIZONTAL) MADE UP OF T.W SCANTLING OF 150MM X37,50MM INCLUDING COST OF BWR GRADE PLYWOOD AND LABOUR FOR FIXING IN POSITION, COST OF MATERIALS, ALUMINIUM FURNITURE FITTINGS SUCH AS 6 NOS. OF 3" OF ALUMINIUM BUTT HINGES, 2 NOS. OF 4 ORNAMENTAL HANDLE, LOCK AND KE ARRANGEMENTS (LEAVER TYPE) OF BEST APPROVED QUALITY WITH BRASS SCREWS AND ALSO PAINTING WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT OVER ON COAT OF WOOD PRIMER OF APPROVED QUALITY ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTA OFFICERS (THE LOCK AND KEY, BWR GRADE PLYWOO) QUALITY AND SHADE AND ALUMINIUM FURNITURE FITTINGS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)	R V P P P P P P P P P P P P P P P P P P		
40	71.30 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 2.5 SQMM PV INSULATED SINGLE CORE MULTI STRAND FIR	C Rs.200.00 E (Rupees two hundred only)	1.Rmt. (ONE RUNNING METRE)	14260.
	×.	RETARDANT FLEXIBLE COPPER CABLE WITH IS MARK CONFORMING TO IS: 694/1990, 1.1 KV GRAD CABLE WITH CONTINUOUS EARTH BY MEANS OF 2 SQMM PVC INSULATED SINGLE CORE MULTI STRANS FIRE RETARDANT FLEXIBLE COPPER CABLE WITH IS MARK CONFORMING TO IS: 694/1990, 1.1 KV GRAD CABLE IN FULLY CONCEALED 19/20MM DIA RIGID PVC CONDUIT PIPE WITH ISI MARK ETC. INCLUDING COSOF ALL MATERIALS, SPECIALS ETC. ALL COMPLETE AN AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	E		~
					_
1	N. BUILD	HRS .		(20)	954975

Organish)

NO. OF CORRECTIONS

			2		PAGE - 10
SNO	QUANTITY	DESCRIPTION OF WORK	RATE EXCLUSIVE OF GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	(12332)
1	2	3	4	5	6
41	20.20 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 4 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1, KV, GRADE CABLE IN FULLY CONCEALED 19MM/20MM DIA RIGID PVC CONDUIT PIPE HEAVY DUTY WITH ISI MARK COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE.	Rs,220.00 (Rupees two hundred and twenty only)	1.Rmt. (ONE RUNNING METRE)	954975.46 4444.00
42	1 NO.	SUPPLYING AND FIXING OF ELECTRO MECHANICALLY OPERATED THREE PHASE EARTH LEAKAGE CIRCUIT BREAKERS/RESIDUAL CURRENT CIRCUIT BREAKER (ELCB/RCCB) COMBINED WITH OVER LOAD AND SHORT CIRCUIT PROTECTION HAVING A RUPTURING CAPACITY OF 6 KA WITH 30 MILLI AMPS FIXED SETTING SENSITIVITY AND RATES FOR 25 A IN SUITABLE SHEET STEEL ENCLOSURE CONFIRMING TO IS 12640/1988 INCLUDING COST OF ELCB/RCCB ON FULLY CONCEALED SUITABLE M.S BOX WITH NECESSARY INTER CONNECTIONS AND EARTH CONNECTIONS USING COPPER CABLE INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE,	(Rupees one thousand and five hundred only)	1.NO. (EACH)	1500.00
43	21.30 Rmt.	SUPPLYING AND FIXING OF 110MM DIA PVC SWR PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992-TYPE 'A' FOR RAIN WATER DOWN FALL PIPE WITH RELEVANT SPECIALS SUCH AS GRATINGS, SHOES, BENDS, OFFSETS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING IS 5382 WITH LEAVING A GAP ABOUT 10MM TO ALLOW THERMAL EXPANSION WITH NECESSARY CLAMPS, TEAK WOOD PLUGS, ETC., OF APPROVED QUALITY AND INCLUDING FIXING C.I. GRATINGS AT THE JUNCTION OF PARAPET AND FLOOR OR ROOF SLAB ETC., INCLUDING FINISHING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS,	(Rupees four hundred only)	1. Rmt. (ONE RUNNING METRE)	8520.00
44	10.00 Rmt.	SUPPLYING AND FIXING THE FOLLOWING DIA PVC (SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'B' FOR SOIL LINE WITH RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING TO IS 5382 WITH LEAVING A GAP ABOUT 10MM TO ALLOW THERMAL EXPANSION, FIXING THE PIPES INTO WALLS WITH NECESSARY WOODEN PLUG, SCREWS, HOLDING WHEREVER NECESSARY AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS,		1.Rmt. (ONE RUNNING	7100.00
	1/2	REQUIRED FVC SPECIALS ETC., ALL COMPLETE.,	only)	METRE)€	-1
45	3 NOS.	SUPPLYING AND FIXING OF BEVELED EDGE MIRROR OF APPROVED QUALITY AND BRAND OF SIZE 500X400X5,5MM SHELF TYPE MOUNTED IN THE PVC, FIBRE GLASS FRAMED WITH NECESSARY HARD BOARD BACKING INCLUDING LABOUR FOR FIXING IN POSITION ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS	(Rupees four hundred and ninety only)	1.NO. (EACH)	1470.00
		TOTAL AMOUNT (EXCLUDING GST)			978009.46
		GST Amount for providing Service to Government Contract Works for the above Construction Works,			117361.14

FOR G.M. BRUPERS TEN AKHS NINETY FIVE THOUSAND THREE HUNDRED AND SEVENTY AND PAISE SIXTY ONLY)

CONTRACTOR

NO. OF CORRECTIONS