SCHEDULE - A

NAME OF WORK: CONSTRUCTION OF BELL OF ARMS AND ADMINISTRATIVE BUILDING WITH DEVELOPMENT WORKS FOR TSP 12TH BATTALION (NOW AT MANIMUTHAR) AT SAKKARAKOTTAI IN RAMANATHAPURAM DISTRICT (GROUP-II)

ITEM.NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	AMOUNT
1	2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS 6	7
1.1		EARTH WORK EXCAVATION FOR FOUNDATION IN ALL SOILS AND SUBSOILS TO THE REQUIRED DEPTH AS MAY BE DIRECTED EXCEPT IN HARD ROCK REQUIRING BLASTING BUT INCLUSIVE OF SHORING, STRUTTING, AND BAILING OUT WATER WHEREVER NECESSARY AND REFILLING THE SIDES OF FOUNDATION WITH EXCAVATED EARTH IN 150 MM THICK LAYERS WELL WATERED RAMMED AND CONSOLIDATED AND DEPOSITING THE SURPLUS EARTH IN PLACES SHOWN CLEARING AND LEVELLING THE SITE WITH AN INITIAL LEAD OF 10 METRES AND LIFT AS SPECIFIED HERE UNDER ETC. COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS. (INCLUDING REFILLING)	17, 23 & 24		, , , , , , , , , , , , , , , , , , ,	
	4635.96 Cu.M.	(a) 0 TO 2M DEPTH		Rs.100.00 (Rupees one hundred only)	1.Cu.M. (ONE CUBIC METRE)	463596.00
	2166.92 Cu.M.	(b) 2 TO 3M DEPTH		Rs.100.00 (Rupees one hundred only)	1.Cu.M. (ONE CUBIC METRE)	216692.00
1.5		EARTH WORK EXCAVATION FOR OPEN FOUNDATION IN ALL SOILS AND SUBSOILS TO THE REQUIRED DEPTH AS MAY BE DIRECTED EXCEPT IN HARD ROCK REQUIRING BLASTING, INCLUSIVE OF SHORING, STRUTTING, AND BAILING OUT WATER WHEREVER NECESSARY (EXCLUDING REFILLING THE SIDES OF FOUNDATION) AND DEPOSITING THE EARTH IN PLACES SHOWN CLEARING AND LEVELLING THE SITE WITH AN INITIAL LEAD OF 10 METRES AND LIFT AS SPECIFIED HERE UNDER ETC. COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD	17 & 20			
	4523.40 Cu.M.	SPECIFICATIONS. (EXCLUDING REFILLING) (a) 0 TO 2M DEPTH	3.4	Rs.50.00 (Rupees fifty only)	1.Cu.M. (ONE CUBIC METRE)	226170.00
	53.80 Cu.M.	(b) 2 TO 3M DEPTH		Rs.50.00 (Rupees fifty only)	1.Cu.M. (ONE CUBIC METRE)	2690.00
1.6		EARTH WORK EXCAVATION FOR OPEN FOUNDATION FOR DRAINS IN ALL SOILS AND SUBSOILS TO THE REQUIRED DEPTH AS MAY BE DIRECTED EXCEPT IN HARD ROCK REQUIRING BLASTING, INCLUSIVE OF SHORING, STRUTTING AND BAILING OUT WATER WHEREVER NECESSARY. (EXCLUDING REFILLING THE SIDES OF FOUNDATION) AND DEPOSITING THE EARTH IN PLACES SHOWN CLEARING AND LEVELING THE SITE WITH AN INITIAL LEAD OF 10 METRES AND LIFT AS SPECIFIED HEREUNDER ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATION (EXCLUDING REFILLING) (DRAIN HAVING BED WIDTH UPTO 1.25 METRE).				
		(a) 0 TO 2M DEPTH		Rs.100.00 (Rupees one hundred only)	1.Cu.M. (ONE CUBIC METRE)	35830.00
Fan d	SMP Ass	ociates				944978.00

Managing Raxiner

NO. OF CORRECTIONS

7	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	TNUOMA
1	2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS	7
						944978.0
11.0	2463.60 Cu.M.	SUPPLYING AND FILLING IN FOUNDATION AND		Rs.500,00	1.Cu.M.	1231800.0
		BASEMENT WITH FILLING SAND IN LAYERS OF 150		(Rupees five hundred only)	(ONE CUBIC	16"
		MM THICKNESS WELL WATERED, RAMMED AND			METRE)	
		CONSOLIDATED COMPLYING WITH RELEVANT STANDARD SPECIFICATION INCLUDING COST OF				
		SUPPLYING FILLING SAND ETC., ALL COMPLETE AND AS	24 & 25		-	
		DIRECTED BY THE DEPARTMENTAL OFFICERS.	v			
1						
.2	252.00 Cu.M.	PROVIDING SAND GRAVEL MIX FOR FOUNDATION		Rs.800.00	1.Cu.M.	201600.0
/	~	AND BASEMENT IN LAYERS OF 150MM THICKNESS		(Rupees eight hundred only)	(ONE CUBIC	. 100
		WELL WATERED, RAMMED AND CONSOLIDATED COMPLYING WITH RELEVANT STANDARD		1/2	METRE)	
	4	SPECIFICATIONS. THE SAND GRAVEL MIX WILL BE A	- x			4.
- "	W. C. W. C. W. C. W. C. W.	PROPORTION OF 1:1 (I.E.) 0.70M3 OF FILLING SAND, 0.72M3 OF GRAVEL FOR EVERY 1.00M3 COMPACTED				
		VOLUME OF SAND GRAVEL MIX INCLUDING COST AND	17 & 20			
		CONVEYANCE OF SAND AND GRAVEL FROM APPROVED	/			
		QUARRYS TO WORK SITE INCLUDING LABOUR CHARGES FOR MIXING SAND AND GRAVEL IN THE REQUIRED				
		PROPORTION AND CONSISTENCY USING SOFT POTABLE				
		WATER INCLUDING ALL LEADS FOR WATER, SPREADING THE MIX IN LAYERS CONSOLIDATING THE SAME AS				
		DIRECTED BY THE DEPARTMENTAL OFFICERS.		1457		
	-					
			- 1			
.3	126.70 Cu.M.	SUPPLYING AND FILLING WITH 40MM SIZE		Rs.1000.00	1.Cu.M.	126700.0
Y		BROKEN BRICK JELLY IN FOUNDATION AND		(Rupees one thousand only)	(ONE CUBIC METRE)	
		BASEMENT AND OTHER SIMILAR WORKS INCLUDING			III III	
- 0		COST OF MATERIALS, LABOUR CHARGES, ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL	17 & 20			
		OFFICERS.				
	G +1	* * * * * * * * * * * * * * * * * * *	. 8			
.6	9.60 Cu.M.	SUPPLYING AND FILLING WITH 40 MM SIZE HARD		Rs.2000.00	1.Cu.M.	19200.0
1	1	BROKEN STONE JELLY IN FOUNDATION AND		(Rupees two thousand only)	(ONE CUBIC	la de
		BASEMENT AND OTHER SIMILAR WORKS INCLUDING			METRE)	
		COST OF MATERIALS, LABOUR CHARGES ETC., ALL				-
		COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
		900 after 21 cmm in	v.			
.7	3.20 Cu.M.	SUPPLYING AND FILLING WITH 20 MM SIZE HARD	10 8	Rs.2000.00	1.Cu.M.	6400.
/	0.20 00	BROKEN STONE JELLY IN FOUNDATION AND	Mull	(Rupees two thousand only)	(ONE CUBIC	0400.
		BASEMENT AND OTHER SIMILAR WORKS INCLUDING			METRE)	
		COST OF MATERIALS, LABOUR CHARGES ETC., ALL				
		COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL				
		OFFICERS.			Line Barr	
	20	The second second				
				_		
.1	2634.70 Cu.M.	PLAIN CEMENT CONCRETE 1:5:10 (ONE OF		Rs.2500.00	1.Cu.M.	6586750.
/	•	CEMENT, FIVE OF SAND AND TEN OF HARD BROKEN		(Rupees two thousand and five	(ONE CUBIC	Marine
		STONE JELLY) FOR FOUNDATION USING 40MM GAUGE HARD BROKEN STONE JELLY INCLUSIVE OF SHORING,	3	hundred only)	METRE)	
		STRUTTING AND BAILING OUT WATER WHEREVER				
		NECESSARY RAMMING, CURING ETC., COMPLETE IN ALL	28			
		RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND AS DIRECTED BY THE	4	282		
50		DEPARTMENTAL OFFICERS				
						-
.2	999.70 Cu.M.	PLAIN CEMENT CONCRETE 1:2:4 (ONE OF CEMENT,		Rs.5000.00	1.Cu.M.	4998500
		TWO OF SAND AND FOUR OF HARD BROKEN STONE		(Rupees five thousand only)	(ONE CUBIC	4535350
		JELLY) USING 20MM GAUGE HARD BROKEN STONE		· ·	METRE)	
	- ,	JELLY EXCLUDING SHUTTERING AND CENTERING BUT INCLUDING LAYING, CURING AND FINISHING WITH		, F , F , F	460	3.0
		RELEVANT STANDARD SPECIFICATIONS IN	1	*	2.0	22.8
		FOUNDATION AND BASEMENT AND OTHER SIMILAR				
		WORKS AND AS DIRECTED BY THE DEPARTMENTAL				
			1			
		OFFICERS.				
	SMP 4					
For	SMP As					14115928

Managing Partner

NO. OF CORRECTIONS

		20
ITEN ST	YTITNAUC	DESCRIPTION OF WO
1	2	3

1	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	AND IN WORDS	AMOUNT
1	2	3	4	5	6	7
						14115928.0
3.3	57.85 Cu.M.	PLAIN CEMENT CONCRETE 1:8:16 (ONE OF		Rs.3000.00	1.Cu.M.	173550.0
V	V	CEMENT, EIGHT OF SAND AND SIXTEEN OF BROKEN BRICK JELLY) FOR FOUNDATION AND OTHER SIMILAR		(Rupees three thousand only)	(ONE CUBIC METRE)	le le
		WORKS USING 20MM GAUGE BROKEN BRICK JELLY			metke)	
	×	INCLUSIVE OF SHORING, STRUTTING AND BAILING OUT			W	
		WATER WHEREVER NECESSARY RAMMING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH	28			
		RELEVANT STANDARD SPECIFICATIONS AND AS	V			
		DIRECTED BY THE DEPARTMENTAL OFFICERS.				
				W		
7.2	491.90 Sq.M.	SUPPLYING AND FIXING OF 20MM THICK		Rs.500.00	1.Sq.M.	245950.0
	- 4 %	BITUMINOUS EXPANSION JOINT FILLER PAD OF	A) - A	(Rupees five hundred only)	(ONE SQUARE	
- 1		APPROVED QUALITY AND MAKE INCLUSIVE OF			METRE)	
		CONVEYANCE CHARGES, CUTTING THE PAD TO THE REQUIRED SIZE, COST OF MATERIALS AND LABOUR			W	
-		CHARGES FOR FIXING IN POSITION WHEREVER				
		NECESSARY FOR ALL FLOORS ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
		DIRECTED BY THE DEPARTMENTAL OFFICERS.				
12.1		BRICK PARTITION WALLS 50MM THICK USING				
		KILN BURNT COUNTRY BRICKS OF SIZE 8 3/4"x4				
		1/4"x2" (22x11x5CM) IN CEMENT MORTAR 1:4 (ONE				
		OF CEMENT AND FOUR OF SAND) FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING				
	×	SCAFFOLDING, CURING ETC., COMPLETE ALL RESPETS	31 & 31-C			
		COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.	V			
		of Edit Ida Hono AND BITAVIINGO.				
	16.50 Sq.M.	(a) IN GROUND FLOOR		Rs.300.00	1.Sq.M.	4950.0
	-	(4) 5.155.15 1 255.1		(Rupees three hundred only)	(ONE SQUARE	4000.0
	17				METRE)	
	7.00 Sq.M.	(b) IN FIRST FLOOR		Rs.300.00	1.Sq.M.	2100.0
	/	(4)		(Rupees three hundred only)	(ONE SQUARE	2100.0
					METRE)	
		375 A 75 1 1884				
	7.00 Sa M	(c) IN SECOND FLOOR	A	Rs.300.00	1.Sq.M.	2100.0
	7100 041111	(c) IN SECOND FLOOR	Seed hery	(Rupees three hundred only)	(ONE SQUARE	2100.0
					METRE)	
					~	
		CURRINAL AND ENVISO OF THE CONTRACT			2	
21.2		SUPPLYING AND FIXING OF TEAK WOOD				
		WROUGHT AND PUT UP FOR FRAMES OF DOORS, WINDOWS, VENTILATORS, CUPBOARD AND ANY OTHER				
		SIMILAR JOINERY WORKS WITH NECESSARY PLUGS,				
		REBATES FOR SHUTTERS, PLASTER GROOVES ON ALL FACES ETC. INCLUDING LABOUR CHARGES FOR FIXING				
		HOLD FASTS COMPLYING WITH RELEVANT STANDARD	/			
-		SPECIFICATIONS ETC IN ALL RESPECTS.				
					-	
	2642.6	5%		D 00000 00	14.5	
	2.042 Gu.M.	(a) TEAK WOOD OVER 2.00 METRE AND BELOW		Rs.90000.00	1.Cu.M. (ONE CUBIC	237780.
		3.00 METRE LENGTH		(Rupees ninety thousand only)	METRE)	
		-				
	1.018 Cu.M.	(b) TEAK WOOD BELOW 2.00 METRE LENGTH		Rs.90000.00	1.Cu.M.	91620.
	*			(Rupees ninety thousand only)	(ONE CUBIC METRE)	-
						/4
			-		- 100-	
			7			
		s				

Managing Ranner CONTRACTOR

NO. OF CORRECTIONS

0/		
2	Sakkarakottai Bell of Arms (Gr-II)	

2	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
1	2	3	4	5	6	7 14873978.00
3.3	65 NOS	SUPPLYING AND FIXING OF BEST APPROVED SUPERIOR VARIETY MAGNETIC DOOR CATCHES SUITABLE FOR DOORS INCLUDING COST OF DOOR CATCHES, ALUMINIUM / STAINLESS STEEL SCREWS FIXING IN POSITION ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAND SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.50.00 (Rupees fifty only)	1.NO. (EACH)	3250.00
25	350 NOS.	SUPPLYING AND FIXING OF MILD STEEL HOLD FASTS HORIZONTALLY TWISTED OF SIZE 230X40X4MM WITH PAIR OF SUITABLE IRON SCREWS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	86	Rs.10.00 (Rupees ten only)	1.NO. (EACH)	3500.00
26	178.49 Cu.M.	FLOORING WITH A BED OF CEMENT CONCRETE 1:5:10 (ONE OF CEMENT, FIVE OF SAND AND TEN OF HARD BROKEN STONE JELLY) USING 40MM SIZE HARD BROKEN STONE JELLY AND TOP LEFT ROUGH TO RECEIVE THE FLOOR FINISH WITH REQUIRED SLOPES INCLUDING RAMMING, CURING ETC., ALL COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	28 & 39- H	Rs.2500.00 (Rupees two thousand and five hundred only)	1.Cu.M. (ONE CUBIC METRE)	446225.0
28	270.90 Sq.M.	FINISHING THE TOP OF FLOORING IN CM 1:4 (ONE OF CEMENT AND FOUR OF SAND) 20MM THICK INCLUDING SURFACE RENDERED SMOOTH INCLUDING PROVIDING PROPER SLOPES, THREAD LINING, CURING AND 150MM WIDE SKIRTING ALROUND WITH THE SAME	56, 57	Rs.200.00 (Rupees two hundred only)	1.Sq.M. (ONE SQUARE METRE)	54180.0
30	816.10 Sq.M.	FINISHING THE TOP OF FLOORING WITH CEMENT CONCRETE 1:3 (ONE OF CEMENT AND THREE OF BLUE GRANITE CHIPS OF SIZE 10MM AND BELOW) 20MM THICK ELLIS PATTERN FLOORING (NO SAND) AND SURFACE RENDERED SMOOTH	31-C	Rs.200.00 (Rupees two hundred only)	1.Sq.M. (ONE SQUARE METRE)	163220.
1	9.60 Cu.M.	INCLUDING 50MM WIDE SKIRTING, PROVIDING PROPER SLOPES, THREAD LINING, CURING ETC., COMPLETE IN ALL FLOORS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS. WEATHERING COURSE WITH CONCRETE BROKEN BRICK JELLY 20MM GAUGE IN PURE BURNT LIME STONE SLAKED AND SCREENED (NO SAND) OVER RCC ROOF	39-G	Rs.2000.00 (Rupees two thousand only)	1.Cu.M. (ONE CUBIC	19200.
		SLAB WITH PROPORTION OF BRICK JELLY TO LIME (FAT LIME) BEING 32:12½ BY VOLUME WELL BEATEN WITH WOODEN BEATERS FOR GIVING THE REQUIRED SLOPE AND THICKNESS COMPLYING WITH RELEVANT STANDARD SPECIFICATION AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	30 & 41		METRE)	
33	12867.20 Sq.M.	PLASTERING WITH CM 1:5 (ONE OF CEMENT AND FIVE OF SAND) 12MM THICK FINISHED WITH NEAT CEMENT INCLUDING PROVIDING BAND CORNICE, CEILING CORNICE, CURING, SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS AND COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.		Rs.120.00 (Rupees one hundred and twenty only)	1.Sq.M. (ONE SQUARE METRE)	1544064.
	5. 8				= . *	17107617

Managing Ranner CONTRACTOR

NO. OF CORRECTIONS

Sakkarakottai Bell of Arms (Gr-II)

0	YTITIALUO	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	TNUOMA
	2	3	4	5	6	7 17107617.0
4	1	PLASTERING WITH CM 1:4 (ONE OF CEMENT AND FOUR OF SAND) 12MM THICK FINISHED WITH NEAT CEMENT INCLUDING PROVIDING BAND CORNICE, CEILING CORNICE, CURING, SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS AND COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.		Rs.120.00 (Rupees one hundred and twenty only)	1.Sq.M. (ONE SQUARE METRE)	155265.6
5	Serve .	SPECIAL CEILING PLASTERING IN CEMENT MORTAR 1:3 (ONE OF CEMENT AND THREE OF SAND) 10MM THICK FOR BOTTOM OF ROOF, STAIR WAIST, LANDING AND SUNSHADES IN ALL FLOORS FINISHED WITH NEAT CEMENT INCLUDING HACKING THE AREAS, PROVIDING BAND CORNICE, SCAFFOLDING CURING ETC., COMPLETE.	56 & 57	Rs.120.00 (Rupees one hundred and twenty only)	1.Sq.M. (ONE SQUARE METRE)	414372.0
6		PLASTERING IN CEMENT MORTAR 1:5 (ONE OF CEMENT AND FIVE OF SAND) 12MM THICK FOR BORDER FINISH IN ALL FLOORS FOR ELEVATION PURPOSES INCLUDING SCAFFOLDING, CURING, FINISHING ETC., ALL COMPLETE.	56 & 57			
	448.90 Rmt.	(a) 150MM WIDE BORDER		Rs.40.00 (Rupees forty only)	1.Rmt. (ONE RUNNING METRE)	17956.
	448.90 Rmt.	(b) 75MM WIDE BORDER		Rs.30.00 (Rupees thirty only)	1.Rmt. (ONE RUNNING METRE)	13467.
	448.90 Rmt.	(c) 50MM WIDE BORDER		Rs.20.00 (Rupees twenty only)	1.Rmt. (ONE RUNNIÑG METRE)	8978.
7.1	3439.40 Sq.M.	WHITE WASHING THREE COATS USING CLEAN SHELL LIME SLAKED INCLUDING COST OF LIME, GUM, BLUE, BRUSHES INCLUDING SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS.	63	Rs.15.00 (Rupees fifteen only)	1.Sq.M. (ONE SQUARE METRE)	51591.
9	12634.50 KG.	SUPPLYING AND FIXING MILD STEEL GRILLS AS PER THE DESIGN APPROVED TO VERANDAH ENCLOSURE OR GATE INCLUDING ONE COAT OF PRIMER AND LABOUR FOR FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.60.00 (Rupees sixty only)	1.KG. (ONE KILOGRAM)	758070
10	250.70 Sq.M.	PAINTING THE NEW WOOD WORK WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT IN ADDTION TO ONE COAT OF PRIMER OF APPROVED QUALITY AND SHADE, THE PAINT SHOULD BE SUPPLIED BY THE CONTRACTOR AT HIS OWN COST (THE QUALITY AND THE SHADE OF PAINT SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE) COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	66 & 66 A	Rs.100.00 (Rupees one hundred only)	1.Sq.M. (ONE SQUARE METRE)	25070
	x 8		2 6			(**)
		ociates				

Managing Pariner

NO. OF CORRECTIONS

EM.NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
	2	3	4	5	6	7 18552386.60
41	2160.30 Sq.M.	PAINTING THE NEW IRON WORK AND OTHER SIMILAR WORKS SUCH AS PVC/ASTM PIPES, KERB STONE AND GRILLS WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT OF APPROVED QUALITY AND BRAND, THE PAINT SHOULD BE SUPPLIED BY THE CONTRACTOR AT HIS OWN COST (THE QUALITY AND THE BRAND OF PAINT SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE) COMPLYING WITH RELEVANT STANDARD SPECIFICATION.	66 & 66A	Rs.100.00 (Rupees one hundred only)	1.Sq.M. (ONE SQUARE METRE)	216030.00
46	2.00 Rmt.	SUPPLYING AND FIXING OF 20MM DIA ALUMHNIUM HANGER ROD TO THE REQUIRED LENGTH WITH ALUMINIUM END BRACKETS INCLUDING COST OF SCREWS, TW PLUGS AND LABOUR CHARGES FOR FIXING IN POSITION ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	(5)	Rs.90.00 (Rupees ninety only)	1.Rmt. (ONE RUNNING METRE)	y 180.0
47	17 NOS.	SUPPLYING AND FIXING OF ALUMINIUM TOWEL RAILS OF 75CM LONG, INCLUDING COST OF SCREWS, TW PLUG AND LABOUR CHARGES FOR FIXING IN POSITION ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.100.00 (Rupees one hundred only)	1.NO. (EACH)	1700.0
48	6 NOS.	SUPPLYING AND FIXING OF ALUMINIUM PLATE WITH FIVE PINS FOR COAT STAND INCLUDING COST OF PLUGS, NAILS, SCREWS AND LABOUR FOR FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.50.00 (Rupees fifty only)	1.NO. (EACH)	300.0
49	219 NOS.	PROVIDING AND FIXING OF IRON CHROMIUM PLATED 8 GAUGE PICTURE HOOKS INCLUDING FIXING IN POSITION ETC., ALL COMPLETE IN ALL RESPECTS AND	ИД	Rs.2.00 (Rupees two only)	1.NO. (EACH) .	438.0
50.2	3010.90 Rmt.	AS DIRECTED BY THE DEPARTMENTAL OFFICERS. SUPPLYING AND FIXING OF PRECAST KERB STONE OF SIZE 450 X 300 X150 MM MADE IN CEMENT CONCRETE 1:3:6 (ONE OF CEMENT, THREE OF SAND AND		Rs.175.00 (Rupees one hundred and seventy five only)	1.Rmt. (ONE RUNNING METRE)	526907.
		SIX OF HARD BROKEN STONE JELLY) USING 20MM SIZE HARD BROKEN STONE JELLY INCLUDING THE COST OF KERB STONE, MOULDING, LAYING, CURING, TRANSPORTING, POINTING AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
50.3	35 NOS.	SUPPLYING AND PLANTING OF AVENUE TREES INCLUDING EARTHWORK EXCAVATION FOR PIT OF SIZE 60X60X60CM FILLED WITH MANURE FOR 20CM DEPTH AND FILLING WITH RIVER SAND AND RED EARTH MIX IN THE RATIO OF 1:1 FOR 40CM DEPTH IN THE SAME PIT AND PLANTING THE AVENUE TREES OF APPROVED VARIETIES TO A HEIGHT OF 200CM FROM THE GROUND LEVEL AND MAINTAINING THEM FOR THE PERIOD CAL MANURING AND REPLACING THE AVENUE TREES IF		Rs.300.00 (Rupees three hundred only)	1.NO. (EACH)	10500.
	*****	DEAD ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (TREE SAPPLING SHALL BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE PLANTING)	- 21			
or \$	SMP Ass	ociates				

Managing Parmer CONTRACTOR

NO. OF CORRECTIONS

Rakkarakottai Bell of Arms (Gr-II)
<i>j</i> =	′

25

EM.NO	QUANTITY 2	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS 6	AMOUNT
						19308442.10
50.4		SUPPLYING AND FIXING OF TRIANGULAR SHAPE CHICKEN MESH TREE GUARD USING 8 CM DIA CASURINA VERTICAL POST AND MIDDLE TIE USING COUNTRY WOOD REAPER OF SIZE 50x25 MM AND 25 GAUGE CHICKEN MESH INCLUDING LABOUR CHARGES FOR FIXING THE TRIANGULAR TREE GUARD AND AS DIRECTED BY THE DEPARTMETAL OFFICERS.		Rs.500.00 (Rupees five hundred only)	1.NO. (EACH)	17500.00
50.5		SUPPLYING, FABRICATION AND ERECTION IN POSITION OF M.S. SCHEME NAME AND LAYOUT BOARD WITH 50X50X6MM, M.S. ANGLE FOR VERTICAL POST AND SUPPORT POSTS WITH 2.5 MM THICK M.S. SHEET FOR A SIZE AT 1.80X1.20M WITH 40X40X6MM M.S. ANGLE AROUND THE BOARD AND 50X6MM FLAT STIFFENERS ON BOTH DIRECTIONS INCLUDING COST OF WELDING CHARGES, PAINTING CHARGES AND DRAWING THE		Rs.10000.00 (Rupees ten thousand only)	1.NO. (EACH)	10000.00
		LAYOUT AND LETTERING THE SCHEME DETAILS AS DIRECTED BY THE DEPARTMENTAL OFFICERS INCLUDING EARTH WORK EXCAVATION FOR 4 NOS OF PITS, PCC 1:5:10 (ONE OF CEMENT, FIVE OF SAND AND TEN OF HB STONE JELLY) FOR PITS. 0.45 X 0.45 X 0.60M BELOW GROUND LEVEL AND P.C.C 1 :2:4 (ONE OF CEMENT, TWO OF SAND AND FOUR OF ZOMM HB STONE JELLY) AT 0.30 X 0.30 X 0.30M ABOVE GROUND LEVEL FOR ERECTION, CONVEYANCE CHARGES ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS				
53.3	8 NOS.	SUPPLYING AND FIXING OF C.I. STEPS OF APPROVED QUALITY AND BRAND (NOT LESS THAN 5KG EACH) INCLUDING COST OF MATERIAL LABOUR CHARGES FOR FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	PAX.	Rs.30.00 (Rupees thirty only)	1.NO. (EACH)	240.00
55.2	6 NOS.	SUPPLYING AND FIXING OF APPROVED BRAND PORCELAIN FLAT BACK URINAL SUPERIOR VARIETY INCLUDING COST OF URINAL LEAD PIPE, WASTE PIPE, 15MM WHEEL VALVE, TW PLUG AND LABOUR FOR FIXING ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE BRAND AND QUALITY SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	8	Rs.1500.00 (Rupees one thousand and five hundred only)	1.NO. (EACH)	9000.00
60	37 NOS.	SUPPLYING AND FIXING OF PVC NAHANI TRAP OF 75MMX50MM 4WAY / 2 WAY (SUPERIOR VARIETY) HAVING MINIMUM OF WATER SEAL OF 50MM CONFIRM TO RELEVANT I.S. SPECIFICATIONS WITH ITS LATEST AMENDMENTS INCLUDING RESTING ON THE BED OF BRICK JELLY CONCRETE 1:5:10 (ONE OF CEMENT, FIVE OF SAND AND TEN OF 40MM GUAGE BRICK JELLY) ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE PVC NAHANI TRAP SHOULD BE GOT APPORVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.100.00 (Rupees one hundred only)	1.NO. (EACH)	3700.00
61.2		SUPPLYING AND LAYING AND LOOSE JOINTING THE FOLLOWING DIA STONE WARE PIPES WITH ISI MARK SUPERIOR VARIETY (GLAZED) WITH SIPGOT AND SOCKET ENDS IN DRY CONDITIONS AND TESTED WITH WATER, AFTER THE PIPES ARE LAID TO PROPER GRADIENT TO THE ALIGNMENT ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	99			
y	32.00 Rmt.	(a) 100MM DIA S.W. PIPE	*2	Rs.200.00 (Rupees two hundred only)	1.Rmt. (ONE RUNNING METRE)	6400.00
						19355282.1

Managing Nartner





Sakkarakottai Bell of Arms (Gr-II)	27

TEM NO	QUANTITY 2	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	RMOUNT
		ELECTRICAL ARRANGEMENTS				19355282.10
72	107 NOS.	SUPPLYING AND FIXING OF BEST APPROVED SUPERIOR VARIETY CONCEALED TYPE FIBRE BOX WITH M.S FAN HOOK OF 100 MM DIA 75 MM DEPTH AND 3 MM THICK INCLUDING COST AND FIXING IN POSITION ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL		Rs.40.00 [#] (Rupees forty only)	1 NO. (EACH)	4280.00
74	107 NOS.	OFFICERS (THE QUALITY SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE) CHARGES FOR ASSEMBLING AND FIXING OF CEILING		Rs.200.00 V	1.NO	21400.00
	- 10 to 10 t	FAN OF DIFFERENT SWEEP WITH NECESSARY CONNECTIONS AND FIXING OF FAN REGULATOR ON THE EXISTING BOARD ETC., ALL COMPLETE (EXCLUDING COST OF FAN).	≥ (.0)	(Rupees two hundred only)	(EACH)	
76	26.00 Rmt.	SUPPLYING AND LAYING OF 8 SWG GI WIRE ON WALL BELOW GROUND LEVELS WITH NECESSARY 'U' NAILS EARTH WORK EXCAVATION AND REFILLING ETC., INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE.		Rs.20.00 (Rupees twenty only)	1.Rmt. (ONE RUNNING METRE)	520.00
77.3	36 NOS.	SUPPLYING, FIXING AND CONCEALING T.W. BOX OF SIZE 8"X8"X4" COVERED WITH 3MM THICK HYLEM SHEET INCLUDING COST OF T.V.LINE SOCKET / TELEPHONE LINE SOCKET ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.75.00 (Rupees seventy five only)	1 NO. (EACH)	2700.00
77.4	178.00 Rmt.	SUPPLYING, LAYING AND CONCEALING OF PVC PIPE OF 20MM DIA WITH NECESSARY SPECIALS AND OTHER MATERIALS INCLUDING RUN OFF 1 NO FISH WIRE (G.I. 22G) FOR DRAWING CABLE FOR T.V./TELEPHONE ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	2)	Rs.50.00 (Rupees fifty only)	1.Rmt. (ONE RUNNING METRE)	8900.00
78	4 NOS.	PROVIDING EARTHING STATION (TYPE I) USING PIPE ELECTRODE AS PER IS 3043 USING 2.5 M OF 40MM DIA AND 1.0 M OF 20MM DIA 'B-CLASS GI PIPE INCLUDING EARTH WORK EXCAVATION, BRICK WORK IN CEMENT MORTAR AND PLASTERING AND COST OF FUNNEL, GI NUTS, BOLTS, WASHERS, CHECK NUTS, GI BEND, REDUCER AND COUPLING, C.I COVER OF 30x30 CM AND INCLUDING CHARCOAL UF 40 KGS AND SALI 10 KGS ETC., ALL COMPLETE.	8	Rs.1000.00 (Rupees one thousand only)	1 NO. (EACH)	4000.0
86	1784.41 Sq.M.	PROVIDING PRE-CONSTRUCTIONAL ANTITERMITE TREATMENT INCLUDING COST OF CHEMICALS LABOUR AS PER STANDARD SPECIFICATIONS FOR PREPARING THE AREA FOR TREATMENT BY SPRAYING CHEMICALS AND OTHER INCIDENTAL CHARGES ETC., COMPLETE. THE RATE SHOULD BE FOR CURING ANTITERMITE TREATMENT FROM THE PLINTH BEAM AND BRICK MASONRY WITH SUPER STRUCTURE IN CONTACT WITH THE BACK FILL EARTH AND AT THE JUNCTION OF THE WALLS. THE TOP SURFACE OF		Rs.30.00 (Rupees thirty only)	1.Sq.M. (ONE SQUARE METRE)	53532.3
		FILLED EARTH FOR FLOORING AND THE SOIL ALONG WITH THE PERIMETER OF THE BUILDING BY MAKING HOLES WITH THE CROW BAR AND POURED 5% TERMICIDE 'CHLORIPYRIFOS" AND SPRAYING THE SAME TERMICIDE SOLUTION ON THE WOODEN FRAMES AND TREATING THE OTHER PERIPHERY OF BUILDINGS ETC., COMPLETE IN ALL RESPECTS AS PER IS 6313 (PART II) /1981 AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS				
						19450614.4

Managing Parmer





Civi, Mi	YUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT 7
1	2	3	4			19450614.40
112		SUPPLYING AND FIXING OF 300 MM DIA SWEEP AC EXHAUST FAN OF APPROVED ISI QUALITY INCLUDING NECESSARY WALL OPENING, FIXING AND FINISHING THE WALL OPENING AND MAKING GOOD INCLUDING COST OF MATERIALS, LABOUR FOR FIXING, CHIPPING AND REDOING NECESSARY INTER CONNECTION, SCAFFOLDING, HIRE CHARGES FOR TOOLS AND PLANTS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.1200.00 (Rupees one thousand and two hundred only)	1 NO. (EACH)	45600.00
238	216.145 MT.	APPLYING ONE COAT OF ANTICORROSIVE TREATMENT ON STEEL REINFORCEMENT RODS (20 LTRS. OF ANTICORROSIVE CHEMICAL FOR ONE MERTIC TONNE OF STEEL REINFORCEMENT RODS) AT SITE INCLUDING COST OF REQUIRED QUANTITY OF ANTICORROSIVE CHEMICALS, (BEST APPROVED QUALITY) CEMENT, CONSUMABLES SUCH AS BRUSHES, GLOVES AND LABOUR FOR ANTICORROSIVE COATING ETC. COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND OF ANTICORROSIVE CHEMICAL SHOULD BE GOT APPROVED BY THE EE BEFORE USE).		Rs.1000.00 (Rupees one thousand only)	1 M.T. (ONE METRIC TONNE)	216145.00
1.9.9	411.00 Rmt.	ANNEXURE AUGER PILE OF 30CM DIA BORE HOLE IN ALL SOILS AND SUB SOILS REQUIRED DEPTH INCLUDING TOOLS AND PLANTS AND LABOUR CHARGES ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.500.00 (Rupees five hundred only)	1.Rmt. (ONE RUNNING METRE)	205500.00
2.1.1	9998.20 Cu.M.	SUPPLYING AND FILLING IN FOUNDATION AND BASEMENT WITH GRAVEL IN LAYERS OF 150 MM THICKNESS WELL WATERED, RAMMED AND CONSOLIDATED COMPLYING WITH RELEVAN STANDARD SPECIFICATIONS INCLUDING COST OF SUPPLYING GRAVEL AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	A D T	Rs.500.00 (Rupees five hundred only)	1.Cu.M. (ONE CUBIC METRE)	4999100.00
4.2.1		PROVIDING AND LAYING IN POSITION, STANDARDISE CONCRETE MIX M-30 GRADE IN ACCORDANCE WIT IS: 456 - 2000 USING 20 MM AND DOWNGRADED HAR BROKEN GRANITE STONE JELLY FOR ALL RCC ITEM OF WORKS NAMELY PLINTH BEAMS, COLUMNS, TI BEAMS, COLUMN FOOTINGS, SLAB ETC., WITH MINIMU CEMENT CONTENT OF 400 KG/M3 AND MAXIMUM WATE CEMENT RATIO OF 0.45, INCLUDING ADMIXTURE (PLASTICISER/SUPER PLASTICISER) IN RECOMMENDE PROPORTIONS AS PER IS:9103 TO ACCELERATI RETARD SETTING OF CONCRETE, IMPROV WORKABILITY WITHOUT IMPAIRING STRENGTH AND URABILITY WITH ABOUT (5.0 CU,M) 7730 KG. OF 20 MACHINE CRUSHED STONE JELLY AND WITH ABOUT	H D S E M R E D L E D			
		(3.3 CU.M.) 5156 KG. OF 10 -12 MM MACHINE CRUSHE STONE JELLY AND WITH ABOUT (4.79 CU.M) 7670 KG. OS SAND FOR MAKING 10M3 CONCRETE BUT EXCLUDING COST OF REINFORCEMENT GRILL AND FABRICATING CHARGES, CENTERING AND SHUTTERING AND ALS INCLUDING LAYING, VIBRATING WITH MECHANIC, VIBRATORS, FINISHING, CURING ETC., COMPLE COMPLYING WITH STANDARD SPECIFICATION AND ADDIRECTED BY THE DEPARTMENTAL OFFICERS. THE COARSE AND FINE AGGREGATES TO BE USED SHOULD COMPLY WITH THE REQUIREMENTS OF IS STANDARD (NO SEPARATE PAYMENT WILL BE MADE BY THE DEPARTMENT FOR THE EXCESS USAGE OF MATERIAL	DF IG IG IG IG IG IE IE IE IE IE IE IE			
	912.30 Cu.M.			Rs.5200.00 (Rupees five thousand and tw	1.Cu.M. (ONE CUBIC METRE)	4743960.
	SMD 45	sociates			+	29660919.

Managing Parmer

NO. OF CORRECTIONS

ITEM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	TNUOMA
1	2	3	4	5	6	7 29660919,40
				100		£5000919,40
6.5.1	581.56 Cu.M.	BRICK WORK IN C.M 1:5 (ONE OF CEMEN'I AND FIVE		Rs.4000.00	1.Cu.M.	2326240.00
V		OF SAND) USING FLY ASH BRICKS OF SIZE		(Rupees four thousand only)	(ONE CUBIC METRE)	
		23X11X7CM IN FOUNDATION AND BASEMENT INCLUDING DEWATERING WHEREVER NECESSARY		-		
		PROPER SETTING, CURING ETC., COMPLETE WITH				
		RELEVANT STANDARD SPECIFICATIONS.				
8.2.1		PROVIDING AND LAYING IN POSITION, STANDARDISED				
Olai!		CONCRETE MIX M-30 GRADE IN ACCORDANCE WITH				
	5.	IS: 456 - 2000 USING 20 MM AND DOWNGRADED HARD				
		BROKEN GRANITE STONE JELLY FOR ALL RCC ITEMS OF WORKS NAMELY PLINTH BEAMS, COLUMNS, TIE				
	- 1 × 5	BEAMS, COLUMN FOOTINGS, SLAB ETC., WITH MINIMUM	- 4		4 4 4	
		CEMENT CONTENT OF 400 KG/M3 AND MAXIMUM WATER CEMENT RATIO OF 0.45, INCLUDING ADMIXTURE				
		(PLASTICISER/SUPER PLASTICISER) IN RECOMMENDED				
		PROPORTIONS AS PER IS:9103 TO ACCELERATE, RETARD SETTING OF CONCRETE, IMPROVE				
		WORKABILITY WITHOUT IMPAIRING STRENGTH AND				
		DURABILITY WITH ABOUT (5.0 CU,M) 7730 KG. OF 20 MM MACHINE CRUSHED STONE JELLY AND WITH ABOUT				
		(3,3 CU.M.) 5156 KG. OF 10 -12 MM MACHINE CRUSHED				
		STONE JELLY AND WITH ABOUT (4.79 CU.M) 7670 KG. OF				
		SAND FOR MAKING 10M3 CONCRETE BUT EXCLUDING COST OF REINFORCEMENT GRILL AND FABRICATING				
		CHARGES, CENTERING AND SHUTTERING AND ALSO		(8)		
		INCLUDING LAYING, VIBRATING WITH MECHANICAL VIBRATORS, FINISHING, CURING ETC., COMPLETE				
		COMPLYING WITH STANDARD SPECIFICATION AND AS				
		DIRECTED BY THE DEPARTMENTAL OFFICERS, THE COARSE AND FINE AGGREGATES TO BE USED SHOULD				
		COMPLY WITH THE REQUIREMENTS OF IS STANDARDS.				
		(NO SEPARATE PAYMENT WILL BE MADE BY THE DEPARTMENT FOR THE EXCESS USAGE OF MATERIALS)				
	G .	SEL PRIMITION THE EXCESS USAGE OF WATERIALS)	3			72
	510.70 Cu.M.	(a) GROUND FLOOR		Rs.5200.00	1.Cu.M.	2655640.00
				(Rupees five thousand and two	(ONE CUBIC	
				hundred only)	METRE)	
	470.73 C. 84	(L) IN EIRET ELOOR		D- F200 00	1.Cu.M.	024505.00
	179.75 Cu.IVI.	(b) IN FIRST FLOOR		Rs.5200.00 V (Rupees five thousand and two	(ONE CUBIC	934596.0
				hundred only)	METRE)	
		MENT FOR V	192			
	183.07 Cu.M.	(c) SECOND FLOOR	14 5	Rs.5200.00	1.Cu.M.	951964.0
			43.64	(Rupees five thousand and two	(ONE CUBIC	
			25.0	hundred only)	merke, v	
	16.60 Cu.M.	(d) IN THIRD FLOOR		Rs.5500.00	1.Cu.M.	91300.0
				(Rupees five thousand and five	(ONE CUBIC METRE)	,
				hundred only)	METAL,	
954		RDICK WORK IN C. M. 4-C (ONE OF OFWENT AND ON				
9.5.1		BRICK WORK IN C.M. 1:6 (ONE OF CEMENT AND SIX			me inc,	
9.5.1		BRICK WORK IN C.M. 1:6 (ONE OF CEMENT AND SIX OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE				
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING				
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN				
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS				
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD				
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS				
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD				
9.5.1	425.20 Cu.M.	OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD			1.Cu.M.	1700800.0
9.5.1	425.20 Cu.M. ⁴	OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.		hundred only)	1.Cu.M. (ONE CUBIC	1700800.0
9.5.1	425.20 Cu.M. ⁴	OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.		hundred only) Rs.4000.00	1.Cu.M.	1700800.0
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS. (a) IN GROUND FLOOR		Rs.4000.00 (Rupees four thousand only)	1.Cu.M. (ONE CUBIC METRE)	1700800.0
9.5.1	425.20 Cu.M. ⁴	OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.		Rs.4000.00 (Rupees four thousand only)	1.Cu.M. (ONE CUBIC	1
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS. (a) IN GROUND FLOOR		Rs.4000.00 (Rupees four thousand only)	1.Cu.M. (ONE CUBIC METRE) 1.Cu.M.	1700800.0 639600.0
9.5.1		OF SAND) USING FLY ASH BRICKS OF SIZE 23X11X7CM FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS. (a) IN GROUND FLOOR		Rs.4000.00 (Rupees four thousand only)	1.Cu.M. (ONE CUBIC METRE) 1.Cu.M. (ONE CUBIC	1

CONMINETORIZING Parmer

NO. OF CORRECTIONS

TEM NO	YTITMAUC	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	TNUOMA
1	2	3	4	5	6	7
						38961059.40
	135.40 Cu.M.	(c) IN SECOND FLOOR		Rs.4000.00 (Rupees four thousand only)	1.Cu.M. (ONE CUBIC METRE)	541600.00
	16.40 Cu.M.	(d) IN THIRD FLOOR		Rs.4000.00 (Rupees four thousand only)	1.Gu.M. (ONE CUBIC METRE)	65600.00
0.5.1		BRICK PARTITION WALL IN C.M 1:4 (ONE OF CEMENT AND FOUR OF SAND) 110MM THICK FOR SUPER STRUCTURE USING FLY ASH BRICKS OF SIZE 23X11X7CM IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLD FASTS, SCAFFOLDING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.				¥ , *··· *
	888.70 Sq.M. ¥	(a) IN FOUNDATION AND BASEMENT		Rs.400.00 (Rupees four hundred only)	1.Sq.M. (ONE SQUARE METRE)	355480.0 ***
	741.50 Sq.M.	(b) IN GROUND FLOOR		Rs.400.00 (Rupees four hundred only)	1.Sq.M. (ONE SQUARE METRE)	296600.0
5.1	350.30 Sq.M.	(c) IN FIRST FLOOR		Rs.400.00 (Rupees four hundred only)	1.Sq.M. (ONE SQUARE	140120.0
	di	1 25 Y	2.3		METRE)	54
	35.70 Sq.M. 🕫	(d) IN SECOND FLOOR		Rs.400.00 (Rupees four hundred only)	1.Sq.M. (ONE SQUARE METRE)	14280.0
	194.90 Sq.M.	(e) IN THIRD FLOOR	11A	Rs.400.00 (Rupees four hundred only)	1.Sq.M. (ONE SQUARE METRE)	77960.0
1.5.1		BRICK PARTITION WALLS 70MM THICK USING FLY ASH BRICKS OF SIZE 23X11X7CM IN CEMENT MORTAR 1:4 (ONE OF CEMENT AND FOUR OF SAND) FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS INCLUDING SCAFFOLDINGS, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.				
	106.00 Sq.M.	(a) IN GROUND FLOOR		Rs.350.00 (Rupees three hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	37100.
	22.70 Sq.M.	(b) IN FIRST FLOOR		Rs.350.00 (Rupees three hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	7945.
	26.50 Sq.M.	(c) IN SECOND FLOOR		Rs.350.00 (Rupees three hundred and fifty	1.Sq.M. (ONE SQUARE	9275.
1	. ти [*] и		Te .	only)	METRE)	
						40507019.

Managing Raylner
CONTRACTOR



EW NO	QUANTITY	DESCRIPTION OF WORK	TNBP No	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	↑MOUNT
1	2	3	4	5	6	7
						40507019.40
4.2.1		SUPPLYING AND FIXING OF PRECAST CEMENT				
		CONCRETE SLAB FOR CUPBOARD/WARD ROBES				
		SHELVES, COVER SLAB FOR CHAMBERS, BAFFLE WALLS SIDE SLABS OF BOXING AROUND WINDOWS AND				
	T	OTHER SIMILAR WORKS IN STANDARDISED				
-		CONCRETE MIX M-30 GRADE IN ACCORDANCE WITH				
		IS: 456 - 2000 USING 3MM - 10MM HARD BROKEN				
		GRANITE STONE JELLY FOR THE ABOVE RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF				
		REINFORCEMENT GRILLS BUT INCLUDING PRECASTING,				
		MOULDING, CURING, FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD				
		SPECIFICATIONS ETC., COMPLETE IN THE FOLLOWING				
		FLOORS (MEASUREMENT WILL BE TAKEN INCLUDING BEARING IN WALL ALSO).			Je-	
4	71 × ×	DEPARTING IN VALLE ALSO).	1	स व व व व	3 × ×	
100		40MM THICK				
	21.80 Sq.M.	(a) IN FOUNDATION AND BASEMENT		Rs.700.00	1.Sq.M.	15260.0
				(Rupees seven hundred only)	(ONE SQUARE METRE)	
	~				,	
-	34.60 Sq.M.	(b) IN GROUND FLOOR		Rs.700.00	1.Sq.M.	24220.0
				(Rupees seven hundred only)	(ONE SQUARE	~
					METRE)	
	9.00 Sg.M.	(c) IN FIRST FLOOR		Rs.700.00	1.Sq.M.	6300.0
				(Rupees seven hundred only)	(ONE SQUARE	les es
					METRE)	
5.1.1		PROVIDING CUDDAPPAH SLAB OF 20MM THICK, FINISHING WITH TWO SIDES FOR CUPBOARD.				
	у.	WARDROBES SHELVES, AND OTHER SIMILAR WORKS			e (4)	
		INCLUDING FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD				
		SPECIFICATIONS ETC., COMPETE IN THE FOLLOWING				
		FLOORS (MEASUREMENT WILL BE TAKEN INCLUDING				
		BEARING ALSO) AS DIRECTED BY THE DEPARTMENTAL OFFICERS (QUALITY OF CUDDAPPAH SLAB SHALL BE				
		GOT APPROVED BY THE EXECUTIVE ENGINEER/				
		SUPERINTENDING ENGINEER/ CHIEF ENGINEER BEFORE USE IN WORKS)				
	197.10 Sα M ¥	(a) IN GROUND FLOOR		Rs.450.00	1.Sq.M.	88695.0
	Torrio oquin	(a) III diodita i zodi	A PA	(Rupees four hundred and fifty	(ONE SQUARE	000001
		7 4 6 2 2	rim.	only)	METRE)	
		Z				
	32.40 Sq.M.	(b) IN FIRST FLOOR		Rs.450.00 v	1.Sq.M. (ONE SQUARE	14580.0
				(Rupees four hundred and fifty only) ▶	METRE)	
				J,		
	37.80 Sq.M.	(c) IN SECOND FLOOR		Rs.450.00	1.Sq.M.	17010.0
	3.100 34.M.	(a) and the first index		(Rupees four hundred and fifty	(ONE SQUARE	17010.
				only)	METRE)	
18.1	/	PROVIDING FORM WORK AND CENTERING FOR				
		REINFORCED CEMENT CONCRETE WORKS INCLUDING SUPPORTS AND STRUTTING UP TO 3.30M HEIGHT FOR		W 1		
		PLANE SURFACES AS DETAILED BELOW WITH ALL				
		CROSS BRACINGS USING MILD STEEL SHEETS OF SIZE 90CMX60CM AND MS 10 GAUGE STIFFENED WITH			77 77 7	
		WELDED MILD STEEL ANGLES OF SIZE				
	(*)	25MMX25MMX3MM FOR BOARDING LAID OVER SILVER OAK OR COUNTRY WOOD JOISTS OF SIZE 10CMX6.5CM				
		SPACED AT ABOUT 90CM CENTRE TO CENTRE AND				
1		SUPPORTED BY CASURINA PROPS 10CM TO 13CM DIA SPACED AT 75CM INTERVALS AND REMOVING THE SAME				
		AFTER A SPECIFIED PERIOD WITHOUT DAMAGING THE		3.		
	- v	R.C.C WORKS ETC., COMPLETE COMPLYING WITH STANDARD SPECIFICATIONS AND AS DIRECTED BY THE			27	
		DEPARTMENTAL OFFICERS.		V	The state of the s	
	2447.00 Sq.M.	(a) FOR COLUMN FOOTINGS, PLINTH BEAM,		Rs.300.00	1.Sq.M.	734100.
	V	GRADE BEAM, RAFT BEAM, RAFT SLAB ETC.,		(Rupees three hundred only)	(ONE SQUARE METRE)	
					:,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
For	SMP As	ociates				4440740
01						41407184

Managing Parmer

NO. OF CORRECTIONS

A NO	NUMBER	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
1	2	3	4	5	6	7
						41407184.40
	6051.00 Sq.M.	(b) PLAIN SURFACES SUCH AS ROOF SLAB,		Rs.300.00	1.Sq.M.	1815300.00
		FLOOR SLAB, BEAMS, LINTELS, LOFTS, SILL		(Rupees three hundred only)	(ONE SQUARE METRE)	-
		SLAB, STAIRCASE WAIST, PORTICO SLAB AND		*	me me	
		OTHER SIMILAR WORKS				
				/-		
	1464.10 Sq.M.	(c) FOR SQUARE AND RECTANGULAR COLUMNS		Rs.300.00	1.Sq.M.	439230.00
		AND SMALL QUANTITIES SUCH AS SUNSHADE,		(Rupees three hundred only)	(ONE SQUARE METRE)	1
		PARAPET CUM DROPS WINDOW BOXING, FIN			WEIRE)	
		PROJECTION AND OTHER SIMILAR WORKS.				
э.				300000		
200						
	1181.20 Sq.M.	(d) FOR VERTICAL WALL		Rs.500.00	1.Sq.M.	590600.00
				(Rupees five hundred only)	(ONE SQUARE	•90
- 1					METRE)	
	0.00 5	(a - a - a - a - a - a - a - a - a - a		D= 4000 00	4.00.00	0000
	6.80 Sq.M.	(f) FOR CURVED SURFACE		(Rupees one thousand only)	1.Sq.M. (ONE SQUARE	6800.0
					METRE)	-
5.2	31.60 Sq.M.	PROVIDING AND FIXING OF FACTORY MADE		Rs.2000.00 V	1.Sq.M.	63200.0
10	/	UNPLASTICIZIED POLYVINYL CHLORIDE (UPVC)		(Rupees two thousand only)	(ONE SQUARE	b
		DOOR FRAME OF SIZE 50X47MM WITH A WALL			METRE)	
		THICKNESS OF 5MM, MADE OUT OF EXTRUDED 5MM RIGID UPVC FOAM SHEET, MITERED AT TWO CORNERS				
		AND JOINED WITH 2 NOS. OF 150MM LONG BRACKETS				
		OF 15X15MM M.S SQUARE TUBE. THE TWO VERTICAL AND HORIZONTAL DOOR PROFILES ARE TO BE				
		REINFORCED WITH 19X19MM M.S SQUARE TUBE OF 19 GAUGES WITH PRIMER COAT. THE DOOR FRAME SHALL	1 -7 -			
		BE FIXED TO THE WALL USING 65MM/100MM LONG M.S				
		SCREW THROUGH THE FRAME BY USING PVC FASTENERS, A MINIMUM OF 4 NOS. SCREWS TO BE				
		PROVIDED FOR EACH VERTICAL MEMBER AND MINIMUM				2 //
		2 NOS. FOR HORIZONTAL MEMBER ETC., PROVIDING AND FIXING OF 30MM THICK FACTORY MADE DOOR	VI THE			
		SHUTTER WITH UNPLASTICIZED POLYVINYL CHLORIDE				
		(UPVC) SOLID PANEL FOAM SHEET, STRUCTURED WITH M.S.TUBE OF 19 GAUGE THICKNESS AND SIZE 19MM X				
		19MM FOR STYLES AND 15MM X 15MM FOR TOP RAIL AND BOTTOM RAIL. PANELLING OF 5MM THICK UPVC				
		ONE SIDE PRINTED LAMINATION SINGLE SHEET TO BE		A de sura		
		FITTED IN THE M.S.FRAME WELDED / SEALED TO THE STYLES AND RAILS COVERED WITH 5MM THICK HEAT		IAJO		
		MOULDED UPVC 'C' CHANNEL OF 30MMX50MM AND 5MM				
		THICK 75MM WIDE UPVC SHEET FOR TOP RAIL. LOCK RAIL AND BOTTOM RAIL ON EITHER SIDE AND 10MM				
		(5MM X 2 NOS.) THICK, 20MM WIDE CROSS UPVC SHEET				
		AS GAP INSERT FOR TOP RAIL AND BOTTOM RAIL, AND	1)		15.	
		JOINED TOGETHER WITH PVC SOLVENT CEMENT ADHESIVE AN ADDITIONAL 5MM THICK UPVC STRIP OF				
		20MM WIDTH IS TO BE STUCK ON THE INTERIOR SIDE OF THE 'C' CHANNEL USING PVC SOLVENT CEMENT				
		ADHESIVE. THE COST AND LABOUR CHARGES FOR				
		FIXING OF 3 NOS. 4" SS BUTT HINGES AND ALUMINIUN FURNITURE FITTING SUCH AS 1 NO. 4" TOWER BOLT, 1				
		NO.5" ALDROP, 2 NOS. 6" FLAT 'D' TYPE HANDLE, ETC				
		ARE INCLUDED. THE FITTING PROVIDED SHALL BEAR IS MARKS. TO ENSURE THE GENUINITY OF PRODUCT, THE				
		DOOR SET SHOULD HAVE 4 NUMBERS OF				
		MANUFACTURER'S LOGO HOLOGRAM OF APPROVED BRAND, EACH AT FRAME, STYLE, RAIL AND INNER				
		PANEL. (THE QUALITY AND BRAND OF DOOR SHUTTER				IX.
		AND FURNITURE FITTINGS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)		9:		
					= =====================================	
2						2 2 X
						44322314

For SMP Associates,

Managing Patiner
CONTRACTOR

NO. OF CORRECTIONS

1	QUANTITY 2	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	7 44322314.40
21.5.3	242.80 Sq.M.	SUPPLYING AND FIXING UPVC (UN PLASTICIZED POLYVINYL CHLORIDE) WINDOWS OF CASEMENT TYPE (OPEN) FROM THE PROFILE THE SIZE OF OUTER FRAME 60MMX58MM AND SHUTTER PROFILE ARE REINFORCEMENT WITH GI/IMM 125GSM AND 100% CORROSION FREE, THE PROFILES ARE MULTI CHAMBERED SECTIONS WITH WALL THICK OF 2MM. THE EPDM RUBBER (BLACK COLOUR) COVERED WITH OVER ALL THE EDGES OF FRAME AND SHUTTER, THE SHUTTER WILL BE PROVIDED WITH ESPAG MULTI POWER POINT LOCKS AND ALSO IT OPERATES AS HANDLE. THE CORNERS AND JOINTS SHOULD BE WELDED AND CLEANED, RADIATIONS FREE PIN HEADED PLAIN OR BROWN COLOUR GLASS-4MM.THICK.SHOULD		Rs.4000.00 (Rupees four thousand only)	1.Sq.M. (ONE SQUARE METRE)	971200.00
		BE PROVIDED TO THE SHUTTER AND IT SHOULD NOT ALLOW LEAKAGE OF WATER EVEN AT MOST RANGING STORMS AND SHOULD HAVE KEY LOCKABLE ACTION, SECURITY PROTECTIVE HINGES, STRONG LOCKING SYSTEMS AND AS PER SIZE FOR ARRESTING NOISE AND ENERGY LOSS. THE CONNECTING MECHANISM BETWEEN SASH AND OUTER FRAME THAT ENABLES OPENING OF THE WINDOW, THE WINDOW SHOULD BE FIXED TO THE WALL WITH 100% PACKING WITH SCREWS AND SILICON PACKING ALL ROUND THE FRAMES ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE BRAND AND QUALITY OF THE WINDOW SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER., BEFORE USE)				
21.5.4	3.30 Sq.M.	SUPPLYING AND FIXING UPVC (UN PLASTICIZED POLYVINYL CHLORIDE) LOUVERED VENTILATORS OF FROM THE PROFILE THE SIZE OF OUTER FRAME 60MMX58MM AND SHUTTER PROFILE SIZE OF 60X78MM BOTH PROFILES ARE REINFORCED WITH GI/1MM 125GSM AND 100% CORROSION FREE, THE PROFILE ARE MULTI CHAMBERED SECTIONS WITH WALL THICK OF 2MM. THE EPDM RUBBER (BLACK COLOUR) COVERED WITH ALL OVER THE EDGES OF FRAME AND		Rs.4000.00 (Rupees four thousand only)	1.Sq.M. (ONE SQUARE METRE)	13200.00
		SHUTTERS. THE CORNERS AND JOINTS SHOULD BE WELDED AND CLEANED. RADIATIONS PIN HEADED GLASS 4MM THICK SHOULD BE PROVIDED IN THE LOUVERS. THE WINDOW SHOULD BE FIXED TO THE WALL WITH 100% PACKING WITH SCREWS AND SILICON PACKING ALL ROUND THE FRAMES ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF THE VENTILATOR SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER., BEFORE USE)	97	BLAN		
22.9		SUPPLYING AND FIXING OF SINGLE LEAF SOLID CORE FLUSH DOOR SHUTTERS USING TEAK WOOD PLY AS PER IS 303-1989, THE CROSS BAND AND FACE VENEERS ARE TO BE BANDED WITH PHENOL FORMALDEHYDE SYNTHETIC RESIN IN HOT PRESS BOTH SIDES AND MANUFACTURING THE SHUTTER BY USING QUALITY TIMBER OF TERMITE PROOF AND SEASONED TO MOISTURE CONTENT NOT MORE THAN 10%, HOT PRESSED WITH HYDRAULIC PRESS AT A TEMPERATURE OF 1500C TO THE NORMS AS PER IS 2002-1983 AND TW PLY ON BOTH SIDE WITH TEAK WOOD LIPPING AROUND, 35MM THICK INCLUDING COST		# *		
3		AND FIXING OF ALUMINIUM FURNITURE FITTINGS SUCH AS 2 NOS, OF 6" DOOR HANDLE, 5 NOS, OF 5" BUTT HINGES, 2 NOS. OF 6"X1/2" TOWERBOLT, 1 NO. OF 10"X5/8" ALDROP, 1 NO 40MM DIA & 60MM LONG RUBBER BUSH, 1 NO. OF ALUMINIUM DOOR STOPPER WITH RUBBER BUSH WITH REQUIRED BRASS SCREWS, LABOUR CHARGES FOR WROUGHT AND PUTUP AND FIXING IN POSITION OF FLUSH DOOR SHUTTERS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND OF MATERIALS SHOULD BE GOT		, 2	3 70	

Commenting Partner

NO. OF CORRECTIONS

W.NO	YTITHAU	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	AMOUNT
7 /	2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS	7
		-				45306714.40
	50.40.5.44			Rs.2500.00	1.Sq.M.	126000 0
	50.40 Sq.M.	SUITABLE FOR DOOR OF SIZE (b) 1000 x 2100MM		(Rupees two thousand and five	(ONE SQUARE	126000.0
		(5) 1000 % 2100		hundred only)	METRE)	
					·	
.9.1		SUPPLYING AND FIXING OF DOUBLE LEAF SOLID				
1		CORE FLUSH DOOR SHUTTERS USING BOILED				
		WATER RESISTANCE (BWR) TEAK WOOD PLY AS PER IS 303-1989, THE CROSS BAND AND FACE VENEERS ARE				
		TO BE BANDED WITH PHENOL FORMALDEHYDE SYNTHETIC RESIN IN HOT PRESS BOTH SIDES AND				
	700 PM 04	MANUFACTURING THE SHUTTER BY USING QUALITY	· V			
		TIMBER OF TERMITE PROOF AND SEASONED TO MOISTURE CONTENT NOT MORE THAN 10%, HOT				e es *
		PRESSED WITH HYDRAULIC PRESS AT A TEMPERATURE OF 1500C TO THE NORMS AS PER IS 2002-1983 AND TW	2			
		PLY ON BOTH SIDE WITH TEAK WOOD LIPPING AROUND, 35MM THICK INCLUDING COST AND FIXING OF				
		ALUMINIUM FURNITURE FITTINGS SUCH AS 4 NOS. OF				20
		6" DOOR HANDLE, 10 NOS, OF 5" BUTT HINGES, 3 NOS.				
		OF 6"X1/2"" TOWER BOLT, 1 NO. OF 10"X5/8" ALDROP, 2 NOS. OF 40MM DIA & 60MM LONG RUBBER BUSH, 2 NOS.				
		ALUMINIUM DOOR STOPPER WITH RUBBER BUSH WITH REQUIRED BRASS SCREWS, LABOUR CHARGES FOR		1. (0)		
		WROUGHT AND PUT UP AND FIXING IN POSITION OF FLUSH DOOR SHUTTERS AND AS DIRECTED BY THE				
		DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND			man har	
		OF MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE.)				
	12.60 Sq.M.	SUITABLE FOR DOOR OF SIZE (a) 1200 × 2100MM		Rs.2200.00 <	1.Sq.M. (ONE SQUARE	27720.
	Entere Property and Property an	(4) 1300 X 2100		hundred only)	METRE)	
		* **				
9.8	300.20 Sq.M.	SUPPLYING AND FIXING OF COLOUR GLAZED TILES		Rs.700.00	1.Sq.M.	210140
	300.20 3q.ivi.	OF BEST APPROVED QUALITY (THE COLOUR AND		(Rupees seven hundred only)	(ONE SQUARE	210140
		SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT			METRE)	
		PLASTERING IN CM 1:2 (ONE OF CEMENT AND TWO OF SAND) 10MM THICK INCLUDING FIXING IN POSITION,				
		CUTTING THE TILES TO THE REQUIRED SIZE				
- 1		WHEREVER NECESSARY, POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING				
		ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY				
		OF TILES SHOULD BE GOT APPROVED FROM THE		MAIR		
		EXECUTIVE ENGINEER BEFORE USE).		" A REE 1948		
			- 7			14-17
					40.11	
	111.50 Sq.M.	SUPPLYING AND LAYING OF CERAMIC TILES (ANTI- SKID) OF BEST APPROVED QUALITY FOR FLOORING		Rs.700.00 (Rupees seven hundred only)	1.Sq.M. (ONE SQUARE	78050
9.9	/		1		METRE)	
9.9	/	AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE				
	/	I		1		
	/	AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK				
		AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY				
		AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT)				
		AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE				
		AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF TILES SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE				
		AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE BRAND AND QUALITY OF TILES SHOULD BE GOT				
		AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTOR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF TILES SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE				

For SMP Associates

Managing Partner

NO. OF CORRECTIONS

SUPERINTENDING ENGINEER/SOUTH CIRCLE.

45748624.40

TEM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	MOUNT
4 1	2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS	7
						45748624.40
32.1.2	1861.70 Sq.M.	FINISHING THE TOP OF TERRACE FLOOR WITH ONE COURSE OF SOLAR REFLECTIVE WATER PROOF, HEAT PROOF AND COOL ROOF CERAMIC TILES OF SIZE 305MMX305MMX7MM THICK OF APPROVED QUALITY LAID IN CEMENT MORTAR 1:3 20MM TK (ONE PART OF CEMENT AND THREE PARTS OF SAND) MIXED WITH		Rs.700.00 (Rupees seven hundred only)	1.Sq.M. (ONE SQUARE METRE)	1303190.00
(₹) =	2	CALCIUM BASED MINERAL POWDER (60 KG FOR 1000 SQFT) (BEFORE LAYING THE TILES, THE TILES SHOULD BE DIPPED WITH SALIN BASED NANO LIQUID) AND TOP GROUTING WITH CEMENT MORTAR 1:3 (ONE PART OF CEMENT AND THREE PARTS OF SAND) MIXED WITH WHITE CEMENT, SILICON POWDER AND POLIMER ADHESIVE (20 KG FOR 1000 SQFT.) AND JOINT POINTED WITH ZYCOSIL OIL (200GM FOR 1000 SQFT.) AFTER GROUTING ACRYLIC SALINE BASED LIQUID WITHOUT	1		4 · · · ·	± :00 1964
æ		BASE CONCRETE INCLUDING POINTING ETC., COMPLETE COMPLYING WITH STANDARD SPECIFICATION INCLUDING COST OF ALL MATERIALS LABOUR CHARGES FOR LIFTING TO OPEN TERRACE, LAYING AND FINISHING AND OTHER INCIDENTAL CHARGES ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (BRAND, QUALITY OF TILES SHOULD BE GOT APPROVED FROM EXECUTIVE ENGINEER BEFORE USE)				
	q			THE PARTY		
35.1	81.34 Sq.M.	PLASTERING IN CM 1:3 (ONE OF CEMENT AND		Rs.150.00 (Rupees one hundred and fifty	1.Sq.M. (ONE SQUARE	12201.0
		PROOF COMPOUND AT 2% BY WEIGHT OF CEMENT		only)	METRE)	
		FOR SUMP INCLUDING SCAFFOLDING CURING, FINISHING ETC., COMPLETE IN ALL RESPECTS AND		The state of the s		
		COMPLYING WITH STANDARD SPECIFICATIONS				
38.4.1	5983.93 Sq.M.	PAINTING THE NEW WALLS WITH TWO COATS OF OIL BOUND DISTEMPER OVER THE EXISTING PRIMING		Rs.40.00 (Rupees forty only)	1.Sq.M. (ONE SQUARE	239357.2
-		COAT OF WHITE CEMENT OF APPROVED BRAND OVER NEW CEMENT PLASTERED WALL SURFACES INCLUDING			METRE)	
		COST OF PAINTS, PUTTY, BRUSHES, WATERING, CURING, ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (PAINTS AND ITS SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	MAN /	NJ8		
	5000.00.00	× × × × × × × × × × × × × × × × × × ×			4.00.00	440070
38.6	5983.93 3 q.M.	PAINTING PRIMER COAT USING APPROVED QUALITY OF WHITE CEMENT OVER THE CEMENT PLASTERED / CONCRETE NEW WALL SURFACES, CEILING OR OTHER SIMILAR WORKS INCLUDING COST OF WHITE CEMENT, PUTTY, BRUSHES, WATERING, CURING, ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL		Rs.20.00 (Rupees twenty only)	1.94.M. (ONE SQUARE METRE)	119678.6
44		OFFICERS.	1			
					1	
43.1.1	216.415 M.T.	SUPPLYING, FABRICATING AND PLACING IN POSITION OF MILD STEEL GRILLS/RIBBED TOR STEELS (WITHOUT CEMENT SLURRY) OF ALL DIAMETERS FOR REINFORCEMENT FOR ALL FLOORS INCLUDING COST OF BINDING WIRE, INSULATED WITH PVC, BENDING, TYING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.53000.00 (Rupees fifty three thousand only)	1 M.T. (ONE METRIC TONNE)	11455685.

						58878736

Managing Partier
CONTRACTOR

NO. OF CORRECTIONS

EM,NO	UANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT 7
1	2	.3	4	3	J.	58878736.20
4.2.a	- /	PROVIDING RAIN WATER HARVESTING PIT OF 1M DIA AND 600MM DEPTH OF EARTH WORK EXCAVATION AND FILLING THE PIT WITH 40MM STONE JELLY TO A DEPTH OF 300MM FROM THE TOP OF THE AUGERING PORTION AND FILLING WITH SAND TO A DEPTH OF		Rs.1300.00 (Rupees one thousand and three hundred only)	1.NO. (EACH)	26000.00
T.		300MM OVER THE STONE JELLY AND COVERED WITH THE PRE-CAST RCC PERFORATED SLAB OF 40MM THICK IN STANDARDISED CONCRETE MIX M-30 GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING 3MM-10MM HARD BROKEN GRANITE STONE JELLY FOR ALL RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING, FINISHING AND FIXING IN POSITION ETC., ALL	- 4°20			* - 8
		COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
4.2.b	60.00 Rmt.	AUGERING 30CM DIA BORE HOLE IN ALL SOILS AND SUB SOILS REQUIRED DEPTH TO PROVIDING RAIN WATER HARVESTING FROM THE CENTRE OF THE RAIN WATER HARVESTING PIT ALREADY EXCAVATED AS DIFLILING THE AUGUERING PORTION WITH 40MM SIZE STONE JELLY ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.300.00 (Rupees three hundred only)	1. Rmt. (ONE RUNNING METRE)	18000.00
14.6.1	360.80 Rmt.	SUPPLYING AND FIXING OF 110MM DIA PVC SWR PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'A' FOR RAIN WATER DOWN FALL PIPE (TO BE GOT APPROVED FROM THE EXECUTIVE ENGINEER,, SUPERINTENDING ENGINEER,, CHIEF ENGINEER, BEFORE USE IN WORKS) WITH RELEVANT SPECIALS SUCH AS GRATINGS, SHOES, BENDS, OFFSETS	u sk	Rs.250.00 (Rupees two hundred and fifty only)	1. Rmt. (ONE RUNNING METRE)	90200.0
		CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING IS 5382 WITH LEAVING A GAF ABOUT 10MM TO ALLOW THERMAL EXPANSION WITH NECESSARY UPVC "U" BRACKET/CLAMPS, TEAK WOOD PLUGS, ETC., OF APPROVED QUALITY AND INCLUDING FIXING C.I GRATINGS AT THE JUNCTION OF PARAPET AND FLOOR OR ROOF SLAB ETC., INCLUDING FINISHING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	ИА			
45.1	3908.00 Sq.M.	STUCCO PLASTERING 12MM THICK USING COLOUF MARBLE CHIP3 OF SIZE 10MM AND BELOW USING 72.00 KGS OF CEMENT 14.50 KGS OF COLOUR CEMENT AND 0.15 CUM. COLOUR MARBLE CHIPS FOR EVERY 10SQLM AREA OVER THE EXISTING PLASTERED SURFACE INCLUDING CURING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	1	Rs.200.00 (Rupees (wo hundred only)	1.Sq.M. (ONE CQUARE METRE)	781600.
50.6	424.80 Sq.M.	SUPPLYING AND FIXING OF FIBRE MIXED PRECAST SLAB OF 50MM THICK OF ALL REQUIRED SHAPES MADE IN CEMENT CONCRETE 1:3:6(ONE OF CEMENT THREE OF SAND AND SIX OF 20MM HARD BROKEN STONE JELLY) USING 20MM HARD BROKEN STONE JELLY MIXED WITH SECONDARY REINFORCEMENT FIBRE OF APPROVED QUALITY AT 0.25% BY WEIGHT OF CEMENT (125GM OF FIBRE FOR 1BAG I.E., 50KG OF CEMENT) USED INCLUDING COST OF ALL MATERIALS MOULDING, CURING, TRANSPORTATION, LAYING		Rs.250.00 (Rupees two hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	106200.
2		POINTING ETC., FOR APPROACH.ROAD, PAVEMEN SLAB AND OTHER CIMILAR WORKS ETC., COMPLETE APER THE RELEVANT STANDARD SPECIFICATIONS AN AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THIS SHAPE OF SLAB AND BRAND AND QUALITY OF FIBR SHOULD BE GOT APPROVED FROM THE EXECUTIVENGINEER BEFORE USE)	T S D E		7	(2)
	1.1					الما و الما

Managing Rarmer

NO. OF CORRECTIONS

Sakkarakottai Bell of Arms (Gr-II)

IEM NO	QUANTITY	DESCRIPTION OF WORK	TNRP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	MOUNT 7
1		3	4	5	6	59900736.20
52.2		SUPPLYING, LAYING, FIXING AND JOINING THE FOLLOWING PVC PIPES AS PER ASTM D-1785 OF SCHEDULE 40 OF WALL THICKNESS NOT LESS THAN THE SPECIFIED IN IS 4985 SUITABLE FOR PLUMBING BY THREADING OF WALL THICKNESS INCLUDING THE COST OF SUITABLE UPVC SPECIALS LIKE ELBOW, TEE, REDUCERS, PLUG, UNIONS, BEND, COUPLER, NIPPLE, UPVC GATE VALVE, UPVC CHECK AND UPVC/BALL VALVE WHEREVER REQUIRED ABOVE THE GROUND LEVEL INCLUDING THE COST OF TEFLON TAPE, PVC SPECIAL CLAMPS, NAILS ETC., FIXING ON WALL TO THE PROPER GRADIENT AND ALIGNMENT AND REDOING THE CHIPPED OF MASONRY ETC., AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (BRAND NAME AND QUALITY OF PVC/UPVC PIPES AND SPECIALS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER./ SUPERINTENDING ENGINEER./ CHIEF ENGINEER./ BEFORE USE IN WORKS)				one in Artic
	146.04 Rmt.	(a) 32MM ASTM-D SCHEDULE 40 THREADED PVC PIPE WITH NECESSARY UPVC SPECIALS AND PVC SPECIAL CLAMP ETC.,		Rs.150.00 (Rupees one hundred and fifty only)	1. Rmt. (ONE RUNNING METRE)	21906.00
		w - - - -				
	326.82 Rmt.	(b) 25MM ASTM-D SCHEDULE 40 THREADED PVC PIPE WITH NECESSARY UPVC SPECIALS AND PVC SPECIAL CLAMP ETC.,		Rs.140.00 (Rupees one hundred and forty only)	1. Rmt. (ONE RUNNING METRE)	45754.8
				The state of the s		
52.4.1		SUPPLYING, LAYING, FIXING AND JOINING THE FOLLOWING PVC PIPES AS PER ASTM D-1785 OF SCHEDULE 40 OF ALL THICKNESS NOT LESS THAN THE SPECIFIED IN IS 4985 SUITABLE FOR PLUMBING BY THREADING OF WALL THICKNESS INCLUDING THE COST OF SUITABLE UPVC SPECIALS LIKE ELBOW, TEE, REDUCERS, PLUG, UNIONS, BEND, COUPLER, NIPPLE, UPVC GATE VALVE, UPVC CHECK AND UPVC/BALL VALVE WHEREVER REQUIRED ABOVE THE GROUND LEVEL INCLUDING THE COST OF TEFLON TAPE, PVC SPECIAL CLAMPS, NAILS ETC., FULLY CONCEALED FIXING ON WALL TO THE PROPER GRADIENT AND ALIGNMENT AND REDOING THE CHIPPED OF MASONRY ETC., AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (BRAND NAME AND QUALITY OF PVC/UPVC PIPES AND SPECIALS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER/ SUPERINTENDING ENGINEER/CHIEF ENGINEER BEFORE USE IN WORKS)	1/1/	18		
	160.22 Rmt.	(c) 20MM ASTM-D SCHEDULE 40 THREADED PVC PIPE WITH NECESSARY UPVC SPECIALS AND PVC SPECIAL CLAMP ETC.,		Rs.140.00 (Rupees one hundred and forty only)	1. Rmt. (ONE RUNNING METRE)	22430.8
53.4	4 NOS.	SUPPLYING AND FIXING OF C.I. MANHOLE COVER		Rs.2000.00	1.NO.	8000.0
-		WITH LOCKING ARRANGEMENTS OF APPROVED QUALITY AND BRAND OF SIZE 0.6 M X 0.6 M(50 KG) AS PER STANDARD SPECIFICATIONS INCLUDING COST OF MATERIAL, LABOUR CHARGES FOR FIXING ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		(Rupees two thousand only)	(EACH)	
	1 . (*)				e r'e	a,
		sociates				

CONTRACTOR

Sometions 2 No. of corrections

31- OF SECU SUPERINTENDING ENGINEER/SOUTH CIRCLE.

TEM NO	ZUVNILLA	DESCRIPTION OF WORK	TNRP No	RATE FXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	TAUOMA
1	2	3	4	5	6	7
		_ 2				59998827.80
-0.5	40 1105	CHICALVING AND FIXING OF DODGELIN WACH HAND		Rs.2200.00	1.NO.	41800.00
53.5	19 NOS.	SUPPLYING AND FIXING OF PORCELIN WASH HAND BASIN (WHITE), SUPERIOR VARIETY OF SIZE		(Rupees two thousand and two	(EACH)	1/1000101
		550X400MM WITH ALL ACCESSORIES SUCH AS POWDER		hundred only)		
		COATED CAST IRON BRACKETS, 32MM DIA C.P. WASTE COUPLING, RUBBER PLUG AND ALUMINIUM CHAIN,				
		32MM DIA 'B' CLASS G.I. PVC WASTE PIPE, ANGLE				
		VALVE, 15MM DIA NYLON CONNECTION, 15MM DIA BRASS NIPPLES, 15MM C.P. PILLAR TAP & REQUIRED				
		GRATING ETC., COMPLETE IN ALL RESPECTS (WASH HAND BASIN SHALL BE GOT APPROVED BY THE				
		EXECUTIVE ENGINEER BEFORE FIXING).				
. 4					16	· · · · · · · · · · · · · · · · · · ·
54.1.2	47 NOS.	SUPPLYING AND FIXING OF 15MM DIA ENGINEERING		Rs.200.00 ¥	1.NO.	9400.00
/		POLYMER TAP (LONG BODY) INCLUDING COST OF		(Rupees two hundred only)	(EACH)	
		MATERIALS, LABOUR CHARGES FOR FIXING ETC., AND ALL COMPLETE AND AS DIRECTED BY THE			-	
		DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND				
		OF ENGINEERING POLYMER TAP SHOULD BE GOT APPROVED FROM THE EXECUTIVE				
		ENGINEER/SUPERINTENDING ENGINEER/ CHIEF ENGINEER BEFORE USE IN WORKS)				
	V					
54.2.2	33 NOS.	SUPPLYING AND FIXING OF 15MM DIA ENGINEERING		Rs.200.00	1.NO.	6600.0
		POLYMER TAP (SHORT BODY) INCLUDING COST OF MATERIALS, LABOUR CHARGES FOR FIXING ETC., AND		(Rupees two hundred only)	(EACH)	
		ALL COMPLETE AND AS DIRECTED BY THE				
		DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND OF ENGINEERING POLYMER TAP SHOULD BE GOT				
		APPROVED FROM THE EXECUTIVE ENGINEER, /SUPERINTENDING ENGINEER, /CHIÉF				
		ENGINEER,, BEFORE USE IN WORKS)			T-7	
	40					
56.3.1	6 NOS.	SUPPLYING AND FIXING OF INDIAN WATER CLOSET		Rs.2200.00	1.NO.	13200.0
/	2	WHITE GLAZED (ORIYA TYPE) OF SIZE		(Rupees two thousand and two	(EACH)	-
		580MMX440MM OF APPROVED MAKE WITH ISI MARK (TO BE GOT APPROVED FROM THE EXECUTIVE ENGINEER		hundred only)		
		BEFORE USE) WITH PVC SWR GRADE P OR S TRAP	光色多数	Nel Cl		
		WITH EARTH, FLOORING THE AREA WITH 75MM THICK				
		BRICK JELLY CONCRETE IN CC 1:8:16 (ONE OF CEMENT, EIGHT OF SAND AND SIXTEEN OF BRICK JELLY) USING				
		40MM SIZE BRICK JELLY AND TOP LEFT ROUGH TO	-			
		RECEIVE THE FLOOR PLASTERING BUT INCLUDING ANTISYPHONAGE CONNECTION, CURING, ETC. ALL				
		COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (IN GROUND FLOOR)				
	4			Pr 2500 00	1.NO.	10000.0
56.4.1	4 NOS.	SUPPLYING AND FIXING OF INDIAN WATER CLOSET WHITE GLAZED (ORIYA TYPE) OF SIZE		Rs.2500.00 (Rupees two thousand and five	(EACH)	10000.0
		580MMX440MM OF APPROVED MAKE WITH ISI MARK (TO		hundred only)		
		BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE) WITH PVC SWR GRADE P OR S TRAF				
		WITH BRICK JELLY LIME CONCRETE PROPORTION OF				
		BRICK JELLY TO LIME BEING 32:121/2 BY VOLUME (32 CF)	-			
		OF 20MM GAUGE BRICK JELLY AND 12 1/2 CFT OF SLAKED LIME) (NO SAND) AND TOP 75MM THICK BRICK	(
		JELLY CONCRETE IN CC 1:8:16 (ONE OF CEMENT, EIGHT OF SAND AND SIXTEEN OF BROKEN BRICK JELLY				
		USING 40MM SIZE BRICK JELLY INCLUDING PLASTERING				
	e e	THE SIDES OF SUNK PORTION IN CM 1:3 (ONE OF CEMENT AND THREE OF SAND) 12MM THICK	<			
		MIXED WITH WATER PROOFING COMPOUND AT	T.			
	15 "	PLOOR PLASTERING BUT INCLUDING ANTISYPHONAGE	Ē	2. 77	- "	10 d
		CONNECTION, ONE COAT OF BITUMEN FOR THE SIDES BOTTOM AND CURING ETC., COMPLETE IN ALL FLOORS				
		(OTHER THAN GROUND FLOOR)				
Foi	SMP A.	ssociates				60079827

Managing Pariner

NO. OF CORRECTIONS

Sakkarakottai Bell of Arms (Gr-II)

EM,NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
1	2	3	-4	5	6	7 60079827.80
57.2	8 NOS.	SUPPLYING AND FIXING EWC (WHITE) SUPERIOR VARIETY 500MM WITH PVC SWR GRADE 'P' OR 'S' TRAP INCLUDING COST AND FIXING OF DOUBLE FLAPPED PLASTIC SHEET COVER PVC FLUSHING CISTERN IN APPROPRIATE LEVEL AS DIRECTED BY THE DEPARTMENTAL OFFICERS AT A MAXIMUM LEVEL OF 5'6" AND OF APPROVED BRAND OF 10 LITRES CAPACITY INCLUDING FITTINGS SUCH AS CI BRACKETS. PVC CONNECTION GM WHEEL VALVE, HEX NIPPLE, ETC., COMPLETE (EWC AND PLASTIC COVER SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE FIXING).		Rs.5000.00 (Rupees five thousand only)	1.NO. (EACH)	40000.00
6		e		45 16 767 A		2 18°
58.3		SUPPLYING AND FIXING THE FOLLOWING DIA PVC (SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'B' FOR SOIL LINE WITH RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING TO IS 5382 WITH LEAVING A GAP ABOUT 10MM TO ALLOW THERMAL EXPANSION, FIXING THE PIPES INTO WALLS WITH NECESSARY WOODEN PLUG, SCREWS, HOLDING WHEREVER NECESSARY AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	×			
	159.10 Rmt.	(a) 110MM DIA PVC SWR PIPE INCLUDING ALL		Rs.400.00	1.Rmt.	63640.00
		REQUIRED PVC SPECIALS ETC., ALL COMPLETE.		(Rupees four hundred only)	(ONE RUNNING METRE)	
	164.55 Rmt	(b) 75MM DIA PVC SWR PIPE INCLUDING ALL REQUIRED PVC SPECIALS ETC., ALL COMPLETE.		Rs.300.00 (Rupees three hundred only)	1.Rmt. (ONE RUNNING METRE)	49365.0
58.4	36.00 Rmt.	SUPPLYING, LAYING AND CONCEALING THE 50MM DIA PVC (SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'B' FOR WASTE WATER LINE WITH RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	9 1	Rs.80.00 (Rupees eighty only)	1.Rmt. (ONE RUNNING METRE)	2880.0
58.5		SUPPLYING AND FIXING THE FOLLOWING DIA PVC(SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992-TYPE 'A' WITH PVC COWL AND RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING TO IS 5382 WITH LEAVING A GAP 10MM TO ALLOW THERMAL EXPANSION AND FIXING THE PIPES INTO WALLS OR OVER THE SEPTIC TANK WITH NECESSARY WOODEN PLUG, SCREWS, HOLDING WHEREVER NECESSARY AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
	2 NOS.	(a) 110MM DIA PVC SWR PIPE OF 3METRE WITH REQUIRED PVC COWL & PVC SPECIALS ETC., ALL COMPLETE.		Rs.500.00 (Rupees five hundred only)	1.No. (EACH)	1000.0
	•	* * * * * * * * * * * * * * * * * * * *				- 4
		sociates				60236712.8

Managing Purmer

NO. OF CORRECTIONS



rew.No	YTITABUQ	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	THUOMA
1	2	3	4	5	£	7 60236 712. 80
59.5,1		SUPPLYING AND FIXING 150MM X 100MM SIZE STONE WARE GULLY TRAP WITH IRON GRATINGS OVER A BED OF 150MM THICK BRICK JELLY CONCRETE IN CC 18:16 (ONE OF CEMENT, EIGHT OF SAND AND SIXTEEN OF BROKEN BRICK JELLY) USING 40MM SIZE BRICK JELLY AND BRICK MASONRY WALL 110 MM THICK USING FLY ASH BRICKS OF SIZE (23X11X7CM) IN CM 1:5 (ONE OF CEMENT AND FIVE OF SAND) PLASTERED WITH CM 1:3 (ONE OF CEMENT AND THREE OF SAND) 12MM THICK ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.700.00 (Rupees seven hundred only)	1.NO. (EACH)	14700.00
61.1.1	*	SUPPLYING, LAYING AND JOINTING THE FOLLOWING DIA UPVC NON PRESSURE PIPE OF SN8 SDR 34 (S 16.5) AS PER IS 15328/2003, SUPERIOR VARIETY AND TESTED WITH WATER INCLUDING NECESSARY EARTH WORK EXCAVATION FOR TRENCHES AND CONSOLIDATED AFTER THE PIPES ARE JOINTED AND LAID TO PROPER GRADIENT TO THE ALIGNMENT AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (SN8 SDR 34 (S 16.5) AS PER IS 15328/2003 SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER., SUPERINTENDING ENGINEER., CHIEF ENGINEER., BEFORE USE IN WORKS)				
	90.60 Rmt.	(a) 110MM DIA UPVC NON PRESSURE PIPE	100	Rs.300.00 (Rupees three hundred only)	1.Rmt. (ONE RUNNING METRE)	27180.0
	92.84 Rmt.	(b) 160MM DIA UPVC NON PRESSURE PIPE		Rs.500.00 (Rupees five hundred only)	1.Rmt. (ONE RUNNING METRE)	46420.0
64.1.1		WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED UNSHEATHED SINGLE COPPER MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) OF REQUIRED THICKNESS CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET CONTROLLED BY 5 AMPS FLUSH TYPE SWITCH INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS SPECIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	2 %	(A.18		
	272 POINTS	(a) LIGHT POINT WITH CEILING ROSE		Rs.500.00 (Rupees five hundred only)	1 POINT (EACH POINT)	136000.
	119 POINTS	(b) LIGHT POINT WITHOUT CEILING ROSE		Rs.500.00 (Rupees five hundred only)	1 POINT (EACH POINT)	59500 .
•/-	16 POINTS	(c) POINT WIRING FOR CALLING BELL/ BUZZOF WITH PUSH TYPE SWITCH		Rs.500.00 (Rupees five hundred only)	1 POINT (EACH POINT)	8000.
	2 18					
						60528512

Managing Rayiner
CONTRACTOR

NO. OF CORRECTIONS

		Y ,				
ITEM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	MOUNT
1	2	3	4	5	6	7 60528512.8
						00328312.0
5.1.1	107 POINTS	WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI		Rs.500.00 (Rupees five hundred only)	1 POINT (EACH POINT)	53500.0
		STRAND FIRE RETARDANT FLEXIBLE COPPER		~	-	
		CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) OF REQUIRED THICKNESS CONCEALED AND COVERED				
35 S	in the second	WITH 3MM THICK LAMINATED HYLEM SHEET FOR FAN POINT CONTROLLED BY 5 AMPS FLUSH TYPE SWITCH INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE AND AS DIRECTED BY	* 5 ³ 8		a, y v	
		THE DEPARTMENTAL OFFICERS.				
56.1.1	8 POINTS	WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQMM PVC		Rs.2000.00 (Rupees two thousand only)	1 POINT (EACH POINT)	16000.0
		INSULATED UNSHEATHED SINGLE CORE-MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K,V, GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) OF REQUIRED THICKNESS CONCEALED AND COVERED WITH 3MM THICK	3			
w .a.		LAMINATED HYLEM SHEET FOR STAIRCASE LIGHT POINT CONTROLLED BY 5 AMPS FLUSH TYPE TWO WAY SWITCH INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	2 2			k in
57.1.2	64 POINTS	WIRING WITH 1.5 SQMM PVC INSULATED SINGLE		Rs.300.00	1 POINT	19200.0
		CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1.K.V. GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SOMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE	36 50	(Rupees three hundred only)	(EACH POINT)	
		RETARDANT FLEXIBLE COPPER CABLEWITH ISI MARK CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF				*
ē		CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH				
58.2.1	43 POINTS	CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE.		Rs.500.00 (Rupees five hundred only)	1 POINT (EACH POINT)	
58.2.1	43 POINTS	CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED UNSHEATHED SINGLE				
8.2.1	43 POINTS	CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS				
8.2.1	43 POINTS	CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH SUITABLE SIMPLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX)				
58.2.1	43 POINTS	CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED UNSHEATHED SINGLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) OF REQUIRED THICKNESS CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT CONVENIENT PLACES CONTROLLED BY 5 AMPS				
58.2.1	43 POINTS	CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED UNSHEATHED SINGLE COPE CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) OF REQUIRED THICKNESS CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT				
68.2.1		CONFORMING TO IS: 694/1990,1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT SWITCH BOARD ITSELF INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQ.MM COPPER PVC INSULATED UNSHEATHED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED UNSHEATHED SINGLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE PVC BOX (FIRE RETARDED BOX) OF REQUIRED THICKNESS CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN PLUG SOCKET POINT AT CONVENIENT PLACES CONTROLLED BY 5 AMPS FLUSH TYPE SWITCH INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE				21500.i

Managing Partner

NO. OF CORRECTIONS

EM.NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
4	Z	3	4	5	6	7 60638712.80
69.1	28 NOS.	SUPPLYING AND FIXING OF 15 AMPS 3 PIN FLUSH TYPE PLUG SOCKET USING ON A SUITABLE 150MM PVC ELECTRICAL BOX (FIRE RETARDED BOX) OF		Rs.125.00 (Rupees one hundred and twenty five only)	1.NO. (EACH)	3500.00
		REQUIRED THICKNESS CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET INCLUSIVE OF ALL CONNECTIONS AND COST OF ALL MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY OF THE MATERIAL SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)				
71.2	2 NOS.	SURPLYING AND FIXING OF 32 AMPS TRIPLE POLE MAIN SWITCH WITH FUSE AND NEUTRAL LINK ON A SUITABLE WELL VARNISHED TEAK WOOD BOARD INCLUDING NECESSARY INTER CONNECTION COST OF ALL MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.1300.00 (Rupees one thousand and three hundred only)	1.NO. (EACH)	2600.00
-						
75.1.2		SUPPLYING AND DELIVERY OF FOLLOWING ELECTRIC CEILING FAN WITH ISI MARK WITH BLADES AND DOUBLE BALL BEARING, CAPACITOR, ETC., COMPLETE WITH 300MM DOWN ROD, CANOPIES, CAPACITOR, SHACKLE BLADES WITH ELECTRONIC DIMMER SUITABLE FOR OPERATION ON 230 VOLTS 50 HTZ SINGLE PHASE AC SUPPLY CONFORMING TO ISS NO.374/79 AND PROVIDED WITH INSULATION. (THE				
	e - 1	BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE SUPPLY MADE).			ž. ta	
	107 NOS.	(a) 48" ELECTRIC FAN 1200MM SWEEP		Rs.1200.00 (Rupees one thousand and two hundred only)	1.NO. (EACH)	128400.0
77.5	336.00 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 1.5 SQ.MM. PVC INSULATED SINGLE CORE MULTI STRAND FIRE	7	Rs.75.00 (Rupees seventy five only)	1.Rmt. (ONE RUNNING METRE)	25200.0
		RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990,1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1. KV, GRADE CABLE IN FULLY CONCEALED 19MM/20MM DIA RIGID PVC CONDUIT PIPE HEAVY DUTY WITH ISI MARK COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE.			me recy	
						1
77.6	1140.00 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 4 SQMM PVO INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH IS MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRANDE FIRE RETARDANT FLEXIBLE COPPER CABLE WITH IS MARK CONFORMING TO IS: 694/1990, 1.1. K.V. GRADE CABLE IN FULLY CONCEALED 19MM/20MM DIA RIGID PVC CONDUIT PIPE HEAVY DUTY WITH ISI MARK COSTOF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE.		Rs.125.00 (Rupees one hundred and twenty five only)	1.Rmt. (ONE RUÑNING METRE)	142500.
's 'te			38. 12.		2.0	8/

Managing Parmer
CONTRACTOR

ON TWO
NO. OF CORRECTIONS

EM NO	OUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	THILDWA
1	2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS 6	7
77.7	210.00 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI		Rs.125.00 (Rupees one hundred and twenty five only)	1.Rmt. (ONE RUNNING METRE)	609 4 0912.8
		MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE IN FULLY CONCEALED 19/20MM DIA RIGID PVC CONDUIT PIPE WITH ISI MARK ETC. INCLUDING COST OF ALL MATERIALS, SPECIALS ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS,				
9.2.1	2 NOS.	SUPPLYING AND FIXING 3 NOS. OF 32 AMPS 500 VOLTS GRADE PORCELAIN FUSE UNIT ON SUITABLE TEAKWOOD PLANK VARNISHED TO BE FIXED ON THE TOP OF POLE EB STREET POLE WITH NECESSARY CLAMPS INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE.	* 1	Rs.600.00 (Rupees six hundred only)	1.NO. (EACH)	1200.
5.1	4.00 Rmt.	SUPPLYING AND FIXING OF 40MM DIA 'B' CLASS GIPPE CONFIRMING TO ISS FOR EB SERVICE CONNECTION FOR PASSING THROUGH FROM TOP OF HOUSE/FLATS BUILDING TO THE EB BOARD INCLUDING COST OF PIPE, SPECIALS, LABOUR FOR FIXING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.		Rs.400.00 (Rupees four hundred only)	1.Rmt. (ONE RUNNING METRE)	1600
7.1	7 NOS.	SUPPLYING AND FIXING OF ELECTRO MECHANICALLY OPERATED THREE PHASE EARTH LEAKAGE CIRCUIT BREAKERS/RESIDUAL CURRENT CIRCUIT BREAKER (ELCB/RCCB) COMBINED WITH OVER LOAD AND SHORT CIRCUIT PROTECTION HAVING A RUPTURING CAPACITY OF 6 KA WITH 30 MILLI AMPS FIXED SETTING SENSITIVITY AND RATES FOR 25 A IN SUITABLE SHEET STEEL ENCLOSURE CONFIRMING TO IS 12640/1988 INCLUDING COST OF ELCB/RCCB ON FULLY CONCEALED SUITABLE M.S BOX WITH NECESSARY INTER CONNECTIONS AND EARTH CONNECTIONS USING COPPER CABLE		Rs.2000.00 (Rupees two thousand only)	1.NO. (EACH)	14000
00.2	1803.90 Sq.M.	PROVIDING ADDITIONAL STRUTTING TO CENTERING OF R.C.C SLAB OF ALL SURFACES OR ANY OTHER FORM WORKS REQUIRED AT SITE DURING EXECUTION OF WORK FOR EVERY ADDITIONAL 1 METRE HEIGHT OR PART THERE OF BUT NOT LESS THAN 30 CM OVER THE INITIAL 3.30 MT HEIGHT.		Rs.20.00 (Rupees twenty only)	1.Sq.M. (ONE SQUARE METRE)	36078
9.2		SUPPLYING AND FIXING OF BEST INDIAN TEAK WOOD PANELLED DOOR OF DOUBLE LEAVES SHUTTERS IN POSITION USING 75MMX37.5MM STYLES AND 6 NOS. OF 150X37.5MM RAILS (TOP, INTERMEDIATE AND LOCK RAILS), BOTTOM RAIL OF 75MMX37.5MM THICK AND 18.75MM TK PLANKS FOR PANELS INCLUDING COST AND LABOUR FOR FIXING THE BRASS FITTINGS SUCH AS 2 NOS. OF MAJESTIC DOOR HANDLE WITH BRASS SCREWS, 6 NOS. OF 6" BRASS BUTT HINGES, 4 NOS. OF 8" BRASS TOWER BOLTS, 1 NO. OF MORTICE LOCK WITH HANDLE, 2 NOS. OF RUBBER BUSH AND 2 NOS. OF DOOR STOPPER ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE				
		QUALITY OF BRASS FITTINGS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING)				70 9
1						

Managing Rartner

NO. OF CORRECTIONS

EM NO QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	AMOUNT
1 2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS	7
					61020040.8
8.70 Sq.M.	SUITABLE FOR DOOR OF SIZE		Rs.5000.00	1.Sq.M.	43500.0
	(c) 1800 x 2400 MM		(Rupees five thousand only)	(ONE SQUARE	-
				METRE)	
13.1 25.00 Sq.M.	SUPPLYING AND FIXING OF PUSH AND PULL TYPE		Rs.3000.00	1.Sq.M.	75000.0
	STEEL ROLLING SHUTTERS (GEAR OPERATED)		(Rupees three thousand only)	(ONE SQUARE	90
`	(FROM 8 SQM TO 12 SQM AREA) OF BEST APPROVED QUALITY TO THE REQUIRED SIZE USING 10 GAUGE			METRE)	
	CHANNELS, 14 GAUGE BRACKETS, 18 GAUGE STRIPPER				
	SIDE AND USING 'C' CLASS MS PIPE WITH REQUIRED SPRINGS, DRUM WALL BEARING, LOCKING				
51	ARRANGEMENTS WITH ONE COAT OF RED OXIDE,				
4 2 4 4	PRIMER, FIXING ETC., COMPLETE IN ALL RESPECTS AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE		8 6 4 W		NO. INC. 18
e si e s	QUALITY AND BRAND OF ENTIRE COMPONENTS OF	81 00	5 2 5 5		> 81
9	ROLLING SHUTTERS SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).				
	THE EXECUTIVE ENGINEER BEFORE USE).				
38.1 12.00 M.T.	APPLYING ONE COAT OF ANTICORROSIVE		Rs.2000.00	1 M.T.	24000.0
/ /	TREATMENT FOR STEEL WINDOW/M.S. GRILLS		(Rupees two thousand only)	(ONE METRIC TONNE)	_
	(USING 5 LITERS OF ANTICORROSIVE CHEMICAL PER ONE MT OF STEEL) AT SITE INCLUDING COST OF PAINT			TOIRILE,	
	(NITOZINC RICH PRIMER), BRUSHES, GLOVES, LABOUR				
	CHARGES FOR APPLYING ANTICORROSIVE PAINT ETC BEFORE THE APPLICATION OF SYNTHETIC ENAMEL				
	PAINT, (THE QUALITY AND THE BRAND OF THE				
	ANTICORROSIVE PAINT, SHOULD BE GOT APPROVED FROM THE EE BEFORE USE) AND AS DIRECTED BY THE				
	DEPARTMENTAL OFFICERS. •				
agents and	The second secon				
44.2 19 NOS.	SUPPLYING AND FIXING OF BEVELED EDGE MIRROR		Rs.500.00	1.NO.	9500.
1	OF APPROVED QUALITY AND BRAND OF SIZE		(Rupees five hundred only)	(EACH)	- Section 1
	500X400X5,5MM SHELF TYPE MOUNTED IN THE PVC/ FIBRE GLASS FRAMED WITH NECESSARY HARD BOARD				
	BACKING INCLUDING LABOUR FOR FIXING IN POSITION ETC., COMPLETE AND AS DIRECTED BY THE				
	DEPARTMENTAL OFFICERS.				
		58 Aug 1			
		A4	RLANK	1	
		9 D S	a at 10 Mills book that		
361 105.00 Sq.M.	SUPPLYING AND LAYING SUPERIOR VARIETY		Rs.750.00	1.Sq.M.	78750.
	1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM		(Rupees seven hundred and fifty	(ONE SQUARE METRE)	
	THICK, INCLUDING FIXING IN POSITION, CUTTING THE		only)	metre)	
	TILES TO THE REQUIRED SIZE WHEREVER NECESSARY, POINTING THE JOINTS WITH WHITE/COLOUR CEMENT,				
	FINISHING, CURING ETC., COMPLETE AND AS DIRECTED			15 M	
	BY THE DEPARTMENTAL OFFICERS. (THE BRAND QUALITY OF TILES SHOULD BE GOT APPROVED FROM				
	THE EXECUTIVE ENGINEER BEFORE USE).	1			
367 22.50 Sq.M.	PROVIDING WOODEN MELAMEN BOLISH FOR MAIN		Rs.500.00	1.Sq.M.	11250
ZZ.SU SQ.M.	PROVIDING WOODEN MELAMEN POLISH FOR MAIN DOOR NEW WOOD BY REMOVING BY BLADE		(Rupees five hundred only)	(ONE SQUARE	11230
	SCRAPPING THE EXISTING DIRT FROM THE WOODEN	1		METRE)	
	SURFACE WITH M50 SAND PAPER AND REPEAT M80 SAND PAPER TO GET A SMOOTH SURFACE, LEAVE				
	ATLEAST 4HRS DRYING AND PREPARE SURFACE BY	1			
	MIND SAND PAPER AND CLEAR THE CHREACE ARRIVA				
	M100 SAND PAPER AND CLEAR THE SURFACE APPLY ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND	7			
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE			1	
*	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED	[
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED QUALITY THINNER AFTER DRYING APPLY ONE COAT OF				
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED		8 - 8	(•	-
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED QUALITY THINNER AFTER DRYING APPLY ONE COAT OF SANDING SEALER AND ATTEND THE SURFACE TO GET		A	e	
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED QUALITY THINNER AFTER DRYING APPLY ONE COAT OF SANDING SEALER AND ATTEND THE SURFACE TO GET THOROUGHLY DRIED SMOOTHER SURFACE WITH			•	3.00
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED QUALITY THINNER AFTER DRYING APPLY ONE COAT OF SANDING SEALER AND ATTEND THE SURFACE TO GET THOROUGHLY DRIED SMOOTHER SURFACE WITH			5.	
	ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED QUALITY THINNER AFTER DRYING APPLY ONE COAT OF SANDING SEALER AND ATTEND THE SURFACE TO GET THOROUGHLY DRIED SMOOTHER SURFACE WITH				- 1

Munuging Partner

NO. OF CORRECTIONS

LEW NO	YTITMALLO	DESCRIPTION OF WORK	TNBP No	RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	AMOUNT
	2	2	4	FIGURES AND IN WORDS	AND IN WORDS	7
1	2	3	4			61262040.8
		HOLES AND DOTS BY PUTTY AND PACKING TO GET THE SURFACE CLEAN, APPLY SURFACE BY WAX EMERY SHEET NO.250, APPLY FIRST COAT OF MELAMEN SEALER WITH THE THINNER FOR PREPARING THE SURFACE AND APPLY SECOND COAT OF THE SAME BY		a		
174		AFTER DRYING PREPARING THE SURFACE WITH WATER EMERY NO.320 AND APPLY TWO COATS OF MELAMEN MATT MIXED WITH GLOZING AND THINNER 106 PREPARE THE SURFACE WATER EMERY NO.400 AND APPLY TWO COATS OF SAME AND FINALLY SMOOTHER ETC., ALL COMPLETE INCLUDING COST OF ALL MATERIALS AND LABOUR ETC., AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND SHADE OF THE POLISH SHOULD BE GOT, APPROVED FROM THE EE BEFORE USE).			. x.*.	vgr a _ a .
378.1	1873.60 Sq.M.	SUPPLYING AND FIXING OF VITRIFIED TILES OF BEST		Rs.700.00 <	1.Sq.M.	1311520.0
*		APPROVED QUALITY (IVORY) 600X600X8MM FOR FLOORING AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT		(Rupees seven hundred only)	(ONE SQUARE METRE)	
		MORTAR 1:3 (ONE OF CEMENT AND THREE OF SAND) 20MM THICK INCLUDING FIXING IN POSITION CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER) CURING FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS,				
796	1344.90 Sq.M.	PAINTING THE NEW WALLS WITH TWO COATS OF APPROVED BEST READY MIXED PLASTIC EMULSION		Rs.150.00 (Rupees one hundred and fifty	1.Sq.M. (ONE SQUARE	201735.
		PAINT IN ADDITION TO ONE COAT OF APPROVED PRIMER COAT OVER CEMENT PLASTERED WALL SURFACES AND CEILING INCLUDING COST OF PLASTIC EMULSION PAINT, PUTTY, BRUSHES ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE EMULSION PAINT AND ITS SHADE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING)		only)	METRE)	-
		PAG	NV	IAJN		-
		TOTAL AMOUNT (EXCLUDING GST)		- mill #40		62775295.
		GST Amount for providing Service to Government Contract Works for the above Construction Works.				7533035
		GRAND TOTAL				70308331

For SMP Associates

CONTRACTOR

Managing Netner

NO, OF CORRI

NO, OF CORRECTIONS