Work :- Construction of District Office building for Tamil Nadu Pollution Control Board at Vadaveeranaicken Patti Village in Theni District

io.	Qty	Description	Rate using [C.S Sand]	Unit	Amount
.1	538.10	Earth work excavation in all soils (including refilling) a. 0 to 2 mt.			
.5		Earth work excavation for Open	/224.82	2 Cum.	120975.64
	135.30	foundation (excluding refilling)  a. 0 to 2 mt.			
6			106.25	Cum.	14375.63
	/	Earth work excavation for Open foundation for drains (excluding refilling) width upto 1.25 m			1
.1.3	22.50	a. 0 to 2 mt.	/159.38	Cum.	3586.05
V	/220.10	Filling C.S. sand	1468.74	Cum.	335019.59
.6	7.20	Supply and filling of 40 mm HBSJ	/1244.61	Cum.	8961.19 X
.7	2.40	Supply and filling of 20 mm HBSJ	1657.61	Cum.	3978.26
1.1	48.20	C.C.1:5:10 for Foundation & Basement	A533.36	Cum.	218507.95
2.)	4.20	P.C.C. 1:2:4 for Foundation & Basement and other similar works	6079.24	Cum.	25532.81
3.	0.10	P.C.C. 1:8:16 using 20 mm broken brick jelly	/3882.04	Cum.	388.20
\$.) \	148.20	Brick work in C.M. 1:5 (F& B) using Kiln Burnt Country bricks of size 22 x 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4")	6358.29	Cum.	942298.58
5.1		Brick work in C.M. 1:6 using Kiln Burnt Country bricks of size 22 x 11 x 7 cm ( 8 3/4" x 4 1/4" x 2 3/4")			
1	100.90	a. In Ground Floor	6360.61	Cum.	641785.55
V	97.30	b. In First Floor	6511,51	V	633569.92
~	/83.70	c. In Second Floor	6662.41	Cum.	557643.72
1	17.70	d. In Third Floor	6813.31	Cum.	120595.59

SI. No.	Qty	Description	Rate using [C.S Sand]	Unit	Amount
10.5.1		Brick partition work in C.M. 1:4 Kiln Burnt Country bricks of size 22 x 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4") 110 mm tk (B.P.)		/	
1	153.40	a. In Foundation and basement	771.25	Sqm.	118309.75
/	164.40	b. In Ground Floor	779.48	Sqm.	128146.51
1	193.20	c. In First Floor	796.08	/ Sqm.	153802.66
,	100.20	d. In Second Floor	812.68	Sqm.	81430.54
	/ 123.80	e. In Third Floor	829.28	Sqm.	/102664.86
11.55	·1	Brick work in C.M. 1:4 Kiln Burnt Country bricks of size 22 x 11 x 7 cm (8 3/4" x 4 1/4" x 2 3/4") 70 mm tk (B.P.)			
	7.60	a. In Ground Floor	530.47	Sqm.	/ 4031.57 X
	/ 22.30	b. In First Floor	541.03	Sqm.	12064.97
	25.20	c. In Second Floor	551.59	Sqm.	13900.07
13.1	109.20	Filling with Excavated Earth	36.95	Cum.	4034.94
21.2		Teak wood Wrought & Put up			`
	0.788	a. T.W. over 2 m & below 3 m	124580.00	Cum.	98169.04
	0.306	b. T.W. below 2 m length.	. 112380.00	Cum.	34388.28
23.3	26.00	S&F of Magnetic door catches	52.00	Each	1352.00
-24:1	2060:4	Manufacturing & supply of steel windows (Weight basis)	69.60	Kg.	143403.84
25.	0 /150.00	M.S.Holdfast	9.60	Each	1440.00
26.	9 / 32.60	Flooring in C.C.1:5:10	4533.36	Cum.	147787.54
28	.0 30.90	Floor plastering in C.M. 1:4, 20 mm tk.	483.84	Sqm.	14950.66
30	.0 / 13.60	Ellispattern	425.99	Sqm. 🗸	5793.46
31	.0 / 35.40	) Weathering course	3511.95	Cum.	3808.56

l. o.	Qty	Description	Rate using [C.S Sand]	Unit	Amount
1.1	490.40	Pressed tiles (23cmx23cmx20mm) mixed with Water proofing compound	1146.41	Sqm.	562199.46
(P.	5509.20	Plastering in C.M. 1:5, 12 mm tk.	237.34	Sqm.	1307553.53
1.9	165.80	Plastering in C.M. 1:4, 12 mm tk.	243.43	Sqm.	40360.69
0.0	1466.30	Spl. Ceiling plastering in C.M. 1:3, 10 mm tk.	272.88	Sqm.	400123.94
0.1	288.20	a. 150 mm wide	76.14	Rmt	21943.55
1	288.20	b. 75 mm wide	49.63	Rmt	14303.37
1	/137.60	c. 50 mm wide	36.96	Rmt	5085.70
7.1	/1466:30	White washing 3 coats (slaked)	43.03	Sqm.	63094.89
9.0/	2867:40	M.s Grills	70.15	Kg.	201148.11
1.0	333.10	Painting - New "iron work"	133.84	Sqm.	44582.10
6.0	16.00	S & F 20 mm dia Alu. Hanger Rod	58.00	Rmt	928.00
7.0	8.00	S & F Alu Towel rail 75 cm long	95.00	Each	760.00
8.0	16.00	S & F 5 pin Coat stand	55.00	Each	880.00
9.0	/96.00	S & F chromium plated 8 guage Picture Hook	1.50	Each	144.00
0.2	1 278.00	Providing precast Kerb stone in C.C. 1:3:6, 450 x 300 x 150 mm	249.62	Rmt	69394.36
0.3	10.00	Supply and planting avenue trees	349.30	Each	/ 3493.00
0.4	10.00	Providing Tree guard	862.73	Each	/ 8627.30
50.5	1.00	Supplying. Fabricating and erection of M.S Scheme Name board	18651.79	Each	18651.79
51.0	1.00	HDPE water tank 700 lit capacity with ISI mark	7035.00	Each	<b>1</b> 28140.00
52.0		PVC Water supply (ASTM)			
	60.00	a. 32 mm dia	243.38	Rmt	/ 14602.80
	537.00	b. 25 mm dia	225.77	Rmt	/121238.49

Description  Dipe 20mm dia for Hot water line  Ny Concealed in walls)	302.81	Rmt	/ 20591
Pipe 20mm dia for Hot water involve Concealed in walls)			1
The second secon	30.00	Each	150.00
Steps (5 kg)	1896.82	Each	15174.56
illy Trap using Kiln burnt country cks 22 x 11 x 7 cm.	160.00	Each	1280.00
lectrical arrangements			/6600.00 ×
5 Amp. Power plug	150.00		V .
Box type Fibre Fan hook	33.90	Each	2983.20
Charges for fixing of "Fan"	571.00	Each	50248.00
3 SWG wire	26.30	Rmt	✓ 263.00 ×
S&F of TV/Telephone line Socket	77.00	Each	616.00
S&F of 20mm dia PVC pipe for TV/Telephone line	85.69	Rmt	8569.00
Earthing Station IS3043 (Type I)	2921.00	Each	2921.00
Anti termite treatment	34.00	Sqm.	14752.60
ANNEXURE			
Precast Cupboard slab 20 mm tk.using standardised concrete mi M20 (annexure)	ix		
a. In Stilt / Ground Floor	1403.4	9 Sqm	. / 3929.77
b. In First floor	1408.0	1 Sqm	54489.99
c. In Second floor	1412.5	3 Sqm	n. \ \ 66388.91 \
Precast cupboard slab 40 mm tkusing standardised concrete m M20 (annexure)	ix		
a. In Foundation & basement	1541.	29 Sqn	V .
b. In Stilt / Ground Floor	1545.		•
c. In First floor	1554.	92 Sqr	m. / 24723.23
	cks 22 x 11 x 7 cm.  //C Nahani trap (4way/2way)  //C Nahai trap (4way/2wa	cks 22 x 11 x 7 cm.  //C Nahani trap (4way/2way)  //C Nahani trap (4way/a)  //C Nahani trap (4way/a)  //C Nahani trap (4way/a)  //C	cks 22 x 11 x 7 cm.  /C Nahani trap (4way/2way)  /ectrical arrangements  5 Amp. Power plug  flox type Fibre Fan hook  Charges for fixing of "Fan"  S SWG wire  S&F of TV/Telephone line Socket  For TV/Telephone line  Earthing Station IS3043 (Type I)  Anti termite treatment  ANNEXURE  Precast Cupboard slab 20 mm  Ek. using standardised concrete mix  M20 (annexure)  a. In Stilf / Ground Floor  Precast cupboard slab 40 mm  Ekusing standardised concrete mix  M20 (annexure)  a. In Second floor  Precast cupboard slab 40 mm  Ekusing standardised concrete mix  M20 (annexure)  a. In First floor  Precast cupboard slab 40 mm  Ekusing standardised concrete mix  M20 (annexure)  a. In Foundation & basement  1541.29 Sqn  2. In Stilf / Ground Floor  1545.88 Sqr

SI. Io.	Qty	Description	Rate using [C.S Sand]	Unit	Amount
.4.1		Standardised concrete Mix M20 Grade Concrete			
/	/170.30	a. In Foundation and basement	7522.25	Cum	1281039.18
4.1	94.10	b. Stilt / Ground Floor	7635.85	Cum	718533.49
	109.40	c. In First Floor	7859.65	Cum	859845.71
	109.40	d. In Second Floor	8083.45	Cum	884329.43
J	/ 12.20	e. In Third floor	8307.25	Cum	/101348.45
1.14	/20.50	Plastering with CM 1:3, 12mm with WPC	262.12	Sqm	5373.46
18.1		Formwork using M.S.Sheet			
7	692.30	a.For Column footings,plinth beam,Grade beam,Raftbeam,Raft slab etc.,	809.35	Sqm	560313.01
7	2300.00	b.Plain surfaces such as Roof slab,floorslab,Beams,lintels,lofts,sill slab,staircase,portico slab and other similar works	905.40	Sqm	2082420.00
. ,	905.50	c.For Square and rectangular columns and small quantities	1086.48	Sqm /	983807.64
	/ 19.90	f.Curved surface	1358.10	Sqm	27026.19
21.5	. /17.40	Supply and Fixing Soild UPVC door Shutter with frame	3325.00	Sqm	57855.00
2.1.	118.00	Supplying and filling with gravel	393.73	Cum	46460.14
14	158.30	Supplying and filling with 3 to 10mm HBSJ	915.99	Cum	/145001.22
99	<b>Y</b>	TW panelled single door shutter without brass fittings.			
	38.80	a. 1000X2100mm.(Single leaf) For Qtrs	6607.18	Sqm	256358.58
99	14.40	a. 1500X2100mm.(Double leaves) with Brass fittings	6458.42	Sqm ·	93001.25
29	.8. 1 146.40	Glazed tiles using Grout (Tile Joint Filler), C.M 1:2, 10mm tk	1327.55	Sqm	194353.32

iI.			Rate using		47
0,	Qty	Description	[C.S Sand]	Unit	Amount
).9,	178.60	Floor ceramic tiles (Anti-skid) using Grout (Tile Joint Filler).	1167.54	Sqm	1
9	54.86	Fabrication of Mild steel / RTS grills (without cement slurry) for all sizes of rods.	87298.50	МТ	1
.6	85.70	PVC SWR 110 mm dia with ISI mark type- A for Rain water down fall pipe	335.61	Rmt	/
.6.	60.20	Precast slab 50 mm tk.in C.C. 1:3:6 with fibre	386.33	Sqm	23257.07
2.4	10.00	20mm dia PVC water supply ASTM pipe (fully consealed in walls)	222.98	Rmt	2229.80
.4	2.00	S&F of C.I Manhole cover 60 x 60 cm (50kg weight)	1864.00	Each	3728.00
3.	8.00	Wash Hand Basin of size 550 x 400 mm (White without Pedestal)	3255.82	Each	26046.56
3.3	4	PVC SWR pipe (Soil line) with ISI mark - type 'B'.			
>	69.00	a. 110 mm dia.	696.55	Rmt	/48061.95
/	97.80	b. 75 mm dia.	579.25	Rmt	/ 56650.65 X
3.4	32.00	Supplying, Laying & Concealing the 50mm dia PVC (SWR) pipe with ISI mark type - 'B' with relevant specials.	114.45	Rmt	3662.40
3.5	/ 1.00	PVC(SWR) pipe with ISI mark - type 'A' for Ventilating shaft with cowl	454.00	Each	454.00
۲.۱		Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark			
-	92.00	a. Light point with ceiling rose	1630.00	Each	149960.00
<b>\</b>	132.00	b. Light point without ceiling rose	1633.00	Each	215556.00
7	2.00	c. Calling bell point with Buzzer/Calling bell	1670.00	Each	3340.00
5.1	88.00	Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Fan point	1705.00	Each	150040.00

SI. No.	Qty	Description	Rate using [C.S Sand	g J Un	it Amount	
√65.1 ✓	4.00	Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 for Staircase Light Point.	3052.0	00 E	ach / 12208.00	X
7.1		Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 for 5 amps 5 pin plug socket point @ Switch Board Itself	835.0	0 Ea	ch 30895.00	7
1	50.00	Wiring with 1.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990 for 5 amps 5 pin plug socket point @ Convenient Places	1133.00	Eac	h / 56650.00	X
1.2/	88.00	Supply and delivery of 48" (1200 mm) Fan with ISI mark with Eletronic Dimmer	1552.70	Each	136637.60	1
7.6	270.00	Run of 2 Wires of 4 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.	266.00	Rmt	√71820.00 ×	1
7.7	333.50	Run of 2 Wires of 2.5 sqmm PVC insulated single core multi strand fire retardant flexible copper cable with ISI mark confirming IS: 694:1990.	226.00	Rmt	75371.00	
5.1/	30.0	4 x 4 Sq mm copper PVC insulated unsheathed single core cable for 3 phase EB service connection	270.00	Rrnt	8100.00	
1	6.00	S & F of Exsaust Fan 225mm dia	2150.00	Each	12900.00	
14.2.1		Rain water harvesting using defunct borewell and providing perforated cover slab	The state of the s			
1	7.00	a). Providing pit (M20)	1952.05	Each	13664.35	
12	8.00	b) Augering 30cm dia	463.98	Rmt	12991.44	
44.2	9.00	S&F of Bevelled edge mirror 500 x 400 x 5.5mm	398.30	Each	3584.70	
83.9 12	26.00	Providing single nosing to the edges of Granite slab [PWD SR-2022-23/p-36]	195.70	Rmt	24658.20	
384 🗸	4.0	S&F of PVC flushing cistern	1714.50 E		6858.00	

SI. No.	Qty	Description	Rate using [C.S Sand]	Unit	Amount 500
71.2	1.00	Supplying and fixing of 32 AMPS Triple pole main switch	2159.00	Each	2159.063
80.1 79.2.1	10.00 1.0 2472.90	450 x 375 x 20 mm thick TW plank 3 Nos. of 32Amps - Fuse Unit Plastic Emulsion PAINT including	1309.00 825.00 222.41	Each Each Sqm	13090.00 825.00 549997.69
796.	2531.76	exterior Emulsion PAINT including primer for outer walls (Two coat)	223.97	Sqm	567038.29
63 164	68.70	Supplying & fixing of Stainless steel Hand Rails for Staircase (PWD SR 22- 23/p-50)	5536.00	Sqm	380323.20
448.2	8.00	Providing PVC Tee with end cap	132.70	Each	1061.60
367	134.70	Providing wooden <b>Melamine</b> polish for new wood work	1385.99	Sqm	186692.85
378.7	895.50	Supply and Laying of Nano Polish Virtified tile Flooring with in C.M 1:3 20mm Thick incl.(Ivory)	1210.98	Sqm	1084432.59
361.1	/166.60	Concrete designer tiles flooring	1440.90	Sqm	240053.94
379.5.	304.90	Supply and fixing of Granite tiles Jet black C.M 1:2, 10mm tk for Staircase wall portion	1582.68	Sqm	482559.13
21.5	5.40	Supplying and fixing in position of UPVC Ventilator louvered ventilator type for all sizes PWD SR 2022-2023 p-66	8106.00	Sqm	43772.40
21.5.3	97.70	Supplying and fixing in position of UPVC window of casement type( open) for all sizes SR 2022-2023 p-65	7482.00	Sqm	730991.40
10000	1.00	Supply and erection of 250 Amps capacity floor mounting type metering panel board (Cubical type)	161100.00	Each	161100.00
Y D	78.50	B) 3.5 core 35mm sqmm LT UG cable	260.90	RMT	/
117	/ 2.00	Supply and fixing of brass cable gland suitable for 3.5 core 35 Sq.mm with earth strips around the cable termination with crimping of terminals with lugs etc (for Incoming Cable)		Each	123.40
		The state of the s			26841295.49

SI. No.	Qty	Description	Rate using [C.S Sand]	
SX,X		Run off mains with 4 wires of 6 Sqmm copper PVC insulated unsheathed single core 1.1KV cable wire containuous earth by means of 2.5 Sqmm copper PVC insulated unsheathed single core 1.1 KV grade cable in fully concealed 19 mm / 20 mm dia rigid PVC conduit pipe heavy duty with ISI mark including cost of all materials, specials, etc., all complete.	493.0	0 Rmt 12325.00
115	70.00	Labour charge for laying of 3.5 core 35 sq.mm approved quality excluding civil works such as providing trench below G.L	253.00	Rmt 17710.00
116 ~	17.00	Labour charge for laying of 3.5 core 35 sq.mm approved quality excluding fixing vertical wall above ground level	165.00	Rmt 2805.00
35901 Tale	3.00	Supplying and fixing of three phase DB box hylin sheet steel encloser with detabased gland plates for flush/surface mounting with bus bar neutral lines and earth bus bar ( without Mcb's ) etc.,	3625.00	Each 10875.00
10.9	3.00	Supply and fixing of 8 way single pole and neutral MCB sheet steel enclosure distribution board with double door 50 b	3191.00 7	Each 9573.00
108	3.00	Supplying and fixing of 4 pole 40 amps 30ml ELCB etc., P-133	2770.00	Each 8310.00
116	18.00	Supplying and fixing of single pole to 32 A 10 KA MCB's etc., 8 132	388.00	Each / 6984.00
7 160.	3.00	Supplying and fixing of rotary switch (or) etc., Potary handle p-134	893.00	Each 2679.00
86.	37.80	Providing Cup-board Shutter with frame wing termit/ water Proof Plywood of 19 mm thick	5049.00	m2 /190776.60)

SI. No.	Qty Description	Rate using [C.S Sand]	HIIII AMOUNT
21.5.5	Providing of 35mm thick factory made pre-laminated ABS (Acrolynitrile Butadiene Styrene) Door Shutter moulded in different designs, consisting of all round frame made out of water proof solid foam PVC bar of size 20 x 32mm, reinforced by 32 x 32mm - 2 Nos., for vertical made out of LVL (Laminated Veneer Lumber), core material of 32mm thick high density craft paper honey comb board, sandwiched on both sides with	ng	0 Sqm 56487.0
	butterfly hinges - 3 Nos.,	SR-66	
379.7	S & F of Granite slab of size 4'x2', 18 to 20mm Thick For kitchen arrangements (jet black) C.M 1:3, 20mm tk		
6.00	a. In Ground floor		
11.30		1949.15	Sqm / 11694.90
/	/ #3t 1100/	1953.63	Sqm / 22076.02
31.50	c. In Second floor	1958.11	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
),)	UPVC Non Pressure pipe of SN8 SDR 34 ( S 16.5) as per IS 15328/2003		Sqm 61680.47
72.00	a. 110 mm UPVC Non Pressure pipe		
1		472.40	Rmt /34012.80
26.00	b. 160 mm UPVC Non Pressure pipe	795.90	Rmt / 20693.40 \
-1	PVC Specials as per IS 10124/1982		
2.00	Part II a. 110 mm dia PVC bend (TWAD SR 21-22)	175.20	Each / 350.40
/	b. 160 mm dia PVC bend (TWAD SR 21-22 )	560.20	Each / 560.20
)	PVC Equal Tee as per BIS		1
	. 110 mm dia PVC Equal tee (TWAD	197.50	Each 197.50
/	SR 21-22)		Each / 371.80

mount				11
Qty	Description	Rate using [C.S Sand]	Unit	Amount
3.2	S & F of Indian Water closet white glazed (Oriya type) of size 580 x 440mm with PVC SWR grade ' P' or "S' trap - in G.F.	3211.18	Each	6422.36
4.2	S & F of Indian Water closet white glazed (Oriya type) of size 580 x 440mm with PVC SWR grade ' P' or "S' trap- Other than G.F.	4969.82	Each	19879.28
5.00	S & F of E.W.C.(White) 500 mm with PVC SWR grade "P" or "S" TRAP	6876.30	Each	34381.50
.),\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	S & F of 15mm dia half turn CP long body tap	480.00	Each	8160.00
.2. 11.00	S & F of 15mm dia half turn CP short body tap	432.00	Each	/ 4752.00 ×
42 1055.20 0	Supply and Laying Rubber Moulded Hyraulic Pressed Paver Block 83 mm thick including labour charges for laying etc ( as per DB/1469/2018)	790.78	Sqr.	834431.06
24.00	Supply and fixing of 9 watts LED bulb (PWD SR-2022-23/p-115)	135.00	Each	3240.00
132.00	Supply and fixing of 4' 18 watts LED Tube Light	690.00	Each	91080.00
03/6.00	Supply and fixing of Bulk Head fitting suitable for 12W LED Bulb	517.00	Each	3102.00
01/10.00	Supply, fiing of 25W LED street light etc.,	3367.00	Each /	33670.00
04 / 6.00	Supply and fixing of 12 watts LED bulb (qtn)	170.00	Each /	1020.00
2472.90	Providing one coat of Wallputty for new plastered surface	91.11	Sqm	225305.92
	Supply & Installtion of star rated Air- Conditioner with copper coil including cost of 3m copper tube and fixing charge etc (PWD SR 2022-			

il. Qty	Description	Rate using [C.S Sand]	Unit Amount
14.00	ia. 2.00 TR Split Type AC unit (5 Star Rated) P - 142	56370.00	Each 789180.00
14.00 ,75	b. Supply and installation of 5 KVA capacity Automatic Voltage Stabilizer with time delay relay (V- Guard/ Equivalent) (PWD SR 2022-23, P-142)	4940.00	Each 69160.00
74.3 136.0	d. Supply and fixing of AC drain pipe (PWD SR 2022-23, P-142)	64.10	Rmt 8717.60 X
4.2 14.0	e. Supply and fixing of MS stand for fixing outdoor unit (PWD SR 2022-23, P-142)	1088.00	Rmt / 15232.00
70.0	pipe (Extra beyond 3 metrs supplied with AC unit) (PWD SR 2022-23, P-142)	1037.00	Rmt 72590.00
62.9	Providing APB membran Coating (Water Proof Coating) for sunken portion of toilet with following specification and the surface shall be cleaned to remove all dust, foregin, matters lose materials or a ny other deposits of contamination by rubbing with wire brush.	700.00	Sqm / 44030.00
415.0	PVC insulated 3 core 4 sqmm (SR 2022-2023) flat type copper cable	194.00	Rmt 80510.00
375.00	Supply and delivery of UPVC pipe 32mm dia	148.10	Rmt / 55537.50
24	Supply and delivery of Follwing G.I specials		
15.00	a. 25 mm G.I. Pipe (PWD SR 2022- 2023)	128.00	Nos 1920.00
J 5.00	b. 40 mm G.I. Pipe (PWD SR 2022- 2023)	163.00	Nos / 815.00
92.00	b. 50 mm G.I. Pipe (PWD SR 2022- 2023)	209.00	Nos 19228.00

Qty	Description	Rate using [C.S Sand]	Unit	Amount
1.00 a	a) 50 mm non return valve 20-21 P TWADS 22-23 Pat	ate 2082.00 e 2498.00	Nos	V
3.00 b	b. 50 mm Gate valve	1241.00	Nos	/
/ 3.00 C	c. 50 mm G.I Union	266.30	Nos	V
/ 5.00 d	e. 50 mm G.I. hex nipple	87.00	Nos	435.00
/1.00 e	e. 50 mm G.I. foot valve with stainer	Date - 434.00 Date - 461.00	Nos	434.00
	e. 50 mm G.I. Tee	139.80		419.40
10.00 9	e. 50 mm G.I. Bend (PWD SR 2020- 2021)	116.30	Nos	1163.00
26.00	f. 50 mm G.I. Coupling	69.80	Nos	·
5.00	f. 50 mm x 32mm G.I. Tee	139.80	Nos	699.00
2.00	c. 32 mm G.I Union	127.50	Nos	/ 255.00
2.00	c. 32 mm G.I elbow	87.00	Nos	174.00
/ 2.00	e. 32 mm G.I. hex nipple	58.10	Nos	116.20
2.00 m	n f. 25 mm G.I. Coupling	28.60	Nos	57.20
	Supply and delivery of Follwing PVC pipe 10 Kg/cm2		-	
15.00	a. 32 mm PVC Pipe (PWD SR 2022- 2023)	61.70	Nos	925.50
95.00	b. 50 mm PVC Pipe (PWD SR 2022- 2023)	144.70	Nos	13746.50
220.00	Labour charges for laying of G.I pipe and PVC pipe below ground level	103.19	Rmt	22701.80
1.00	Design Engineering Supply, Fabrication, Erection, Testing, commissioning and handling of 13 persons (884 kg) capacity Passenger lift as per the following Technical Specifications	1857100.00 SR-146	Nos	1857100.00

SI. Qty	Description	Rate using [C.S Sand]	Unit	
)32	Drilling of 150mm dia vertical bores in hardrock formation to any required depth using "DTH Rig" as directed by the departmental officers including labour charges for inserting casing pipe assembly in the drilled hole including welding the joints if necesary grouting the casing pipe etc., and including			
	transportation charges for the rig and supporting vehicles from one place to another including hire charges for rig fuel labour for drilling and water required for drilling at the site shown and as directed by the departmental officers.CER.No.110/2020-21			
375.00	(a) Drilling of borewell in rock area	295.00	m/	110625.00
30.00	Supply and delivery of 150mm OD of PVC casing pipes (6kglcm2) as per IS 12818 11992 of approved quality for borewells with average wall thickness of Imm and inner/outer threaded ends in standard length of 3m including transporting charges to site of work and all other taxes etc.TWAD SR-2022-23,p	644.50	m	19335.00
1.00	Supplying and fixing of 150mm dia PVC end cap for borewell of best approved quality with ISI mark confirming to IS specifications including cost of materials conveyance to site and labour charges for fixing in position etc. all complete.	144.30	Nos	144.30
2.00	Supply and delivery of 2HP monoblock pumpset three phase circuit unit of approved brand including accessoring.(Duty 450X20)	21377.00	Nos	42754.00
2.00	Supplying and fixing of Dol starter confirming to I.S specification.	5641.00	Nos /	11282.00
2.00	Lobour charges for errection of 2HP monoblock pumpsets including bed block fixing in position etc, complete.	8131.20	Nos	468 69.78

	Qty	Description	Rate using [C.S Sand]	Unit	Amount
1	1.00	Supply and delivery of 7HP submersible pumpset 50 stages at bore well (three phase).(Duty 50X175)	63167.00	Nos	63167.00
0/	1.00	Lobour charges for errection of 7HP vs submersible pumpsets at bore well 5 etc, complete.	HP-12669	Nos 80	11056.10
1.1	1.00	Supplying and fixing of 7HP panel board for submersible pumpsets.	6 HP 15 SR	7 Nos	15573.00
: 5	ome gate	NUMBERING AND LETTERINGS			
in 5	1.00	Supplying aud fixing of Aluminium TNPHC Emblem	3000.00	Nos	3000.00
30.	29.00	Supplying and fxing of 9" height Aluminum letters $SR - 67$	1179.00	Nos	34191.00
	J <sup>237.00</sup>	Supplying and fixing of 6" height Aluminium letters	748.00	Nos	/177276.00
7.2	14.00	Supply and fixing of 20 Amps DP plug and socket in sheet enclosure with 32 A DP MCB in flush with wall with earth connection ( For AC Plug ) ( Legrand / Hager ( L& T) Make)  Data G (SD-140)	1839,00	Each	25718:00 25746.00
		Total			32169717.72 3,21,69,745.
		. 10		3,	21,70,878.
		92	000 103	(A 105	7