SCHEDULE - A

NAME OF WORK : CONSTRUCTION OF BUILDING FOR FIRE AND RESCUE SERVICES STATION WITH DEVELOPMENT WORKS AT KADAMALAIKUNDU IN THENI DISTRICT

EMNO	QUANTITY	DESCRIPTION OF WORK	TNBP No	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	THUOMA
1	2	3	4	5	6	7
1.4		EARTH WORK EXCAVATION FOR FOUNDATION IN ALL SOILS AND SUB-SOILS TO THE REQUIRED DEPTH AS MAY BE DIRECTED EXCEPT IN HARD ROCK REQUIRING BLASTING BUT INCLUSIVE OF SHORING, STRUTTING, AND BAILING OUT WATER WHEREVER NECESSARY AND REFILLING THE SIDES OF FOUNDATION WITH EXCAVATED EARTH IN 150MM THICK LAYERS WELL WATERED RAMMED AND CONSOLIDATED AND DEPOSITING THE SURPLUS EARTH IN PLACES SHOWN CLEARING AND LEVELLING THE SITE WITH AN INITIAL LEAD OF 10 METRES AND LIFT AS SPECIFIED HERE UNDER ETC. COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS, (INCLUDING REFILLING)	17, 23 & 24			
	V			× ×		*
	370.90 Cu.M.	(a) 0 TO 2M DEPTH		Rs.100.00	1.Cu.M. (ONE CUBIC	37090.00
		>		(Rupees one hundred only)	METRE)	
				, and the second		
				^	7	
- 1						
1.5		FOUNDATION IN ALL SOILS AND SUB-SOILS TO THE				
X		REQUIRED DEPTH AS MAY BE DIRECTED EXCEPT IN				
		HARD ROCK REQUIRING BLASTING, INCLUSIVE OF SHORING, STRUTTING AND BAILING OUT WATER WHEREVER NECESSARY (EXCLUDING REFILLING THE SIDES OF FOUNDATION) AND DEPOSITING THE EARTH IN PLACES SHOWN CLEARING AND LEVELLING THE SITE WITH AN INITIAL LEAD OF 10 METRES AND LIFT AS SPECIFIED HEREUNDER ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS, (EXCLUDING REFILLING)	~			
ì	-		ĺ	,		¥-
	316.70 Cu.M.	(a) 0 TO 2M DEPTH		Rs.70.00	1,Cu.M.	22169.00
	/	×		(Rupees seventy only)	(ONE CUBIC METRÉ)	×
				V 4	λ	
	Y			Rs.92.00	1.Cu.M.	4=40.00
	16.50 Cu.M.	(b) 2 TO 3M DEPTH		(Rupees ninety two only)	(ONE CUBIC	1518.00
	Ψ.	V		(Kupees limety two olly)	METRE)	•
				+	+	
1.6		EARTH WORK EXCAVATION FOR OPEN	ı	-	1	
v.		FOUNDATION FOR DRAINS IN ALL SOILS AND		_		
X		SUBSOILS TO THE REQUIRED DEPTH AS MAY BE DIRECTED EXCEPT IN HARD ROCK REQUIRING BLASTING, INCLUSIVE OF SHORING, STRUTTING AND BAILING OUT WATER WHEREVER NECESSARY (EXCLUDING REFILLING THE SIDES OF FOUNDATION AND DEPOSITING THE EARTH IN PLACES SHOW! CLEARING AND LEVELING THE SITE WITH AN INITIAL				
		LEAD OF 10 METRES AND LIFT AS SPECIFIED HEREUNDER ETC., COMPLETE IN ALL RESPECTS)			
		COMPLYING WITH RELEVANT STANDARD)			
		SPECIFICATION (EXCLUDING REFILLING) (DRAIN HAVING BED WIDTH UPTO 1.25 METRE).	4			
		HAVING BED WIDTH OF TO 1.23 METAL).	1	1		
	~				4.00.10	1
	34.10 Cu.M.	(a) 0 TO 2M DEPTH		Rs.100.00 X	1.Cu.M. (ONE CUBIC	3410.0
				(Rupees one hundred only)	METRE)	+
	\			V	1	
	X			4	1	
2 × V	· ·	RUCTIONS		4	t	
or A	· ·	RUCTIONS		4	t t	64187.0
	· ·			4	*	64187.0





		KADAMALAIKUNDU ITR	E 190 BEST	1,75	T	ge Nis Z
DU,MELL	OUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT 7
2.6		SUPPLYING AND FILLING WITH 40MM SIZE HARD BROKEN STONE JELLY IN FOUNDATION AND BASEMENT AND OTHER SIMILAR WORKS INCLUDING COST OF MATERIALS, LABOUR CHARGES, ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL		Rs 800 00 (Rupees cight hundred only)	1.Cu,M (ONE CUBIC METRE)	64187.00 4800.00
2.7	2.00 Cu.M.	SUPPLYING AND FILLING WITH 20MM SIZE HARD BROKEN STONE JELLY IN FOUNDATION AND BASEMENT AND OTHER SIMILAR WORKS INCLUDING	*	Rs.900.00 (Rupees nine hundred only)	1.Cu.M. (ONE CUBIC METRE)	1800.0
13.1	76,20 C u.M.	COST OF MATERIALS, LABOUR CHARGES ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. FILLING IN FOUNDATION AND BASEMENT AND		Rs.25.00	1.Cu.M.	1905.0
Y	×	OTHER SIMILAR WORKS WITH EXCAVATED EARTH IN LAYERS OF 150MM THICK WELL WATERED RAMMED AND CONSOLIDATED COMPLYING WITH RELEVANT STANDARD SPECIFICATION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		(Rupees twenty five only)	METRE)	Ť
21.2		SUPPLYING AND FIXING OF TEAK WOOD				
X		WROUGHT AND PUT UP FOR FRAMES OF DOORS WINDOWS, VENTILATORS, CUPBOARD AND ANY OTHER SIMILAR JOINERY WORKS WITH NECESSARY PLUGS REBATES FOR SHUTTERS, PLASTER GROOVES ON ALL FACES ETC., INCLUDING LABOUR CHARGES FOR FIXING HOLD FASTS, COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS ETC., IN ALL RESPECTS.	72 & 74			
	0.648 Cu.M.	(a) TEAK WOOD OVER 2.00 METRE AND BELOW 3.00 METRE LENGTH		Rs.117000.00 (Rupees one lakh and seventeen thousand only)	1.Cu.M. (ONE CUBIC METRE)	× 75816.
	0.459 Cu.M/	(b) TEAK WOOD BELOW 2.00 METRE LENGTH		Rs.100000.00 (Rupees one lakh only)	1.Cu.M. (ONE CUBIC METRE)	× 45900
23.3	16 NOS. X	SUPPLYING AND FIXING OF BEST APPROVED SUPERIO VARIETY MAGNETIC DOOR CATCHES SUITABLE FO DOORS INCLUDING COST OF DOOR CATCHES ALUMINIUM / STAINLESS STEEL SCREWS FIXING I POSITION ETC., COMPLETE AND AS DIRECTED BY TH DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAN SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	R S, IN HE ID	Rs.50.00 \\ (Rupees fifty only)	1.NO. (EACH)	× 800
24	4539.20 KG.	WINDOWS CONFIRMING TO IS 1038/19 SPECIFICATION WITH STEEL SECTION USED FO	83 DR	Rs.62.00 (Rupees sixty two only)	1.KG. (ONE KILOGRAM)	X 28143
rΔP	CONSTR	FABRICATION OF WINDOWS AS PER IS7452/19 SPECIFICATION AND AS PER THE APPROVED TYI DESIGN FOR ALL SIZE APPLICABLE FOR THE WOF WITH IRON OXIDIZED HANDLES WITH LOCKIN ARRANGEMENTS, PEG STAYS AND INCLUDING CO. FOR ONE COAT OF RED OXIDE PRIMER ET. COMPLETE AND AS DIRECTED BY THE DEPARTMENT OFFICERS (WINDOWS SHOULD BE WEIGH! EXCLUDING ALUMINIUM BEEDING AND GLASS PANE THE STANDARD MODELS OF WINDOW WITH GR DESIGN DRAWINGS ARE ENCLOSED IN THE ANNEXUF HOWEVER THE WINDOWS GRILL AND DESIGN SHOULD BE COT APPROVED BY THE EXECUTIVE ENGINE	PE RK IG. IG. ST 81 C., AL ED EL, IILL ILL		+	
	John	- your out to so.	-	9 El A		47663
AT N		1				41003

SUPERINTENDING ENGINEERS OUTH CYCLE

	-3
F WORK TNBP No. RATE EXCLUSIVE FOR GST IN UNIT IN FIGURES AID IN WORDS AND IN WORDS	NOUN
wt 5 6	7

		HURAIAIAIAIAIAA	HENNEY KER	ur (r.y.		Pluge No. 3
TEM NO	QUANTITY 2	DESCRIPTION OF WORK	TNBP No	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT
25	96 NOS.	SUPPLYING AND FIXING OF MILD STEEL HOLD FASTS HORIZONTALLY TWISTED OF SIZE 230X40X4MM WITH PAIR OF SUITABLE IRON SCREWS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	86	Rs.9.00 (Rupees nine only)	1.NO. (EACH)	7 476638,40
30	59.UU Sq.M.	FINISHING THE TOP OF FLOORING WITH CEMENT CONCRETE 1:3 (ONE OF CEMENT AND THREE OF DLUC GRANTE CHIPS OF SIZE 10MM, AND BELOW) 20 MM THICK ELLIS PATTERN FLOORING (NO SAND) AND		Rs.270.00 (Rupees two hundred and seventy only)	1.Sq.M. (ONE SQUARE METRE)	15930.00
2		SURFACE RENDERED SMOOTH INCLUDING 50MM WIDE SKIRTING, PROVIDING PROPER SLOPES, THREAD LINING, CURING ETC., COMPLETE IN ALL FLOORS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	39 - G	<i>y</i> 1	فف	e#i
31 ¥	46.80 Cu.M.	WEATHERING COURSE WITH CONCRETE BROKEN BRICK JELLY 20MM GAUGE IN PURE BURNT LIME STONE SLAKED AND SCREENED (NO SAND) OVER RCC ROOF SLAB WITH PROPORTION OF BRICK JELLY TO LIME (FAT LIME) BEING 32: 12 1/2 BY VOLUME WELL BEATEN WITH WOODEN BEATERS FOR GIVING THE REQUIRED SLOPE AND THICKNESS COMPLYING WITH RELEVANT STANDARD SPECIFICATION AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.2500.00 (Rupees two thousand and five hundred only)	1.Cu.M. (ONE CUBIC METRE)	117000.00
37.1 \(\text{\chi}\)	910.00 Sq.M.X	WHITE WASHING THREE COATS USING CLEAN SHELL LIME SLAKED INCLUDING COST OF LIME, GUM, BLUE, BRUSHES, INCLUDING SCAFFOLDING ETC., COMPLETE IN ALL RESPECTS.	63	Rs.20.00 (Rupees twenty only)	1.Sq.M. (ONE SQUARE METRE)	18200.00
39	1357.00 KG.	SUPPLYING AND FIXING MILD STEEL GRILLS AS PER THE DESIGN APPROVED TO VERANDAH ENCLOSURE OR GATE INCLUDING ONE COAT OF PRIMER AND LABOUR FOR FIXING IN POSITION ETC. ALL COMPLETE.		Rs.62.00 (Rupees sixty two only)	1.KG. (ONE KILOGRAM)	84134.00
40 V V	114.10 Sq.M.	PAINTING THE NEW WOOD WORK WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT IN ADDITION TO ONE COAT OF PRIMER OF APPROVED QUALITY AND SHADE, THE PAINT SHOULD BE SUPPLIED BY THE CONTRACTOR AT HIS OWN COST (THE QUALITY AND THE SHADE OF PAINT SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE) COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	66 & 66 A	Rs.150.00 (Rupees one hundred and fifty only)	1.Sq.M. (ONE SQUARE METRE)	17115.00
41, ×	253.40 Sq.M.	PAINTING THE NEW IRON WORK AND OTHER SIMILAR WORKS SUCH AS PVC / ASTM PIPES, KERB STONE AND GRILLS WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT OF APPROVED QUALITY AND BRAND, THE PAINT SHOULD BE SUPPLIED BY THE CONTRACTOR AT HIS OWN COST, (THE QUALITY AND THE BRAND OF PAINT SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE) COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.	66 & 66A	Rs.90.00 (Rupees ninety only)	1.Sq.M. (ONE SQUARE METRE)	22806.0
46	8.00 Rmt.	SUPPLYING AND FIXING OF 20MM DIA ALUMINIUM HANGER RODS TO THE REQUIRED LENGTH WITH ALUMINIUM END BRACKETS INCLUDING COST OF		Rs.50.00 (Rupees fifty only)	1.Rmt. (ONE RUNNING METRE)	400.0
or A		SCREWS, TW PLUGS AND LABOUR CHARGES FOR FIXING IN POSITION ETC. COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS		\(\times_{\text{\chi}}\)	1	ed to
				4	S 6	753087.4





		KADAMALAIKI NIN HIR	ism ness	19		Prise No. 4
TEi≙NO	QUANTITY	DESCRIPTION OF WORK	INER No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	TNUOMA
4	2	3	4	5		753087.40
47	1	SUPPLYING AND FIXING OF ALUMINIUM TOWEL RAILS OF 75CM LONG INCLUDING COST OF		Rs.70.00 (Rupers seventy only)	1.NO (EACH)	> 560.00
		SCREWS, TW PLUGS AND LABOUR CHARGES FOR FIXING IN POSITION ETC. COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		3/	3*	4
48 🗸	10 NOS.	SUPPLYING AND FIXING OF ALUMINIUM PLATE WITH FIVE PINS FOR COAT STAND INCLUDING COST OF		Rs.40.00 (Rupees forty only)	1.NO. (EACH)	400.00
*	>	PLUGS, NAILS, SCREWS, AND LABOUR FOR FIXING IN POSITION ETC, ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS			7	4
49,	100 NOS.	PROVIDING AND FIXING IRON CHROMIUM PLATED 8 GAUGE PICTURE HOOKS INCLUDING FIXING IN		Rs.1.00 // (Rupee one only)	1.NO. (EACH)	100.00
×	>	POSITION ETC., ALL COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		1	1	je.
50.3	15 NOS.	SUPPLYING AND PLANTING OF AVENUE TREES INCLUDING EARTH WORK EXCAVATION FOR PIT OF SIZE		Rs.250.00 (Rupees two hundred and fifty	1.NO. (EACH)	3750.00
λ	×.	60X60X60CM FILLED WITH MANURE FOR 20CM DEPTH AND FILLING WITH RIVER SAND AND RED EARTH MIX IN THE RATIO OF 1:1 FOR 40CM DEPTH IN THE SAME PIT AND PLANTING THE AVENUE TREES OF APPROVED		only)	7	j.
		VARIETIES TO A HEIGHT OF 200CM FROM THE GROUND LEVEL AND MAINTAINING THEM FOR THE PERIOD OF 6 MONTH INCLUDING WATERING, PERIODICAL MANURING AND REPLACING THE AVENUE TREES IF DEAD ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (TREE SAPLING SHALL BE GOT APPROVED FROM EE BEFORE PLANTING).	-			
w (V-			~	4.100	×
50.4	15 NOS.	SUPPLYING AND FIXING OF TRIANGULAR SHAPE CHICKEN MESH TREE GUARD USING 8CM DIA CASURINA VERTICAL POST AND MIDDLE TIE USING COUNTRY WOOD REEPER OF SIZE 50X25MM AND 25		Rs.450.00 (Rupees four hundred and fifty only)	1.NO. (EACH)	^ 6750.00
*		GAUGE CHICKEN MESH INCLUDING LABOUR CHARGES FOR FIXING THE TRIANGULAR TREE GUARD AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		×		
52 🖍		SUPPLYING, LAYING, FIXING AND JOINTING THE FOLLOWING PVC PIPES AS PER ASTMD - 1785 OF SCHEDULE 40 OF WALL THICKNESS NOT LESS THAN THE SPECIFIED IN IS 4985 SUITABLE FOR PLUMBING BY THREADING OF WALL THICKNESS INCLUDING THE COST OF SUITABLE PVC/GI SPECIALS /GM SPECIALS LIKE ELBOW, TEE REDUCERS, PLUG, UNION, BEND COUPLER, NIPPLE/ GM GATE VALVE, CHECK AND WHEEL VALVE ETC., WHEREVER REQUIRED ABOVE THIS GROUND LEVEL INCLUDING THE COST OF TEFLOT TAPE, SPECIAL CLAMPS, NAILS, ETC., FIXING ON WALTOTHE PROPER GRADIENT AND ALIGNMENT AND REDOING THE CHIPPED OF MASONRY ETC., AUDIRECTED BY THE DEPARTMENTAL OFFICERS.				
	50.00 Rmt.×	a) 32MM ASTM D SCHEDULE 40 THREADED PV		Rs.165.00 X	1.Rmt.	8250.00
	×c	PIPE WITH NECESSARY PVC/GI SPECIALS		(Rupees one hundred and sixt five only)	METRE)	3
	60.00 Rmt. /	b) 25MM ASTM D SCHEDULE 40 THREADED PV PIPE WITH NECESSARY PVC/GI SPECIALS	C	Rs.175.00 (Rupees one hundred and seventy five only)	1.Rmt. (ONE RUNNING METRE)	10500.00
For	A.P.CONS	STRUCTIONS		×	5 ₁ *	783397.40

SUPERINTENDING ENGINEER/SOUTH CRCLE.

		KABAMALAIKUNDU EL	B AND BEST	2/_		Page No. S
ITEM.NO	QUANTITY	DESCRIPTION OF WORK	TNBF No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
		3	4	5	6	7 783397.40
52.1	6.00 Rmt)	SUPPLYING AND FIXING OF 20 MM BIA SI FIPE 'B' CLASS OF BEST APPROVED QUALITY FOR HOT WATER LINE FULLY CONCEALED IN WALLS INCLUDING COST OF	*	Rs.246.06 (Rupees two hundred and forty	1.Rmt. (ONE RUNNING METRE)	1440.00
2		PIPES AND SPECIALS, LABOUR CHARGES FOR LAYING, JOINTING, TESTING AND REDOING THE DISMANTLED PORTIONS WITH NEAT FINISH ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		enly)		Ē
53.3	5 NOS.	SUPPLYING AND FIXING OF C.I. STEPS OF APPROVED QUALITY AND BRAND (NOT LESS THAN 5KG EACH) INCLUDING COST OF MATERIAL LABOUR CHARGES FOR		Rs.30.00 (Rupees thirty only)	1 NO. (EACH)	150.00
5.		FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS		4.	٨	<i>-</i>
55.2	4 NOS.	SUPPLYING AND FIXING OF APPROVED BRAND PORCELAIN FLAT BACK URINAL SUPERIOR VARIETY INCLUDING COST OF URINAL LEAD PIPE, WASTE PIPE, 15MM WHEEL VALVE, TW PLUG AND LABOUR FOR		Rs.1800.00 (Rupees one thousand and eight hundred only)	1 NO. (EACH)	7200.00
2	Þ	FIXING ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE BRAND AND QUALITY SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		*	Z4.	<i>-</i> A
69	20 NOS.	ELECTRICAL ARRANGEMENTS >> SUPPLYING AND FIXING OF 15 AMPS 3 PIN POWER		Rs.120.00	1 NO.	2400.00
1	/	PLUG TYPE SOCKET ON A SUITABLE MS BOX 16G THICK CONCEALED AND COVERED WITH 3 MM THICK		(Rupees one hundred and	(EACH)	2400.00
	×	LAMINATED HYLEM SHEET INCLUSIVE OF ALL CONNECTIONS AND COST OF ALL MATERIALS.		twenty only) o	ž.	*
72	16 NOS.	SUPPLYING AND FIXING OF BEST APPROVED SUPERIOR VARIETY CONCEALED TYPE FIBRE BOX WITH M.S. FAN HOOK OF 100MM DIA, 75MM DEPTH AND 3MM		Rs.30.00 (Rupees thirty only)	1 NO. (EACH)	480.00
2	58 #	THICK INCLUDING COST AND FIXING IN POSITION ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE).		×.	×	Ž
		>		V		
73.2	2 NOS.	SUPPLYING AND FIXING OF 1 NO THREE PHASE DISTRIBUTION BOARD WITH 4 WAY PER PHASE 32A / PER WAY WITH NEUTRAL LINK ON SUITABLE WELL VARNISHED TEAKWOOD PLANK INCLUDING NECESSARY		Rs.3400.00 (Rupees three thousand and four hundred only)	1.NO (EACH)	6800.00
	×	INTERCONNECTIONS AND EARTH CONNECTIONS COST OF ALL MATERIALS ETC., ALL COMPLETE.		\$	X	
74	16 NOS.	CHARGES FOR ASSEMBLING AND FIXING OF CEILING FAN OF DIFFERENT SWEEP WITH NECESSARY		Rs.300.00	1.NÒ (EACH)	4800.00
y		CONNECTIONS AND FIXING OF FAN REGULATOR ON THE EXISTING BOARD ETC., ALL COMPLETE (EXCLUDING COST OF FAN)		(Rupees three hundred only)	×.	a ^E
76		SUPPLYING AND FIXING OF 8 SWG GI WIRE ON WALL / BELOW GROUND LEVELS WITH NECESSARY 'U' NAILS, EARTH WORK EXCAVATION AND REFILLING ETC		Rs.20.00 (Rupees twenty only)	1.Rmt. (ONE RUNNING METRE)	[≿] 460.00
2	×	INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE.		2	7)	A.
77.3 ✓	5 NOS	SUPPLYING, FIXING AND CONCEALING TW BOX OF SIZE 8'X6'X4" COVERED WITH 3MM THICK HYLEM SHEET INCLUDING COST OF TV LINE SOCKET / TELEPHONE		Rs.60.00 (Rupees sixty only)	1 NO. (EACH)	× 300.00
For A	.P.CONSTI	LINE SOCKET ETC., ALL COMPLETE AND AS DIRECTED OFFICERS.		>	×	7





807427.40

		EADAMALAIKUNDU M	ndasa msa	an 60		Photo Roy 6
ITEM,NO	YTITNAUO	DESCRIPTION OF WORK	тивкио.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	AMOUNT
77.4	30.00 Rmt	SUPPLYING, LAYING AND CONCEALING OF PVC PIPE OF 20MM DIA WITH NECESSARY SPECIALS AND OTHER MATERIALS INCLUDING RUN OFF LIND, FISH WIRE (G.L. 22G) FOR DRAWING CABLE FOR T.V., / TELEPHONE ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	4	Rs.65.00 (Rupees sixty five only)	1.Rmt (ONE RUNNING METRE)	807427.40 1950.00
78	2 NOS	PROVIDING EARTHING STATION (TYPE I) USING PIPE ELECTRODE AS PER IS 3043 USING 2.5M OF 40MM AND 1.0 M OF 20MM B-CLASS GIPIPE INCLUDING EARTH WORK EXCAVATION, BRICK WORK IN CEMENT MORTAR AND PLASTERING AND COST OF FUNNEL, GI NUTS, BOLTS, WASHERS, CHECK NUTS, GI BEND, REDUCER AND COUPLING, C.I. COVER OF 30X30CM AND INCLUDING CHARCOAL OF 40 KGS AND SALT 10 KG ETC., ALL COMPLETE.		Rs.2000.00 (Rupees two thousand only)	1 NO. (EACH)	4000.00
81	0.80 Sq.M _, ∕\	SUPPLYING AND FIXING BEST COUNTRY WOOD METER CUPBOARD WITH SHUTTERS DOUBLE LEAVES WITH 230MMX25MM SIZE CW PLANKS FOR ALROUND SIDES 62,5 MM X31,25MM STYLES AND RAILS FOR SHUTTERS AND 75MM X 25MM WELD MESH OF 6 AND 10 GAUGE FOR PANELS INCLUDING LABOUR CHARGES FOR FIXING IN POSITION OF SHUTTERS AND COST OF 1'L CLAMPS 6 NOS OF SIZE 150X150MM SIZE WITH 25MMX4MM MS FLATS, 1 NO OF 6" X 1/2" ALUMINIUM ALDROP WITH BOLTS AND NUTS 6 NOS OF 3" SIZE 1.0. BUTT HINGES WITH SCREWS 2 NOS OF 2" SIZE 1.0. HOOKS & EYES, TW PLUGS SCREWS ETC. COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS AND AS PER DRAWINGS.		Rs.2100.00 (Rupees two thousand and one hundred only)	1.Sq.M. (ONE SQUARE METRE)	1680.00
86	239.30 Sq.M.	PROVIDING PRE-CONSTRUCTIONAL ANTITERMITE TREATMENT INCLUDING COST OF CHEMICALS LABOUR AS PER STANDARD SPECIFICATIONS FOR PREPARING THE AREA FOR TREATMENT BY SPRAYING CHEMICALS AND OTHER INCIDENTAL CHARGES ETC., COMPLETE. THE RATE SHOULD BE FOR CURING ANTITERMITE TREATMENT FROM THE PLINTH BEAM AND BRICK MASONRY WITH SUPER STRUCTURE IN CONTACT WITH THE BACK FILL EARTH AND AT THE JUNCTION OF THE WALLS. THE TOP SURFACE OF FILLED EARTH FOR FLOORING AND THE SOIL ALONG WITH THE PERIMETER OF THE BUILDING BY MAKING HOLES WITH THE CROW BAR AND POURED 5% TERMICIDE 'CHLORIPYRIFOS" AND SPRAYING THE SAME TERMICIDE SOLUTION ON THE WOODEN FRAMES AND TREATING THE OTHER PERIPHERY OF BUILDINGS ETC., COMPLETE IN ALL RESPECTS AS PER IS 6313 (PART II) 1981 AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.25.00 (Rupees twenty five only)	1.Sq.M. (ONE SQUARE METRE)	5982.50
2.1.2	381.20 Cu.M.	ANNEXURE SUPPLYING AND FILLING IN FOUNDATION AND BASEMENT WITH WELL GRAVEL IN LAYERS OF 150 MM THICKNESS WELL WATERED, RAMMED AND CONSOLIDATED COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS INCLUDING COST OF SUPPLYING WELL GRAVEL AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.600.00 \(\text{(Rupees six hundred only)}\)	1.Cu.M.\ (ONE CUBIC METRE)	228720.00
2.1.3 >> or A.F	70.70 CU.M.	SUPPLYING AND FILLING IN FOUNDATION AND BASEMENT WITH FILLING CRUSHED STONE SAND IN LAYERS OF 150 MM THICKNESS WELL WATERED, RAMMED AND CONSOLIDATED COMPLYING WITH RELEVANT STANDARD SPECIFICATION INCLUDING COST OF SUPPLYING FILLING CRUSHED STONE FOR SUPPLYING FILLING FI		Rs.1000.00 (Rupees one thousand only)	1.Cu.M. (ONE CUBIC METRE)	70700.00
1-1	141-	PARTNER			i i	1120459.90





F

		KADAMALAIKU NDU 34	Se very little	W 849		Page No. 7
ITEM.NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT 7
-						1120459.90
2,1.6	73.70 Cu.M.	SUPPLYING OF STONE DUST INCLUDING CONVEYANCE AND COST OF MATERIALS ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.250.00 (Rupees two hundred and sixty only)	1.6a.M. (ONE CUBIC METRE)	19162.00
3.1.1	62.20 Cu.M.	PLAIN CEMENT CONCRETE 1:5:10 (ONE OF		B. 3800.00	1.Cu.M.	226260 00
3.1,1	02.20 Cu.W.	CEMENT, FIVE OF CRUSHED STONE SAND AND TEN OF HARD BROKEN STONE JELLY) FOR FOUNDATION		Rs.3800.00 (Rupees three thousand and eight hundred only)	(ONE CUBIC METRE)	236360.00
		AND BASEMENT USING 40MM GAUGE HARD BROKEN STONE JELLY INCLUSIVE OF SHORING, STRUTTING AND BAILING OUT WATER WHEREVER NECESSARY RAMMING, CURING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		>	٩	
L	2	and the second s		y .~		
3.2.1	6.40 Cu.M.	PLAIN CEMENT CONCRETE 1:2:4 (ONE OF CEMENT TWO OF CRUSHED STONE SAND AND FOUR OF HARD BROKEN STONE JELLY) USING 20M GAUGE HARD BROKEN STONE JELLY EXCLUDING SHUTTERING AND		Rs.5700.00 (Rupees five thousand and seven hundred only)	1.Cu.M., (ONE CUBIC METRE)	36480.00
		CENTERING BUT INCLUDING LAYING, CURING AND FINISHING WITH RELEVANT STANDARD SPECIFICATIONS IN FOUNDATION AND BASEMENT, AND OTHER SIMILAR WORKS & AS DIRECTED BY THE DEPARTMENTAL OFFICERS.			+	
3.10.1	9.40 Cu.M.	PLAIN CEMENT CONCRETE 1:3:6 (ONE OF CEMENT, THREE OF CRUSHED STONE SAND AND SIX OF HARD		Rs.4200.00 (Rupees four thousand and two	1.Cu.M. (ONE CUBIC METRE)	39480.00
*		BROKEN STONE JELLY) FOR FOUNDATION USING 20MM GAUGE HARD BROKEN STONE JELLY FOR STORM WATER DRAINS SIDE WALL AND OTHER SIMILAR WORKS USING 20MM GAUGE HARD BROKEN STONE JELLY EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS, SHUTTERING, CENTERING AND VIBRATING BUT INCLUDING LAYING, CURING, FINISHING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS,		hundred only)	*	4
4.4.1		PROVIDING AND LAYING IN POSITION, STANDARDISED				
*		CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING 20 MM AND DOWNGRADED HARD BROKEN STONE JELLY FOR ALL RCC WORKS NAMELY COLUMN, COLUMN FOOTINGS, PLINTH BEAM, GRADE BEAM, RAFT BEAM, RAFT SLAB ETC., WITH MINIMUM CEMENT CONTENT OF 325 KG/M3 AND MAXIMUM WATER CEMENT RATIO OF 0.55, INCLUDING ADMIXTURE (PLASTICISER/SUPER PLASTICISER) IN RECOMMENDED PROPORTIONS AS PER IS:9103 TO ACCELERATE, RETARD SETTING OF CONCRETE, IMPROVE WORKABILITY WITHOUT IMPAIRING STRENGTH AND DURABILITY WITH ABOUT (5.0 CU.M)				
		7730 KG. OF 20 MM MACHINE CRUSHED STONE JELLY AND WITH ABOUT (3.3 CU.M.) 5156 KG. OF 10 -12 MM MACHINE CRUSHED STONE JELLY AND WITH ABOUT (4.79 CU.M) 7670 KG. OF CRUSHED STONE SAND FOR MAKING 10M3 CONCRETE BUT EXCLUDING COST OF REINFORCEMENT GRILL AND FABRICATING CHARGES, CENTERING AND SHUTTERING AND ALSO INCLUDING LAYING, VIBRATING WITH MECHANICAL VIBRATORS, FINISHING, CURING ETC., COMPLETE COMPLYING WITH STANDARD SPECIFICATION AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, THE COARSE AND FINE AGGREGATES TO BE USED SHOULD COMPLY WITH THE REQUIREMENTS OF IS STANDARDS. (NO SEPARATE PAYMENT WILL BE MADE BY THE DEPARTMENT FOR THE EXCESS USAGE OF MATERIALS)				
or A.	136.20 Cu.M. P.CONSTR	(a) IN FOUNDATION AND BASEMENT		Rs.6900.00 (Rupees six thousand and nine hundred only)	1.Cu.M. (ONE CUBIC METRE)	939780.00
					7	2391721.90





		KADAMALAIKUNDI IV	a Jenus	70. O' /		Page No: I
EM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	TNUOMA
an i	2	3	7	-		2391721.90
0.1	95.50 Cu.M.	OF CRUSHED STONE SAND WITH ADMIXTURE USING		Rs 5900.00 (Rupees five thousand and nine	1.Cu.M. (ONE CUBIC METRE)	563450.00
	*	KILN BURNT COUNTRY BRICKS OF SIZE 8%"X4%"X2%" (22X11X7CM) IN FOUNDATION AND BASEMENT INCLUDING DEWATERING WHEREVER NECESSARY PROPER SETTING, CURING ETC., COMPLETE WITH RELEVANT STANDARD SPECIFICATIONS		hundred only)	1	À
.4.1		PROVIDING AND LAYING IN POSITION, STANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING 20 MM AND DOWNGRADED HARD BROKEN STONE JELLY FOR ALL RCC ITEMS OF WORKS NAMELY TEE, ELL OR RECTANGULAR BEAMS, LINTELS, PARAPET CUM DROPS, WAIST AND LANDING SLAB, CANOPHY, CIRCULAR COLUMN, FIN PROJECTIONS, SUNSHADES, WINDOW BOXING SLAB, SLAB AND OTHER SIMILAR WORKS WITH MINIMUM CEMENT CONTENT OF 325 KG/M3 AND MAXIMUM WATER CEMENT RATIO OF 0.55, INCLUDING ADMIXTURE (PLASTICISER) IN RECOMMENDED PROPORTIONS				
		AS PER IS:9103 TO ACCELERATE, RETARD SETTING OF CONCRETE, IMPROVE WORKABILITY WITHOUT IMPAIRING STRENGTH AND DURABILITY WITH ABOUT (5,0 CU,M) 7730 KG, OF 20 MM MACHINE CRUSHED STONE JELLY AND WITH ABOUT (3.3 CU,M.) 5156 KG, OF 10 -12 MM MACHINE CRUSHED STONE JELLY AND WITH ABOUT (4,79 CU,M.) 7670 KG, OF CRUSHED STONE				
		SAND FOR MAKING 10M3 CONCRETE BUT EXCLUDING COST OF REINFORCEMENT GRILL AND FABRICATING CHARGES, CENTERING AND SHUTTERING AND ALSO INCLUDING LAYING, VIBRATING WITH MECHANICAL VIBRATORS, FINISHING, CURING ETC., AND PROVIDING FIXTURES LIKE FAN CLAMPS IN THE RCC FLOOR/ROOF SLABS WHEREVER NECESSARY WITHOUT CLAIMING EXTRA, ETC., COMPLETE COMPLYING WITH STANDARD SPECIFICATION AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. THE COARSE AND FINE AGGREGATES TO BE USED SHOULD COMPLY WITH THE REQUIREMENTS OF IS STANDARDS (NO SFPARATE PAYMENT WILL BE MADE BY THE DEPARTMENT FOR THE EXCESS USAGE OF MATERIALS).				
	72.10 Cu.M.X	(a) IN GROUND FLOOR		Rs.6900.00 (Rupees six thousand and nine hundred only)	1.Cu.M. (ONE CUBIC METRE)	497490.0
	X	X		λ,	X	
	113.60 Cu.M.	(b) IN FIRST FLOOR		Rs.6900.00 λ (Rupees six thousand and nine	1.Cu.M. (ONE CUBIC METRE)	783840.0
	X	*		hundred only)		1
	8.00 Cu.M.	(c) IN SECOND FLOOR		Rs.6900.00 (Rupees six thousand and nine hundred only)	1.Cu.M. (ONE CUBIC METRE)	55200.0
	×			x	1	1
).6.1 X	*	BRICK WORK IN CEMENT MORTAR 1:6 (ONE OF CEMENT AND SIX OF CRUSHED STONE SAND) WITH ADMIXTURE USING KILN BURNT COUNTRY BRICKS OF SIZE 8%"X4½"X2½" (22X11X7CM) FOR SUPERSTRUCTURE IN THE FOLLOWING FLOORS INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN POSITION, FIXING OF HOLE FASTS, SCAFFOLDINGS, CURING ETC., COMPLETE IN ALL RESPECT COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.	4 5 6 6 6 7 7			
	/			Rs.5900.00	1.Cu.M.	549880.
	93.20 Cu.M.	(a) IN GROUND FLOOR		(Rupees five thousand and nith	(ONE CUEIC	
rA.	P.CONSTR	CHOHONS			7	7

т		KADAMALAIKUNDIA F	agleza acz	CUE OS		Page No. 9
rem.no	QUANTITY	DESCRIPTION OF WORK	тивь ио.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	AMOUNT
1	2	3	4	5	6	7
						4841581.90
	94.30 Cu.M.	(b) IN FIRST FLOOR		Rs.5900.00 (Rupees five thousand and nine	1.Cu.M. (ONE CUBIC	556370.00
	40	~		hundred only)	METRE)	Dr.
	N.	¥				7
	18.00 Ca.M.	(c) IN SECOND FLOOR		Rs.5900.00 (Rupees five thousand and nine	1.Cu.M. (ONE CUBIC METRE)	106200.0
	X	*		hundred only)	4	
0.6.1		BRICK PARTITION WALL IN CEMENT MORTAR 1:4		**		
Å	*	(ONE OF CEMENT AND FOUR OF CRUSHED STONE SAND) WITH ADMIXTURE 110MM THICK FOR SUPER STRUCTURE IN THE FOLLOWING FLOORS USING KILN BURNT COUNTRY BRICKS OF SIZE 83"X4"X23" (22X11X7CM) INCLUDING LABOUR FOR FIXING THE DOORS, WINDOWS AND VENTILATOR FRAMES IN			(ii	
		POSITION, FIXING OF HOLD FASTS, SCAFFOLDINGS, CURING ETC., COMPLETE IN ALL RESPECT COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS.				
	230.90 Sq.M	(a) IN FOUNDATION AND BASEMENT		Rs.540.00 (Rupees five hundred and forty	1.Sq.M. (ONE SQUARE METRE)	124686.0
	X			only)	4	4
	¥° ;	· · · · · · · · · · · · · · · · · · ·		_		JA:
	252.80 Sq.M.	(b) IN GROUND FLOOR		Rs.540.00 (Rupees five hundred and forty	1.Sq.M. (ONE SQUARE METRE)	136512.0
	×			only)	, s	
	50.40 Sq.M.	(c) IN FIRST FLOOR		Rs.540.00 (Rupees five hundred and forty	1.Sq.M. (ONE SQUARE	27216.0
	>			only)	METRE)	-
1.6.1		BRICK PARTITION WALLS 70MM THICK USING				
X		KILN BURNT COUNTRY BRICKS OF SIZE 8%"X4%"X2%" (22X11X7CM) IN CEMENT MORTAR 1:4 (ONE OF CEMENT AND FOUR OF CRUSHED STONE SAND) WITH ADMIXTURE FOR SUPER STRUCTURE IN		,		
	~	THE FOLLOWING FLOORS INCLUDING SCAFFOLDINGS, CURING ETC., COMPLETE IN ALL RESPECT COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND DRAWINGS		<i>y</i>		
	39.30 Sq.M.	(a) IN GROUND FLOOR		Rs.440.00 \(1.Sq.M. (ONE SQUARE)	17292.
	×	×		(Rupees four hundred and forty only)	METRE)	Y.
	W				4	
	26.00 \$ q.M.	(b) IN FIRST FLOOR		Rs.440.00 (Rupees four hundred and forty	1.Sq.M.\(\text{ONE SQUARE}\)	X11440.
	×	X ,,		only)	METRE)	
2.1.1		BRICK PARTITION WALLS 50MM THICK USING				
*		KILN BURNT COUNTRY BRICKS OF SIZE 8%"X4%"X2" (22X11X5CM) IN CEMENT MORTAR 1:4 (ONE OF CEMENT AND FOUR OF CRUSHED STONE SAND, WITH ADMIXTURE FOR SUPERSTRUCTURE IN THE FOLLOWING FLOORS INCLUDING SCAFFOLDINGS CURING ETC., COMPLETE IN ALL RESPECT COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND				
		DRAWINGS.		·	×	×
	7.70 Sq.M.	(a) IN GROUND FLOOR		Rs.320.00	1.Sq.M.	2464
r A.	P.CONSTR	UCTIONS	y	(Rupees three hundred and twenty only)	(ONE SQUARE METRE)	





THE NAME OF CONTROL OF COUNTY OF COU			KADAMAI AIKUNDI (1)	0.12/10.70	31		Page No. 10
5.00 Sq.M. (D) IN PRIST PLOOR DIFFERENCE SAME FOR COMPANIES AND FOREST CEREMY COMPANIES AND FOREST COMPANIES AND	V25		DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	AND IN WORDS	AMOUNT
14.2.2 OUT YOUNG AND PRICE OF IMPECAL COMES (AS FOR CHAMPERS, APPH) OUTER SINCER COVER SLAS FOR CHAMPERS, APPH (WIT RESEARCH COVER SLAS FOR CHAMPERS, APPH (WILL SINCE) SLAS FOR CHAMPERS, APPH (W			3				5823761.90
CONCRETE SLAB FOR CUPBOARDOWNED PROSES SENIORS COVER READ TO CHAMBERS, DATE OF CONCRETE SIMILAR WORKS IN STANDARDISED OTHER SIMILAR WORKS		9.00 Sq.M.	(b) IN FIRST FLOOR		(Rupees three hundred and	(ONE SQUARE	2880,00
CONCRETE SLAB FOR CUPBOARDOWNED PROSES SENIORS COVER READ TO CHAMBERS, DATE OF CONCRETE SIMILAR WORKS IN STANDARDISED OTHER SIMILAR WORKS					2		
82.90 Sq.M. (a) IN GROUND FLOOR Re.950.00 (Rupees nine hundred and fifty only) SUPPLYING AND FIXING OF PRECAST CEMENT CONCRETE SLAB FOR CUMBANERS BAFFLE WALLS SIDE SLAB FOR CHAMBERS BAFFLE WALLS SIDE SLAB FOR CONCRETE WITH IS. 456 – 2000 USING RUSHED STONE SILLY FOR THE ABOVE FOR CHIEF OF THE ABOVE FOR C	14.2.2		CONCRETE SLAB FOR CUPBOARD/WARD ROBES SHELVES, COVER SLAB FOR CHAMBERS, BAFFLE WALLS SIDE SLABS OF BOXING AROUND WINDOWS AND OTHER SIMILAR WORKS IN STANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING CRUSHED STONE SAND AND 3 TO 10 MM THICK HARD BROKEN STONE JELLY FOR THE ABOVE RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING, FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS ETC., COMPLETE IN THE FOLLOWING FLOORS (MEASUREMENT WILL BE TAKEN INCLUDING BEARING	3			
36.20 Sq.M. (b) IN FIRST FLOOR RE-950.00 (Rupees nine hundred and fifty only) 14.2.3 SUPPLYING AND FIXING OF PRECAST CEMENT CONCRETE SLAB FOR CUPBOARDOWARD ROBES SHELVES, COVER SHELVES, C			20 MM THICK				
36.20 Sq.M. (b) IN FIRST FLOOR (Rupees nine hundred and fifty only) SUPPLYING AND FIXING OF PRECAST CEMENT CONCRETE SIAB FOR CUPBOARDAWARD ROBES SHELVES, COVER SIAB FOR CUPBOARDAWARD ROBES SHELVES, COVER SIAB FOR CHAMBERS, BAFEE WALLS SIDE SIABS OF BOXING AROUND WINDOWS AND OTHER SIMILAR WORKS IN STANDARDISED CONCRETE MIX MAZ GRADE IN ACCORDANCE WITH S. 455 2000 USING CRUSHED STONE SAND AND 3 TO 10 MM THICK HARD BROKEN STONE SALD FOR THE ABOVE RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REIN-POCKEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING, FINISHING AND EXISTING MAD SHEED FLOATIONS ETC., COMPLETE IN THE FOLORISM MAZADREMENT WILL BE TAKEN INCLUDING BEARING MAY MALL ALSO.) 40 MM THICK 11.40 Sq.M. (a) IN FOUNDATION AND BASEMENT (b) IN GROUND FLOOR RS.1000.00 (Rupees one thousand only) RS.1000.00 (Rupees one thousand only) 1.Sq.M. (ONE SQUARE METRE) ** ** ** ** ** ** ** ** **		82.90 S q.M.	(a) IN GROUND FLOOR		(Rupees nine hundred and fifty only)	(ONE SQUARE METRE)	78755.00
SUPPLYING AND FRING OF PRECAST CEMENT CONCRETE SLAB FOR CUPPOARDWARD ROBES SHELVES, COVER SLAB FOR CHAMBERS, BAFFLE WALLS SIDE SLABS OF BOXING AROUND WINDOWS AND OTHER SIMILAR WORKS IN TATANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS 456 -2000 LUBING CRUSHEDS STONE SAMD AND 3 TO 5 MM THICK HARD BROKEN STONE SHLY FOR THE AMOD FARRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING, FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS ETC., COMPLETE IN THE FOLLOWING FLOORS (MEASUREMENT WILL BE TAKEN INCLUDING BEARING IN WALL ALSO). 40 MM THICK 11.40 Sq.M. (a) IN FOUNDATION AND BASEMENT 8.10 Sq.M. (b) IN GROUND FLOOR RE.1000.00 (Rupees one thousand only) RE.1000.00 (Rupees one thousand only) RE.1000.00 (Rupees one thousand only) A P CONSTRIL CTIONS		36.20 Sq.M.	(b) IN FIRST FLOOR			1.Sq.M.	34390.00
SUPPLYING AND FIXING OF PRECAST CEMENT CONCRETE SLAB FOR CUMBOROWARD ROBES SHELVES, COVER SLAB FOR CUMBOROWARD ROBES SHELVES, COVER SLAB FOR CHAMBERS, BAFFLE WALLS SIDE SLABS OF BOXING AROUND WINDOWS AND OTHER SMILLAR WORKS IN STANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 465 - 2000 USING CRUSHED STONE SAND AND 3 TO 10 MM THICK HARD BROKEN STONE JELLY FOR THE ABOVE RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS BUT INCLIDING PRECASTING, MOULDING, PRECASTING, MOULDING, PERCASTING, MOULDING, CHING, PERCASTING, MEASUREMENT WILL BE TAKEN INCLUDING BEARING IN WALL ALSO). 40 MM THICK 11.40 Sq.M. (a) IN FOUNDATION AND BASEMENT RS.1000.00 (Rupees one thousand only) RS.1000.00 (Rupees one thousand only) RS.1000.00 (Rupees one thousand only) 1.Sq.M. (ONE SQUARE METRE) A SQ.M. (c) IN FIRST FLOOR RS.1000.00 (Rupees one thousand only) 1.Sq.M. (ONE SQUARE METRE) A SQ.M. (NE SQUARE METRE) A P CONSTRICTIONS		X	*			METRE)	+
SUPPLYING AND FIXING OF PRECAST CEMENT CONCRETE SLAB FOR CUPBOARDWARD ROBES SHELVES, COVER SLAB FOR CUPBOARDWARD ROBES SHELVES, COVER SLAB FOR CHAMBERS, BAFFLE WALLS SIDE SLABS OF BOXING AROUND WINDOWS AND OTHER SIMILAR WORKS IN STANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 468 - 2000 USING CRUSHED STONE SAND AND 3 TO 10 MM THICK HAPD BROKEN STONE JELLY FOR THE ABOVE RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING, FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS ETC., COMPLETE IN THE FOLLOWING FLOORS (MEASUREMENT WILL BE TAKEN INCLUDING BEARING IN WALL ALSO). 40 MM THICK 11.40 Sq.M. (a) IN FOUNDATION AND BASEMENT (Rupees one thousand only) RS.1000.00 (Rupees one thousand only) RS.1000.00 (Rupees one thousand only) A P CONSTRICTIONS			.,,		×	+	
11.40 sq.M. (a) IN FOUNDATION AND BASEMENT Rs.1000.00 (Rupees one thousand only)			CONCRETE SLAB FOR CUPBOARD/WARD ROBES SHELVES, COVER SLAB FOR CHAMBERS, BAFFLE WALLS SIDE SLABS OF BOXING AROUND WINDOWS AND OTHER SIMILAR WORKS IN STANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING CRUSHED STONE SAND AND 3 TO 10 MM THICK HARD BROKEN STONE JELLY FOR THE ABOVE RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS ETC. COMPLETE IN THE FOLLOWING FLOORS (MEASUREMENT WILL BE TAKEN INCLUDING BEARING IN WALL ALSO).				
Rs.1000.00 (Rupees one thousand only) 8.10 Sq.M. (b) IN GROUND FLOOR Rs.1000.00 (Rupees one thousand only) A P CONSTRICTIONS		2			to provide		1
8.10 Sq.M. (b) IN GROUND FLOOR Rs.1000.00 (Rupees one thousand only) Rs.1000.00		. ,	(a) IN FOUNDATION AND BASEMENT			(ONE SQUARE	
Rs.1000.00 (Rupees one thousand only) Rs.1000.00 (Rupees one thousand only) Rs.1000.00 (Rupees one thousand only) A P CONSTRUCTIONS					7-	+	
8.10 Sq.M. (c) IN FIRST FLOOR RS.1000.00 / (Rupees one thousand only) RS.1000.00 / (Rupees one thousand only) A P CONSTRUCTIONS		8.10 Sq.M.	(b) IN GROUND FLOOR				8100.00
(Rupees one thousand only) A P CONSTRUCTIONS (Rupees one thousand only)		X			V	METRE)	1
(Rupees one thousand only) A P CONSTRUCTIONS (Rupees one thousand only)		~			/		
Dr A P CONSTRUCTIONS					II.	(ONE SQUARE	
or A.P.CONSTRUCTIONS					λ .	7	
	or A.P	.CONSTRI	CTIONS				5967386.90



		KADAMALAIRI NDU VI	ic your	2-		Page No. 11
EMLNO :	QUANTITY	DESCRIPTION OF WORK	тиве ид.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
4		3	45	3	6	7 5967386.90
6.1.1		PRECAST CEMENT CONCRETE JALLY				
1		GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING				
7		20MM AND DOWNGRADED HARD BROKEN STONE JELLY FOR THE ABOVE RCC ITEM OF WORK WITHOUT				
1		VIBRATING CHARGES EXCLUDING THE COST AND				
		FABRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING,				
		FINISHING AND FIXING IN POSITION COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS ETC.,				
		COMPLETE IN THE FOLLOWING FLOORS.				
		50 MM THICK		İ	1	
	9.40 Sq.M.	(a) IN GROUND FLOOR		Rs.2000.00	1.Sq.M.	18800.0
		(,		(Rupees two thousand only)	(ONE SQUARE	
i	X	i		V	METRE) 💝	1.6
İ					1	1
	9.00 Sq.M.	(b) IN FIRST FLOOR		Rs.2000.00	1.Sq.M.	18000.0
				(Rupees two thousand only)	(ONE SQUARE METRE)	
	X				,	Je
					t	1
B.1		PROVIDING FORM WORK AND CENTERING FOR REINFORCED CEMENT CONCRETE WORKS INCLUDING			¥.	
		SUPPORTS AND STRUTTING UP TO 3,30M HEIGHT FOR			*	
		PLANE SURFACES AS DETAILED BELOW WITH ALL CROSS BRACINGS USING MILD STEEL SHEETS OF SIZE				
		90CMX60CM AND MS 10 GAUGE STIFFENED WITH				
		25MMX25MMX3MM FOR BOARDING LAID OVER SILVER			1	
		OAK OR COUNTRY WOOD JOISTS OF SIZE 10CMX6.5CM SPACED AT ABOUT 90CM CENTRE TO CENTRE AND				
		SUPPORTED BY CASURINA PROPS 10CM TO 13CM DIA				
		SPACED AT 75CM INTERVALS AND REMOVING THE SAME AFTER A SPECIFIED PERIOD WITHOUT DAMAGING				
1		THE R.C.C WORKS ETC., COMPLETE COMPLYING WITH STANDARD SPECIFICATIONS AND AS DIRECTED BY THE				
- 1		DEPARTMENTAL OFFICERS.				
- 1						-
	518.60 Sq.M.	(a) FOR COLUMN FOOTINGS, PLINTH BEAM,		Rs.600.00	1.Sq.M. (ONE SQUARE	311160.0
	5.	GRADE BEAM, RAFT BEAM, RAFT SLAB ETC.,		(Rupees six hundred only)	METRÉ)	
1	Y	_			` \	
	1338.10 Sq.M.	(b) PLAIN SURFACES SUCH AS ROOF SLAB,		Rs.680.00 X	1.Sq.M.	000000
	\ \	FLOOR SLAB, BEAMS LINTELS, LOFTS, SILL		(Rupees six hundred and	(ONE SQUARE	909908.
	`	SLAB, STAIRCASE WAIST, PORTICO SLAB AND		eighty only)	METRE)	+
	*	OTHER SIMILAR WORKS		4	+	f
	V-	λ			\	
	526.10 Sq.M.	(c) FOR SQUARE AND RECTANGULAR COLUMNS,		Rs.800.00	1.Sq.M.	× 420880.
		AND SMALL QUANTITIES SUCH AS SUNSHADE,		(Rupees eight hundred only)	(ONE SQUARE	420000.0
1	X	PARAPET CUM DROPS, WINDOW BOXING, FIN			METRE)	+
	×.	PROJECTION AND OTHER SIMILAR WORKS			<i>\</i>	
		X				
	V			ples occaregore	×	W-
	45.90 Sq.M.	(d) FOR VERTICAL WALL		Rs.900.00	1.Sq:fM, (ONE SQUARE	41310.
	\=	,		(Rupees fine hundred only)	METRE)	
	1			1	1	
	2 20 6- 44	(A) EOD CURVER CURTAGE		D- 4400 00 Å		\
	Z.3U SQ.M.	(f) FOR CURVED SURFACE		Rs.1100.00 (Rupees one thousand and one	1.Sq.M. (ONE SQUARE	2530.
	X	4		hundred only)	METRE)	1
- 1).	,			· +	7
	X			1		1/2
		(g) DOUBLE CENTERING		Rs.1400.00 X	1.Sq.M.	608440.
	434.60 \$q.M.			(Rupees one thousand and four	(ONE SQUARE)	
		5 a		Brown day of and S. A.	METRE)	
A.P		ICTIONS A	=	hundred only)	METRE)	+
			-	hundred only)	METRE)	. +

		KADAMALAIRUNDI UR	A See Leave	OF OF		ige No. 12
EW NO	OUANTITY		TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	TNUOMA
5	Ž	3	4.	5	U	82.0414.90
1,5,2	ZU.SU ລີຖຸ.M.	PROVIDING AND FIXING OF FACTORY MADE UNPLASTICIZIED POLYVINYL CHLORIDE (UPVC) DOOR FRAME OF SIZE 50X47MM WITH A WALL THICKNESS OF		Rs.3165.00 (Rupees three thousand one hundred and sixty five only)	1.Sq.M. (ONE SQUARE METRE)	64882.50
2	Χ	5MM, MADE OUT OF EXTRUDED 5MM RIGID UPVC FOAM SHEET, MITERED AT TWO CORNERS AND JOINED WITH 2 NOS OF 150MM LONG BRACKETS OF 15X15MM M.S SQUARE TUBE THE TWO VERTICAL AND HORIZONTAL DOOR PROFILES ARE TO BE REINFORCED WITH		*	+	+
		19X19MM M.S SOUARE TUBE OF 18 GAUGES WITH PRIMER COAT THE DOOR FRAME SHALL BE FIXED TO THE WALL USING 65MM/100MM LONG M.S SCREW THROUGH THE FRAME BY USING PVC FASTENERS. A MINIMUM OF 4 NOS. SCREWS TO BE PROVIDED FOR EACH VERTICAL MEMBER AND MINIMUM 2 NOS. FOR HORIZONTAL MEMBER ETC., PROVIDING AND FIXING OF 30MM THICK FACTORY MADE DOOR SHUTTER WITH UNPLASTICIZED POLYVINYL CHLORIDE (UPVC) SOLID DANIEL FOAM SHEFT STRUCTURED WITH M.S., TUBE OF				
	5	19 GAUGE THICKNESS AND SIZE 19MM X 19MM FOR STYLES AND 15MM X 15MM FOR TOP RAIL AND BOTTOM RAIL. PANELLING OF 5MM THICK UPVC ONE SIDE PRINTED LAMINATION SINGLE SHEET TO BE FITTED IN THE M.S. FRAME WELDED / SEALED TO THE STYLES AND RAILS COVERED WITH 5MM THICK HEAT MOULDED UPVC 'C' CHANNEL OF 30MMX50MM AND 5MM THICK 75MM WIDE UPVC SHEET FOR TOP RAIL, LOCK RAIL AND BOTTOM RAIL ON EITHER SIDE AND 10MM (5MM X NOS.) THICK, 20MM WIDE CROSS UPVC SHEET AS GAI INSERT FOR TOP RAIL AND BOTTOM RAIL, AND JOINED				
		TOGETHER WITH PVC SOLVENT CEMENT ADHESIVE, ALL ADDITIONAL 5MM THICK UPVC STRIP OF 20MM WIDTH INTO BE STUCK ON THE INTERIOR SIDE OF THE "CHANNEL USING PVC SOLVENT CEMENT ADHESIVE THE COST AND LABOUR CHARGES FOR FIXING OF NOS. 4" SS BUTT HINGES AND ALLUMINIUM FURNITUR FITTING SUCH AS 1 NO. 4" TOWER BOLT, 1 NO. 4LDROP, 2 NOS. 6" FLAT "D' TYPE HANDLE, ETC AR INCLUDED. THE FITTING PROVIDED SHALL BEAR IS MARKS. TO ENSURE THE GENUINITY OF PRODUCT, THE	3 E 5" E 51			
		DOOR SET SHOULD HAVE 4 NUMBERS OF MANUFACTURER'S LOGO HOLOGRAM OF APPROVE BRAND, EACH AT FRAME, STYLE, RAIL AND INTERPANEL. (THE QUALITY AND BRAND OF DOOR SHUTTE AND FURNITURE FITTINGS SHOULD BE GOT APPROVE BY THE EXECUTIVE ENGINEER BEFORE USE)	R R			
21.5.5		SUPPLYING AND FIXING OF UPVC (UNPLASTICISE POLYVINYL CHLORIDE) WINDOW FRAM HAVING 2 TRACKS FOR 2 SHUTTER OF UP PROFILE SECTION OF SIZE 62MM X 60MM X 60M HAVING OUTER WALL THICKNESS OF 2.3MM (+/- 0.3M WITH 3 BOX MULTI-CHAMBER CONSTRUCTION, SLIDI SHUTTER SHALL BE MADE OF 66MMX42MMX50M HAVING OUTER WALL THICKNESS OF 2.3MM (+/- 0.3M ALL PROFILES OF FRAMES AND SASH SHALL REINFORCED WITH GALVANIZED MILD STEEL SECTIOF 1.2MM WALL THICKNESS, AT WHEREVER REQUIR ALL THE CORNERS AND JOINTS OF THE FRAME & 57 SHALL BE MITRED CUT & FUSION WELDED WITHOUT	VC VMM VMM VMM VMM VMM VMM VMM VMM VMM V			
		ANY MECHANICAL JOINT, ALL WELDED JOINTS ARE BE NEATLY TRIMMED & FEATURE GROOVED / RAIS NIB FINISH SO AS TO MAKE THE FINISHED PRODUCE FREE FROM ALL SHARP EDGES & BURRS. SYS'S SHALL HAVE ADEQUATE DRAINAGE MECHANISM PERMIT THE ESCAPE OF WATER FROM HORIZON MEMBER BENEATH EACH SEALED UNIT. SYSTEM SHBE PROVIDED WITH SUITABLE UPVC BEADING OF \$24.5MMX16MM FOR GLAZING AND INTERLOCK PROFILE OF SIZE 45MMX36MM WITH 5MM THE PINHEAD GLASS (SINGLE), DULY CUT AT CORR DEGREE & FITTED WITH EPDM GASKETS. WINDOWN TO BE PROVIDED WITH VARIETY OF SECULDEVISE LIKE TOUCH LOCK OR CRESCENT LOCK, NY ROLLERS ETC., AS PER THE REQUIREMENT,	TAL IALL SIZE SING HICK ECT DWS RITY			83632
For A	.P.CONS	TRUCTIONS		E) = =		



ITEM;NO	YTITMAUD	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
1	2	3	4	FIGURES AND IN WORDS 5	AND IN WORDS	7
		COMPLAINT WITH RELEVANT SPECIFICATION AND AS DIRECTED BY THE DEPARTMENT PERSONNEL THE COMPLETE WINDOW SHALL BE FIXED INTO THE PREFINIONED OFFICE PLACES, BY DRILLING & FIXING THROUGH THE OUTER FRAME USING HIGH QUALITY FASTENERS & SILICON SEALANT IS APPLIED TO FILL UP THE GAP BETWEEN WALL & WINDOW FRAME FOR LEAK-PROOF INSTALLATION, AND COMPLETION. (THE OUALITY AND BRAND SHALL BE GOT APPROVED FROM THE EE/SE/CE BEFORE USE)				8363297.4
	4.50 Sq.M.	a) 0.90 X 1.65 MT. WINDOW (TWO TRACK)		Rs.5000.00 (Rupees five thousand only)	1.Sq.M. (ONE SQUARE METRE)	22500.0
	2			*	METALE)	4
21.5.6		SUPPLYING AND FIXING OF UPVC (UNPLASTICISED			t	
X		POLYVINYL CHLORIDE) WINDOW FRAMES HAVING 3 TRACKS FOR 3 SHUTTER OF UPVC PROFILE SECTION OF SIZE 112MM X 52MM X 112MM HAVING OUTER WALL THICKNESS OF 2.3MM (+/- 0.3MM) WI H 3 BOX MUL 1-CHAMBER CONSTRUCTION, SLIDING SI IUTTER SHALL BE MADE OF 92MMX42MMX76MM HAVING OUTER WALL THICKNESS OF 2.3MM (+/- 0.3MM), ALL PROFILES OF FRAMES AND SASH SHALL BE REINFORCED WITH GALVANIZED MILD STEEL SECTION OF 1.2MM WALL THICKNESS, AT WHEREVER REQUIRED, ALL THE CORNERS AND JOINTS OF THE FRAME & SASH SHALL BE MITRED CUT & FUSION WELDED WITHOUT ANY MECHANICAL JOINT, ALL WELDED JOINTS ARE TO				
		BE NEATLY TRIMMED & FEATURE GROOVED / RAISED NIB FINISH SO AS TO MAKE THE FINISHED PRODUCTS FREE FROM ALL SHARP EDGES & BURRS. SYSTEM SHALL HAVE ADEQUATE DRAINAGE MECHANISM TO PERMIT THE ESCAPE OF WATER FROM HORIZONTAL MEMBER BENEATH EACH SEALED UNIT. SYSTEM SHALL BE PROVIDED WITH SUITABLE UPVC BEADING OF SIZE 24.5MMX16MM FOR GLAZING AND INTERLOCKING PROFILE OF SIZE 49MMX45MM WITH 5MM THICK PINHEAU GLASS (SINGLE), DULY CUI AT CORRECT DEGREE & FITTED WITH EPDM GASKETS. WINDOWS HAS TO BE PROVIDED WITH VARIETY OF SECURITY DEVISE LIKE TOUCH LOCK OR CRESCENT LOCK, NYLON ROLLERS ETC., AS PER THE REQUIREMENT,				
		COMPLAINT WITH RELEVANT SPECIFICATION AND AS DIRECTED BY THE DEPARTMENT PERSONNEL. THE COMPLETE WINDOW SHALL BE FIXED INTO THE PREFINISHED OPENED PLACES, BY DRILLING & FIXING THROUGH THE OUTER FRAME USING HIGH QUALITY FASTENERS & SILICON SEALANT IS APPLIED TO FILL UP THE GAP BETWEEN WALL & WINDOW FRAME FOR LEAK-PROOF INSTALLATION, AND COMPLETION, (THE QUALITY AND BRAND SHALL BE GOT APPROVED FROM THE EE/SE/CE BEFORE USE)				
		z a			•	X
	12.40 Sq.M. X	a) 1.50 X 1.65 MT. WINDOW (THREE TRACK)		Rs.6200.00 X (Rupees six thousand and two hundred only) Y	1.Sq.M. (ONE SQUARE METRE)	² 76880.0
22.3.3	15.20 Sq.M.	PROVIDING T.W. DOUBLE LEAF SHUTTERS FOR CUPBOARD/WARD ROBES WITH 9MM THICK		Rs.5200.00 (Rupees five thousand and two	1.Sq/M. (ONE SQUARE METRE)	79040.0
*	X	PHENOL BONDED BWR GRADE PLYWOOD AS PER IS 303-1989 (GENERAL) WITH IS 5539 1969 (FOR PRESERVATIVE TREATMENT) AND IS 848-1974 (FOR ADHESIVE) WITH RELEVANT IS SPECIFICATIONS AND ITS LATEST AMENDMENT FOR SHUTTERS. THE ALL ROUND FRAME MADE UP OF T.W SCANTLING OF 75MMX37.50MM AND THE STYLES MADE UP OF T.W. SCANTLINGS OF 75MM X 37.50MM AND SHUTTER MIDDLE RAIL (HORIZONTAL) MADE UP OF T.W. SCANTLING OF 150MM X37.50MM INCLUDING COST OF BWR GRADE PLYWOOD AND LABOUR FOR FIXING IN		hundred only)	+	+
A.P	CONSTRU	CTION				8541717.
	1101110	CHONS		, , ,	,	

RTNER

NO. OF CORRECTIONS

SUPERINTENDING ENGINEERSOUTH CHICLE.

		KADAMALAIKUNDU HI	L. Opense	11.57		Page No. 14
NG	OUANTITY 2	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT
		POSITION, COST OF MATERIALS, ALUMINIUM FURNITURE FITTINGS SUCH AS 6 NOS OF 3 OF ALUMINIUM BUTT HINGES 2 NOS OF 4 OF ALUMINIUM TOWER BOLT, 2 NOS OF 4 ORNAMENTAL HANDLE, LOCK AND KEY ARRANGEMENTS (LEAVER TYPE) OF BEST APPROVED QUALITY WITH BRASS SCREWS AND ALSO PAINTING WITH TWO COATS OF APPROVED FIRST CLASS SYNTHETIC ENAMEL READY MIXED PAINT OVER ONE COAT OF WOOD PRIMER OF APPROVED QUALITY ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE LOCK AND ALUMINIUM FURNITURE FITTINGS SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)				8541717.40
3.3		SUPPLYING AND FIXING OF SINGLE LEAF SOLID CORE FLUSH DOOR SHUTTERS USING BOILED WATER RESISTANCE (BWR) TEAK WOOD PLY AS PER IS 303-1989, THE CROSS BAND AND FACE VENEERS ARE TO BE BANDED WITH PHENOL FORMALDEHYDE SYNTHETIC RESIN IN HOT PRESS BOTH SIDES AND MANUFACTURING THE SHUTTER BY USING QUALITY TIMBER OF TERMITE PROOF AND SEASONED TO MOISTURE CONTENT NOT MORE THAN 10%, HOT PRESSED WITH HYDRAULIC PRESS AT A TEMPERATURE OF 1500C TO THE NORMS AS PER IS 2002-1983 AND THE PLY ON BOTH SIDE WITH TEAK WOOD LIPPING AROUND, 35MM THICK INCLUDING COST AND FIXING OF ALUMINIUM FURNITURE FITTINGS SUCH AS 2 NOS. OF				
	38.40 Śa.M.	6" DOOR HANDLE, 4 NOS. OF 5" BUTT HINGES, 2 NOS. OF 6"X1/2" TOWER BOLT, 1 NO. OF 10"X5/8" ALDROP, 1 NO 40MM DIA & 60MM LONG RUBBER BUSH, 1 NO ALUMINIUM DOOR STOPPER WITH RUBBER BUSH WITH REQUIRED BRASS SCREWS, LABOUR CHARGES FOW WOUGHT AND PUT UP AND FIXING IN POSITION OF FLUSH DOOR SHUTTERS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND OF MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE,)		Rs.5000.00	1.Sq.M.	192000
	38.40 Sq.m.	a) 1200 X 2400 MM		(Rupees five thousand only)	(ONE SQUARE METRE)	+
	3.80 Sq.M.	b) 900 X 2400MM		Rs.5400.00 (Rupees five thousand and four hundred only)	1.Sq.M. (ONE SQUARE METRE)	20520
×.2.1	113.00 Sq.M.	SUPPLYING AND FIXING OF 4 MM THICK PIN HEADE GLASS PANELS WITH ALUMINIUM ANODIZED 'U' SHAP BEADING OF SIZE 12X12 MM WITH 107 GRAM INTERIOR OF THE SHORTH WITH ALUMINIUM BOLTS AND NUTS FOR THE SHUTTERS OF THE STEE WINDOWS ALREADY SUPPLIED TO SUIT ALL THE SIZE AND AS DIRECTED BY THE DEPARTMENTAL OFFICER: (THE QUALITY OF GLASS AND ALUMINIUM BEEDIN SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	E N N L L E S. G	Rs.680.00 X (Rupees six hundred and eighty only)	1.Sq.M. (ONE SQUARE METRE)	76840
6.1	61.00 Cu.M.	FLOORING WITH A BED OF CEMENT CONCRET 1:5:10 (ONE OF CEMENT, FIVE OF CRUSHED STONS SAND AND TEN OF HARD BROKEN STONE JELLY AN TOP LEFT ROUGH TO RECEIVE THE FLOOR FINISH WIT REQUIRED SLOPES INCLUDING RAMMING, CURING ETG ALL COMPLETE COMPLYING WITH RELEVANS STANDARD SPECIFICATIONS.	Y)	Rs.4000.00 (Rupees four thousand only)	1.Cu.M. (ONE CUBIC METRE)	244000
						907507

HIA TIPARTNER

NO. OF CORRECTIONS



		KADAMAI AIKUNDI PII	mylas Pa	14. 1-12	Р ики I	(e: 15
N NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES ! AND IN WORDS ! 6	AMOUNT
.1		PLASTERING THE TOP OF FLOORING IN CM 1:4 (ONE OF CEMEN, AND FOUR OF CRUSHED STONE SAND) 20MM THICK INCLUDING SURFACE RENDERED SMOOTH INCLUDING PROVIDING PROPER SLOPES, THREAD LINING, CURING AND 150MM WIDE SKIRTING ALROUND WITH THE SAME CEMENT MORTAR ETC. COMPLETE IN ALL RESPECTS.		Rs.350,00 (Rupees three hundred and fifty only)	1.Sq.M. (ONE SOUARE METRE)	145530.00
8.1	164.10 Sq.M.	SUPPLYING AND FIXING OF COLOUR GLAZED TILES OF BEST APPROVED QUALITY (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT PLASTERING IN CM 1:2 (ONE OF CEMENT AND TWO OF CRUSHED STONE SAND) 10MM THICK INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY, POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER) CURING, FINISHING ETC., ALL COMPLETE AND AND DIRECTED BY THE DEPARTMENTAL OFFICERS. (THI BRAND AND QUALITY OF TILES SHOULD BE GO'APPROVED FROM THE EXECUTIVE ENGINEER BEFORM USE).	100	Rs.1100.00 (Rupees one thousand and one hundred only)	1.Sq.M (ONE SQUARE METRE)	180510.00
×.9.1	53.00 Sq.M.	SUPPLYING AND LAYING OF CERAMIC TILES (ANT SKID) OF BEST APPROVED QUALITY FOR FLOORIN AND OTHER SIMILAR WORKS (THE COLOUR AND SHAD SHALL BE GOT APPROVED FROM THE EXECUTIVENGINEER BEFORE USING) OVER CEMENT MORTOR I (ONE OF CEMENT AND THREE OF CRUSHED STON SAND) 20MM THICK INCLUDING FIXING IN POSITION CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY, POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER), CURING, FINISHIN ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE BRAND AND QUALITOF TILES SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).	3 E 1 F E H G E Y	Rs.1000.00 (Rupees one thousand only)	1.Sq.M. (ONE SQUARE METRE)	53000.0
2.1.1	579.70 Sq.M.	FINISHING TOP OF ROOF WITH ONE COURSE HYDRAULIC PRESSED TILES OF APPROVED SUPERIOR QUALITY OF SIZE 23CMX 23CMX20MM THICK LAD OVER WEATHERING COURSE IN CM 1:3 (ONE CEMENT AND THIFF OF CRUSHED STONE SAN 12MM THICK MIXED WITH WATER PROOFING COMPOUND AT 2% BY WEIGHT OF CEMENT USED A POINTED NEATLY WITH THE SAME CEMENT MORT MIXED WITH WATER PROOFING COMPOUND INCLUDIC CURING ETC., AS PER STANDARD SPECIFICATION (THE QUALITY OF TILES SHALL BE GOT APPROVERED TO THE EBEFORE USE)	ND AR NG NS.	Rs.900.00 A (Rupees nine hundred only)	1.Sq.M. (ONE SQUARE METRE)	521730
33.1	4058.20 Sq.M.	PLASTERING WITH CM 1:5 (ONE OF CEMENT AFFIVE OF CRUSHED STONE SAND) 12MM THIS FINISHED WITH NEAT CEMENT INCLUDING PROVIDED BAND CORNICE, CEILING CORNICE, CURISCAFFOLDING ETC., COMPLETE IN ALL RESPECTS ACCOMPLYING WITH RELEVANT STANDAM SPECIFICATIONS.	CK ING NG, AND	Rs.200.00 (Rupees two hundred only)	1.Sq.M.\ (ONE SQUARE METRE)	81164
34.1	185.50 Sq.M	PLASTERING WITH CM 1:4 (ONE OF CEMENT FOUR OF CRUSHED STONE SAND) 12MM THE FINISHED WITH NEAT CEMENT INCLUDING PROVIDE BAND CORNICE, CEILING CORNICE, CURSCAFFOLDING ETC., COMPLETE IN ALL RESPECTS COMPLYING WITH STANDARD SPECIFICATIONS,	ICK ING ING,	Rs.220.00 (Rupees two hundred and twenty only)	1.Sq.M. (ONE SQUARE METRE)	4081
22 A	TI COMOT	RUCTIONS				1082829

SUPERINTENDING ENGINEER/SOUTH CIRCLE.

		KAHAMALAIRUNDU H	HE SECTION	100		Perperfue 16
EM NO	QUANTITY 2	DESCRIPTION OF WORK 3	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	amount 7
		101				10828297.4
5.1.1	35.10 S a.M.	PLASTERING IN CM 1:3 (ONE OF CEMENT AND THREE OF CRUSHED STONE SAND) 12MM TK. MIXED WITH WATER PROOF COMPOUND AT 2 % BY		Rs.220.00 (Rupees two hundred and twenty only)	1.Sq.M. (ONE SQUARE METRE)	7727 (
	3	WEIGHT OF CEMENT FOR SUMP INCLUDING SCAFFOLDING CURING, FINISHING ETC. COMPLETE IN ALL RESPECTS AND COMPLYING WITH STANDARD SPECIFICATIONS.		A	+	Hor
35.2	910.00 Sq.M	SPECIAL CEILING PLASTERING IN CEMENT MORTAR 1:3 (ONE OF CEMENT AND THREE OF		Rs.230.00 (Rupees two hundred and thirty	1 Sq M (ONE SQUARE METRE)	209300.
λ.	×	CRUSHED STONE SAND) 10MM THICK FOR BOTTOM OF ROOF, STAIR, WAIST, LANDING AND SUNSHADES IN ALL FLOORS FINISHED WITH NEAT CEMENT INCLUDING HACKING THE AREAS, PROVIDING BAND CORNICE, SCAFFOLDING, CURING ETC., COMPLETE.		only)	,	Ť
36.1		PLASTERING FOR BORDER IN CM 1:5 (ONE OF CEMENT AND FIVE OF CRUSHED STONE SAND) 12MM THICK FINISH IN ALL FLOORS FOR ELEVATION PURPOSES, INCLUDING SCAFFOLDING, CURING, FINISHING ETC., ALL COMPLETE.				
	337.80 Rmt.	(a) 150MM WIDE BORDER	>:	Rs.50.00 (Rupees fifty only)	1.Rmt. \ (ONE RUNNING METRE)	16890.
					+	1
	337.80 Rmit.	(b) 75MM WIDE BORDER		Rs.35.00 (Rupees thirty five only)	1.Rmt. (ONE RUNNING METRE) \	11823.
	Y	X		, , , , , , , , , , , , , , , , , , ,	7	-1
	144.00 Rmt.	(c) 50MM WIDE BORDER		Rs.30.00 (Rupees thirty only)	1.Rmt. (ONE RUNNING	4320.
	5.	X		*	METRE	+
8.4.1	1891.40 Sq.M.	PAINTING THE NEW WALLS WITH TWO COATS OF OIL		Rs.100.00 ×	1.Sq.M.	189140
À	4	BOUND DISTEMPER OVER THE EXISTING PRIMING COATS OF VER COAT OF WHITE CEMENT OF APPROVED BRAND OVER NEW CEMENT PLASTERED WALL SURFACES INCLUDING COST OF PAINTS, PUTTY, BRUSHES, WATERING, CURING, ETC., ALL COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (PAINTS AND ITS SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		(Rupees one hundred only)	(ONE SQUARE METRE)	7
8.4.2	1891.40 Sq.M.	SUPPLYING AND APPLYING OF WALL PUTTY ONE COAT WITH APPROVED MAKE WALL PUTTY FOR SMOOTH FINISHING OVER THE NEW CEMENT PLASTERED WALLS INCLUDING COST OF PUTTY, BUILDING WALLS INCLUDING COST OF PUTTY.		Rs.120.00 (Rupees one hundred and twenty only)	1.Sq.M. (ONE SQUARE METRE)	226968.
\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	*	BRUSHES, WATERING CURING LABOUR CHARGES FOR APPLY PUTTY, BLADE ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY OF THE MATERIAL SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE.)		X	+	
38.6	1891.40 Sq.M.	PAINTING PRIMER COAT USING APPROVED QUALITY OF WHITE CEMENT OVER THE CEMENT PLASTERED A	1	Rs.90.00 (Rupees ninety only)	1.Sq.M\ (ONE SQUARE METRE)	170226
メ		CONCRETE NEW WALL SURFACES, CEILING OR OTHER SIMILAR WORKS INCLUDING COST OF WHITE CEMENT, PUTTY, BRUSHES, WATERING, CURING, ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		*	4	+
or A	.P.CONSTI	RUCTIONS	~	5, B	#1	11664686

SUPERINTENDING ENGINEER/SO/TH CIRCLE.

		KADAMALAIKUNDI 191	Freshore	etik: 45		Page No. 17
EM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT 7
13.1	38,707 M.T.X	SUPPLYING FABRICATING AND PLACING IN POSITION OF MILD STEEL GRILLS/RIBBED TOR STEELS (WITHOUT CEMENT SLURRY) OF ALL CLAMETERS FOR REINFORCEMENT FOR ALL FLOORS INCLUDING		Rs.79000.00 (Rupees seventy nine thousand only)	1 M.T. (ONE METRIC TONNE)	11664686.40 3057853.00
	+	COST OF BINDING WIRE, BENDING, TYING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS FOR ALL SIZES.		+	76	+
2.1.a	4 NOS.	PROVIDING RAIN WATER HARVESTING PIT OF 1M DIA AND 600MM DEPTH OF EARTH WORK EXCAVATION AND FILLING THE PIT WITH 40MM STONE JELLY TO A		Rs.1650.00 (Rupees one thousand six	1.NO. (EACH)	6600.00
λ	×	DEPTH OF 300MM FROM THE TOP OF THE AUGERING PORTION AND FILLING WITH CRUSHED STONE SAND TO A DEPTH OF 300MM OVER THE STONE JELLY AND COVERED WITH THE PRE-CAST RCC PERFORATED SLAB OF 40MM THICK IN STANDARDISED CONCRETE MIX M-20 GRADE IN ACCORDANCE WITH IS: 456 - 2000 USING 3MM-10MM HARD BROKEN STONE JELLY FOR ALL RCC ITEMS OF WORKS EXCLUDING THE COST AND FABRICATION OF REINFORCEMENT GRILLS BUT INCLUDING PRECASTING, MOULDING, CURING, FINISHING AND FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		+	-d-	+
.2.1.b	15.00 Rmt.	AUGERING 30CM DIA BORE HOLE IN ALL SOILS AND		Rs.350.00 \	1. Rmt. X	5250.0
X	* *	SUB SOILS REQUIRED DEPTH TO PROVIDING RAIN WATER HARVESTING FROM THE CENTRE OF THE RAIN WATER HARVESTING PIT ALREADY EXCAVATED AND FILLING THE AUGUERING PORTION WITH 40MM SIZE STONE JELLY ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		(Rupees three hundred and fifty only)	METRE)	+
14.3	4 NOS.	PROVIDING WELL RING OF CIRCULAR SHAPE OF 90CM DIA, 60CM DEPTH, 50MM THICKNESS USING M20 GRADE USING 3-10MM HBSJ INCLUDING COST OF ALL MATERIALS INCLUDING LABOUR CHARGES FOR STEEL FABRICATION, MOULDING CHARGES, CASTING CHARGES, CURING, HIRE CHARGES FOR TOOLS AND PLANTS AND FIXING IN POSITION OF RCC WELL RING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS		Rs.1000.00 (Rupees one thousand only)	1.NO. (EACH)	4000.0
14.6	73.80 Rmt.	SUPPLYING AND FIXING OF 110MM DIA PVC SWEPPE WITH ISI MARK CONFIRMING TO IS 13952:1992 TYPE 'A' FOR RAIN WATER DOWN FALL PIPE WITH RELEVANT SPECIALS SUCH AS GRATINGS, SHOES BENDS, OFFSETS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING IS 5382 WITH LEAVING A GAP ABOUT 10MM TO ALLOW THERMAI EXPANSION WITH NECESSARY CLAMPS, TEAK WOOD PLUGS, ETC., OF APPROVED QUALITY AND INCLUDING FIXING C.I. GRATINGS AT THE JUNCTION OF PARAPETAND FLOOR OR ROOF SLAB ETC., INCLUDING FINISHING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS.		Rs.300.00 (Rupees three hundred only)	1. Rmt. (ONE RUNNING METRE)	22140.0
60.2.1 ×	164.80 Rmt.	SUPPLYING AND FIXING OF PRECAST KERB STONI OF SIZE 450X300X150MM MADE IN CC 1:3:6 (ONE OF CEMENT, THREE OF CRUSHED STONE SAND AND SIZE OF HARD BROKEN STONE JELLY) USING 20MM SIZE HARD BROKEN STONE JELLY INCLUDING THE COST OF KERB STONE MOULDING, LAYING, CURING TRANSPORTING, POINTING AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	= (Rs.200.00 (Rupees two hundred only)	1. Rmt. (ONE RUNNING METRE)	32960.
For	A.P.CONS	TRUCTIONS				



		KADAMALAIKUNDI FIR	Ė 12 plaza	w. 4 7		Page No. 18
ITEM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT 7
50.5.1	1 NO.	SUPPLYING TABRICATION AND ERECTION IN POSITION OF M.S. SCHEME NAME AND LAYOUT BOARD WITH SOX50X0MM M.S. ANGLE FOR VERTICAL POST AND		Rs.14000.00 (Rupees fourteen thousand	1.NO. (EACH)	14793489.40
<i>></i>		SUPPORT POSTS WITH 2.5 MM THICK M.S. SHEET FOR A SIZE AT 1,80X1.20M WITH 40X40X6MM M.S. ANGLE AROUND THE BOARD AND 50X6MM FLAT STIFFENERS ON BOTH DIRECTIONS INCLUDING COST OF WELDING CHARGES, PAINTING CHARGES AND DRAWING THE LAYOUT AND LETTERING THE SCHEME DETAILS AS DIRECTED BY THE DEPARTMENTAL OFFICERS INCLUDING EARTH WORK EXCAVATION FOR 4 NOS OF PITS, FCC 1,5,10 (ONE OF CEMENT, FIVE OF CRUSHED		only)	4	+
		STONE SAND AND TEN OF HB STONE JELLY) FOR PITS. 0.45 X 0.45 X 0.60M BELOW GROUND LEVEL AND P.C.C 1 :2:4 (ONE OF CEMENT, TWO OF CRUSHED STONE SAND AND FOUR OF 20MM HB STONE JELLY) AT 0.30 X 0.30 X 0.30M ABOVE GROUND LEVEL FOR ERECTION, CONVEYANCE CHARGES ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
50.6.1	47.60 Sq.M.	SUPPLYING AND FIXING OF FIBRE MIXED PRECAST		Rs.330.00 \	1.Sq.M.	15708.00
50.6.1	-1.00 Sq.M.	SLAB OF 50MM THICK OF ALL REQUIRED SHAPES MADE IN CEMENT CONCRETE 1:3:6(ONE OF CEMENT,		(Rupees three hundred and thirty only)	(ONE SQUARE METRE)	13706,00
×	>	THREE OF CRUSHED STONE SAND AND SIX OF 20MM HARD BROKEN STONE JELLY) USING 20MM HARD BROKEN STONE JELLY MIXED WITH SECONDARY REINFORCEMENT FIBRE OF APPROVED QUALITY AT 0,25% BY WEIGHT OF CEMENT (125GM OF FIBRE FOR 18AG I.E., 50KG OF CEMENT) USED INCLUDING COST OF ALL MATERIALS, MOULDING, CURING, TRANSPORTATION, LAYING, POINTING ETC., FOR APPROACH ROAD, PAVEMENT SLAB AND OTHER SIMILAR WORKS ETC., COMPLETE AS PER THE RELEVANT STANDARD SPECIFICATIONS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE SHAPE OF SLAB AND BRAND AND QUALITY OF FIBRE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		X	+	
51.2	2 NOS.	SUPPLYING AND ERECTION OF WHITE FRP/PPFRP		Rs.13500.00 ¥	1.NO. (EACH)	27000.00
		CAPACITY, NEITHER CORRODE NOR RUST DUE TO THE EMPLOYMENT OF HIGH QUALITY MATERIAL,		(Rupees thirteen thousand and five hundred only) ✓	(EAOII)	ן ע
	X	WHEREAS THE THREE LAYERS OF THE TANKS ARE UV STABILIZED AND CONTROL THE INSIDE TEMPERATURE OF THE WATER WITH TOP LID WITH PROVISIONS OF LOCKING INCLUDING NECESSARY SPECIALS AND FITTINGS FOR STORING POTABLE WATER AND MANUFACTURED WITH MATERIAL WHICH DO NOT IMPORT ANY TASTE/ ODOUR/ ANY TOXIC EFFECT AND NOT TO CONTAMINATE ETC WITH CARBON BLOCK CONTENT AND DISPERSION IN ACCORDANCE WITH RELEVANT SPECIFICATION AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS ETC. COMPLETE. (THE TANK SHOULD BE GOT APPROVED FROM THE EE BEFORE		X		
52.4		SUPPLYING, LAYING, FIXING AND JOINTING THE FOLLOWING PVC PIPES AS PER ASTM D - 1785 OF SCHEDULE 40 OF WALL THICKNESS NOT LESS THAN THE SPECIFIED IN IS 4985 SUITABLE FOR PLUMBING BY THREADING OF WALL THICKNESS INCLUDING THE COST OF SUITABLE PVC/GI SPECIALS /GM SPECIALS LIKE ELBOW, TEE REDUCERS, PLUG, UNIONS, BEND, COUPLER, NIPPLE/ GM GATE VALVE, CHECK AND WHEEL VALVE ETC., WHEREVER REQUIRED ABOVE THE GROUND LEVEL INCLUDING THE COST OF TEFLON TAPE ETC., FULLY CONCEALED IN WALLS TO THE PROPER GRADIENT AND ALIGNMENT AND REDOING THE CHIPPED PORTION OF MASONRY ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.			*:	
For A	P.CONSTI	UCTIONS	28			14850197.40
1.1			ķ		d	

SUPERINTENDING ENGINEER/SOUT CIRCLE

-		KADAMALAIKUNGI (P	No distriction	7 7		Page No. 19
EM_NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS 6	AMOUNT 7
-	-		-			14850197.40
	60.00 Rmt	(c) 20MM ASTM D SCHEDULE 40 THREADED PVC PIPE WITH NECESSARY PVC/GI SPECIALS		Rs.185.00 (Rupees one hundred and eighty five only)	1, Rmt (ONE RUNNING METRE)	11100.00
	×	×		eighty live only)	*	+
53.4	3 NOS.	SUPPLYING AND FIXING OF C.I. MANHOLE COVER WITH LOCKING ARRANGEMENTS OF APPROVED QUALITY AND BRAND OF SIZE 0,6 M X 0,6 M(50 KG) AS		Rs.1800.00 (Rupees one thousand and eight hundred only)	1.NO. (EACH)	5400.0
×		PER STANDARD SPECIFICATIONS INCLUDING COST OF MATERIAL, LABOUR CHARGES FOR FIXING ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		eight funded only)	2	- 4
	×				4 NO	2
33.5	10 NOS.	BUPPLYING AND FIXING OF PORCELIN WASH HAND BASIN (WHITE WITHOUT PEDESTAL TYPE), SUPERIOR VARIETY OF SIZE 550X400MM (22"X16") WITH ALL ACCESSORIES SUCH AS POWDER COATED CAST IRON BRACKETS, 32MM DIA C.P. WASTE COUPLING, RUBBER PLUG AND ALUMINIUM CHAIN, 32MM DIA GI 'B' CLASS PVC WASTE PIPE, 15MM DIA CP ANGLE VALVE, 15MM DIA NYLON CONNECTION, 15MM DIA BRASS NIPPLES, 15MM C.P. PILLAR TAP & REQUIRED GRATING ETC.		Rs.2500.00 (Rupees two thousand and five hundred only)	1.NO. (EACH)	25000.0
		COMPLETE IN ALL RESPECTS (WASH HAND BASIN WITH CP FITTINGS SHALL BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE FIXING).				
i.1.1	12 NOS.	SUPPLYING AND FIXING OF HALF TURN BRASS CORE CP LONG BODY TAP OF 15MM DIA OF BEST QUALITY INCLUDING COST OF HALF TURN CP TAP WITH REQUIRED SPECIALS AND LABOUR FOR FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.450.00 (Rupees four hundred and fifty only)	1.NO. (EACH)	5400.0
3.2.1	12 NOS.	SUPPLYING AND FIXING OF HALF TURN BRASS CORE CP SHORT BODY TAP OF 15MM DIA OF BEST QUALITY INCLUDING COST OF HALF TURN CP TAP WITH REQUIRED SPECIALS AND LABOUR FOR FIXING ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.430.00 X (Rupees four hundred and thirty only) Y	1.NO. (EACH)	5160.
5.3.2 ^V	3 NO\$.X	SUPPLYING AND FIXING OF INDIAN WATER CLOSET WHITE GLAZED (ORIYA TYPE) OF SIZE	1	Rs.2000.00 X	1.NO. (EACH)	₹ 6000.
×	¥.	580MMX440MM OF APPROVED MAKE WITH ISI MARK (TO BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE) WITH PVC SWR GRADE P OR S TRAFINCLUDING CONCRETE PACKING, FILLING PORTION WITH EARTH, FLOORING THE AREA WITH 75MM THICK BRICK JELLY CONCRETE IN CC 1:8:16 (ONE OF CEMENT EIGHT OF CRUSHED STONE SAND AND SIXTEEN OF BRICK JELLY) USING 40MM SIZE BRICK JELLY AND TO LEFT ROUGH TO RECEIVE THE FLOOR PLASTERING BUT INCLUDING ANTISYPHONAGE CONNECTION, CURING ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (IN GROUND FLOOR)			+	+
				· a		14908257





		KADAMALAIKUNDI (AR	EAN PRES	11 21		Page Nu 20
TEM,NO	OUANTITY 2	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS G	AMOUNT 7
56,4,2	3 NOS.	SUPPLYING AND FIXING OF INDIAN WATER CLOSET. WHITE GLAZED (ORIYA TYPE) OF SIZE 580MMX440MM OF APPROVED MAKE WITH ISI MARK (TO		Rs.3000.00 (Rupees three thousand only)	1.NU. (EACH)	9000.00
	×	BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE) WITH PVC SWR GRADE P OR S TRAPINCLUDING CONCRETE FILLING THE SUNK PORTION WITH BRICK JELLY LIME CONCRETE PROPORTION OF BRICK JELLY TO LIME BEING 32:12½ BY VOLUME (32 CFT OF 20MM GAUGE BRICK JELLY AND 12½ GFT OF SLAKED LIME) (NO SAND) AND TOP 75MM THICK, BRICK JELLY CONCRETE IN CC 1:8:16 (ONE OF CEMENT, EIGHT OF CRUSHED STONE SAND AND SIXTEEN OF		×	+	+
		BROKEN BRICK JELLY) USING 40MM SIZE BRICK JELLY INCLUDING PLASTERING THE SIDES OF SUNK PORTION IN CM 1:3 (ONE OF CEMENT AND THREE OF CRUSHED STONE SAND) 12MM THICK MIXED WITH WATER PROOFING COMPOUND AT 2KG/SQM AND TOP LEFT ROUGH TO RECEIVE THE FLOOR PLASTERING BUT INCLUDING ANTISYPHONAGE CONNECTION, ONE COAT OF BITUMEN FOR THE SIDES, BOTTOM AND CURING ETC., COMPLETE IN ALL FLOORS, (OTHER THAN GROUND FLOOR)				
56.4.4	22.00 Sq.M.	PROVIDING POLYMER COATING (WATER PROOF		Rs.400.00	1.Sq.M. (ONE SQUARE	8800.00
×	X	COATING) FOR SUNKEN PORTION OF TOILET WITH FOLLOWING SPECIFICATION AND THE SURFACE SHALL BE CLEANED TO REMOVE ALL DUST, FOREGIN, MATTERS LOSE MATERIALS OR ANY OTHER DEPOSITS OF CONTAMINATION BY RUBBING WITH WIRE BRUSH, SLURRY: DRY BLEND AND POLYMER LIQUID BLEND SHALL BE MIXED INTO THE DESIRED RATIO AS PER RECOMMENDATION OF THE SUPPLIER. THE MIX SHALL BE STIRRED THOROUGHLY UNTIL NO BUBBLES REMAIN IN THE MIX, ANY LUMPS FOUND IN MIX SHALL BE REMOVED, APPLY FIRST COAT OF POLYMER MODIFIED CEMENTITIOUS SLURRY BY BRUSH ON WET CLEANED		(Rupees four hundred only)	METRE)	*
		SURFACE AFTER DRYING, SECOND COAT SHALL BE APPLIED ON THE FIRST COAT AS DIRECTED BY THE DEPARTMENTAL OFFICERS ETC, THE RATE INCLUSIVE OF COST OF MATERIALS AND LABOUR, ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF THE MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)				
57.2	1 NO.	SUPPLYING AND FIXING EWC (WHITE) SUPERIOR VARIETY 500MM WITH PVC SWR GRADE 'P' OR 'S' TRAP		Rs.5000.00 (Rupees five thousand only)	1.NO. (EACH)	5000.0
×	×	INCLUDING COST AND FIXING OF DOUBLE FLAPPED PLASTIC SHEET COVER PVC FLUSHING CISTERN IN APPROPRIATE LEVEL AS DIRECTED BY THE DEPARTMENTAL OFFICERS AT A MAXIMUM LEVEL OF 5'6" AND OF APPROVED BRAND OF 10 LITRES CAPACITY INCLUDING FITTINGS SUCH AS CI BRACKETS. PVC CONNECTION GM WHEEL VALVE, HEX NIPPLE, ETC., COMPLETE (EWC AND PLASTIC COVER SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE FIXING).		*	X	•*
58.3		SUPPLYING AND FIXING THE FOLLOWING DIA PVC (SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'B' FOR SOIL LINE WITH RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING TO IS 5382 WITH LEAVING A GAP ABOUT 10MM TO ALLOW THERMAL EXPANSION, FIXING THE PIPES INTO WALLS WITH NECESSARY WOODEN PLUG, SCREWS, HOLDING WHEREVER NECESSARY AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC. COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
or A	P.CONST	RUCTIONS		0 ×		14931057.

NO. OF CORRECTIONS



		KADAMALAIKUNDU (1	RE ZO RES	NAME OF THE OWNER OWNER O		Page No 21
TEM.NO	QUANTITY	DESCRIPTION OF WORK	тивнио.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES AND IN WORDS	AMOUNT
1	2	3:	4	5	G	7 14931057.40
	24.00 Rmt.	(a) 110MM DIA PVC SWR PIPE INCLUDING ALL REQUIRED PVC SPECIALS ETC., ALL COMPLETE.		Rs.580.00 (Rupces five hundred and eighty only)	1.Rmt. (ONE RUNNING METRE)	13920.00
	79.40 Rmt.	(b) 75MM DIA PVC SWR PIPE INCLUDING ALL REQUIRED PVC SPECIALS ETC., ALL COMPLETE.		Rs.470.00 (Rupees four hundred and seventy only)	1.Rmt, (ONE RUNNING METRE)	X 37318.00
TO 4	×	20/2003				
58.4	28.00 Rmt.	SUPPLYING, LAYING AND CONCEALING THE 50MM DIA PVC (SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'B' FOR WASTE WATER LINE WITH RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE		Rs.80.00 (Rupees eighty only)	1.Rmt. (ONE RUNNING METRE)	2240.00
58.5 ×		SUPPLYING AND FIXING THE FOLLOWING DIA PVC(SWR) PIPE WITH ISI MARK CONFIRMING TO IS 13952:1992- TYPE 'A' WITH PVC COWL AND RELEVANT SPECIALS CONFIRMING TO IS 14735 INCLUDING JOINTING WITH SEAL RING CONFIRMING TO IS 5382 WITH LEAVING A GAP 10MM TO ALLOW THERMAL EXPANSION AND FIXING THE PIPES INTO WALLS OR OVER THE SEPTIC TANK WITH NECESSARY WOODEN PLUG, SCREWS, HOLDING WHEREVER NECESSARY AND MAKING GOOD OF THE DISMANTLED PORTION WITH NECESSARY CONNECTIONS TO SANITARY FITTINGS ETC., COMPLETE IN ALL RESPECTS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.				
	1 NO.	(a) 110MM DIA PVC SWR PIPE OF 3METRE WITH		Rs.400.00\	1.No.	400.00
	X	REQUIRED PVC COWL & PVC SPECIALS ETC., ALL COMPLETE.		(Rupees four hundred only)	(EACH)	× 100,00
0.1	22 NOS,X	SUPPLYING AND FIXING OF PVC NAHANI TRAP NOT LESS THAN 75MM 4 WAY /2 WAY (SUPERIOR VARIETY)			(EACH) 1.No. (EACH)	2200.00
0.1 ×	22 NOS,X	COMPLETE. SUPPLYING AND FIXING OF PVC NAHANI TRAP NOT		Rs.100.00	1.No.	×
1.1.1	22 NOS,X	SUPPLYING AND FIXING OF PVC NAHANI TRAP NOT LESS THAN 75MM 4 WAY /2 WAY (SUPERIOR VARIETY) HAVING MINIMUM OF WATER SEAL OF 50MM CONFIRM TO RELEVANT I.S. SPECIFICATIONS WITH ITS LATEST AMENDMENTS INCLUDING RESTING ON THE BED OF BRICK JELLY CONCRETE 1:5:10 (ONE OF CEMENT, FIVE OF CRUSHED STONE SAND OF TEN OF 40 MM GAUGE BRICK JELLY) ETC., COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE PVC NAHANI TRAP SHOULD BE GOT APPROVED FROM THE EE BEFORE		Rs.100.00	1.No.	X
X 1.1.1 X	22 NOS.X	SUPPLYING AND FIXING OF PVC NAHANI TRAP NOT LESS THAN 75MM 4 WAY /2 WAY (SUPERIOR VARIETY) HAVING MINIMUM OF WATER SEAL OF 50MM CONFIRM TO RELEVANT I.S. SPECIFICATIONS WITH ITS LATEST AMENDMENTS INCLUDING RESTING ON THE BED OF BRICK JELLY CONCRETE 1:5:10 (ONE OF CEMENT, FIVE OF CRUSHED STONE SAND OF TEN OF 40 MM GAUGE BRICK JELLY) ETC., COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE PVC NAHANI TRAP SHOULD BE GOT APPROVED FROM THE EE BEFORE USE) SUPPLYING, LAYING AND JOINTING THE FOLLOWING DIA UPVC NON PRESSURE PIPE OF SN8 SDR 34 (SM 16.5) AS PER IS 15328/2003, SUPERIOR VARIETY AND TESTED WITH WATER INCLUDING NECESSARY EARTH WORK EXCAVATION FOR TRENCHES AND REFILLING THE SAME, WELL RAMMED AND CONSOLIDATED AFTER THE PIPES ARE JOINTED AND LAID TO PROPER GRADIENT TO THE ALIGNMENT AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (SN8 SDR 34 (S 16.5) AS PER IS 15328/2003 SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER, JOINTED AND SUPERINTENDING ENGINEER, CHIEF ENGINEER, SEFORE USE IN WORKS)		Rs.100.00	1.No.	X
,1.1 ×	22 NOS.X	SUPPLYING AND FIXING OF PVC NAHANI TRAP NOT LESS THAN 75MM 4 WAY /2 WAY (SUPPERIOR VARIETY) HAVING MINIMUM OF WATER SEAL OF 50MM CONFIRM TO RELEVANT I,S. SPECIFICATIONS WITH ITS LATEST AMENDMENT'S INCLUDING RESTING ON THE BED OF BRICK JELLY CONCRETE 1:5:10 (ONE OF CEMENT, FIVE OF CRUSHED STONE SAND OF TEN OF 40 MM GAUGE BRICK JELLY) ETC., COMPLETE AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE PVC NAHANI TRAP SHOULD BE GOT APPROVED FROM THE EE BEFORE USE) SUPPLYING, LAYING AND JOINTING THE FOLLOWING DIA UPVC NON PRESSURE PIPE OF SN8 SDR 34 (S 16.5) AS PER IS 15328/2003, SUPERIOR VARIETY AND TESTED WITH WATER INCLUDING NECESSARY EARTH WORK EXCAVATION FOR TRENCHES AND REFILLING THE SAME, WELL RAMMED AND CONSOLIDATED AFTER THE PIPES ARE JOINTED AND LAID TO PROPER GRADIENT TO THE ALIGNMENT AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (SN8 SDR 34 (S 16.5) AS PER IS 15328/2003 SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER, SEFORE USE IN WORKS) BY 110MM DIA UPVC NON PRESSURE PIPE		Rs.100.00 (Rupees one hundred only) Rs.350.00 (Rupees three hundred and	1.No. (EACH)	2200.00 X

SUPERINTENDING ENGINEER/SOUTH CIRCLE.

		KADAMALAIKUN OLEH	VALUE	10 C D D	- 9	ige No. 72
EM NO	QUANTITY	DESCRIPTION OF WORK	TUBE No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
-						15024585.40
	74.00 Rmt.	(b) 160MM DIA UPVC NON PRESSURE PIPE		Rs.565.00 (Rupees five hundred and sixty five only)	1.Rmt (ONE RUNNING METRE)	41810.00
				~	1 8	
2.1.1	s	SUPPLYING AND FIXING OF FOLLOWING DIA OF PVC BEND FABRICATED 6 KSC PVC SPECIALS AS PER IS 10124/1982 PART II INCLUDING COST OF MATERIAL AND LABOUR CHARGES FOR FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND OF PVC BEND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).				
	6 NOS.	(a) 110MM DIA PVC BEND		Rs.170.00	1.No. (EACH)	1020.00
				(Rupees one hundred and seventy only)	(2)	
	X	X		***		
	4 NOS.	(a) ACOMM DIA DVC DEND		Rs.230.00 \	1.No.	920.00
	4 1103.	(a) 160MM DIA PVC BEND		(Rupees two hundred and thirty	(EACH)	320.0
	×			only)		+
	1			X	\	1
2.2.1		SUPPLYING AND FIXING OF FOLLOWING DIA PVC EQUAL TEE (MOULD) BIS 7834/1975 PVC SPECIALS AS PER IS 10124/1982 PART II INCLUDING COST OF MATERIAL AND LABOUR CHARGES FOR FIXING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND OF PVC EQUAL TEE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).				
	2 NOS.X	(a) 110MM DIA PVC EQUAL TEE		Rs.190.00 (Rupees one hundred and	1.No. (EACH)	∕ 380.0
	>			ninety only)		4
	2 NOS.	(b) 160MM DIA PVC EQUAL TEE		Rs.250.00 (Rupees two hundred and fifty only)	1.No. (EACH)	500.0
	X			, , , , , , , , , , , , , , , , , , ,		+
54.1	`	WIRING WITH 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT		*		
×		FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE MS BOX OF 16 G THICK CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET CONTROLLED BY 5 AMPS FLUSH TYPE SWITCH INCLUDING CIRCUIT MAINS COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE.				
	50 POINTS	(a) LIGHT POINT WITH CEILING ROSE		Rs.800.00	1 POINT	40000.
		The state of the s		(Rupees eight hundred only)	(EACH POINT)	
	×	X,		•	X	+
	A4 POINT	(A) LIGHT BOINT WITHOUT CEPTING BOSE		Rs.800.00	1 POINT	×32800.
	41 POINTS	(b) LIGHT POINT WITHOUT CEILING ROSE		(Rupees eight hundred only)	(EACH POINT)	- 520UU.
	×	l x		*	^	X
	X				×	
		(c) POINT WIRING FOR CALLING BELL/ BUZZEF WITH PUSH TYPE SWITCH	R	Rs.1000.00 (Rupees one thousand only)	1 POINT (EACH POINT)	2000.
ord	P.CONST	RUCTIONS		- H	\rightarrow	
OI A.	1/2.	7				

SMERINTENDING ENGINEER/SOUTH CIRCLE.

		KADAMAI AIKUN MERI	ý 180 ma	57		Fage No. 23.
EM.NO	QUANTITY	DESCRIPTION OF WORK	THEP NO.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT 7
35.1		WIRING WITH 1.5 SQMM PVC INSULATED SINGLE		Rs.1000.00	1 POINT (EACH POINT)	16000.00
×	×	FIRE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS 694/1990, LLK.V. GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SOMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE MS BOX OF 18C THICK CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR FAN POINT CONTROLLED BY 5 AMPS FLUSH TYPE SWITCH INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE.		(Rupees one thousand only)		+
66.1	2.POINTS	WIRING WITH 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1.K.V. GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE MS BOX OF 16G THICK CONCEALED AND COVERED WITH 3MM		Rs.2200.00 (Rupees two thousand and two hundred only)	1 POINT (EACH POINT)	4400.00
57.1 ×	16 POINTS	THICK LAMINATED HYLEM SHEET FOR STAIRCASE LIGHT POINT CONTROLLED BY 5 AMPS FLUSH TYPE TWO WAY SWITCH INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS, SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1,1.K.V. GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLEWITH ISI MARK CONFORMING TO IS: 694/1990,1,1.K.V. GRADE CABLE IN FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAVY DUTY WITH ISI MARK WITH SUITABLE SIZE MS BOX OF 16G THICK CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS 5 PIN		Rs.600.00 (Rupees six hundred only)	1 POINT (EACH POINT)	9600.0
68.2 ·	14 POINTS	PLUG SOCKET POINT AT SWITCH BOARD ITSELI INCLUDING CIRCUIT MAINS, COST OF ALL MATERIALS SPECIALS, ETC., ALL COMPLETE. WIRING WITH 1.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARI CONFORMING TO IS: 694/1990, 1.1.K.V. GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLEWITH ISI MARI CONFORMING TO IS: 694/1990, 1.1.K.V. GRADE CABLE II FULLY CONCEALED PVC RIGID CONDUIT PIPE HEAV		Rs.600.00 (Rupees six hundred only)	1 POINT (EACH POINT)	¥8400.
or /	A.P.CONST	DUTY WITH ISI MARK WITH SUITABLE SIZE MS BOX OF NO (EACH) 16G THICK CONCEALED AND COVERED WITH 3MM THICK LAMINATED HYLEM SHEET FOR 5 AMPS PIN PLUG SOCKET POINT AT CONVENIENT PLACES INCLUDING CIRCUIT MAINS, COST OF ALMATERIALS, SPECIALS, ETC., ALL COMPLETE.	1 H 5 T			4746046-
OI /	I.P.CONST	RUCTIONS				15182

ONS SUPERINTENDING ENGINEER/SOUTH CIRCLE

PARTNER

		KADAMALAIKUNDA IBI	afranasi	10 0/		Page No. 74
TEMINO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	e fount
71.2	3 NOS.	SUPPLYING AND FIXING OF 32 AMPS TRIPLE POLE MAIN SWITCH WITH FUSE AND NEUTRAL LINK ON A SUITABLE WELL VARMISHED TEAK WOOD BOARD INCLUDING NECESSARY INTER CONNECTION COST OF ALL MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.	4	Rs.1875.00 (Rupees one thousand eight hundred and seventy five only)	1.NC. (EACH)	7 15182415.40 5625.00
75.1.2		SUPPLYING AND DELIVERY OF FOLLOWING ELECTRIC CEILING FAN WITH ISI MARK WITH BLADES AND DOUBLE BALL BEARING, CAPACITOR, ETC., COMPLETE WITH 300MM DOWN ROD, CANOPIES, CAPACITOR, SHACKLE BLADES WITH ELECTRONIC DIMMER SUITABLE FOR OPERATION ON 230 VOLTS 50 HTZ SINGLE PHASE AC SUPPLY CONFORMING TO ISS NO.374/79 AND PROVIDED WITH INSULATION. (THE BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE SUPPLY MADE).				
	16 NOS.	(a) 48" ELECTRIC FAN 1200MM SWEEP		Rs.1600.00 (Rupees one thousand and six hundred only)	1.NO. (EACH)	25600.00
77.5	291.00 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 1.5 SQ.MM. PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990,1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 1.5 SQ.MM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1, K.V. GRADE CABLE IN FULLY CONCEALED 19MM/20MM DIA RIGID PVC CONDUIT PIPE HEAVY DUTY WITH ISI MARK COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE,		Rs.120.00 (Rupees one hundred and twenty only)	1.Rmt. (ONE RUNNING METRE)	34920.00
77.6	40.00 Rmt.	RUN OFF MAIN WITH 2 WIRES OF 4 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1,1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1,1, K,V. GRADE CABLE IN FULLY CONCEALED 19MM/20MM DIA RIGID PVC CONDUIT PIPE HEAVY DUTY WITH ISI MARK COST OF ALL MATERIALS, SPECIALS ETC., ALL COMPLETE.		Rs.120.00 (Rupees one hundred and twenty only)	1.Rmt.X (ONE RUNNING METRE)	4800.00
77.7 _~	50.00 Rmt	RUN OFF MAIN WITH 2 WIRES OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE IN FULLY CONCEALED 19/20MM DIA RIGID PVC CONDUIT PIPE WITH ISI MARK ETC. INCLUDING COST OF ALL MATERIALS, SPECIALS ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.130.00 (Rupees one hundred and thirty only)	1.Rmt. X (ONE RUNNING METRE)	6500.0
79.1.1	3 ноз	SUPPLYING AND FIXING 1 NO. OF 32 AMPS 500 VOLTS GRADE PORCELAIN FUSE UNIT ON SUITABLE TEAKWOOD PLANK VARNISHED TO BE FIXED ON THE TOP OF POLE EB STREET POLE WITH NECESSARY CLAMPS INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY	1	Rs.450.00 (Rupees four hundred and fifty only)	1.NO. (EACH)	× 1350.0
For	A.P.CONS	PARTNER			÷	15261210.4
	114	PARTNER	Į.	ji	Ĥ	į.



CADAMALATEI NIII MIN ARMINATTI

					Page No: 2h
OUANTITY	DÉSCRIPTION OF WORK	THEPING	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
	SUPPLYING AND FIXING 3 NOS, OF 32 AMPS 500 VOLTS GRADE PORCELAIN FUSE UNIT ON SUITABLE TEAKWOOD PLANK VARNISHED TO BE FIXED ON THE TOP OF POLE EB STREET POLE WITH NECESSARY CLAMPS INCLUDING COST OF ALL		Rs.700.00 (Rupees seven hundred only)	1.NO. (EACH)	15261210.40 1400.00
1 NO.	THICK TW PLANK WELL VARNISHED WITH 3 NOS, OF 32 AMPS 250 VOLTS PORCELIN FUSE UNIT AND 1 NO. COPPER EARTH PLATE OF SUITABLE SIZE BOLTS AND NUTS ON WALL FOR EB SERVICE CONNECTIONS		Rs.1100.00 (Rupees one thousand and one hundred only)	1.NO. (EACH)	<u></u>
25.00 Rmt.	INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SOMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE IN FULLY CONCEALED 25MM DIA RIGID PVC CONDUIT PIPE WITH ISI MARK ETC, INCLUDING COST	-	Rs.400.00 (Rupees four hundred only)	1.Rmt. L (ONE RUNNING METRE)	10000.00
62.40 Rmt. χ	PIPE CONFIRMING TO ISS FOR EB SERVICE CONNECTION FOR PASSING THROUGH FROM TOP OF HOUSE/FLATS BUILDING TO THE EB BOARD INCLUDING COST OF PIPE, SPECIALS, LABOUR FOR FIXING ETC.,		Rs.120.00 \\ (Rupees one hundred and twenty only)	1.Rmt. (ONE RUNNING METRE)	7488.00
2 NOS.	OPERATED THREE PHASE EARTH LEAKAGE CIRCUIT BREAKERS/RESIDUAL CURRENT CIRCUIT BREAKER (ELCB/RCCB) COMBINED WITH OVER LOAD AND SHORT CIRCUIT PROTECTION HAVING A RUPTURING CAPACITY OF 6 KA WITH 30 MILLI AMPS FIXED SETTING SENSITIVITY AND RATES FOR 25 A IN SUITABLE SHEET STEEL ENCLOSURE CONFIRMING TO IS 12640/1988 INCLUDING COST OF ELCB/RCCB ON FULLY CONCEALED SUITABLE M.S BOX WITH NECESSARY INTER CONNECTIONS AND EARTH CONNECTIONS		Rs.2600.00 (Rupees two thousand and six hundred only)	1.NO. (EACH)	5200.00
	DOUBLE LEAF PANELLED DOOR SHUTTER IN POSITION USING 75MM X 37,5MM OUTER STYLES 4 NOS AND INTERMEDIATE RAILS OF 6 NOS. 150MM X 37,5MM AND 18,75MM TK PLANKS FOR PANELS INCLUDING COST AND LABOUR FOR FIXING THE BRASS FITTINGS 2 NOS, OF 200MM BRASS ORNAMENTAL DOOR HANDLE, 8 NOS, OF 125MMX30MM BRASS HINGES, 4 NOS, OF 200MMX12MM BRASS TOWER BOLTS, 1 NO, OF MORTICE LOCK WITH HANDLE, 2 NOS, OF 40MM DIA & 60MM LONG NYLON BUSH AND 2 NOS, OF DOOR STOPPER WITH RUBBER BUSH WITH BRASS SCREWS BEST APPROVED QUALITY AND SHADE ETC.,				
	1 NO.	2 NOS. SUPPLYING AND EMING 3 NOS, OF 32 AMPS 500. VOLTS GRADE FORCELAIN FUSE UNIT ON SUITABLE TEACHWOOD PLANK VARPHISHED TO BE PURD ON THE TOP OF POLE BE STREET POLE WITH NECESSARY CLAMPS INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPART IMENTIAL OFFICIERS. 1 NO. SUPPLYING AND FIXING OF 1 NO. OF 450X375X20MM THICK TW PLANK WELL VARNISHED WITH 3 NOS. ON COPPER EARTH PLATE OF SUITABLE SIZE BOLTS AND NUTS ON WALL FOR EB SERVICE CONNECTIONS INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE. 25.00 Rmt. RUN OFF MAIN WITH 4 WIRES OF 6 SQMM PVC INSULATED SINGLE COPPER CABLE WITH IS NUTS ON WALL FOR EB SERVICE CONNECTIONS INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE. 25.00 Rmt. RUN OFF MAIN WITH 4 WIRES OF 6 SQMM PVC INSULATED SINGLE COPPER CABLE WITH IS MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SQMM PVC INSULATED SINGLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE IN FOLLY CONCEALED 25MM DIA RIGID PVC CONDUIT PIPE WITH ISI MARK ETC. INCLUDING COST OF ALL MATERIALS, SECILALS ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. 32.40 Rmt. SUPPLYING AND FIXING OF 40MM DIA 'B' CLASS GI PIPE CONFIRMING TO ISS FOR EB SERVICE CONNECTION FOR PASSING THROUGH FROM TOP OF HOUSE/FLATS BUILDING TO THE EB BOARD INCLUDING COST OF PIPE, SPECIALS, LABOUR FOR FIXING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS. 2 NOS. 2 NOS. SUPPLYING AND FIXING OF ELECTRO MECHANICALLY POPERATED THREE PHASE EARTH LEAKAGE CIRCUIT BREAKER (ELEBRICE) COMPLETE AND SON WITH NECESSARY INTER CONNECTIONS AND EARTH CONNECTIONS USING COPPER CABLE INCLUDING COST OF ALL MATERIALS SECONS OF ED SERVICE ON FORM AND AND AND STATE CONNECTIONS AND EARTH CONNECTIONS USING COPPER CABLE INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE. SUPPLYING AND FIXING OF BEST INDIAN TEAK WOOD AND INTERMEDIATE RAILS OF 6 NOS. 150MM X 37.5MM AND 18.75MM TK PLANKS FOR PARELS INCLUDING COST AND LABOUR FOR FIXING THE BRASS FITTINGS 2	2 NOS. SUPPLYING AND FIXING 3 NOS, OF 32 AMPS 500 MOLTS GRADE PORCELAIN FUSE UNIT ON SURGILE TEXAMOROUS AGAINATED TO BE PARD ON THE TOP OF POILE BE STREET POLE WITH MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICIENS. 1 NO. SUPPLYING AND FIXING OF 1 NO. OF 450X375X20MM THICK TW PLANK WELL VARNISHED WITH 3 NOS. OF 32 AMPS 250 VOLTS PORCELIN FUSE UNIT AND 1 NO. COPPER EARTH PLATE OF SUITABLE SIZE BOLTS AND NUTS ON WALL FOR EB SERVICE CONNECTIONS INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE. RUN OFF MAIN WITH 4 WIRES OF 6 SQMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE WITH CONTINUOUS EARTH BY MEANS OF 2.5 SOMM PVC INSULATED SINGLE CORE MULTI STRAND FIRE RETARDANT FLEXIBLE COPPER CABLE WITH ISI MARK CONFORMING TO IS: 694/1990, 1.1 KV GRADE CABLE IN FLULY CONCEALED 25MM DIA RIGID PVC CONDUIT PIPE WITH ISI MARK ETC, INCLUDING COST OF ALL MATERIALS, SPECIALS ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. 32.40 Rmt. SUPPLYING AND FIXING OF 40MM DIA 'B' CLASS GI PIPE CONFIRMING TO ISS FOR EB SERVICE CONNECTION FOR PASSING THROUGH FROM TOP OF HOUSEPLATS BUILDING TO THE EB BOARD INCLUDING CONNECTION FOR PASSING THROUGH FROM TOP OF HOUSEPLATS BUILDING TO THE EB BOARD INCLUDING CONNECTION FOR PASSING THROUGH FROM TOP OF HOUSEPLATS BUILDING TO THE EB BOARD INCLUDING COST OF PIPE, SPECIAL, LAROUR FOR FIXING ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS. 2 NOS. SUPPLYING AND FIXING OF ELECTRO MECHANICALLY OPERATED THREE PHASE EARTH LEAKAGE CIRCUIT BREAKERS/RESIDUAL CURRENT CIRCUIT BREAKER (ELCBROCE) COMBINED WITH OVER LOAD AND HATCH CONTROL OF THE DEPARTMENTAL OFFICERS. 32.40 Rmt. SUPPLYING AND FIXING OF BEST INDIAN TERM WOOD DOUBLE LEAF PANELLED DOOR SHUTTER IN POSITION USING 75MM X 37.5MM AND BL7.5MM AND BL7.5MM X 37.5MM 2 NOS. 3 NOS NOS NOS NOS NOS NOS NOS NOS NOS NOS	2 NOS. 2	

PARTNER

NO. OF CORRECTIONS

SUPERINTENDING ENGINEER/SOUTH CACLE.

9. 3	21.50
RADAMALAIKUNDU MIRIA DERESEUE	6/

ITEM_NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS	UNIT IN FIGURES	PASOUNT
1	2	3 - 12 10	4	5	6	7 15455010.40
119	100	SUPPLYING AND DELIVERY OF 5 HP CLEAR WATER VERTICAL WET TYPE SUBMERSIBLE PUMPSET THREE PHASE SUITABLE FOR 159MM OW POREWELL		Rs.57000.00 (Rupees fifty seven thousand	1 NO (EACH)	57000.00
. 18	*	CONFORMING TO IS 8034/2002 WITHOUT PANEL BOARD AS AMENDED THEREAFTER AND BEE 3 STAR RATED CAPABLE OF DISCHARGING NOTED LPM AGAINST HEAD OF WATER COLUMN DUE TO ALL CAUSES THE PUMP SHALL BE WITH STAINLESS STEEL SHAFT AND DYNAMICALLY BALANCED BRONZE OR CAST SS IMPELLER, BRASS SCREWS AND CLIFG 200 GRADE PUMP BOWL/DIFFUSER WITH ISLMARK THE PUMP SHALL BE DIRECTLY COUPLED TO A CONTINUOUS		4	*	4
		SHALL BE DIRECTLY COUNTABLE WET TYPE VERTICAL SQUIRREL CAGE INDUCTION MOTOR AS PER IS 9283/1995 AS AMENDED THEREAFTER, SUITABLE FOR OPERATION IN AC THREE PHASE 415 V+/-10%, 50+JZ +/-5% ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND BRAND OF THE SUBMERSIBLE PUMP SET ARRANGEMENTS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)				
		DUTY - 50 LPM X 175 M				
119.1,	3 NOS. X	SUPPLYING AND DELIVERY OF 2 HP ELECTRIC MONOSET CENTRIFUGAL PUMP CONFORMING TO IS 9079:2002 AS AMENDED FROM TIME TO TIME, WITH CIFG 200 CASING, HYDRAULICALLY AND DYNAMICALLY BALANCED BRONZE GRADE LTB-2 IMPELLER, IMPELLER RING AND CASING RING, STAINLESS STEEL SHAFT		Rs.18000.00 \(\) (Rupees eighteen thousand only)	1.NO. (EACH)	54000.00
>		CAPABLE OF DISCHARGING REQUIRED QUANTITY OF WATER AGAINST A TOTAL HEAD NOTED BELOW DUE TO ALL CAUSES. PUMP SHALL OF BEE 3 STAR RATED AND CAPABLE OF DISCHARGING THE SPECIFIED QUANTITY AT THE HEAD NOTED AT THE MINIMUM NPSHA AT SITE CONDITIONS. THE SHUT OFF HEAD SHALL BE ATLEAST 25% OVER AND ABOVE THE HEAD AT DUTY POINT. THE PUMP SHALL BE SUITABLE FOR OPERATION IN AC SINGLE PHASE, 230 V +/- 10%, 50HZ +/- 5%. SQUIRREI				
		CAGE INDUCTION MOTOR FOR CONTINUOUS OPERATION. THE SPEED OF THE PUMP AND MOTOR SHALL BE NOT LESS THAN 2700 TO 2900 RPM RESPECTIVELY.	3			
		D017 - 450 LPM X 20 M		Æ		1
120	1 NO.X	LABOUR CHARGES FOR THE ERECTION OF SUBMERSIBLE PUMPSET IN BOREWELL/OPENWEL (UPTO 5 HP) INCLUDING FIXING AND JOINTING SUBMERSIBLE CABLE WITH PROPER CLAMPS UPTO THE STARTER TO THE REQUIRED DEPTH AND ALSO FIXING OF RISER PIPES TO THE REQUIRED DEPTH VALVE ERECTION CLAMPS, PRESSURE GAUGES UPTO THE EXTERIOR WALL OF PUMP ROOM AND ERECTION OP PANEL BOARD CONSISTING OF TPICN SWITCHE STARTER, VOLTMETER, AMMETER, THREE PILO (INDICATING) LAMPS CAPACITOR SINGLE PHASINE PREVENTOR, WATER LEVEL GUARD AND LAYING AN	G E G S E F S T G D	Rs.5000.00 (Rupees tive thousand only)	1.NO. (FACH)	5000.00
420.4	3 NOS	JOINTING THE CABLES AND TWIN EARTHING AS PER I RULES ETC., COMPLETE AND TESTING THE PUMPSE AND TRAIL RUN FOR 10 DAYS ETC., ALL COMPLETE AN AS DIRECTED BY THE DEPARTMENTAL OFFICERS. LABOUR CHARGES FOR THE ERECTION COMPLETED IN THE PROPERTY OF THE PROPERT	T D	Rs.2500.00 X	1.NO. \	7500.00
120.1	3 NOS.	HORIZONTAL SHAFT, CENTRIFUGAL PUMPSET UPTO HP (COUPLED / MONOBLOCK) IN BOREWELL		(Rupees two thousand and five	(EACH)	
*	+	OPENWELL INCLUDING FIXING OF SUCTION PIPE AN FOOT VALVE UPTO A MAXIMUM DEPTH OF 7 METRE AND DELIVERY PIPES TO THE REQUIRED LENGTH WIT VALVES, PRESSURE GAUGES UPTO THE EXTERIO WALL OF PUMP ROOM AND ERECTION OF PANE BOARD CONSISTING OF TPIC SWITCHES STARTED VOLTMETER, AMMETER, CAPACITOR SINGLE PHASIN PREVENTOR AND LAYING AND JOINTING THE CABLE AND TWIN EARTHING AS PER IE RULES INCLUDING PROVIDING BED BLOCKS ETC., COMPLETE AN	S H BR L R. I G I G I G I D I D	+	+	+
For/	A.P.CONST	PROTECTION OF THE PUMPS AND TRIAL RUN FOR 10 DAY	rs HE			41
		DEPARTMENTAL OFFICERS.				15578510.40

SHIERINTENDING ENGINEER/SOUTH TITCLE.

	and a	KADAMALAIRUNDÜ HI		RATE EXCLUSIVE FOR GST IN	UNIT IN FIGURES	AMOUNT
40	QUANTITY	DESCRIPTION OF WORK	тиве йо	PIGURES AND IN WORDS 5	AND IN WORDS	7
+	2					15578510.40
1	1 NO.	SUPPLYING AND DELIVERY OF THREE PHASE		Rs.11000.00	1.NO. (EACH)	11000.00
		PANEL BOARD OF DIRECT ONLINE STARTER WITH TWO LEVEL GUARD AND AUTO START (5		(Rupees eleven thousand only)		
	λ.	HP) CONFIRMING TO IS 13947 AND IEC 60947-1			160	1
	Þ	SUITABLE KW RATING FOR OPERATION IN AC/THREE PHASE/50 HZ (± 5%) AND 415 V (± 10%) INCLUDING AMMETER, VOLTMETER, THERMAL OVER LOAD RELAY, 16 AMPS 2 POLE MAGNETIC CONTACTOR WITH UNDER VOLTAGE PROTECTION, INDICATION LAMP, STARTING CAPACITOR, RUNNING CAPACITOR AND ON/OFF PUSH BUTTON SWITCHES, 5 WAY CONNECTOR, WIRING WITH 1 SQMM./ 1.5 SQMM COPPER PVC INSULATED CABLE, POWDER COATED VERMIN PROOF BOX INCLUDING THE CAPACITOR (THE COST OF CAPACITOR IS TO BE TAKEN				
		SEPARATELY) AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE THREE PHASE PANEL BOARD ASSEMBLY SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)				
.2	3 NOS.	SUPPLYING AND DELIVERY OF DIRECT ONLINE STARTER WITH SINGLE PHASING PREVENTOR 2 HP FOR MONOBLOCK MOTOR WITH ANALOG	2	Rs.5200.00 X (Rupees five thousand and two hundred only)	1.NO. (EACH)	15600.0
X	X	AMMETER AND VOLTMETER CONFORMING TO IS 13947-1 WITH AUTO RESTART FACILITY FOR PUMIFIC 60947-1 WITH AUTO RESTART FACILITY FOR PUMIFIC 60947-1 WITH AUTO RESTART FACILITY FOR PUMIFIC FOR WHERE PANEL BOARDS ARE AVAILABLE THEREAFTER SUITABLE KW RATING FOR OPERATION IN ACTHREE PHASE/50HZ(+/- 5%) AND 415 V(+/- 10% INCLUDING AMMETER, OVERLOAD RELAY, UNDET VOLTAGE RELEASE WITH NO VOLT COIL, AIR BREAM		*	4	+
		CONTACTORS SUITABLE FOR NEXT STANDARD HIGHEI KW RATING, SINGLE PHASING PREVENTOR, DR RUNNING PREVENTER AND ON/OFF PUSH BUTTOI SWITCHES, INCLUDING THE CAPACITOR (THE COST OCAPACITOR IS TO BE TAKEN SEPARATELY) AND A DIRECTED BY THE DEPARTMENTAL OFFICERS. (TH SINGLE PHASE PANEL BOARD ASSEMBLY SHOULD B GOT APPROVED FROM THE EXECUTIVE ENGINEE BEFORE USE)	Y F S E E			
22		SUPPLYING AND FIXING OF THE FOLLOWING DIA OF THE GI, CI & GM SPECIALS CONFIRMING TO SPECIFICATION WITH ISI MARK OF APPROVE SUPERIOR QUALITY ALL, ETC., COMPLETE AND A DIRECTED BY THE DEPARTMENTAL OFFICERS. (T) QUALITY OF THE GI, CI & GM SPECIALS SHOULD BE GO APPROVED BY THE EXECUTIVE ENGINEER DEFORMUSE)	IS AS HE DT			
	5 NOS.	a) 50 MM X 40 MM DIA GI REDUCER TEE 🔨		Rs.135.00 X (Rupees one hundred and this five only)	1.NO. (EACH)	675
	26 NOS,	b) 50 MM DIA GI COUPLING		Rs.70.00 (Rupees seventy only)	1.NO. (EACH)	1826
	3 NOS.	c) 50 MM DIA GM GATE VALVE (HEAVY DUTY)		Rs.1200.00 (Rupees one thousand and thundred only)	1.NO. (EACH)	3600
	1 NO.	d) 50 MM DIA GM NON RETURN VALVE		Rs.2000.00 (Rupees two thousand only)	1.NO. (EACH)	200
-		e) 50 MM DIA GI UNION		Rs.265.00 (Rupees two hundred and s	1.NO. (EACH)	
Fo	A.P.CON	STRUCTIONS		ive only)	17	1561400
1	11-1-1	111	1/2	I.	,	*11

SUPERINTENDING ENGINEER/SOUTH CIRCLE

	1		11-1-1
		\ .	//
TOTAL STATE	A 11/11/5/101	Seite 18:15 101	C4 W 121

			II AND RESU			
ITEM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES : AND IN WORDS	e' JNT
-1-1	2	3	4	9		15614000.40
				-		40
1	5 NOS.	f) 50 MM DIA GI HEX NIPPLE		Rs.85.00	T.NU.	425.00
		· ·		(Rupees eighty five only)	(EACH)	A
1						1
		,		₩.		91
	1 NO.	g) 50 MM DIA C.I. FOOT VALVE WITH STAINER		Rs.430.00	1.NO. \ (EACH)	430.00
1				(Rupees four hundred and	(27.01.)	
i				thirty only)		
İ	3 N OS .	h) 50 MM DIA GI TEE		Rs.130.00	1.NO.	390.00
	4) or min and or a	_	(Rupees one hundred and thirty	(EACH)	
i i				only)		
				2		
					1	
	10 NOS.	i) 50 MM DIA GI BEND		Rs.150.00	1.NO.	1500.00
	⋖ ,	^.		(Rupees one hundred and fifty	(EACH)	1 4
	2			only)		X
				_		
	2 NOS.	j) 32 MM DIA GI UNION 🔪		Rs.120.00	1.NO.	240.00
	2 1105.	I) 32 MINI DIA GI ONION		(Rupees one hundred and	(EACH)	\
	. >	``\		twenty only)		Α
				/		
				-		
	2 NOS.	k) 32 MM DIA GI ELBOW		Rs.85.00	1.NO. (EACH)	170.00
	•			(Rupees eighty five only)	(2,70.1)	
				ga.		-
	2 NOS.	I) 32 MM DIA GI HEX NIPPLE		Rs.55.00	1.NO. (EACH)	110.00
				(Rupees fifty five only)	(EAGII)	
1				· /		
	1					p.
	2 NOS.	m) 25 MM DIA GI COUPLING		Rs.25.00	1.NO. (EACH)	50.00
	-	°		(Rupees twenty five only)	(ENOIT)	
- }				-) e
123	325.00 Rmt.	SUPPLYING AND DELIVERY OF PVC INSULATED AND		Rs.185.00	1.Rmt. (ONE RUNNING	60125.00
*	· ·	SHEATHED 3 CORE 4 SQ.MM FLAT TYPE COPPER		(Rupees one hundred and	METRE)	
	\times	CABLE CONFIRMING TO IS 694/1990 BEST APPROVED QUALITY WITH ISI MARK INCLUDING COST OF CABLE		eighty five only)		as Ar
	- 3	DELIVERY AT SITE AND FIXING THE CABLE IN BORE	=	K	λ	
		WELL ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY OF THE	3 1	,	,	
		MATERIAL SHOULD BE GOT APPROVED FROM	1			
		EXECUTIVE ENGINEER BEFORE USE)				
			1			
		S09467544	j			
124		SUPPLYING AND DELIVERY OF FOLLOWING DIA G PIPE 'B' CLASS OF BEST APPROVED QUALITY				
Ť		CONFIRMING TO IS SPECIFICATIONS WITH ISI MAR				
		FOR PROVIDING UG CABLE ETC., ALL COMPLETE ANI	D			į.
		AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY OF THE GI PIPES SHOULD BE GOT APPROVE				
		FROM EXECUTIVE ENGINEER BEFORE USING).				
	1					-
	15.00 Rmt.	a) 25 MM DIA GI PIPE		Rs.125.00	1.Rmt. (ONE RUNNING	/ 1875.0
				(Rupees one hundred and twenty five only)	METRE)	×
				twenty five only)	A)	1
	5.00 Rmt	b) 40 MM DIA GI PIPE 人		Rs.160.00	1.Rmt.	> 800.0
	-			(Rupees one hundred and sixt	y (ONE RUNNING METRE)	X
			1	only)	1	
For A	PCONST	RUCTIONS		. ×.		
	1.001131	TUCTIONS			-	15680115.4
	. 4.	1	l,	I .		4
1-1						
1-1	21.1h	PARTNER				

SUPERINTENDING ENGINEER/SQUTH ORCLE

		KADAMALAIKI SHE SA	g annus	118.		Pape No. 31
TTEM.NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS 6	AMOUNT
_4	158.00 Rmt.	c) 50 MM DIA GI PIPE	4	Rs.200.00 (Rupees two hundred only)	1.Rmt. (ONE RUNNING METRE)	7 15680115,40 31600.00
125		SUPPLYING AND DELIVERY OF FOLLOWING DIA PVC PIPE INCLUDING COST OF ALL MATERIALS OF BEST APPROVED SUPERIOR QUALITY WITH ISI MONOGRAM ETC ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE PVC PIPE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)			البر	
	70.00 Rmt.	a) 50MM DIA PVC PIPE/10 KG/CM ²		Rs.140.00 (Rupees one hundred and forty only)	1.Rmt. \ (ONE RUNNING METRE)	9800.00
	15.00 Rmt.	b) 32MM DIA PVC PIPE/10 KG/CM ²		Rs.61.00 (Rupees sixty one only)	1.Rmt. (ONE RUNNING METRE)	915.00
125.1	220.00 Rmt	LABOUR CHARGES FOR LAYING THE GI AND PVC PIPE BELOW GROUND LEVEL INCLUDING EARTH WORK		Rs.82.00 (Rupees eighty two only)	1.Rmt. \ (ONE RUNNING	18040.00
X	+	EXCAVATION, CUTTING, THREADING, JOINTING, LOWERING, LAYING TO PROPER GRADE AND ALIGNMENT AND REFILLING THE TRENCH WITH EXCAVATED EARTH ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		+	METRE)	+
125.3	300.00 Rmt.)	SUPPLYING OF 32MM DIA UPVC PIPE OF BEST APPROVED SUPERIOR QUALITY WITH ISI MARK INCLUDING COST OF ALL MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE UPVC PIPE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.140.00 (Rupees one hundred and forty only)	1.Rmt. (ONE RUNNING METRE)	42000.00
126.1	6 SET,X	SUPPLYING AND FIXING OF THE 65MM DIA OF THE MS CLAMP SET OF SUPERIOR QUALITY ALL, ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY OF THE MS CLAMP SET SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)		Rs.300.00 X (Rupees three hundred only)	1.Set. (ONE SET)	1800.00
127	310.00 Rmt. X	SUPPLY AND DELIVERY OF REQUIRED DIA NYLON ROPE OF SUPERIOR QUALITY FOR SUBMERSIBLE PUMPSET IN BOREWELL AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE QUALITY OF NYLON ROPE SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE SUPPLY)		Rs.10.00 (Rupees ten only)	1.Rmt. (ONE RUNNING METRE)	3100.00
129.1		SUPPLYING AND FIXING IN POSITION OF ALUMINIUM DYECASTING TNPHC LOGO EMBLEM OF SIZE 2-0" (24") HEIGHT INCLUDING DRAWING MODEL LETTERS ON THE PAPER, PREPARING THE DESIGN, MOULDING, CASTING, FILING, COLOURING TO THE REQUIREMENT BY SPRAYING THE PAINT, TRANSPORTING TO SITE AND LABOUR FOR SCAFFOLDING DRILLING AND FIXING THE LETTERS BY USING PROJECTED ROD FEVICOL QUICK FIX AND CEMENT SLURRY AND REDOING THE DAMAGED AREA AND COLOURING ETC ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE DESIGN SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE MOULDING)				
For	A.P.CONS	RUCTIONS	= -	- 15 B	7 3	15787370.40
1-	44	12.5				1

NO. OF CORRECTIONS

SUPERINTENDING ENGINEERISQUIM CIRCLE.

		KADAMALAIKI NDUJE	VZD3620	30%		Page Ho 32
TEM NO	QUANTITY	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
	1 NO.	a) 60 CM SIZE		Rs.3000.00 (Rupees three thousand only)	1.NO. (EACH)	3000.00
130		SUPPLYING AND FIXING OF ALUMINIUM DYE CAST LETTERS OF APPROVED SIZE AND COLOUR. THE COLOUR TREATMENT PROCESS IS ACHIEVED WITH MRE COLOUR COAT AND THEN THE PROCESSED COLOURED LAYER IS SET INTO THE KILN FOR THE HEAT TREATMENT PROCESS FOR THE FOLLOWING SIZES ETC, ALL COMPLETE, AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE DESIGN SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE MOULDING)				
	47 NOS.	a) ALUMINIUM DYE CAST LETTER 9" SIZE		Rs.1000.00 (Rupees one thousand only)	1.NO. (EACH)	47000.00
	116 NOS.	b) ALUMINIUM DYE CAST LETTER 6" SIZE		Rs.690.00 (Rupees six hundred and ninety only)	1.NO. (EACH)	80040.00
132.1	300.00 Rmt.	DRILLING OF 150MM DIA BORE WELLS IN ALLUVIAL SOILS TO THE REQUIRED DEPTH INCLUDING LABOUR CHARGES FOR INSERTING CASING PIPES, INCLUDING COST OF RIG, FUEL ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.275.00 (Rupees two hundred and seventy five only)	1.Rmt. (ONE RUNNING METRE)	82500.00
133	25.00 Rmt.	SUPPLYING AND DELIVERY OF 150MM DIA PVC CASING PIPE SHALLOW DEPTH WITH REQUIRED DEPTH AS PER IS 12818/2010 ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY OF THE CASING SHALLOW DEPTH PIPE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.615.00 X (Rupees six hundred and fifteen only) ✓	1.Rmt. (ONE RUNNING METRE)	5375.00 15375.00
134 ×	1 NO.	SUPPLYING AND FIXING OF 160MM DIA PVC END CAP FOR CORRECTING THE BOREWELL CASING PIPE OF APPROVED BRAND ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE QUALITY AND BRAND OF PVC END CAP SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)		Rs.130.00 × (Rupees one hundred and thirty only)	1.NO. (EACH)	[↑] 130.00
140	73.70 Cu.M.	SUPPLYING OF 3 TO 10MM SIZE HBSJ INCLUDING CONVEYANCE AND COST OF MATERIALS ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS.		Rs.700.00 X (Rupees seven hundred only)	1.Cu.M. (ONE CUBIC METRE)	^{.†} 51590.00
142	490.80 Sq.M.	SUPPLYING AND DELIVERY OF 83MM TK RUBBER MOULDED HYDRAULIC PRESSED PAVER BLOCK ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY OF PAVER BLOCK SHOULD BE GOT APPROVED BY THE EXECUTIVE ENGINEER BEFORE USE)		Rs.800.00 (Rupees eight hundred only)	1.Sq.M. (ONE SQUARE METRE)	392640.00
or A	.P.CONSTI	RUCTIONS				

		KADAMALAIKUNDU FIL	all distribution	10. (/		uge No. 33
TEM.NO	QUANTITY	BESCHI HONG! WORK	TNBP No	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
1	2	3	4	,		16459645.40
143	490.80 S q.M.	LABOUR CHARGES FOR SPREADING AND LEVELLING OF 3MM TO 10MM SIZE HESJ AND		Rs.100.00 (Rupees one hundred only)	1 Sq.M (ONE SQUARE METRE)	49000.00
	٨	STONE DUST TO THE REQUIRED THICKNESS WITH COMPACTION BY EARTH RAMMER FURTHER LAYING OF 83MM THICK PAVER BLOCK AND FILLING THE GAP BETWEEN THE PAVER BLOCKS INCLUDING LABOUR CHARGES AND MACHINERY CHARGES ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS		<i>x</i> *	1	સ
144	6 NOS.	SUPPLYING AND FIXING OF CP SHOWER ARM WITH		Rs.900.00	1.NO. (EACH)	5400.00
× X	X	OVERHEAD SHOWER ROSE INCLUDING COST OF MATERIALS AND LABOUR CHARGES FOR FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE BRAND AND QUALITY OF THE MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE		(Rupees nine hundred only)	×	*
145	6 NOS.	SUPPLYING AND FIXING OF CP TWO WAY BIB COCK WITH HEALTH FAUCET INCLUDING COST OF		Rs.950.00 (Rupees nine hundred and fifty	1.NO. (EACH)	5700.00
X	X	MATERIALS AND LABOUR CHARGES FOR FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF THE MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		only)	*	+
146	6 NOS.\	SUPPLYING AND FIXING OF CP ANGLE COCK TAP INCLUDING COST OF MATERIALS AND LABOUR CHARGES FOR FIXING IN POSITION ETC., ALI COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF THE MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)	-	Rs.750.00 (Rupees seven hundred and fifty only)	1.NO. (EACH)	×4500.00
147	60.00 Rmt.	SUPPLYING AND FIXING OF PVC TRIMS (BEADING INCLUDING COST OF MATERIALS AND LABOUI CHARGES FOR FIXING IN POSITION ETC., AI COMPLETE AND AS DIRECTED BY THE DEPARTMENTA OFFICERS. (THE QUALITY OF THE MATERIALS SHOULI BE GOT APPROVED FROM THE EXECUTIVE ENGINEE BEFORE USE)	T L D	Rs.50.00 (Rupees fifty only)	1.Rmt. (ONE RUNNING METRE)	3000.00
159	1 NO.	METERING PANEL FOR 4 SERVICES (2 FLATS + COMMON AND 1 SPARE) 2 IN 1 (G+1 ONLY)	1	Rs.25000.00 (Rupees twenty five thousand	1.NO. (EACH)	25000.00
X	×	SUPPLY AND ERECTION OF 125 AMPS CAPACITY FLOOMOUNTING METERING PANEL BOARD (CUBICAL TYPLOF SIZE 3'-0"X 6'-5"X1'-0" SUITABLE FOR 2 IN 1 (G ONL'WITH BUS BAR CHAMBER MADE UP OF 16 SWG M SHEET FOR 3 PHASE 4 WIRE SYSTEM WITH 25MMX 3M TIN COATED COPPER FLATS FOR PHASES AN NEUTRAL: INDIVIDUAL METERING CHAMBER AND WIT 2 NOS, OF 25X3MM GI FLAT FOR THE EARTH BUS CITHE REAR SIDE OF THE PANEL BOARD: NECESSAF INTERCONNECTIONS BY COPPER FLAT OF SUITABL SIZES; SUITABLE PVC COLOUR SLEEVES FOR THINTERCONNECTING COPPER FLATS/RIGID COPPER	E) Y) IS M ID H IV X Y	only) ×	X	
For	A.P.CONS	WIRE; EARTH CONNECTIONS TO ALL SWITCHES / BU BAR BY GI FLATS OF SUITABLE SIZES FROM THE EART BUS:1 SET LED PILOT LAMPS FOR EACH METERING CHAMBER WITH SWITCHES, FUSE UNITS, SUITABLANGLE IRON FRAME SIZE OF 40X40X6MM WITH PAINTING IN TWO COATS OF SUITABLE COLOUR OVER ONE COAT OF RED OXIDE AND WITH NUMBERING SUPERSCRIPTION OF CABLE SIZES, CAPACITY OF SWITCHES ETC AND INCORPORATING THE FOLLOWINTRUCTIONS	TH IG LE TH ER G;		4	
\	1.					16552325.4
~ ~	MA M	145	9		1.71	IL:



4		KADAMAI AIKUNDU FII	AND HISE	179		Page No: 34
EM_NO	QUANTITY 2	DESCRIPTION OF WORK	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT
		INCOMING: 3 NOS. 200 A CUT OUTS BUS CAPACITY: 125A 3 PHACE 4 WIRES COPPER FLATS FOR PHASES AND NEUTRAL OUTGOINGS: 2 NOS. METERING CHAMBER EACH CHAMBER CONTAINING 3 NOS OF 63A FUSE UNITS.1 NO 25X3MM COPPER FLATS FOR NEUTRAL LINK, 40 AMPS 4 POLE ISOLATOR FOR 3 PHASE AND SPACE PROVISION FOR FIXING TNEB ENERGY METER AND GLASS COVER OF SUITABLE SIZE FOR TAKING METER READINGS AND ALSO 1 NO OF 32A FUSE UNIT WITH NEUTRAL LINK AND 40 AMPS 2 POLE ISOLATOR FOR SINGLE PHASE SERVICES FOR COMMON LIGHTING PURPOSES AND 1 NO. OF DUMMY PROVISIONS. ALSO NECESSARY WIRING WITH 6SQ MM PVC INSULATED COPPER CABLES FROM TNEB CUT OUT OF ENERGY METER AND FROM ENERGY METER TO 40 AMPS - 4 POLE ISOLATOR. 1 SET LED PILOT LAMPS WITH FUSE UNITS, SWITCHES & INTERCONNECTIONS; INTERCONNECTIONS TO THE BUS BAR BY 25X3MM TC COPPER FLATS FOR PHASES AND NEUTRAL FROM 200A CUTOUTS TO THE BUS AND NO.6 SWG COPPER FOR THE PHASES AND NEUTRAL FROM THE 63A FUSE UNITS TO THE BUS; FIXING OF 6MM THICK HYLEM SHEET FOR FIXING ENERGY METERS, INSULATORS FOR THE SUPPORT FOR THE BUS; SUPER-SCRIBING ON THE PANEL BOARD THE SIZE, CAPACITY OF CABLE, SWITCHES, LOCATION ETC, 2 NOS METALLIC DANGER BOARDS ETC. ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE QUALITY AND BRAND SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE SUPPLY AND USE)				16552325.40
163	2 NOS.	SUPPLYING AND FIXING OF 63 AMPS TPN SWITCH DISCONNECTOR FUSE UNITS IN SHEET STEEL ENCLOSURE WITH HRC FUSES DOUBLE BREAK INCLUDING COST OF MATERIALS AND LABOUR CHARGES FOR FIXING IN POSITION ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY OF THE MATERIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.500.00 X (Rupees five hundred only)	1.NO. (EACH)	1000.00
14.2 X	8 NOS.	SUPPLYING AND FIXING OF BEVELED EDGE MIRROR OF APPROVED QUALITY AND BRAND OF SIZE 500X400X5.5MM SHELF TYPE MOUNTED IN THE PVC/FIBRE GLASS FRAMED WITH NECESSARY HARD BOARD BACKING INCLUDING LABOUR FOR FIXING IN POSITION ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS,		Rs.340.00 (Rupees three hundred and forty only)	1.NO. (EACH)	k 2720.0
61.1	77.00 sq.M.	SUPPLYING AND LAYING SUPERIOR VARIETY CONCRETE DESIGNER TILES FOR FLOORING IN CM 1:3 (ONE OF CEMENT AND THREE OF CRUSHED STONE SAND) 20MM THICK, INCLUDING FIXING IN POSITION, CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY, POINTING THE JOINTS WITH WHITE/COLOUR CEMENT, FINISHING, CURING ETC., COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND QUALITY OF TILES SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE).		Rs.900.00 (Rupees nine hundred only)	1.Sq.M. (ONE SQUARE METRE)	69300.0
		9				16625345.4
		RUCTIONS	1	T.	1	31

NO. OF CORRECTIONS

SUPERINTENDING ENGINEER/SOUTH CIRCLE.

M. S.

		KADAMALAIKUNDU HIR	AND RES	TI S/		hope No: 35
EM NO	QUANTITY	,	TNBP No.	RATE EXCLUSIVE FOR GST IN FIGURES AND IN WORDS 5	UNIT IN FIGURES AND IN WORDS	AMOUNT 7
367	17.80 Sq.M.	PROVIDING WOODEN MELAMEN POLISH FOR MAIN DOOR NEW WOOD BY REMOVING BY BLADE SCRAPPING THE EXISTING DIRT FROM THE WOODEN. SURFACE WITH M50 SAND PAPER AND REPEAT M80 SAND PAPER TO GET A SMOOTH SURFACE LEAVE ATLEAST 4HRS DRYING AND PREPARE SURFACE BY M100 SAND PAPER AND CLEAR THE SURFACE APPLY	71	Rs.900.00 (Rupues nine hundred only)	1,Sq.M. (ONE SQUARE METRE)	16020.00
		ONE COAT OF TOUCH WOOD STAINER BY BRUSH AND LEAVE FOR TWO HRS. FOR DRYING, PREPARE THE SURFACE BY M100 SAND PAPER AND APPLY ONE COAT OF ASH SANDING SEALER MIXED WITH APPROVED QUALITY THINNER AFTER DRYING APPLY UNE COAT OF SANDING SEALER AND ATTEND THE SURFACE TO GET THOROUGHLY DRIED SMOOTHER SURFACE WITH				
		NO.250 WATER EMERY WOOD CLEANER FILL THE HOLES AND DOTS BY PUTTY AND PACKING TO GET THE SURFACE CLEAN, APPLY SURFACE BY WAX EMERY SHEET NO.250, APPLY FIRST COAT OF MELAMEN SEALER WITH THE THINNER FOR PREPARING THE SURFACE AND APPLY SECOND COAT OF THE SAME BY AFTER DRYING PREPARING THE SURFACE WITH				
		WATER EMERY NO.320 AND APPLY TWO COATS OF MELAMEN MATT MIXED WITH GLOZING AND THINNER 106 PREPARE THE SURFACE WATER EMERY NO.400 AND APPLY TWO COATS OF SAME AND FINALLY SMOOTHER ETC., ALL COMPLETE INCLUDING COST OF ALL MATERIALS AND LABOUR ETC., AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS, (THE QUALITY AND SHADE OF THE POLISH SHOULD BE GOT APPROVED FROM THE LE BEFORE USE).				
78.2	351.40 Sq.M.	SUPPLYING AND FIXING OF VETRIFIED TILES OF BEST		Rs.1000.00	1.Sq.M. X	351400.0
λ	×	APPROVED QUALITY (IVORY) 600X600X8MM FOR FLOORING AND OTHER SIMILAR WORKS (THE COLOUR AND SHADE SHALL BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING) OVER CEMENT MORTAR 1:3 (ONE OF CEMENI AND THREE OF CRUSHED STONE SAND) 20MM THICK INCLUDING FIXING IN POSITION CUTTING THE TILES TO THE REQUIRED SIZE WHEREVER NECESSARY POINTING THE JOINTS WITH GROUT (TILE JOINT FILLER) CURING FINISHING ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS,		(Rupees one thousand only)	(ONE SQUARE METRE)	*
48.2	8 NOS. \	SUPPLYING AND FIXING OF PVC TEE WITH END CAP OF 32MM DIA AND COUPLING OF BEST APPROVED QUALITY WITH ISI MARK TO THE SINK AND WASH BASIN INSTEAD OF BOTTLE TRAP ETC., COMPLETE COMPLYING WITH RELEVANT STANDARD SPECIFICATIONS AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS. (THE BRAND AND QUALITY OF PVC SPECIALS SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USE)		Rs.120.00 \(\sum_{\text{(Rupees one hundred and twenty only)}}\)	1.NO. (EACH)	960.C
796	1882.60 Sq.M.)	PAINTING THE NEW WALLS WITH TWO COATS OF APPROVED BEST READY MIXED PLASTIC EMULSION		Rs.150.00 \(\text{(Rupees one hundred and fifty)}\)	1.Sq.M.	282390.0
X	X	PAINT IN ADDITION TO ONE COAT OF APPROVED PRIMER COAT OVER CEMENT PLASTERED WALL SURFACES AND CEILING INCLUDING COST OF PLASTIC EMULSION PAINT, PUTTY, BRUSHES ETC., ALL COMPLETE AND AS DIRECTED BY THE DEPARTMENTAL OFFICERS (THE EMULSION PAINT AND ITS SHADE SHOULD BE GOT APPROVED FROM THE EXECUTIVE ENGINEER BEFORE USING)		only)	METRE)	+
		TOTAL AMOUNT (EXCLUDING GST)				17276115.
		GST Amount for providing Service to Government Contract Works for the above Construction Works.				2073133.
		GRAND TOTAL				19349249.

TRUPLES ONE TO HE LAKHS FORTY NINE THOUSAND TWO HUNDRED AND FORTY NINE AND PAISE TWENTY FIVE ONLY)

PARTNER

NO. OF CORRECTIONS

SUPERINTENDING ENGINEER/SOUTH CITCLE

*