

GROUND FLOOR PLAN

SCHEDULE OF JOINERY TYPE DESCRIPTION SILL TOP SIZE						
	MD - T.W FRAMED DOOR WITH T.W DOUBLE LEAF	DILL	70P	1800X24		
MU	PANELLED DOOR SHUTTERS WITH BRASS FITTINGS		2000	1000724		
FW1	FRENCH WINDOW-T.W GLAZED WINDOW WITH M.S GRILL	300	2400	900X21		
	SITOUT DOOR-T.W FRAMED DOOR WITH T.W SINGLE LEAF		2400	900X24		
RV	PANELLED DOOR SHUTTERS WITH BRASS FITTINGS					
FW	FRENCH WINDOW-T.W GLAZED WINDOW WITH M.S GRILL	300	2400	600X21		
RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		BB	1500X06		
)1/FW	SITOUT DOOR—T.W FRAMED DOOR WITH T.W SINGLE LEAF		2400	750X24		
FW	PANELLED DOOR SHUTTERS WITH BRASS FITTINGS FRENCH WINDOW—T.W GLAZED WINDOW WITH M.S GRILL	300	2400	750X21		
RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS	000	BB	1500X06		
	SITOUT DOOR-T.W FRAMED DOOR WITH T.W SINGLE LEAF			1200X24		
-w	PANFLLED DOOR SHUTTERS WITH BRASS FITTINGS					
	FRENCH WINDOW-T.W GLAZED WINDOW WITH M.S GRILL			1100X21		
RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS			2100X06		
FW/	FRENCH WINDOW-T.W GLAZED WINDOW WITH M.S GRILL	300		1650X21		
RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		BB	1650X06		
	DOOR- T.W FRAMED DOOR WITH T.W DOUBLE LEAF PANELLED DOOR SHUTTERS WITH BRASS FITTINGS			1800X24		
DO/ RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		BB	1800X06		
	DOOR T.W FRAME WITH SOLID CORE FLUSH DOOR(SINGLE LEAF)		2400	1200X24		
1 /RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS			1200X24		
1A/	T.W FRAMED DOOR WITH T.W PANELLED DOOR SHUTTERS			1200X24		
v"	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS			1200X06		
A/RV	T.W FRAMED DOOR WITH T.W PANELLED DOOR SHUTTERS		2400	1500X24		
,	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS			1500X06		
TD_	DOOR PVC (TOILET)		2100	750X21		
D1/R	/DOOR - T.W PANNELLED DOOR (TOILET)		2400	900X24		
DΩ	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		2400	900X06		
D2	T.W FRAMED DOOR WITH T.W PANELLED DOOR SHUTTERS	750		1800X16		
W W1	WINDOW T.W GLAZED WINDOW WITH M.S GRILE WINDOW T.W GLAZED WINDOW WITH M.S GRILE	750 750	2100 2100	1500X16		
W2	WINDOW T.W GLAZED WINDOW WITH M.S GRILE	750	2400	1350X16		
W3	WINDOW T.W GLAZED WINDOW WITH M.S GRILE	750	2400	900X16		
W4	WINDOW T.W GLAZED WINDOW WITH M.S GRILE	750	2400	1200X16		
ŴŚ	STAIRCASE TW GLAZED WINDOW WITH M.S. GRILE	750	2400	1200X16		
	(750 SILL FROM LANDING) VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS	750	2400	1200X16		
SI W	SLIDING WINDOW UPVC GLAZED WINDOW WITH M.S GRILE	750	2400	1500X16		
SLW1	SLIDING WINDOW UPVC GLAZED WINDOW WITH M.S GRILE	750	2400	900X16		
TW	WINDOW T.W GLAZED WINDOW WITH M.S GRILE	750	2400	900X13		
٧	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		2400	900X 7		
٧1	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		2400	750X 7		
RV	VENTILATOR -T.W FRAMED GLAZED VENTILATOR WITH BARS		2400	1500X 9		
RV1	VENTILATOR -T.W FRAMED GLAZED VENTILATOR	RO	OF LV	750X S		
	PECIFICATION					

| SPECIFICATION

FOUNDATION : R.C.C COLUMN & B.W IN CM 1:5
SUPERSTRUCTURE: BRICK WORK IN C.M 1 : 5
ROOF : RCC SLAB WITH SUITABLE REINFORCEMENT
AND PROTECTED PRESSED TILES— SLOPE 1:60
FLOORING : IVORY COLOUR VITRIFIED TILE FLOORING FOR ALL ROOMS,
RCC 1:2:4 FLOORING FOR GARAGE
ANTISKID CERAMIC TILE FLOORING FOR TOILET
WITH GLAZED WALL TILES TO A HEIGHT OF 2100MM
CUPBOARD SLAB : IN RCC/CUDAPPAH FOR COASTAL AREA
CUPBOARD ARE COVERD WITH T.W STYLES AND RAILS
AND BWR PANNEL FOR SHUTTERS.
PAINTING : LIME WHITE WASH 3 COATS FOR CEILING. INNER WALL
— OBD 2 COATS OVER 1 COAT PRIMER WHITE CEMENT.
OUTER WALL—PLASTIC EMULSION PAINT INCLUDING PRIMER

OUTER WALL-PLASTIC EMULSION PAINT INCLUDING PRIMER

ENTRANCE MAIN DOOR-TEAK WOOD FRAME WITH TEAK WOOD SHUTTER,
INNER DOORS-T.W FRAME WITH SOLID CORE FLUSH SHUTTERS.

STEEL WINDOWS & VENTILATORS (OPENABLE)
FOR ALL SIZES — WITH GLAZED SHUTTER WITH MS GRILL
PIPES / TAPS : P V C / HALF TURN C.P TAP

NOTE

1. PLINTH HEIGHT 900MM FROM FORMED LVL
2. SILL LEVEL 750MM FROM FL.
3. LINTEL HEIGHT 2400MM&2100 FROM FINISHED FLOOR LEVEL.
4. ROOF HEIGHT 3600MM INCLUDING SLAB THK.
CARAGE ROOF HEIGHT FROM GARAGE FFL 6.75M(ROOF TOP)
5. HEIGHT OF PARAPET WALL IN IS 900MM, 300MM
6. SUNKEN SLAB IS 450MM
7. WIDTH OF SUNSHADE IS 600MM.
8. ALL DIMENSIONS ARE IN MM & LEVELS IN METRE.
9. STAIRCASE: - TREAD-300 MM, RISER-23 EQ RISER(150)

8. ALL DIMENSIONS AND STARCASE: - TREAD-300 MM, RISER-22 - AREA STATEMENT

GROUND FLOOR AREA GARAGE (DOR 10P) 6.75M HT FROM FINSHED GARAGE LVL) = 193.99
GROUND FLOOR OFFICE AREA(ROOF TOP 3.6M) = 226.25
FNTFRANCE VERANDAH & PORTICO(HALF AREA) = 12.58
238.83 = 253.50 = 686.32 = 15.31 701.63 FIRST FLOOR OFFICE AREA (ROOF TOP 3.6M)

STAIRCASE HEAD ROOM(HALF AREA)

PROPOSED CONSTRUCTION OF FIRE STATION CUM GARAGE BUILDING

SURVEY No. : 473/1B

VILLAGE THIRUVAIYARU WEST TOWN/TALUK : THIRUVAIYARU

DISTRICT : THANJAVUR



GROUND FLOOR PLAN

Scale = 1:100	Drg. No. DD/ 428 /2022	SHEET NO.01/04
Sd., 30/03/22 Asst. Architect	Sd., 30/03/22 AEE/Arch	Sd., 30/03/22 EE (PLG)
Sd., 30/03/22 Supdt.Engineer (C.C)		Sd., 01/04/22 CHAIRMAN/MD



TAMILNADU POLICE HOUSING CORPORATION LTD. NO:132, E.V.R.SALAI, KILPAUK, CHENNAI-600 010.