24/11

useEffect

handle
useEffect is a React hook used to perform side effects such as API calls, timers, event listeners or updating DOM.

It runs after component renders

side Effect

Anything that happens outside the normal UI rendering process such as
- fetching data from an API
- updating the DOM manually
- using timers

Types of useEffect

1) useEffect with no dependency array
   runs after every re-render

2) useEffect with empty dependency array[
   runs only once

3) usEffect with dependencies [state]
   runs only when dependency changes

syntax

```
useEffect(() => { }, [dependencies]);
useEffect(() -> { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { ], [dependencies]);
useEffect(() => { ], [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
useEffect(() => { }, [dependencies]);
```