

Here are the step-by-step notes on how to perform Update and Delete operations in Java using JDBC, based on the video:

General Setup & Update Operation [00:03:00]

1. **Set Up Java Class:** Create a Java class with a `main` method. Use `throws Exception` or a try-catch block to handle any SQL exceptions.

2. **Load Driver Class:** Use `Class.forName("com.mysql.cj.jdbc.Driver");` to load the MySQL driver.

Follow the third step only when you are creating a new project.

3. **Add JAR File:** Add the MySQL Connector JAR file to your project. (Right-click project -> Build Path -> Configure Build Path -> Add External JARs).

4. **Create Connection:** Establish a connection to the database using `DriverManager.getConnection()`. You need to provide the database URL, username, and password.

- *Example:* `DriverManager.getConnection("jdbc:mysql://localhost:3306/jdbc_db", "root", "root");`

5. **Write SQL Update Query:** Write the update query using positional parameters (`?`). Always use a `WHERE` clause to avoid updating all rows.

- *Example:* `UPDATE register SET city=? WHERE email=?`

6. **Prepare Statement:** Pass the query to a `PreparedStatement` object using `con.prepareStatement(query);`.

7. **Set Parameter Values:** Provide values for the `?` parameters using methods like `ps.setString()`.

- *Example:* `ps.setString(1, "Pune");` and `ps.setString(2, "kamal@gmail.com");`

8. **Execute Update:** Run the query using `ps.executeUpdate();`. This method returns an integer representing the count of affected rows.

9. **Verify Success:** Check if the count is greater than 0. If it is, print "Updated successfully". Otherwise, print "Updation failed".

Delete Operation [00:11:00]

1. **Initial Setup:** Loading the driver and establishing the connection are identical to the Update operation steps. *(Note: You do not need to re-add the JAR file if working within the same project).*

2. **Write SQL Delete Query:** Define the delete query using positional parameters ('?'). Always include a 'WHERE' clause to prevent accidental deletion of all table records.

- *Example:* `DELETE FROM register WHERE email=?`

3. **Prepare Statement:** Pass the SQL query to a 'PreparedStatement' object using the connection.

4. **Set Parameter Values:** Assign the target value to the parameter index using methods such as `ps.setString()`.

- *Example:* `ps.setString(1, "email1");`

5. **Execute Delete:** Execute the operation by calling `ps.executeUpdate();`.

6. **Verify Success:** Evaluate the returned integer. A value greater than 0 indicates success (e.g., "Deletion Success"), while 0 indicates no record was found (e.g., "Deletion Failed").

Video Link:  [#3 Update and Delete Operation using JDBC || CRUD Operation || Java MyS...](#)