Read   Discuss   Courses   Practice   Video

HTML | Quotations

Difficulty Level : Easy   ●   Last Updated : 28 Jun, 2022

The Quotation elements in HTML are used to insert quoted texts in a web page, that is portion of texts different from the normal texts in the web page. Below are some of the most used quotation elements of HTML:

1. **<q> element:** The <q> element is used to set a set of text inside the quotation marks. It has both opening and closing tags.

Example:

HTML

```
<!DOCTYPE html>
<html>
<head>
    <title>Quotations</title>
</head>
<body>
    <h3>GeeksforGeeks</h3>


<p>The quick brown fox jumps over the lazy dog<br></p>


    <!--Inside quotes-->


<p><q>The quick brown fox jumps over the lazy dog</q></p>


</body>
</html>
```

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

GeeksforGeeks

The quick brown fox jums over the lazy dog

"The quick brown fox jums over the lazy dog"

Mega Job-a-thon   DSA   Data Structures   Algorithms   Interview Preparation   Data Science   Te

2. **<blockquote> element:** The <blockquote> element is also used for quotations in a different way. Instead of putting the text in quotes, it adds space before the start of the sentence, with this tag we can also indent the start of the new paragraph. It has both opening and closing tags.

Example:

HTML

```
<!DOCTYPE html>
<html>
<head>
```

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

```html
<p>The quick brown fox jumps over the lazy dog<br></p>


    <!--Inside blockquotes-->


<p><blockquote>The quick brown fox jumps
over the lazy dog</blockquote></p>


</body>
</html>
```

Output:

GeeksforGeeks

The quick brown fox jums over the lazy dog

The quick brown fox jums over the lazy dog

3. **<address> element:** Using the <address> element, we can define an address in a webpage and the text put inside the address tag will be emphasized. Usually line break is added before and after the address tag and content inside this tag is generally renders in italic format. It helps screen reader also It has both opening and closing tags.

Example:

Start Your Coding Journey Now!

Read	Discuss	Courses	Practice	Video

```html
<html>
<head>
    <title>Address</title>
</head>
<body>
    <h3>GeeksforGeeks</h3>
    <address>


<p>Address:<br>
    710-B, Advant Navis Business Park,<br>
    Sector-142, Noida Uttar Pradesh – 201305</p>


    </address>
</body>
</html>
```

Output:

GeeksforGeeks

Address:
710-B, Advant Navis Business Park,
Sector-142, Noida Uttar Pradesh – 201305

4. **<abbr> element:** The <abbr> element is used to define a text as an acronym or abbreviations. The title attribute can be used to show the full version of the

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

Example:

HTML

```html
<!DOCTYPE html>
<html>
<head>
    <title>Abbreviations</title>
</head>
<body>
    <h3>GeeksforGeeks</h3>
    <!--Here the marked text is the acronym-->


<p>Welcome to <abbr title="GeeksforGeeks">GfG</abbr></p>


</body>
</html>
```

Output:

GeeksforGeeks

Welcome to GfG

5. **<bdo> element:** The <bdo> element is used to define a bidirectional override which means that, the text written from right to left or left to right. It has both opening and

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

HTML

```html
<!DOCTYPE html>
<html>
<head>
    <title>Bidirectional</title>
</head>
<body>
    <h3>GeeksforGeeks</h3>
    <!--Normal text-->


<p>The quick brown fox jumps over the lazy dog<br></p>


    <!--Inside <bdo> tag-->


<p><bdo dir="rtl">The quick brown fox jumps over the lazy dog</bdo></p>


</body>
</html>
```

Output:

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

GeeksforGeeks

The quick brown fox jums over the lazy dog

god yzal eht revo smuj xof nworb kciuq ehT

6. **<cite> element:** This element is used to define a title of a work and emphasizes a text.

Example:

HTML

```html
<!DOCTYPE html>
<html>
<head>
    <title>Cite</title>
</head>
<body>
    <h3>GeeksforGeeks</h3>
    <!--The title is kept in cite tag-->


<p>The <cite>GeeksforGeeks</cite> is the best site to<br>
    to search for articles and practice problems.</p>


</body>
</html>
```

Output:

Start Your Coding Journey Now!

The *GeeksforGeeks* is the best site to
to search for articles and practice problems.

Supported Browser:

- Google Chrome
- Microsoft Edge
- Firefox
- Opera
- Safari

Like   69

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

1.   How to add quotations and citations to the web pages using HTML ?

2.   How to display long quotations in HTML ?

3.   HTML <html> Tag

4.   HTML Course | Structure of an HTML Document

5.   HTML Course | Basics of HTML

6.   HTML | DOM HTML Object

7.   HTML | <html> xmlns Attribute

8.   What is the difference between <html lang="en'> and <html lang="en-US'> ?

9.   Inline HTML Helper - HTML Helpers in ASP.NET MVC

10.   How to return HTML or build HTML using JavaScript ?

Article Contributed By :

Chinmoy Lenka
@Chinmoy Lenka

Vote for difficulty

Current difficulty : _Easy_

| Easy | Normal | Medium | Hard | Expert |

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

Article Tags :   HTML and XML,   HTML-Basics,   HTML,   Web Technologies

Practice Tags :   HTML

Improve Article   Report Issue

GeeksforGeeks

A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company
About Us

Careers

In Media

Contact Us

Privacy Policy

Copyright Policy

Advertise with us

Learn
DSA

Algorithms

Data Structures

SDE Cheat Sheet

Machine learning

CS Subjects

Video Tutorials

Courses

News
Top News

Technology

Work & Career

Languages
Python

Java

CPP

Start Your Coding Journey Now!

Read   Discuss   Courses   Practice   Video

Knowledge   Kotlin

Web Development   ## Contribute

Web Tutorials   Write an Article

Django Tutorial   Improve an Article

HTML   Pick Topics to Write

JavaScript   Write Interview Experience

Bootstrap   Internships

ReactJS   Video Internship

NodeJS